## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-14-122-1 Relating to Certification of New Motor Vehicles

## TOYOTA MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Toyota Motors Corporation exhaust emission control systems are certified as described below for gasoline-powered light-duty trucks:

Engine Family	Displacement Liters (Cubic Inches)		Exhaust Emission Control Systems (Special Features)		
JTY2.4T5FBE3	2.4	(144.4)	Air Injection - Valve Exhaust Gas Recirculation Heated Oxygen Sensor Three-Way Catalyst (Electronic Port Fuel Injection) (On-Board Diagnostics)		

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Loaded Vehicle Weight	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per mile	Nitrogen Oxides Grams per Mile
3751-5750	0.50	9.0	1.0

The following are the certification emission values for this engine family:

Loaded Vehicle Hydrocarbons Weight Grams per Mile		Carbon Monoxide Grams per Mile	Nitrogen Oxides Grams per Mile
3751~5750	0.23	2.8	0.2

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s] ..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seg.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order supersedes Executive Order A-14-122 dated August 26, 1987.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 15 day of October, 1987.

K. D. Drachand, Chief Mobile Source Division

a. F. Donnelly (for KDD)

17.11.00 Supplemental data sheets

1988 AIR RB	SOURCES BOARD SUPPLEMENTAL DATA SH	BET B.O. # A-14-122-1 Page 1
Manufacturer Toyota Motor Corp  By B		4T5FBE3 . in-line
Ignition System  CA-Centrifugal Advance  ECU-Electronic Control Unit  EI-Electronic Ignition  ESAC-Electronic Spark Advance  Control	Exhaust Emissions Control System AIP-Air Injection-Pump AIV-Air Injection-Valve DBC-Dual Bed Catalyst EGR-Exhaust Gas Recirculation EIC-Electronic Injection Control	Special Features  CCV-Combustion  Chamber Valve  CFI-Central Fuel  Injection  DID-Diesel
VA-Vacuum Advance VR-Vacuum Retard  Puel System CFI, CL, DID, DIP, EFI, MFI nV-nVenturi Carburetor	EM-Engine Modification OC-Oxidation Catalyst OS-Oxygen sensor HOS-Heated Oxygen Sensor SPL-Smoke Puff Limiter or Throttle Delay TOC-Trap Oxidizer, Continual TOP-Trap Oxidizer, Periodical TWC-Three-Way Catalyst WUOC-Warm-Up Oxidation Catalyst WUTWC-Warm-Up Three-Way Catalyst	Injection- Direct DIP-Diesel Injection- Prechamber  EFI-Electronic Fuel Injection IC-Intercooler or aftercooler MFI-Mechanical Fuel Injection OBD-On-Board Diagnostics TC-Turbocharger
VEHICLE MODELS:  4-Runner 4WD RN61LG-MDEAMSEA RN61LV-MSEAPDEAPSEA	,	
Engine: Front <u>x</u> Mid Drive: FWD RWD	Rear 4WD Full time 4WD Pa	rt time <u>x</u>

Page : 17.11-70

Issued : 05/26/87

Passenger (	1988 Al Cars Light-Do				NTAL DATA SH	Page	e esel
_	er <u>Toyota Mo</u>						
Liter (CID)	2.4	(144.4)		Eng.	Type 4 cyl.	in-line	···
Emission Co	ontrol Sys. (Spe	cial Fe	atures)	<u></u> NIV	+ BGR + HOS	+ TWC (BFI -	OBD)
-	Vehicle Models (If Coded see attachment) (Dyno Hp: Refer to 08.13.03.00)	Туре	Test	BEC.EI.ESAC   Part No.   [Computer]   [Knock +1	CL, EFI Part No. [Computer]	!	Catalyst Part No.
21 thru 24	RN61LG-MDEA -MSEA RN61LV-MSEA	M5	3,750 3,875	89615-35030	89661-35130 22250-35020 23250-35030		18450-73040
25 thru 28	RN61LV-PDEA -PSEA	A4	3,875				

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

Note \*1 Maker: 89615-35030: MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.

89615-35040 : NIPPONDENSO CO., LTD.

Page : 17.11-71 Issued : 05/26/87