(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-278-A Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Fuel Type: Gasoline

Engine Family: STY3.41JGFEK Displacement: 3.4 Liters (206.1 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Exhaust Gas Recirculation Heated Oxygen Sensors (two) Three Way Catalytic Converter On-Board Diagnostic II

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (alternative in-use compliance standards in parentheses) for this engine family in grams per mile are:

Loaded Vehicle	Miles	Non-Methane	Carbon	Nitrogen
Weight (lbs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>
0-3750	50,000	0.25 (0.32)	3.4 (5.2)	0.4 (n/a)
	100,000	0.31 (n/a)	4.2 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle	_Miles_	Non-Methane	Carbon	Nitrogen
Weight (lbs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>
0-3750	50,000	0.16	2.2	0.2
	100,000	0.17	2.5	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 60 percent of the manufacturer's projected sales of 1995 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 30

R. B. Summerfiel

Assistant Division Chief Mobile Source Division

day of November, 1994.

E.O.	#_A	-14-	27	8-A
	Page	ť	of	ī

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA			Engine Fa	mily:	STY3,41JGFEK	
Evaporative Family: STY1047DYM00			Evap Std:	50K x Usef	ul Life with P/L	
Exh Std:	Tier-0 Tier-1	X TLEV	LEV	ULEV ZEV	; EPA Tie	r-0 EPA Tier-1_x
Veh Class	s(es): PCLI	OTI_x LDT2	·	MDV1 MDV	2 MDV3	MDV4MDV5
Single Co	ert Std for Multi	i-Class Eng H	 am:	(specify: N/	A. LDT1. MDV1	, MDV2, MDV3, MDV4)
Exh Cert	Fuel(s): Indo x	_ Ph2 Di	esel:	13 CCR 2282	or 40 CFR 86	.113-90 or -94
	M85	CNG LE	PG (Other (specif	y)	
Fuel Type	e(s): Dedicated_z	r Flex-Fuel	ים	ual-Fuel	Gasoline x	DieselM85
	CNGLNC	GLPG	Other	(specify)		
Hybrid: !	Type A B	C, APU (cycle (e.g., Otto, D	iesel, Turbin	e) <u>Otto</u>
Engine Co	onfiguration: <u>V-(</u>	<u>Displace</u>	ement:	3.4 /	Liters <u>206.1</u>	/ Cubic Inches
Engine:	Front $\underline{\mathbf{x}}$ Mid $\underline{}$	Rear	Dr.	ive: FWD	RWD x 4WD	-FT 4WD-PT
Exhaust 1	ECS (eg., EGR, MI	FI, TC, CAC):		SFI, E	GR, HO2S(2),	TWC 08D2
					per SAE J1930	
Engine	Vehicle Models	Trans. ETW	DPA	Ignition	EGR	Catalytic
Code/	(If Coded see	Type:			1	converter
(Cert.	•	A or L			i -	Part No.
std.)		-Auto				
		M-Man.				1
1	VZN150L-CRMDKAB	M5 3,250	11.4	89661-04030	25620-62050	S98
2	VZN150L-CRMDKAB	3,37	5 12.5	ļ		
3	VZN150L-CRSDKAB	L4 3,37	5 11.4	89661-04040	25620-62060	
	VZN150L-CRSDKAB		5 12.5			

Comments: Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

VEHICLE MODELS:

TOYOTA TACOMA 2WD

VZN150L-CRMDKAB

-CRSDKAB

Page : 17.11-STY3.41JGFEK-1

Issued: 10/28/94