State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-353 Relating to Certification of New Motor Vehicles

CHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Chrysler Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Fuel Type: Gasoline

Engine Family: VCR23228G1EK Displacement: 3.3 Liters (201 Cubic Inches)

3.8 Liters (232 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Exhaust Gas Recirculation Heated Oxygen Sensors (two) Three Way Catalytic Converter Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle Weight(lbs.)	Miles	Non-Methane <u>Hydrocarbons</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	Carbon Monoxide (20° F)
3751-5750	50,000	0.32	4.4	0.7	12.5
	100,000	0.40	5.5	0.97	n/a

The certification exhaust emission values for this engine family in grams per mile

Loaded Vehicle Weight(lbs.)	Miles	Non-Methane <u>Hydrocarbons</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	Carbon Monoxide (20° F)
3751-5750	50,000	0.13	1.6	0.2	7.2
	100,000	0.15	1.7	0.24	n/a

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this ______ day of July 1996.

R. B. Summerfield

Assistant Division Chief Mobile Source Division

E.O.	#	A-9-35	3
		Page 1	of1_

L997 MODEL	YEAR	AIR RESOURCE	S BOARD	SUPPLEMENTAL	DATA SHEET
PASSENGER	CARS	. LIGHT-DUTY	TRUCKS	AND MEDIUM-DU	TY VEHICLES

Manufacturer: <u>Chrysler Corporation</u> Exh Eng Fam: <u>VCR23228G1EK</u> Evap Fam: <u>VCR1098AYP1A</u> All Eng Codes in Eng Fam: CA X 49S 50S AB965
Std: CA Tier-1_X TLEV LEV ULEV ZEV; US EPA Tier-1X
Evap Std: 50K Useful Life with R/L_X_ In-Use Exh Std: Full In Use Alt In Use
Veh Class(es): PC LDT1 LDT2_X_ MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: N/A (Specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Level Gasoline X Diesel
CNGLNGLPGM85Other (specify)
Emis Test Fuel(s): IndoPh2_X_CNGLPGM85Other(specify)
Diesel: 13 CCR 2282 or 40 CFR 86.113-90 or 40 CFR 86.113-94
Service Accum: Std AMA Mod AMA Mfr ADP _X Other (Specify)
NMOG Test Procedure: N/A Std Equiv X R/L Test Proce: SHED Pt Source X
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine) Otto
Engine Configuration: $V-6$ Displacement: $3.3 / 3.8$ Liters $201 / 232$ Cubic Inches
Valves per Cylinder: 2 Rated HP: 162/162 @ 4800/4400 RPM
Engine: Front X Mid Rear Drive: FWD X RWD 4WD-FT X 4WD-PT
Exhaust ECS (eg., EGR, MFI, TC, CAC): <u>EGR. TWC. SFI. HO2S(2). OBD II</u> (use abbreviations per SAE J1930 SEP91)

Engine Code (also list (A/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type M5 A4	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Converter Part No.
CA-100 (CA)	NSKP53 NSYP53 NSYS53 NSKP52 NSYP52	A4	4500 4250	S E E	04727189AA	04287189	04682430 04682433
CA-200 (CA)	NSCP53 NSCS53 NSDH53 NSDP53		4750	T A C H M E N T	04727190AA		04682806

Date Issued:

Revisions:	_

Vehicle MFR: CHRYSLER

Engine Family: VCR23228G1EK Evaporative Fam: VCR1098AYP1A

Certificate #:

		7 - 1 - 2 - 2 - 2
Model 1D	Car Line	CALITORNIA CALITORNIA
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		W D 50
NSKP52	Caravan IF 250	
NSDP53	Case a case of figures.	u (
NSKP53		20 H
647.64		TES
2000	CIPY) SE CALTO DESCRIP	YES
NSCP53	Town & Country LX (AMD)) U
RSYP53	Town & Country 1 x 240	-) - 1 - 1
E SUUS N		100
7 (7)	TOWN & COUNTRY LX1 (AND)	YES
NO. NO. NO.	Town & Country LXi 2MD	YES
NSYP52	Town & Country SX 2MD	Y.

	Van Wagon Wagon		D=Dodge AWD P=Plymouth AWD C=Chrysler AWD	
	Body Style 12=113" wb 13=119" wb 52=113" wb 53=119" wb	Price Class HaHigh Line Perremium	Model K=Dodge H=Plymouth Y=Chrysler	Body Code NS=Minivan
Model Codes	.:		_:	- :

MGT	:
'EHICLE	
OADED Y	
STED L	
ADJU	-

		<	_	¥		TIRE D	TIRE DESCRIPTION	TION	COAST	*DYNO	TIRE	COLD CO ELECTRIC DYNO COEFFICIENTS		COAST		핊
HODET EN	ENG TRANS C GVI	s S	ďΛ	TYPE LYW		USE YR	000	YR COD MFG OPT		£	E	(LINE 1 IS 20 DEG COEFFS LINE 2 IS 50 DEG WHEN WEGNED)	7	NA CO	*DYNO PRI	PRES
: : : :		:	1 + 1			:	:			•	:	CALLES ALLES	AL 4	1		¥
NSCP53 EGH DGL 4W Y	H DGL	7 7	0	0	4750	STD 97	TM3	YZ.	16.79	10.7	35 35				:	;
						0PT 97		HZ.	16.14	10.4	35 35					
NSCS53 EG	EGH DGL 1	7	0	-		STD 87	呈	HZ.	16.14	10.4	35 35					
NSDH53 EG	H DGL	<u>+</u> ×	0	9	4750	STD 97	至	YZ.	16.79	10 7	35 35					
NSDP53 EG	, 100 H	, M	0	7		STD 97	Ħ	X 2.	16.79	10.7	35 35				-	_
						OPT 97	丟	HZ.	16.14	10.4	35 35					
NSKP52 EGH DGL FW Y D	190 H	<u></u>	0	0	4250	STD 97	盖	TZH	16.64	8.9	35 35					
						OPT 97	1	HZ.	16.13	. .	35 35					
						OPT 97	Ħ	Y2.	16.56	10.1						
MSKP53 EGH DGL FW Y O	190 H	- X #-	0	Ü	4500	\$TD 97	Ξ	HZ	17.35	8	35 35					
						OPT 97	<u>1</u>	HZ.	16.82	0.6						
					-	OPT 97	鼍	YZ,	17.27	10.1	35 35					
NSYP52 EGH DGL FW Y O	# DGF #	1 A M	0	9	4250	STD 97		TH.	16.13	9.1	35 35					
						OPT 97	Ξ	, TH	16.13	9.1	35 35					
NSYP53 EGH	H DGL F	DGL FW Y O	6	ů	1500	STD 97	Ξ	H2.	17.35	8.8	35 35					
					-	0PT 97	£	TH.	16.82	9.0	35 35					
i						OPT 97	Ē	Y2	17.27	10.1	35 35					
NSYS53 EGH DGL FW Y O	∓ DGL F	~ ≥	6	٠ 4	4500	STD 97	呈	HZ.	16.82	9.0	35 35					

Report Date: 06/07/96 Time: 08:05:57

/ 10. - 1003 - 400 /

* - For DYNO HP = 0.00 Ref to FRONTAL AREA