## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-259-60 Relating to Certification of New Motor Vehicles

## SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

<u>Fuel Type</u>: Gasoline

Engine Family: WSKXV.993TNC Displacement: 1.0 Liters (61 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Throttle Body Fuel Injection
Three Way Catalytic Converter
Warm Up Three Way Catalytic Converter

Heated Oxygen Sensors (two) Exhaust Gas Recirculation

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1998 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane <u>Organic Gas</u>	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>	
50,000	0.052	0.5	0.1	0.001	1.4	
100,000	0.058	0.6		0.001	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this \_\_\_\_\_\_day of \_une 1997.

R. B. Summerfield, Chief

Mobile Source Operations Division

E.O.# A-259-60 Page 1 of 1

## 1998 MODEL YEAR AIR RESOURCE BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Moni	footume CITIE	I MOTOR CORP	Evh	Eng Fa	m· WSK	XV.993TNC	EVAP Fam: WS	KXE00952MA
All E	nactuler. <u>SUZUN</u>	ng Fam: CA <u>X</u> 495	S 50S	AB	1965	ORVR: YE	s NO X	
		er 1TLEV <u>X</u> I						
EXT S	Sta: Her U He	SF1ILEV_X_I	-Ev	A4D\/1	_ <u>~</u>		MDV4 MD	0V5
Veh Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5								
Single Cert Std for Multi-Class Eng Fam: (specify: N/A, LDT1, LDT2,MDV1,MDV2,MDV3,MDV4,MDV5)  Fuel Type (s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel								
Fuel '	Type (s): Dedicat	edX Flex-Fu	el	Dual-Fu	iel	Bi-Fuel Gas	Soline X Dies	eı
	CNG_	LNG	LPG	<u> </u>	Othe	r (specify)		
Emis	s Test Fuel (s):Ind	to CBG _X	_CNG_	LPG	M	85 Other (s	specify)	
	Die	esel: 13CCR 2282		40CFR 8	6.113-90	40CF	R 86.113-94	
<b>EVAF</b>	Emission Test F	Procedure: Californi	ia <i>X</i> _	*	_ Fed	eral <u>X</u>		
Servi	ce Accum: St	d AMA X N	lod AMA		Mfr ADF	Other (sp	ecify)	
NMO	G Test Procedure	: N/A S	td X	E	quiv	_ R/L Test Proc:	SHED Pt·S	ource X
Hybri	d: Type A	BC,	APU C	ycle (e.g	g. Otto, Di	esel, Turbine)		
Engine configuration: L3 (in line) Displacement: 1.0 Liter or 61 cubic inches								
Valves per Cylinder: 2 Rated HP 55 @ 5,700 RPM								
Engine: Front X Mid Rear Drive: FWD X RWD 4WD-FT 4WD-P1								
Exhaust ECS (eg., EGR, MFI, TC, CAC): TBI / HO25 WU-TWC / TWC / EGR								
(per SAE J1930 SEP91)								
			<del>_</del> _					
•	Engine Code	Vehicle Models	Trans	ETW	(DPA)	Ignition		
<b>6</b> .	(also list	(re: p.21.00)	type		or	(ECM/PCM)	Part No.	Converter Part
	CA/49ST/50ST)				RLHP_	Part No.		No.
•					ļ			14150-51G00
	CVTBM		M5	2125	7.3	33920-50GK0	18111-86010	14130-31000
	(CA,NY,MA & CT)	(Hatchback)						14150-50G00

Date Issued: 17MAR97

Revised: