State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-48-43 Relating to Certification of New Motor Vehicles

ROLLS-ROYCE & BENTLEY MOTOR CARS LIMITED

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Rolls-Royce & Bentley Motor Cars Limited exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: YRRXV05.4NAT <u>Displacement</u>: 5.4 Liters (328 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20⁰F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20⁰F)</u>
50,000	0.15	1.8	0.3	4.4
100,000	0.19	2.6	0.3	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988-2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235.)

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965.)

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988-2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995-2005 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978-2000 Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998-2000 Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 9th day of December 1999.

AR. B. Summerfield, Chief

Reghard Summerty


Mobile Source Operations Division



54 12 RA/50ST

Rolls-Royce Silver Seraph

Rolls-Royce Park Ward





17 - 13

E.O.	# <u></u>	-48-	43
		Pa	ge

TWC

PJ 20469 PJ 20470

N/A

PB 20359

2000 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Rolls-R	oyce & Bentley Mot	or Cars Ltd	Exh B	ing Fam :	YRRXV05.4NA	Evap	Fam: YRRXR0	200E96
All Engine Codes in Eng	ine Family: CA	498	50S,	X	AB965	ORVR:	YES_X_N)
Exh Std:CA Tier-1X	TLEV LE	V UL8	EV	SULEV	US EPA Tier	·1X	_	
Veh Class(es):PCX	LDT1 N	IDV1	_ MDV2_	N	1DV3N	1DV4	MDV5	
Single Cert Std for Multi	-Class Eng Fam: _N	V/A(spe	cify: N/A,	LDT1, MD	V1, MDV2, MDV	3, MDV4)		
Fuel Type(s): Dedicate	d X Flex-Fu	el	_Dual-Fue	I	_Bi-Fuel	Gasoline	X Diesel	
CNG	LNGLP	G	M85		Other (specify)			
Exh Emiss Test Fuel(s):	IndoX CBG_	CNG	LI	PG	M85 Oti	ter (specify)		
Diesel: 13 CCR 2282								
Evaporative Emission T	est Procedure: Califor	nia		Fi	ederal	X		••
Service Accum: Std AM	A Mod AMA _		Mfr ADI	<u> </u>	Other (spe	cify)A	MDF	
NMOG Test Procedure:	N/A N/A S	td	Equiv	R	/L Test Proc: S	HED	_ Pt Source	<u> </u>
Hubrid Type A B C APU Cycle (e.g., Otto, Diesel, Turbine)								
Engine Configuration: V-12 Displacement: 5.4 Liters 328.7/ Cubic Inches								
Valves per Cylinder: 2 Rated HP: 322 @ 5000 RPM								
Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT								
Exhaust ECS (e.g., MFI, EGR, TC, CAC): <u>2TWC, 2HO2S(2), SFI, AIR</u> (use abbreviations per SAE J1930 JUN93)								
						ECB	Catalytic	
	Vehicle Models		ETW	DPA	Ignition (ECM/PCM)	1	_	
(Also list	(if coded see	(M5,A4 etc)	or Test	or RLHP	· ·	Part		
CA/49ST/50ST)	attachment	erc)	1831	i Vani II		No.		ı

5500

L5

11.84

19.1

•			
Issue Date	31.08.99	Revision Date	YRR54N17.lwp