



BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0137 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			CATEGORY vehicle: T	EMISSION STANDA (LEV=low emis LEV= transitional LEV EV; SULEV=super UL	sion :	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200	2	2BMXV01.6R50				PC			LEV		100K / 100K	Gasoline			
No.		VAPORATIVE AMILY (EVAF)				SPECIAL FEAT EMISSION CONTROL		S (ECS)	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC					
1	2BM	2BMXR0093R50			1	WU-TWC, TV	WC, HO2S	(2), SFI, OB	AF	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust					
2		*			2	WU-TWC, TWC, HO2S(2), SFI, SC, CAC, OBD (F)					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*			3		*		-∏тв	TBI= throttle body injection TC/SC=turbo /super charges					
4		*			4		*		dia	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
EVAI No.	. ,	CS No.	ENGINE SIZE (L)			VEHICLE VEHICLES SUBJECT TO SFTP A MAKES & MODELS STANDARDS ARE UNDERLINED C					BBREVIATIONS: /B/ = Buick /C/ = Chevrolet /CD/ = adillac /G/ = GMC /O/ = Oldsmobile /P/ = Pontlac				
1		1	1.6			BMW: Mini Cooper									
1_	2 1.6				BMW: Mini Cooper S										
*	* *		* *			*									
*	* *					*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]			RAF=0.94 RAF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	CERT STD		NMOG	NMHC	NMHC STD	mg=millig	resuan Ki	– քնչայի–ւտ	nning loss 000 miles	URV	rK [g/ga⊪o⊩	n dispensed] ahrenheit	=on-board ı	refueling vap plemental fe	or recovery	g≂gram	
0.06	1	0.068	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]	NC	x [g/mi]			[mg/mi]		g/mi] STD	Hwy NO		
		@ 50K	[9/111]	[g/m]		CERT	STD	CERT	ST	D	CERT	STD	CERT		CERT		
	18 小原设		0.053	*	0.075	0.7	3.4	0.1	0.2	2	1	15	*	*	0.02	0.3	
			0.057	*	0.090	0.8	4.2	0.1	0.3	3	1	18	*	*	0.02	0.4	
	@ 50	°F & 4K	0.140	•	0.150	1.8	3.4	0.02	0.2	2	1	30	*	*	*		
CO [@ 20	°F&	LEV) or 50K (Tier 1, TLEV)						g/mi] NMHC+N osite) [g/mi] [US					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	50K		= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	ST	TD CE	RT ST			CERT	STD	
CERT	1.9	183	1.5	SFTP 1	*	*	*	*	*	•		* *	*	*	*	*	
STD	10.0		19 18 18	SFTP 2	*	*	*	*	*	*		• •	+	+	*	+	
@ UL	E	VAPOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2 EVA					EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORVE		2-D	RL	ORVR	
CERT	1.7	0.8	0.01	0.13	*	*	*	*	*	*		*		+	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*		+		*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of February 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch