## BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0139 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

EVA No.		ENGINI SIZE (L 2.5			IICLES SUB. NDARDS AF						
4	*	£6			en James	OBD (F) / OBD (P) = on-board diagnostics; full / par compliance (prefix) 2 = parallel (2) (suffix) = se					
3	*		3	*		MFI = multiport fuel injection SFI = sequential MFI TC/SC = turbo/super charger CAC = charge air cooler					
2	2BMXR01	2BMXR0136E46		*		HO2S = heated O2S					
1	2BMXR01	R0160E39		2TWC, 2HO2S(2),		D (F)	catalytic converter O2S = oxygen sensor				
No.		APORATIVE MILY (EVAP)		SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation				
200	2 2BMX	(V03.0LEF	۲	Passenger Car	Low E	Emission Vehicle (LEV)	Gasoline				
YEA		TEST GROUP		VEHICLE TYPE		AUST EMISSION PARD CATEGORY	FUEL TYPE				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]		NMOG [g/mi] @RAF = 0.94		CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor													
CERT	RT STD		CH4 RAF = *			CO [g/mi]			NOx [g	/mi]	HCHO [mg/mi]		PM [g/mi]			Hwy NOx [g/mi]	
0.061	0.068		CERT		STD	CERT STD		C	CERT STD		CERT	CERT STD			TD	CERT	STD
	@	50K	0	0.016 0.075		0.5	3.4	(	0.1	0.2	0.2	15	*	* *		0.002	0.3
K = 1000 miles	@	100K		.018	0.090	0.6	4.2	0.	0.1	0.3	0.2	18	*	*	*	0.002	0.4
	@ 50°	F, 4K	0	.036	0.150	0.4	3.4	0	0.05	0.2	0.2	30	*		*	*	*
	[g/mi] °F, 50K			g = gr ma =	am milligram	NMHC+NOx [g/mi] (composite)		i] NN	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMH	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	ST	STD		mi = mile		CERT	STD	CI	ERT	STD	CERT	STD	CER	CERT S		CERT	STD
2.1	10.0				@ 4K	*	*	0.08		0.14	0.7	8.0	0.16	0.16 0.20		0.4	2.7
F = degree	Fahrenheit		@ 100K		*	*		*	*	*	*	•	*		*	*	
@	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
100K	3-D	2-0	7	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.7	1.8		0.03	0.04	1.1	1.9	0.03	0.10	*	*	*	*	*	*	*	*
STD	2.0	2.5	;	0.05	0.20	2.0	2.5	0.05	0.20	*	*	*	*	*	*	+	*
2-D, 3-D [g/	/test] = 2-	day, 3-	day o	diurnal a	nd hot-soak		RL [g/m	] = runni	ng loss		ORVR [g/ga	illon of fue	l dispense	d] = on-b	oard refu	leling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 20th day of September 2001

Summerfield Chief

Mobile Source Operations Division