DAIMLERCHRYSLER AG

EXECUTIVE ORDER A-003-0228 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP		VEHICLE TYPE		UST EMISSION ARD CATEGORY	FUEL TYPE							
2002		(V05.5LTF	₹	Passenger Car	Low E	Emission Vehicle (LEV)	Gasoline							
No.	EVAPORATIVE FAMILY (EVAP)		No.	SPECIAL FEATURE EMISSION CONTROL SYST	S & TEMS (ECS)	* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation							
1	2MBXR01	55LNZ	1	SFI, 2WUTWC, 2TWC, 2		GR, OBD (F)	catalytic converter O2S = oxygen sensor							
2	*		2		*		HO2S = heated O2S EGR = exhaust gas recirculation AIR = secondary air injection PAIR = pulsed AIR							
3	*	3			*	MFI = multiport fuel injection SFI = sequential MFI TC/SC = turbo/super charger CAC = charge air cooler								
4	*		4		*	OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = series								
EVAI No.	P ECS No.					IECT TO SFTP	ABBREVIATIONS:							
1	1	1 5.5		MERCEDES-BENZ CLK55 AMG, CLK55 AMG CABRIOLET										
*	*	* *		•										
*	*			*										
*	•	* *				*								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

	G FLEE1 AGE [g/m			NMOG @RAF	[g/mi] = 0.94	CH4 = m NOx = 0	ethane i cides of nitr	MOG =	non-CH- HCHO	4 organic = formald			H4 hydrod			carbon mo	
CERT	CERT STD		CH4 RAF = *			CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		Р	PM [g/mi]		Hwy NOx [g/mi]	
0.061	.061 0.068		CERT		STD	CERT STD		CE	CERT STD		CERT	CERT STD		T STD		CERT	STD
	@	@ 50K		.039	0.075	0.4	3.4	3.4 0.03 0.2		0.2	0.3	15	*		•	0.02	0.3
K = 1000 miles	@	@ 100K		.046	0.090	0.5	4.2	0.0	04	0.3	0.3	18	*		•	0.02	0.4
	@ 50°	0°F, 4K 0.		.042	0.150	0.3	3.4	0.03	03	0.2	4	30	*	1	•	*	*
	[g/mi] 9°F, 50K		g = gram mg = milligram		NMHC+NOx [g/mi] (composite)		NMI	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC	NMHC+NOx [g/mi]		CO [g/mi] [SC03]		
CERT	CERT STD			mi = mile		CERT	STD	CE	RT	STD	CERT STD	CERT	r s	STD	CERT	STD	
1.3	10.0		5	@ 4K		*	*	*		*	*		*	-	*	*	*
F = degree	Fahrenh	ahrenheit		@ 100K		*	*	•	•		*	*	*	* *		*	*
@	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 E				ΕV	VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
100K	3-D	2-D)	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	~ 2-D	RL	ORVR
CERT	1.1	1.0		0.02	0.10	*	*	*	*	*	*	*	*	*	*	*	+
STD	2.0	2.5		0.05	0.20	*	*	*	* *		+	*	*	*	*	*	+
2-D, 3-D [g/	/test] = 2-	day, 3-c	lay d	liurnal a	nd hot-soak	· · · · · · · · · · · · · · · · · · ·	RL [g/mi] :	running	g loss		ORVR [g/ga	lion of fue	l dispense	d] = on-b	oard ref	ueling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2001.

R. B. Summerfield, Chief Mobile Source Operations Division