

ř

## DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0524-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

T IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MOD         | NR . | TEST GROUP                                    |      |   | VEHICLE TYPE PC=passenger car; LDT=light-duty MDV=medium-duty vehicle; LVW=l vehicle weight; ALVW=adjusted L | truck; CA  | ATEGORY vehicle; TLI  | MISSION STANDAI<br>(LEV=low emiss<br>EV= transitional LEV;<br>V; SULEV=super ULE                          | on EVAPORATIVE USEFUL LIFE       | FUEL TYPE<br>(CNG/LNG=compressed/<br>liquefied natural gas;<br>LPG=liquefied petroleum gas) |  |  |  |  |
|-------------|------|---|------|---|--|--|---|---|----------------------------------|---|--|--|--|--|
| 200         |      | 2CRXV02.4VD0                                  |      |   | PC   |  |   | LEV   | 100K / 100K                      | Gasoline  |  |  |  |  |
| No.         | FAM  | APORATIVE<br>MILY (EVAF)                      |      | No. SPECIAL FEATURES EMISSION CONTROL SYSTE |  |  | CS)   | * = not applicable  | OC/TWC=oxidizing/3-way           | cat. ADSTWC=adsorbing TWC   |  |  |  |  |
| 1           | 2CR) | (R010   | 1GBA | 1   | TWC, HO2   | S(2), EGR, S   | FI, OBD (F  | ))  | APS/HAPS=air-fuel ratio s        | IO2S=oxygen sensor/heated O2S<br>sensor/heated AFS EGR=exhaust                              |  |  |  |  |
| 2           |      | *   |      |   |  | *  | <del></del>   | gas recirculation AIR/PA  | R≂secondary air injection/pulsed |   |  |  |  |  |
| 3           |      | *   |      |   |  | *  | TBI= throttle body injection, TC/SC=turbo (super shares   |   |                                  |   |  |  |  |  |
| 4           |      | •   |      |   |  | *  |   | CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series |                                  |   |  |  |  |  |
| EVAF<br>No. |      | CS ENGINE VEHICLE No. SIZE (L) MAKES & MODELS |      | VEHICLE<br>STANDAR                          | S SUBJEC   | T TO SFTP A  | BBREVIATIONS: /B/ = Buick /C/ = Chevrolet /CD/ = adillac /G/ = GMC /O/ = Oldsmobile /P/ = Pontiac |   |                                  |   |  |  |  |  |
| 1           | İ    | 1   | 2.4  |   | Chrysler PT Cruiser (Engine Code NA-202 Automatic)   |  |   |   |                                  |   |  |  |  |  |
| *           |      | *   | *    | $\neg$                                      |  | Chrysler PT Cruiser, Chrysler Sebring, Chrysler Sebring Convertible, Dodge Stratus |   |   |                                  |   |  |  |  |  |
| *           |      | *   | *    |   |  |  |   |   |                                  |   |  |  |  |  |
| *           | * *  |   | *    |   |  |  |   | *   |                                  |   |  |  |  |  |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| NN<br>AVE | NMOG FLEET      |        | NMOG @ RAF=0.94<br>CH4 RAF = * |             | NMOG or                                     |                          |           |        |                         |      |           | H4 hydroca<br>RAF=reactiv |             |                                   |             |                |  |
|-----------|-----------------|--------|--------------------------------|-------------|---|--------------------------|-----------|--------|-------------------------|------|-----------|---------------------------|-------------|-----------------------------------|-------------|----------------|--|
| CEF       |                 |        | NMOG                           | RT CERT     |   | diurnal+ho<br>mg=milligr |           | . [8,] | nning lòss<br>000 miles | UNVN | [g/gallor | ı aispensedi              | =on•poard r | 'efuelina var                     | OF FREAVARY | O=Gram         |  |
| 0.06      |                 |        | CERT<br>[g/mi]                 |             |   |                          | CO [g/mi] |        | x [g/mi]                | НСНО |           | [mg/mi]                   | PM [        | SFTP=supplemental fe<br>PM [g/mi] |             | x [g/mi]       |  |
|           | 200             |        |                                | 10:34-1     | <del></del>                                 | CERT                     | 310       | CERT   | STI                     | ) Ç  | CERT      | STD                       | CERT        | STD                               | CERT        | STD            |  |
| 40元       | 0.7             | @ 50K  | 0.042                          | *           | 0.075                                       | 1.7                      | 3.4       | 0.1    | 0.2                     | 2    | 1         | 15                        | *           | *                                 | 0.04        | 0.3            |  |
|           | 1.74            | @ UL   | 0.042                          | *           | 0.090                                       | 1.7                      | 4.2       | 0.1    | 0.3                     | 3    | 1         | 18                        | *           | *                                 | 0.04        | 0.4            |  |
|           | @ 50°           | F & 4K | *                              |             | •   | *                        | *         | *      | *                       |      | *         | •                         | *           | *                                 | *           | *              |  |
| @ 20      | [g/mi]<br>)°F & | LI     | = @ 4K (SUL<br>EV) or 50K (T   | er 1, TLEV) | NMHC+NOx [g/mi] CO [g<br>(composite) (compo |                          |           |        | NMHC+NOx C              |      |           | CO [g/mi]<br>[US061       |             | HC+NOx                            |             | [g/mi]<br>203] |  |
|           | K               | SFTP 2 | = @ UL (Tier                   | 1, TLEV)    | CERT  | STD                      | CERT      | STD    | CERT                    | STD  | CE        |                           |             |                                   | CERT        | STD            |  |
| CERT      | 4.0             | E. all |                                | SFTP 1      | •   | *                        | *         | *      | 0.03                    | 0.14 | 3.        | 9 8.0                     | 0.03        | 0.20                              | 1.1         | 2.7            |  |
| STD       | 10.0            | 100    | 1425                           | SFTP 2      | *   | *                        | *         | *      | *                       |      | -         |                           | *           | *                                 | +           | *              |  |
| @ UL      |                 | VAPOR  | ATIVE FAN                      | ILY 1       | EVAPORATIVE FAMILY 2                        |                          |           |        | EVAPORATIVE FAMILY 3    |      |           |                           | F           | EVAPORATIVE FAMILY 4              |             |                |  |
|           | 3-D             | 2-0    | ) RL                           | ORVR        | 3-D   | 2-D                      | RL        | ORVR   | 3-D                     | 2-D  | RL        |                           |             |                                   |             |                |  |
| CERT      | 0.9             | 1.0    | 0.001                          | 0.03        | *   | *                        | *         | *      | -                       | 2-0  | - KL      |                           | -           | 2-D                               | RL          | ORVR           |  |
| STD       | 2.0             | 2.5    |                                |             |   |                          |           |        |                         |      |           | *                         | *           |                                   | *           |                |  |
| 0.0       | 2.0             | 2.3    | 0.05                           | 0.20        |   |                          |           | *      | *                       | *    | *         | *                         | *           | *                                 | *           | *              |  |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-009-0524 dated June 21, 2001.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of May 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch