

NISSAN MOTOR CO., LTD

ORDER A-015-0364 EXECUTIVE New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP		>	VEHICLE TYPE		UST EMISSION ARD CATEGORY	FUEL TYPE					
200		2NSXV01.8D1A		Α	Passenger Car	Ultra Lov	v Emission Vehicle (ULEV)	Gasoline					
	EVAP	ORA	TIVE		SPECIAL FEAT	URES &	* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation					
No.	FAMILY (EVAP)			No.	EMISSION CONTROL	SYSTEMS (ECS)		catalytic converter C2S = oxygen sensor HO2S = heated O2S					
1	2NSXR0085RCA			1	2TWC, TWC, 2	HO2S(2), EGR, SFI,	OBD (F)						
2		•				•							
3						*							
4		•	-	4		*		compliance (prefix) 2 = parallel (2) (suffix) = ser					
EVA No.		CS I	ENGIN SIZE (1		VEHICLE MAKES & MODELS	VEHICLES SUB-	RE <u>UNDERLINED</u>						
1	<del></del>	1	1.8			NISSAN S	I SENTRA XE						
•		•	•	1			•						
		-					•						
-		<del>                                     </del>		<del></del>	-		•						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/ml]		NMOG [g/mi] @RAF = 0.94 CH4 RAF = *		CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor													
CERT STD				CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]			Hwy NOx [g/mi]				
		0.068			STD	CERT STD		CERT		STD	CERT	STD	CERT	CERT ST		CERT	STD
0.061			CERT				1.7	0.0	2	0.2	0.5	8	•	•		0.03	0.3
K = 1000 miles	@ 50K		0.028		0.040	-						1 11				0.04	0.4
	@ 100K		0.031		0.055	0.6 2.1		0.0	4	0.3	1		<del> </del>	*			
	@ 50°F, 4K		0,076		0.080	0.9	1.7	0.1		0.2	1	18					
CO [g/mi] g = gram					NMHC+1	NMHC+NOx [g/mi]		CO [g/mi] [US06]		NMHC+NOx [g/ml] [SC03]		mlj	CO [g/mi] [SC03]				
@ 20°F, 50K					nilligram	CERT	STD	CEF	27	STD	CERT	STD	CERT	S1	TD	CERT	STD
CERT	RT STD			mi = mile		CERT	- 315	<del></del>	- +		1.2	8.0	0.04	0.3	20	0.2	2.7
2.3 10.0			@ 4K		*	- 0.09		9	0.14		1.5		<del> :</del>			*	
F = degree	it	ļΓ	@ 100K		* * *		*			•	<u></u>						
EVAPORATIVE FAMILY 1						EVAPORATIVE FAMILY 2				VAPORATIVE FAMILY 3			EVAPORATIVE FA			MLY 4	
@ 100K						<del>                                     </del>		RL ORVR		3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE
	3-D	2-0	)	RL.	ORVR	3-D	2-D		UNVI		+	+		•	•	<del>                                     </del>	
CERT	0.8	0.8	3	0.001	0.02	•	*	•							<del></del>	+	-
STD	2.0	2.0 2.5		0.05	0.20	•	•	* *		•	*						
	/test) = 2-d	lay, 3-	day di	urnal a	nd hot-soa	k recovery	RL [	g/mi] = r	unning	loss	ORVR [g/g	allon of fue	dispense	d] = on-be	pard ref	ueling vap	or recover

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order

Executed at El Monte, California on this \_

day of July 2001.

R. B. Summerfield, Chief Mobile Source Operations Division