

NEW UNITED MOTOR MANUFACTURING, INC.

EXECUTIVE ORDER A-266-0024 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE YEAR		GROUP		VEHICLE TYPE		UST EMISSION ARD CATEGORY	FUEL TYPE Gasoline						
2002	2NTX	V01.8FFA		Passenger Car	Low E	imission Vehicle (LEV)							
No.	EVAPOR		No.	SPECIAL FEATURE	ES &	* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation						
1	2NTXR01		1	TWC, HO2	S(2), SFI, OBD (P	catalytic converter O2S = oxygen sensor HO2S = heated O2S EGR = exhaust gas recirculation							
2	•	•			•	AIR = secondary air injection PAIR = pulsed AIR MFI = multiport fuel injection SFI = sequential MFI							
3	•				•		TC/SC = turbo/super charger CAC = charge air cooler OBD (F) / OBD (P) = on-board diagnostics; full / partial						
4	•				*	compliance (prefix) 2 = parallel (2) (suffix) = seri							
EVA	ECS No.	ENGIN SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SUB. STANDARDS AF	JECT TO SETP RE UNDERLINED							
1	1	1.8				<u> </u>							
•	•			•									
*	•			*									
						*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET NMOG AVERAGE [g/mi] @RAF			[g/mi] = 0.94	CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment facto												
CERT STD		7	CH4 RAF = *		CO [g/mi]		NOx [g/mi]		ni]	HCHO [mg/mi]		PM [g/mi]			Hwy NOx [g/mi]	
0.061	61 0.068		ERT	STD	CERT	STD	CERT	ERT	STD	CERT	STD	CERT	STD	D.	CERT	STD
	@ 50K	0.	.053	053 0.075		3.4	0.1		0.2	0.5	15	*	•	•	0.1	0.3
K = 1000 miles	@ 100K	0.	.064	0.090	1.3	4.2	0.2		0.3	1	18	•	•	'	0.1	0.4
IIIIsa	@ 50°F, 4K		•	•											•	
					NMHC+NOx [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		/mi]	CO [g/mi] [SC03]		
CERT					CERT	STD	CERT	Г	STD	CERT	STD	CERT	S1	D	CERT	STD
2.1				@ 4K		•	0.11	0.11 0.14	0.14	2.7	8.0	0.12	0,:	20	0.4	2.7
F ≈ degree	Fahrenheit	ahrenheit - 💰		@ 100K		+	*		•	•	*	•	•		•	A
@	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 E			ΕΛ	VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
100K	3-D 2-	D	RL	ORVR	3-D	2-D	RL (ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.4 0.	4	0,02	0.10	+	•	•	•	+	•	•	•	•	•	•	*
STD	2.0 2.	5	0.05	0.20	•	•	*	•		•	*	*	+	•	•	
2-D, 3-D [g/	test] = 2-day, 3	-day o	diurnal a	ind hot-soal	[RL (g/mi) :	running	loss	"	ORVR [g/g:	illon of fue	l dispense	d] = on-bo	ard refi	ieling vapo	recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 30th day of April 2001.

R. B. Summerfield, Chief Mobile Source Operations Division