

EXECUTIVE ORDER A-030-0146 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			MI	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded rehicle weight; ALVW=adjusted LVW)	CATEGOR' vehicle; T	EMISSION STANDA Y (LEV=low emiss LEV= transitional LEV; LEV; SULEV=super ULE	ion EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	3	3ADXV01.8342				PC		ULEV	100K / 100K	Gasoline (Indolene)				
No.		EVAPORATIVE FAMILY (EVAF)			No.	SPECIAL FEATURES EMISSION CONTROL SYSTE		OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation ARI/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
1	3AD)	3ADXR0140232			1	TWC, HO2S(2), SFI, A	IR, TC, CAC,							
2	3ADXR0140262				2	*								
3	*				3	*		TIT BI= throttle body injection	on TC/SC=turbo /super charger					
4		*			4			CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAI No.		CS No.	ENGIN SIZE (I					ECT TO SFTP E UNDERLINED	ABBREVIATIONS: *					
1	1		1.8			VOLKSWAGEN: PASSAT SEDAN / PASSAT WAGON								
2		1 1.8				AUDI: A4 SEDAN, A4 QUATTRO SEDAN, A4 QUATTRO AVANT, CABRIOLET								
*		*	*					*						
*		*	*					*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF= * CH4 RAF = *		NMOG or	CH4=metha	ane NMOG	=non-CH4	organic g PM=par	as NMHC	=non-C	H4 hydroca	rbon CO=c	arbon mono	xide NOx=	oxides of	
	CERT STD		NMOG NMHC		NMHC STD	diurnal+ho mg=milligr	t-soak KL	[g/mi]=run	ning loss	ORVR	g/gallon	dispensed]	<b>=on</b> -board r	efueling vap	or recovery	g≠gram	
0.05	0.056 0.062		CERT [g/mi]	CERT [g/mi]	[g/mi]	CERT CO [	g/mi] STD	CERT	x [ <b>g/</b> mi]		ERT	mg/mi]	PM [			x [g/mi]	
		@ 50K	0.024	*	0.040	1.0	1.7	0.04	0.2		0.2	STD 8	CERT *	STD	0.01	STD 0.3	
		@ UL	0.029	*	0.055	1.1	2.1	0.04	0.3	3	0.2	11	*	•	0.01	0.4	
Maria Company	@ 50°F	= & 4K	0.049	*	0.080	1.1	1.7	0.02	0.2	2 (	0.2	16	*	*	*	*	
CO [ @ 20	°F&	LE	= @ 4K (SULI V) or 50K (Tid	er 1, TLEV)	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)			C+NOx [US06]		O [g/mi] [US06]		MHC+NOx ni] [SC03]		[g/mi] 203]	
50	K	SFTP 2 :	@ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	r STD	CERT	STD	
CERT	1.2		到是求	SFTP 1	*	•	*	•	0.10	0.14	6.	5 8.0	0.12	0.20	1.3	2.7	
STD	10.0		清美表表	SFTP 2	*			*	*		*	*	*	*	*	*	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
_	3-D	2-D	RL	ORVR	3-D	2- <b>D</b>	RL (	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	1.5	1.6	0.00	0.01	1.1	1.2	0.003	0.08	*	*	*	*	*	n	*	*	
STD	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Aller Lyons, Chief

774

New Vehicle / Engine Programs Branch

day of May 2002.