DAIMLERCHRYSLER AG

EXECUTIVE ORDER A-003-0251
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP		M	VEHICLE TYPE =passenger car; LDT=light-duty truck;)V=medium-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	CATEGOR'	EMISSION STAND Y (LEV=low emi LEV= transitional LE LEV; SULEV=super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	2003 3MBXT05.51B			ВІ	1	MDV: 5,751-8,500 pounds ALVW		LEV		120K / 120K Gasoline					
No.			ORATIVE _Y (EVAF)		No.	SPECIAL FEATURES EMISSION CONTROL SYSTE	& MS (ECS)	* = not applicable	000	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	3MB	MBXE0155NNZ			1	SFI, 2WUTWC, 2TWC, 2H	02S(2), AIR, E	₿AF	S/HAFS≖air-fuel ratio s	ensor/heated AFS_EGR=exhaust					
2		*			2		*	ga	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		•			3		*	TB	TBI= throttle body injection TC/SCsturbo /super charger CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
4		•			4		*	dia							
EVAI No.		ECS ENGINE No. SIZE (L)				VEHICLE VE MAKES & MODELS STA	HICLES SUBJ	ABB	ABBREVIATIONS: *						
1		1	5.0			MERCEDES-BENZ G500									
1		1	5.5				MEI	RCEDES-BENZ G5	5 AMG	AMG					
*.		*					•								
*		*													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

N. S. S. S.	AA #1		10164-5		·			-								
NMOG FLEET AVERAGE [g/mi]			NMOG @ CH4 R	RAF=0.94 AF = *	NMOG or	Introden	HUHUSTO	rmaidenvo	e PM≖da	rticula	ita mattar	RAFEreacti	vity adinator	carbon mond ent factor	2/2 D InHack	5-2/2 day
CER	RT STD		NMOG	NMHC	NMHC STD	mg=millig	ram mi	rrile K≕ ≖mile K≕	nning loss 1000 miles	ORY	VR [g/galloi ≔degrees i	n dispensed Fahrenheit	on-board=[] SFTP≖sun	refueling var plemental fe	or recovery derail test or	g=gram ocedure
			CERT [g/mi]	CERT [g/ml]	[g/mi]	CO [g/mi]			Ox [g/ml]			mg/mi)		g/mi]	Hwy NO	
			[8,]	fallini		CERT	STD	CER	T ST	D D	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.028	*	0.195	0.3	5.0	0.1	0.	6	0.4	22		*	0.01	1.2
			0.032	*	0.280	0.3	7.3	0.1	0.	9	1	32		*	0.02	1.8
	@ 50°	F & 4K	0.070	•	0.390	0.5	5.0	0.1	0.	6	1	44		*		*
CO [@ 20	g/mi] °F &	i LE	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			Ox [g/mi] osite)			NMHC+NO [g/mi] [US			CO [g/mi] [US06]		HC+NOx ni] [SC03]		[g/ml] 0031
50	K	SFTP 2 = @ UL (Tier 1, TLEV)			CERT	STD	CERT	STD	CERT	S	TD CE	RT ST			CERT	STD
CERT	1.1	1.0		SFTP 1	*	*	*	•	*		•	* -	*	*	*	•
STD	12.5			SFTP 2	*	*	*	*		T -	*	* .	•	•	•	•
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR					POR	ATIVE F	AMILY 3	EVAPORATIVE FAMILY 4			
	3-D	2-0) RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-	D R	L ORV		2-D	RL	ORVR
CERT	1.2	0.9	0.02	*	*	*	•	*	. *	*		*	•	*	•	•
STD	2.0	2.5	0.05	•		*	*	•	*	*	- 	•	1	•	+	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2/37 day of August 2002.

Allen Lyons, Chief

Mobile Source Operations Division