DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0598-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TEST GROUP			P	M	VEHICLE TYPE C=passenger car; LDT=light-duty t DV=medium-duty vehicle; LVW=loa vehicle weight; ALVW=adjusted LV	ruck; CATE aded veh	EXHAUST EMISSION STANDARI CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200	2003 3CRXT05.95B					MDV: 3,751-5,750 pounds ALV	w ·	TIER 1			120K / 120K	Gasoline (Indolene)			
No.		VAPORATIVE AMILY (EVAF)		1	No.	SPECIAL FEATU EMISSION CONTROL S	IRES & YSTEMS (ECS	& *= not applicable		OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S				
1	3CRXE0174GDL			ä	1	HO2S(2), TWC, SFI, OBD (F)					S/HAFS=air-fuel ratio s	ensor/heated AFS EGR=exhaust			
2	3CRXE0174GEL				2	*					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*			3	*					TBI= throttle body injection TC/SC=turbo /super charger				
4		*			4	*					CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVAI No.	ECS ENGINE No. SIZE (L)				VEHICLE MAKES & MODELS	VEHICLES STANDARD			ABBI	ABBREVIATIONS:					
1		1	5.9				D	WD/4	ND/4WD						
1		1	5.7				D	WD/4	WD						
2	1 5.7					Dodge Ram 1500 Pickup 2WD									
*		*	*		[•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *				NMOG or	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1											
CER	CERT STD		NMOG	NMHC	NMHC STD	mg=millig	or-soak Ki	_ [g/mi]=ru	nning loss 1000 miles	SURVR	₹ [g/gallon	(dispensed	on-board resupp	efueling vap	or recovery	g=gram	
			CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		Ox [g/mi]		нсно [mg/mi]	PM [c		Hwy NO		
44000000			[g/iiii]	[ā,m]		CERT	STD	CER	T ST	D (CERT	STD	CERT	STD	CERT	STD	
		@ 50K	*	0.24	0.32	4.0	4.4	0.7	0.	7	*	*	*	*	0.6	1.4	
			*	0.24	0.46	4.0	6.4	0.72	0.9	8	*	*	*	*	0.63	1.96	
	@ 50	°F & 4K	*	*	•	*	*	*	*		*	•	•	*	*	*	
@ 20	@ 20°F & LE			ULEV, ULEV, (Tier 1, TLEV)	NMHC+NO (comp			CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	50K		SFTP 2 = @ UL (Tie		CERT	STD	CERT	STD	CERT	STE	CE	RT ST	CERT	STD	CERT	STD	
CERT	10.3			SFTP 1	*	*	*	*	*	*	•		*		*	*	
STD	12.5			SFTP 2	•	*	*	*	*	*	-		*	*	1	•	
@ UL			ATIVE FA	MILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E'	EVAPORATIVE FAMILY 4			
	3-D			ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE	₹ 3-D	2-D	RL	ORVR	
CERT	1.1	0.	7 0.00)1 *	1.1	0.7	0.001	٠	*	*	*	*	*	*	*	*	
STD	2.0	2.	5 0.0	5 *	2.5	3.0	0.05	*	*	*	*		*		*	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-009-0598 dated July 12, 2002.

Executed at El Monte, California on this ___27^{rd_} day of November 2002.

Allen Lyons, Chief

Mobile Source Operations Division