GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1096 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEA	MODEL YEAR TEST GROUP			_	M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2003 3GMXT04.3184				4	ا	MDV: 3,751-5,750 pounds ALVW		LEV		120K / 120K	Gasoline (Indolene)				
No.		EVAPORATIVE FAMILY (EVAF)			о.	SPECIAL FEATURES EMISSION CONTROL SYSTEM		* = not applicable	OC	C/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC				
1	3GM)	3GMXE0111911			١ إ	SFI, TWC, 2HO2S	HO2S, OBD	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board							
2	3GMXE0223926				2										
3	3GMXE0133916				3	*									
4		*			ı	*		dia	ignostic prefix 2=para	IBD (F) / (P)≈full /partial on-board lel (2) suffix=series					
EVAF No.		CS lo.	ENGINE SIZE (L					ECT TO SFTP	ABBI	REVIATIONS: *					
1		1	4.3		Chevrolet C1500 Silverado 2WD, K1500 Silverado 4WD; GMC C1500 Sierra 2WD, K1500 Sierra 4WD										
2		1 4.3			Chevrolet G1500/2500 Chevy Express/Van 2WD, G15/25 Van 2WD Conv.; GMC G1500/2500 Savana 2WD Cargo/Passenger, G15/25 Savana 2WD Cargo Conv.										
3		1	4.3			Chevrolet C1500 Silverado 2WD, K1500 Silverado 4WD; GMC C1500 Sierra 2WD, K1500 Sierra 4WD									
*		*	*	\Box				*	***************************************						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ CH4 R		NMOG or	nitrogen	HUHU=TON	naldehvde	PM=parl	ticulate m	anter RA) Fernactivii	on CO=c	ant factor	2/2 D [a/tact	1-2/2 day
CER	CERT STD		NMOG NMHC		NMHC	mg=milligr	am mi≕i	լց/mıյ≖run nlle K=10	ning ioss 000 miles	ORVR [g	g/galion d grees Fah	ispensed]= renheit	on-board re SFTP=supp	efueling vap elemental fe	or recovery derail test or	g=gram ocedure
*	* *		CERT [g/mi]	CERT [g/mi]	[g/mi]		g/mi]		x [g/mi]		CHO [m	g/mi]	PM [g	/mi]	Hwy NO	
7.45.40 (S00 (S00 (S00 (S00 (S00 (S00 (S00 (S				favaul		CERT	STD	CERT	STE	CE	RT	STD	CERT	STD	CERT	STD
.1		@ 50K	0.075	*	0.160	2.0	4.4	0.1	0.4		1	18	*	*	0.1	0.8
		@ UL	0.089	*	0.230	2.5	6.4	0.2	0.6		1	27	*	*	0.2	1.2
	@ 50°	F & 4K	0.132	*	0.320	1.7	4.4	0.04	0.4		1	36	*	*	*	*
@ 20	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV SFTP 2 = @ UL (Tier 1, TLEV)			Ox [g/mi] osite)	CO [g/mi] NMHC+N((composite) [g/mi] [US0					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50						STD	CERT	STD	CERT	STD	CER	STD	CERT	STD	CERT	STD
CERT	3.9			SFTP 1	*	,	•	*	0.03	0.40	2.3	10.5	0.04	0.31	2.9	3.5
STD	12.5	1.3		SFTP 2	*		•		رس	*	*	*	*	*	*	*
@ UL			ATIVE FAM		EVAPORATIVE FAMILY 2 EVAPOR						RATIVE FAMILY 3			EVAPORATIVE FAMILY 4		
_	3-D	2-0		ORVR	3- D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.3	1.4	0.00	*	0.6	0.5	0.00		1.0	1.4	0.00	*	*	*	*	*
STD	2.0	2.5	0.05	*	2.5	3.0	0.05	*	2.5	3.0	0.05	*	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2614 day of February 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch