## **GENERAL MOTORS CORPORATION**

EXECUTIVE ORDER A-006-1110 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2, and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE	ST GRO	UP	M	VEHICLE TYPE E-passenger car; LDT-light-duty tru V-medium-duty vehicle; LVW=load ehicle weight; ALVW=adjusted LVV	ded CATEGO	EMISSION STAND RY (LEV=low emi TLEV= transitional LE a LEV; SULEV=super U	ission V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2003	3 3G	3GMXA06.0189		ľ	MDV: 5,751-8,500 pounds ALV	~	LEV		120K / 120K Gasoline				
No.	FAMILY	APORATIVE MILY (EVAF)		No.	SPECIAL FEATUR EMISSION CONTROL SY		* = not applicable	e OC/	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S				
1	3GMXE	223927		1	SFI, 2WUTWC, 2TW	/C, 2HO2S(2), EG	IO2S(2), EGR, OBD (P) [AFS/HAFS=air-fuel ratio sensor/heated AFS E						
2		*				*	gas AiR	recirculation AIR/PAI	R=secondary air injection/pulsed t fuel injection/sequential MFI				
3		*				*	TBI	TITBI= throttle body injection TC/SC=turbo /super charger					
4	•		77	4		*	diag	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
ÉVAF No.	ECS No.	ENG SIZE			VEHICLE MAKES & MODELS	STANDARDS A	JECT TO SFTP RE UNDERLINED		EVIATIONS: *				
1	1 6.0		)		Chevrolet G1500/2500 Chevy Van/Express 2WD, G15/25 Chevy Van 2WD Conv., G3500 Chevy Van/Express 2WD, G3500 Chevy Van 2WD Conv.; GMC G1500/2500 Savana 2WD Cargo/Passenger, G15/25 Savana 2WD Cargo Conv., G3500 Savana 2WD Cargo/Passenger, G3500 Savana 2WD Cargo Conv.								
*	*	*		* Outside Live Guide Court.									
*	*	*		*									
*	*												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ F AVERAGE [g/mi] CH4 RA				NMOG or	murogen	nunu=tor	maidenvde	PM≐par	ticulate r	matter	R∆F≡reactiv	rity adiustm	arbon mono	2/3 D [a/tact	1-2/2 day		
CER	CERT STD		NMOG NMHC		NMHC STD	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure												
*			CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		NOx [g/mi]		нсно [	mg/mi]	PM [		Hwy NO			
			[8,1111]	[9/111]		CERT	STD	CERT	STE		ERT	STD	CERT	STD	CERT	STD		
		@ 50K	0.071	*	0.195	1.9	5.0	0.2	0.6		1	22	*	•	0.1	1.2		
		@ UL	0.081	*	0.280	3.0	7.3	0.3	0.9	'	2	32	*	*	0.2	1.8		
	@ 50°	F & 4K	*	*	*	*	*	*	*		*	*	*	*	*	*		
	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			x [g/mi] osite)	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]					HC+NOx	CO [g/mi] [SC03]			
50						STD	CERT	STD	CERT	STD	CE	RT STI	CER	STD	CERT	STD		
CERT	*			SFTP 1	*	*	*	*		*	•		*	*	•			
STD	*			SFTP 2	*	*	*	*	*	*	<b>-</b>	*	*	•	*	*		
@ UL	E	VAPOR	ATIVE FAM	ILY 1	EVAPORATIVE FAMILY 2 EVAPO					PORAT	ORATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL	ORVR		
CERT	0.6	0.5	0.00	*	* 1	*	•	*	*	*	*	*	*	*	*	*		
STD	3.0	3.5	0.05	*	*	*	*	*	*	*	*	*	*	*	*	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 674 day of March 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch