

MITSUBISHI MOTORS CORPORATION

EXECUTIVE ORDER A-086-0263 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=ilght-dut truck; MDV=medium-duty vehicle LVW=loaded vehicle weight; ALVW=adjusted LVW)	CATEGOR	EMISSION STAND. LY (LEV=low emis) TLEV= transitional LEV LEV; SULEV=super UI	sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3MTXT02.4GNG				LDT: 0-3750 pounds LVW		100K / 100K	Gasoline						
No.		VAPORATIVE AMILY (EVAF)			No.	SPECIAL FEATUR EMISSION CONTROL SY	RES & STEMS (ECS)	* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC					
1	3MT	3MTXR0140A1A			1		2), EGR, SFI, OBC	AF	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas rectroulation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
2		•			2		*	∥ga:							
3		*			3		*	тв							
4		* 1		4		*	BCA								
EVA	FE	ECS ENGINE VEHICLE VEHICLES SUBJECT TO SFI				FCT TO SETP									
No.		No.	SIZE (L)			MAKES & MODELS	STANDARDS AR	<u>ABBI</u>	BBREVIATIONS: *						
1		1	2.4	2.4		MITSUBISHI OUTLANDER									
*		* *			T										
*		*	*												
*	• •		•		+										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FLI RAGE [RAF=0.94 AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refuelling vapor recovery g=gram											
CER	CERT STD 0.052 0.062		NMOG	NMHC CERT [g/mi]	NMHC STD [g/mi]	diurnal+ho mg=millig	orsoak K	r (g/mij=rui	nning loss 000 miles	ORVE	₹ [g/gailor	n dispensed] ahrenheit	=on-board :	efueling var plementai fe	or recovery	g≕gram	
0.05			CERT [g/mi]				[g/mi]		x [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NO		
200	SECTION AND ADDRESS.			ra1	<u> </u>	CERT	STD	CER1	STI	D	CERT	STD	CERT	STD	CERT	STD	
	@ 50K		0.054	*	0.075	0.5	3.4	0.1	0.2).2 1		15	*		0.01	0.3	
984	U- □ □ @ UL		. 0.061 *		0.090	0.6	4.2	0.1	0.3	3	1	18	*	•	0.03	0.4	
	@ 50°	F & 4K	0.098	*	0.150	0.9	3.4	0.04	0.2	2	1	30	*	*	*	*	
@ 20	@ 20°F&		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)		NMHC+NC (compo	x [g/mi] site)	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		HC+NOx nil [SC03]	CO [g/mi] [SC03]			
50	K	SFTP 2	= @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD	
CERT	5.7	4	ME AND	SFTP 1	*	*	*	*	*	*	·	*	*		•		
STD	10.0	100	41475	SFTP 2	*	*	*	*	*		-		*	*	*		
@ UL			ATIVE FAM	ILY 1	EVAPORATIVE FAMILY 2 EVAPOR					PORA	RATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
	3-D	2-0) RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	₹ 3-D	2-D	RL	ORVR	
CERT	1.0	1.0	0.02	0.004	* 1	*	*	*	•	*	*	•	*	*		•	
STD	2.0	2.5	0.05	0.20	*	*	*	•	*	*	*	*	*		+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of June 2002.

Allen Lyons, Chief

Mobile Source Operations Division