TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0441 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MODI | R | TEST GROUP | | | VEHICLE TYPE (PC≖passenger car; LDT=light-duty truck; MDV≖medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW) | | | EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV) | | | EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles) | FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas) | | | |
|-------------|------|--------------|-----------------|---|---|---|--------------|---|--|-------------|---|---|--|--|--|
| 200 | 3 | 3TYXV02.4JXB | | | | PC | LEV II SULEV | | | 150K / 150K | Gasoline | | | | |
| No. | | | TIVE VAF) | N | o. | SPECIAL FEATU EMISSION CONTROL SY | | | | | OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S | | | | |
| 1 | ЗТҮХ | 3TYXR0135A41 | | | 1] | WU-TWC, TWC, HAFS, HO2S(2), SFI, OBD (P) | | | | | AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air | | | | |
| 2 | • | | | | 2 | • | | | | | | | | | |
| 3 | | * | | | 3 | • | | | | | cooler DOR=direct O3 reduction OBD (F) / (P)=full /partial on- board diagnostic prefix 2=parallel (2) suffix=series | | | | |
| EVAF No. | | CS lo. | ENGIN SIZE (| | | VEHICLE VEHICLES SUBJECT TO SFTP MAKES & MODELS STANDARDS ARE UNDERLINED ABBREVIATIONS: | | | | | | | | | |
| 1 | | 1 2.4 | | | Toyota: Camry | | | | | | | | | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. Since no NMOG RAF is adopted by the Air Resources Board for passenger car SULEVs, the manufacturer has agreed to a default value listed below.

| NMOG FLEET AVERAGE [g/ml] | | | | RAF = 1.00 AF = * | CH4=methane NMOG≃non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NMOG or nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [r | | | | | | | | | | 2/3 D [a/te | stl=2/3 day | |
|------------------------------|---------------|---|----------------|----------------------|--|------------------------|--------------------------|--------------------------|---------------------------|----------------------|---|---------------------|----------------------|---------------------------|----------------|---------------------|--|
| CER | T : | STD | NMOG NMHC | | NMHC STD [g/mi] | diurnai+h mg=millig | | RL [g/mi]≖ru =mile K= | unning loss 1000 miles | lispensed renheit | d]=on-board refueling vapor recovery g=gram SFTP=supplemental federal test procedure | | | | | | |
| 0.055 | | .062 | CERT [g/mi] | CERT [g/mi] | | | [g/mi] | | x [g/mi] | Н | HCHO [mg/mi] | | PM [g/mi] | | Hwy NOx [g/mi] | | |
| #Sage on Supre- | | | [A,ıııı] | | | CERT | STD | CERT | ST | CI | ERT S | STD | CERT | STD | CERT | STD | |
| | | @ 50K | * | * | * | * | | * | | | • | * | | * | * | * | |
| | | @ UL | 0.004 | | 0.010 | 0.1 | 1.0 | 0.01 | 0.02 | 2 (| 0.1 | 4 | • | * | 0.01 | 0.03 | |
| 機響 | @ 50° | F & 4K | 0.016 | • | 0.020 | 0.1 | 1.0 | 0.01 | 0.02 | 2 (| 0.2 | 8 | * | * | * | + | |
| CO (| g/mi] °F & | SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) | | | NMHC+No (comp | | CO [g/mi] (composite) | | NMHC+NOx [g/mi] [US06] | | | CO [g/mi] [US06] | | NMHC+NOx [g/mi] [SC03] | | CO [g/mi] [SC03] | |
| 50 | K | SFTP 2 = @ UL (Tier 1, TLE | | 1, TLEV) | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD | |
| CERT | 1.3 | | | SFTP 1 | • | * | * | * | 0.003 | 0.14 | 3.8 | 8.0 | 0.01 | 0.20 | 0.1 | 2.7 | |
| STD | 10.0 | Electric section | | SFTP 2 | • | * | * | * | * | • | * | • | | • | • | • | |
| @ UL | | | ATIVE FAM | HLY 1 | EVAPORATIVE FAMILY 2 | | | | EVAPORATIVE FAMILY 3 | | | | EVAPORATIVE FAMILY 4 | | | | |
| | 3-D | 2-0 | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR | |
| CERT | 0.23 | 0.2 | 0.004 | 0.08 | * | * | * | * | • | * | * | • | + | | * | * | |
| STD | 0.35 | 0.3 | 5 0.05 | 0.20 | * | • | • | * | • | * | • | • | + | * | * | | |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

BE IT FURTHER RESOLVED: That the manufacturer has requested that the listed vehicles be determined to qualify for a baseline partial zero emission vehicle (PZEV) allowance of 0.2 under 13 CCR Section 1962(c)(2) as amended by the 2001 Zero Emission Vehicle (ZEV) Amendments. A June 11, 2002 preliminary injunction issued by a federal district court and currently on appeal enjoins the Executive Officer from enforcing the 2001 ZEV Amendments with respect to the sale of new motor vehicles in the 2003 or 2004 model years pending final resolution of the litigation. In case the preliminary injunction is lifted or the PZEV status of the vehicles becomes relevant in the context of subsequent amendments to the ZEV regulations (depending on the credit provisions of such amendments), the undersigned has determined that the listed vehicles would qualify for a baseline PZEV allowance of 0.2 under 13 CCR Section 1962(c)(2) if those provisions could be enforced. Nothing in this Executive Order is intended as enforcement of any of the 2001 ZEV Amendments for the 2003 or 2004 model years.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _______ day of December 2002.

Allen Lyons, Chief

Mobile Source Operations Division