

TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0449
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP		Р	MD	VEHICLE TYPE =passenger car; LDT=light-duty truck; V=medium-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3TYXV04.3HHA				PC .	ULEV			100K / 100K	Gasoline				
No.			ORATIVE Y (EVAF) No.			SPECIAL FEATURES Emission control system	& MS (ECS)	* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing					
1	3TY	XR015	OAK1		1	2TWC, TWC, 2HO2		BAL							
2	3TY	3TYXR0160AK1			2	*			gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel. (2) suffix=series						
3		*			3	*		-TE							
4		*			1			dia							
EVAI No.		ECS No.	- ,			VEHICLE VEH MAKES & MODELS STA	HICLES SUBJ	ECT TO SFTP E UNDERLINED	ABB	ABBREVIATIONS:					
1		1	4.3					130							
2	\bot	1	4.3												
*		*	*		Lexus LS 430										
*	* * * * *							*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ I CH4 R		NMOG or	TO THE ONE	,, ucuc-	ionnaiden	/OB PMSD	articulate	matter	RAFERASA	carbons C	mant factor	2/2 17 1-4-	210-14
CER	0,055 0.062		NMOG	NMHC	NMHC STD [g/mi]	diurnal+h mg=millig	Of AROSE TO	∟ (g/mi)=rui	nning loss 1000 miles	UKVK [g.	/gailon d	ispensed):	on-board r	efuelina var	OF recovery	g=gram
0,05			CERT [g/mi]	CERT [g/mi]			[g/mi]	NC	x [g/mi]	H	CHO [m	g/mi]	PM [s	/mi]	Hwy NO	
Commence of the second second second						CERT	STD	CERT	STE	CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	0.026	*	0.040	0.2	1.7	0.1	0.2	0	.2	8	•	*	0.03	0.3
		@ UL	0.030	*	0.055	0.2	2.1	0.1	0.3	0	.3	11	•	•	0.04	0.4
	@ 50	°F & 4K	•		*	*	•	•	•		•	•	•	•	•	*
@ 20	@ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			osite)	(composite) [g/mi]		NMHC [g/ml]				HC+NOx i] [SC03]		[g/mi] C031	
50						STD	CERT	STD.	CERT	STD	CER	T STE	CERT	STD	CERT	STD
CERT	1.7			SFTP 1	•	*	•	•	0.02	0.14	0.3	8.0	0.06	0.20	0.05	2.7
STD	10.0			SFTP 2	•	•	•	*		*	*	•		 		•
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR					PORATIV	ATIVE FAMILY 3 EVAPORATIVE FAMILY 4					
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE		2-D	RL	ORVR
CERT	0.4	0.9	0.01	0.01	0.5	0.6	0.01	0.06	•	•	•	•	•	+	+ :	1
STD	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	•	•	*	•	•	•	•	 •

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this // day of August 2002

Allen Lyons, Chief

Mobile Source Operations Division