EXECUTIVE ORDER A-018-0119 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST GROUP			UΡ	M	VEHICLE TYPE C=passenger car; LDT=ilght-duty truck DV=medlum-duty vehicle; LVW=loaded vehicle weight; GVW=gross VW)	stant d (LEV=low of transitions	AUST EMISSION DARD CATEGORY emission vehicle; TLE at LEV; ULEV=uttra LE LEV=super ULEV)	:V=	EXHAUST (EXH) / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)			
200			3VVXX2.52U2T			PC and LDT \leq 8,500 pounds GVW C: LDT 3,751 – 5750 pounds LVW	/)	LEV II ULEV		120K: EXH/ORVR 100K: EVAF	Gasoline		
No.		APORA VILY (E			No.	SPECIAL FEATURES EMISSION CONTROL SYST	S & EMS (ECS)	* = not applicable	, (OC/TWC=oxidizing/3-way cat	. ADSTWC=adsorbing TWC		
1	3VV	VVXR0133AAA			1	TWC, HO2S, HAFS,	SFI, TC, CAC, C	8 4	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust				
2		*			2		*		gas recirculation AiR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*			3		*		TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=para!lel (2) suffix=series				
4		*			4		*	-16					
EVAI No.		ECS ENGINE VEHICLE VEHICLES SUBJECT TO SFTP No. SIZE (L) MAKES & MODELS STANDARDS ARE UNDERLINED						ABI	BREVIATIONS:				
1_		1 2.5 <u>Volvo: (PC) V70 AWD, S60 AWD; (LDT 3,751 – 5,750) XC 70 AWD, XC 90 AWD, XC 90 FWD</u>									90 FWD		

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE STD [g/mi]		NMOG @ RAF=0.94 CH4 RAF = *		NMOG or	nitrogen	HCHU=tor	maidehvde	PM≖part	iculate ma	itter R	?AF=reactiv	ity adiuetm	arbon mono	2/3 D In/toet	-2/3 days	
PC/LD	DT1	LDT2	NMOG	NMHC	NMHC	mg=millig	ot-soak Ki	L [g/mi]≠rur	oning loss	ORVR [g/	gallon	dispensed] hrenheit	=on-board ı	efueilng vap piemental fe	or recovery	g=gram	
0.06	2	0.093	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]	HC	CHO [r	ng/mi]	PM [Hwy NO		
			[g/m]			CERT	STD	CERT	STD	CE	RT [STD	CERT	STD	CERT	STD	
		@ 50K	0.020	*	0.040	0.3	1.7	0.03	0.05	ō 0.	.1	8	*	*	0.004	0.07	
		@ UL	0.025	*	0.055	0.3	2.1	0.04	0.07	' O.	2	11	*	•	0.01	0.09	
2.4	@:	50°F & 4K	0.060	*	0.080	0.7	1.7	0.02	0.05	0.	2	16	*	*		*	
@ 20		LEV	@ 4K (SULE) or 50K (Tie	r 1, TLEV)	NMHC+NO (comp	osite)	ite) (composite)		NMHC [g/mi] [NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFIPZ	@ UL (Tier '	I, ILEV)	CERT	STD	CERT	STD	CERT	STD	CEF	RT STO	CER	T STD	CERT	STD	
CERT	1.7			SFTP 1	*	*	*	•	0.04	0.14	1.6	8.0	0.10	0.20	1.2	2.7	
STD	10.0			SFTP 2	*	*	*	*	*	*	*	•	*	*	*	•	
@ UL		EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVA				VAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	₹ 3-D	2-D	RL	ORVR	
CERT	0.9	1.8	0.00	0.001	*	*	*	*	*	*	*	*	·	*	•	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	*	•	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.1(m)(6.2) (malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have three deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty-five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2003 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to recind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 3/37

day of October 2002.

Allen Lons, Chief

Mobile Source Operations Division

