

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1157

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP VEHICLE TYPE		EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil	es)	IN-I COMP (*=N/A or A/E=exi	MEDIATE USE LIANCE full in-use; h. / evap. ate in-use)	FUEL TYPE		
2004	4GMXT04,2185	LDT: 3751-5750Pounds LVW	"LEV II" Low Emission Vehicle (LEV II LEV)	Exhaust	EVAP / ORVR	EXH	EVAP	GASOLINE		
	W	and = 8500 Pounds GVW</td <td>,</td> <td>120K</td> <td colspan="2"></td> <td>*</td> <td colspan="2">(Tier 2 Unleaded)</td>	,	120K			*	(Tier 2 Unleaded)		
No.	ECS &	800043	EVAPORATIVE FAMILY (EVAF)			DISPLACEMENT (L)				
1	TWC, HO	4GMXR	4GMXR0175922							
*	and the property of		*				4.2			
*			*							
•		*		*						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _7 th

Allen Lyons, Chief

Mobile Source Operations Division



4GMXR0175922

0.5

2.0

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

		@ RAF=* RAF = *	INMOG OF	HUHU=10	hane; NMOG rmaldehyde;	PM≕particu	ilate matter	: RAF=reac	tivity adiust	ment facto	r: 2/3 D (n/te	ctl=2/3 day.	diumala	• .	
CERT	STD	NMOG	NMHC	NMHC STD [g/mi]	mi=mile;	RL [g/mi]=rur K=1000 miles	nning loss; : F=dearee	ORVR [g/g: s Fahrenhe	allon disper eit: SFTP=se	ised]=on-bo upplementa	ard refuel I federal to	ing vapor red	covery; g=gr	am; mg ≠milli	gram
0.056	0.085	CERT [g/mi]	CERT [g/mi]		CO	CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
	<u> </u>			1	CERT	STD	CERT	STE	CE	RT S	TD ·	CERT	STD	CERT	STD
	@ 50K	0.075	*	0.075	1.6	3.4	0.04	0.0	5 *	1	15.	•	*	0.01	0.07
	@ UL	0.076	*	0.090	2.3	4.2	0.05	0.07	7 *	1	18.	*	٠ *	0.01	0.09
@	50°F & 4K	*	* .	*	*	*	*	*	*		•	*	*	•	*
	CO [g/mi]		MARKET EL						+NOx CO [g/mi] US06] [US06]			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
@ 20°F & 50K			2 1	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	9.4	SFTP @ 4	000 miles	*	*	*	*	0.04	0.25	5.9	10.5	0.04	0.27	1.5	3.5
STD	12.5	SFTP	@ * miles	*	*	*	*	*	*	*	*	*	•	*	*
									Running Loss ams/mile) @ UL				On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
Evaj	porative Far	nily										Re	n-Board i covery (gr	Refueling V ams/gallon	/apor) @ UL

* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel;

2.5

0.00

0.05

0.14

0.20

0.8

2004 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-I COMPI (*=N/A or A/E=exi	IEDIATE USE LIANCE full in-use; n. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
CHEVROLET	TRAILBLAZER 2WD	4GMXR0175922	1	4.2	A	*	SFTP	Full
CHEVROLET	TRAILBLAZER 4WD	4GMXR0175922	1	4.2	Α	*	SFTP	Full
GMC	ENVOY 2WD	4GMXR0175922	1	4.2	Α	*	SFTP	Full
GMC	ENVOY 4WD	4GMXR0175922	1	4.2	Α	*	SFTP	Full
OLDSMOBILE	BRAVADA 2WD	4GMXR0175922	1	4.2	Α	*	SFTP	Full
OLDSMOBILE	BŖAVADA AWD	4GMXR0175922	1	4.2	Α	*	SFTP	Full
BUICK	RAINIER 2WD	4GMXR0175922	1	4.2	Α	*	SFTP	Full
BUICK	RAINIER AWD	4GMXR0175922	1	4.2	A	*	SFTP	Full
ISUZU	ASCENDER 5-PASSENGER 2WD	4GMXR0175922	1	4.2	Α	*	SFTP	Full
ISUZU	ASCENDER 5-PASSENGER 4WD	4GMXR0175922	1	4.2	Α	*	SFTP	Full