DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0648-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MOD YEA | | TEST | TEST GROUP | | | VEHICLE TYPE C=passenger car; LDT=light-duty tru V=medlum-duty vehicle; LVW=load rehicle weight; ALVW=adjusted LVW | ed | STANDA (LEV=low em transitional L | ST EMISSION RD CATEGORY ission vehicle; TLEV= EV; ULEV=ultra LEV; /=super ULEV) | EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles) | FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas) | | | | | |
|------------|-------------------|--------------|---------------------|-----------|----------|---|--------------|---|---|---|--|--|--|--|--|--|
| 200 | 2005 5CRXV02.4VE0 | | | ΕO | | PC | | LI | EV II LEV | EXH: 120K EVAF1/ORVR: 150K/120K EVAF2/ORVR: 100K/100K | Gasoline (Tier 2 Unleaded) | | | | | |
| No. | FAM | ILY (E | RATIVE (EVAF) No | | | SPECIAL FEATUR EMISSION CONTROL SYS | ES 8 STEM | is (ECS) | * = not applicable | OC/TWC=oxidizing/3-way o | eat. ADSTWC=adsorbing TWC | | | | | |
| 1 | 5CRX | 5CRXR0101GBB | | | 1 | HO2S(2), 1 | TWC, | SFI, OBD(F) | AFS/HAFS=air-fuel ratio se | 22S=oxygen sensor/heated O2S nsor/heated AFS EGR=exhaust | | | | | | |
| 2 | 5CRX | RXR0130GBA | | | 2 | | * | | | t≖secondary air injection/pulsed fuei injection/sequential MFI | | | | | | |
| 3 | | • | | | 3 | | * | | TBI= throttle body injection | TC/SC=turbo /super charger | | | | | | |
| 4 | | * | * | | 4 | | * | | diagnostic prefix 2=parall | BD (F) / (P)=full /partial on-board el (2) suffix=series | | | | | | |
| EVA | | CS | ENGIN | | Π | VEHICLE | | | ECT TO SETP | ABBREVIATIONS: | | | | | | |
| No. | | Vo. | SIZE (| <u>L)</u> | | MAKES & MODELS | | | ONDEKLINED | | • | | | | | |
| 1 | 1 1 | | 2.4 | | <u> </u> | | Chi | rysler: PT Cr | onvertible/Cabrio | | | | | | | |
| 2 | | 1 2.4 | | | | Chrysler: Sebring Convertible, Sebring; Dodge Stratus | | | | | | | | | | |
| . * | | * * | | | | | | | | | | | | | | |
| * | | * * | | | | | | | | | | | | | | |
| * | | * * | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| | OG FLEET RAGE [g/mi] | E [g/mi] CH4 RAF = * STD NMOG NMHC | | NMOG o | CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldshyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day dlurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram | | | | | | | | | | |
|-------|-------------------------|---|----------------------|--------|--|---------|----------------------------------|---------------------------|--------------------|-------------------------|-----------------------|------------------------|------------------------------|-------------------------------|----------------|
| CERT | STD | | | NMHC | mg=millig | ram mi= | ∟ [g/mı]≖ru ≔m <u>il</u> e K≕ | inning los: 1000 mile: | s ORVR [g F≖de | g/gallon d grees Fah | ispensed]: renheit | on-board r SFTP=sup | efueling vap plemental fe | or recovery derail test pr | g=gram |
| 0.046 | 0.049 | CERT [g/mi] | CERT [g/mi] | [g/mi] | | [g/mi] | | Ox [g/mi] | | ICHO [m | g/mi] | PM [| /mi] | Hwy NO | x [g/ml] |
| | | | [Shum] | | CERT | STD | CER | T S1 | D CI | ERT | STD | CERT | STD | CERT | STD |
| | @ 50K | 0.039 | | 0.075 | 0.4 | 3.4 | 0.03 | 0.0 | 05 | * | 15 | * | * | 0.01 | 0.07 |
| | @ UL | 0.039 | • | 0.090 | 0.4 | 4.2 | 0.03 | 0.0 | 07 | * | 18 | * | * | 0.01 | 0.09 |
| | @ 50°F & 4K | | | • | | * | * | 1 | ' | * | * | * | * | * | * |
| @ 20 | F & 📳 L | 1 ● @ 4K (SUL .EV) or 50K (T | ler 1, TLEV) | (comp | Ox [g/mi] losite) | | g/mi] posite) | | IC+NOx] [US06] | CC |) [g/mi] US06] | | HC+NOx ij [SC03] | | [g/mi] C03] |
| 501 | (SFIP: | 2 = @ UL (Tiec | 1, TLEV) | CERT | STD | CERT | STD | CERT | STD | CER | T STE | CER | r STD | CERT | STD |
| CERT | 1.4 | s | FTP @ 4K | | * | * | | 0.10 | 0.14 | 2.8 | 8.0 | 0.02 | 0.20 | 0.2 | 2.7 |
| STD | 10.0 | S | FTP @ UL | | * | * | * | * | * | * | * | * | * | * | |
| @ UL | - | ATIVE FAM | EVAPORATIVE FAMILY 2 | | | | EVAPORATIVE FAMILY 3 | | | | E | EVAPORATIVE FAMILY 4 | | | |
| | 3-D 2- | | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVE | ₹ 3-D | 2-D | RL | ORVR |
| CERT | 0.46 0.4 | 19 0.000 | 0.13 | 0.7 | 0.7 | 0.001 | 0.03 | * | * | * | + | * | * | * | • |
| STD | 0.50 0.6 | 0.05 | 0.20 | 2.0 | 2.5 | 0.05 | 0.20 | * | * | * | * | * | * | * | • |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with **Title 13**, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-009-0648 dated December 22, 2003.

Executed at El Monte, California on this 22 ND day of July 2004.

Allen Lyons, Chief

Mobile Source Operations Division