GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1212-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN- COMP (**N/A of A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap, late in-use)	FUEL TYPE			
2005	5GMXT03.5188	LDT: 3751-5750 Pounds LVW	USEPA Bin 9a (opt)	EXH / EVAP 100K 100K		EXH	EVAP	Gasoline (Tier 2			
			Counted as ARB ULÉV			•	•	Unleaded)			
No. ECS & SPECIAL FEATURES			EVAPORATIVE		DISPLACEMENT (L)						
1 WU-TWC,TWC, HO2S(2), SFI, OBD(F)			5GMXR0			(0)					
•		•	•								
•		•	•	·				3.5			
·		•	•	•							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.


The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1212 dated April 5, 2004.

Executed at El Monte, California on this 26⁷⁴ day of October 2004.

Allen yons, Chief

Mobile Source Operations Division



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMQG FLEET AVERAGE [g/mi]		NMOG @ RAF=* CH4 RAF = *		NMOG or	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diumat+not-soak; RL [g/ms]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram											
CERT	T STD	NMOG CERT	NMHC CERT [g/mi]	NMHC STD [g/mi]	mi=mile;	KL (g/m)≃rui K≃1000 miles	nning loss; i; F≃degree	ORVR (g/ga is Fahrenha	allon disper hit; SFTP=s	nsed]≃on-bo upplements	oard refue Il federal t	lina venar red	COVERY DEG	ram; mg=mill	igram	
0.060	0.078	[g/mi]				[g/mi]		NOx [g/mi]		CHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi		
	Ø 50K		+	0.100	CERT 0.5	3.4	CERT				TD	CERT	STD	CERT	STD	
	@ UL			0.130	0.7	4.2	0.1	0.2			15.			0.03	0.27	
and an expense of	@ 50°F & 4K		 	0.130	0.7	4.2	0.2	0.3			18.			0.05	0.40	
and security that	3 00 1 C 410				1	1				`			•		•	
CO [g/mi]		4.7		NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)			+NOx [US06]			NMHC+NOx [g/mi] [SC03]		CO [g/mi] (SC03)		
	'F & 50K			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
CERT	5.1	SFTP @ 4	000 miles	•	- *	•	•	0.08	0.25	2.4	10.5	0.03	0.27	0,2	3.5	
STD	12.5	SFTP	@ 100000 miles	0.26	1.04	•	. *	•	•	4.6	14.6	•	•	1.4	4.9	
3-Days Diurnal + Hot (grams/test) @ U CERT ST 5GMXR0175922 0.5 2.						Running Loss (grams/mile) @ UL			On-Board Refueling Vapor Recovery (grams/gallon) @ UL							
		CERT	S1	TD CT	CERT		STD	CER	T	STD		CERT		STD		
		22	0.5 2.0		0	0.8	0.8		0.00		0.05		0.14		0.20	
•				- 		*		•	•		*	_	•		0.20	
•			•			*		•			•					

*= not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV: TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefled natural gas; LPG=ilquefled petroleum gas; E85="85%" Ethanol Fuel

2005 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; n. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
CHEVROLET	COLORADO 2WD	5GMXR0175922	1	3.5	•	•	SFTP	Full
CHEVROLET	COLORADO 4WD	5GMXR0175922	1	3.5	*	*	SFTP	Full
CHEVROLET	COLORADO CREW CAB 2WD	5GMXR0175922	1	3.5	•	•	SFTP	Full
CHEVROLET	COLORADO CREW CAB 4WD	5GMXR0175922	1	3.5	•	•	SFTP	Fuli
GMC	CANYON 4WD	5GMXR0175922	. 1	3.5	•	•	SFTP	Full
GMC	CANYON CREW CAB 4WD	5GMXR0175922	1	3.5	*	•	SFTP	Full
GMC	CANYON 2WD	5GMXR0175922	1	3.5	•	*	SFTP	Full
GMC	CANYON CREW CAB 2WD	5GMXR0175922	1	3.5	*	•	SFTP	Full
CHEVROLET	COLORADO CAB CHASSIS INCOMPLETE 2WD	5GMXR0175922	1	3.5	*	•	SFTP	Fuil
GMC	CANYON CAB CHASSIS INCOMPLETE 2WD	5GMXR0175922	1	3.5	•	*	SFTP	Fuil