## FERRARI S.p.A.

**EXECUTIVE ORDER A-040-0067-1** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

## IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP VEHICLE TYPE		EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN-I COMP (*=N/A or A/E=ex	IEDIATE USE LIANCE full in-use; h. / evap. late in-use)	FUEL TYPE	
2006			Low Emission Vehicle	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2	
	6FEXV05.7LEV	Passenger Car	(LEV)	100K	150K	*	E	Unleaded)	
No.	ECS & S	EVAPORATIVE			DISPLACEMENT (L)				
1	4WU-TWC,2TWC	6FEXR	203575						
•					44	5.7, 6			
•		•		*					
-		•		•					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-040-0067 dated November 2, 2005.

Executed at El Monte, California on this 1774 day of January 2006.

Mobile Source Operations Division



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

# **ATTACHMENT**

#### EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=*  AVERAGE [g/mi] CH4 RAF = *			NMOG or	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; In HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diumal+											
CERT	STD	NMOG	NMHC											-	
0.075	CERT CERT	[g/mi] CO [g/mi]		NOx	NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]				
0.075	0.075	[g/mi]	/mi] [g/mi]	[8,]	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
	@ 50K	0.037	•	0.075	0.8	3.4	0.01	0.2	*	15.	*	٠	0.00	0.3	
	@ UL	0.042	*	0.090	1.0	4.2	0.02	0.3	•	18.	*	•	0.00	0.4	
<b>445</b> @	50°F & 4K	0.070	*	0.150	0.8	3.4	0.0	0.2	1.3	30.	*	*	•	*	

CO [g/mi]		AND COMMENT		Ox [g/mi] osite)	CO [			+NOx [US06]	CO [ US		NMHC [g/mi]	:+NOx [SC03]	) OO [SC	
@ 2	0°F & 50K		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	\$TD
CERT	3.6	SFTP @ 4000 miles	•	*	*	*	0.05	0.14	0.1	8.0	0.05	0.20	0.2	2.7
STD	10.0	SFTP @ * miles	•	*	*	•	*	*	*	*	*	*	*	*

						On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
CERT	STD	CERT	STD	CERT	STD	CERT	STD	
0.41	0.50	0.42	0.65	0.01	0.05	0.03	0.20	
*	*		•	*	*	*	•	
•	•	*	*	*	*	*	•	
•	*	*	*	*	•	•	•	
	(grams/te		(grams/test) @ UL (grams/te	(grams/test) @ UL (grams/test) @ UL  CERT STD CERT STD	(grams/test) @ UL (grams/test) @ UL (grams/m CERT STD CERT STD CERT	(grams/test) @ UL (grams/test) @ UL (grams/mile) @ UL  CERT STD CERT STD CERT STD	(grams/test) @ UL (grams/test) @ UL (grams/mile) @ UL Recovery (gram  CERT STD CERT STD CERT STD CERT	

\* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=\*85%\* Ethanol Fuel

#### 2006 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-I COMPI (*=N/A or A/E=exi	IEDIATE USE LIANCE full in-use; n. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
FERRARI	612 Scaglietti	6FEXR0203575	1	5.7	*	E	SFTP	Full
FERRARI	612 Scaglietti F1	6FEXR0203575	1	5.7	*	E	SFTP	Full
FERRARI	599 GTB	6FEXR0203575	1	6	*	E	SFTP	Full