

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

No. SPECIAL FEATURES & WUL-warm-up cat. Ozs/Ho25-oxygen sensor/heated AFS EG WUL-warm-up cat. Ozs/Ho25-oxygen sensor/heated	mpressed/ ural gas;	FUEL TYPE (CNG/LNG=compres liquefied natural g LPG=liquefied petrolet	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	UST EMISSION ARD CATEGORY w emission vehicle; EV=ultra LEV; EV=super ULEV)	ck; STAND	VEHICLE TYPE 'C=passenger car; LDT=light-duty truck; IDV=medlum-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	M M	r GROUP	TEST	MODEL YEAR
No. FAMILY (EVAF) No. EMISSION CONTROL SYSTEMS (ECS) 1 6FJXR01253CF 1 TWC(2), HAFS, HO2S, SFI, EGR, OBD (F) 2 6FJXR01253CJ 2 6FJXR01253CJ 3 * 3 * 4 * EVAF CS ENGINE No. SIZE (L) No. No. SIZE (L) 1 2.5 SAAB (PC) 9-2X WAGON AWD WUs warm-up cat. O2S/HO2S=oxygen sensor/laptacle with a price cat. O2S/HO2S=oxygen sensor/laptacle with a p	ne	Gasoline	120K / 150K	LEV II LEV				2006 6FJXX02.5MTC		
2 6FJXR01253CJ 2 * ART MFI/SFI= multiport fuel injection/sequer 3 * Bis throttle body injection TC/SC-turbo /SC-turbo /SC-turb	heated O2S	2S=oxygen sensor/heate	WU= warm-up cat. O2S/HC				No.			
2 6FJXR01253CJ 2 *					TWC(2), HAFS, HO2	1	53CF	FJXR012	1	
ACE-charge air cooler OBD (F) / (P)=full /partidignostic prefix 2=parallel (2) suffix=series EVAF ECS ENGINE No. No. SIZE (L) MAKES & MODELS STANDARDS ARE UNDERLINED 1 1 2.5 SUBARU: (PC) FORESTER AWD, IMPREZA WAGON RS AWD, IMPREZA WAGON OUTBAC SAAB (PC) 9-2X WAGON AWD 2 1 2.5 SUBARU: (PC) LEGACY AWD, LEGACY WAGON AWD	ntial MFI	fuel injection/sequential l	AIR MFI/SFI= multiport		*	2	53CJ	FJXR012	2	
4 * diagnostic prefix 2=parallel (2) suffix=series EVAF	ier charger ial on-board	n TC/SC=turbo /super ch BD (F) / (P)=full /partial on	TBI= throttle body injection CAC=charge air cooler Of		*	3		*	3	
No. No. SIZE (L) MAKES & MODELS STANDARDS ARE UNDERLINED 1 1 2.5 SUBARU: (PC) FORESTER AWD, IMPREZA WAGON RS AWD, IMPREZA WAGON OUTBAC SAAB (PC) 9-2X WAGON AWD 2 1 2.5 SUBARU: (PC) LEGACY AWD, LEGACY WAGON AWD					*	4		•	4	
1 1 2.5 SUBARU: (PC) FORESTER AWD, IMPREZA WAGON RS AWD, IMPREZA WAGON OUTBAC SAAB (PC) 9-2X WAGON AWD 2 1 2.5 SUBARU: (PC) LEGACY AWD, LEGACY WAGON AWD								ENGINE	ECS	EVAF
1 1 2.5 SAAB (PC) 9-2X WAGON AWD 2 1 2.5 SUBARU: (PC) LEGACY AWD, LEGACY WAGON AWD								SIZE (L)	No.	No.
2 1 2.5 SUBARU: (PC) LEGACY AWD, LEGACY WAGON AWD	<u>:K AWD</u> ;	WAGON OUTBACK A	SUBARU: (PC) FORESTER AWD, IMPREZA RS AWD, IMPREZA WAGON RS AWD, IMPREZA WAGON OUTBACK							
			1	2.5	7 1					
CHARLE ADT 2 754 S 750 LVAN OUTBACK AWD OUTBACK WACON AWD				2.5	1	2				
2 1 2.5 SUBARU: (LDT 3,75T = 3.750 LVW) OUTBACK AVID, OUTBACK WAGON AVID			2.5	1	2					
* * *	•								*	*

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *		NMOG or	The life is a second of the company of the second of the s													
STD	S	TD	NMOG	NMHC CERT [g/mi]	NMHC	mg=millig		mile K=	1000 miles	F=de	grees Fat	renheit S	SFTP=supp	lemental fe	deral test pr	ocedure
PC/LD	T1 LI	DT2	CERT		[g/mi]	CO	CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
0.046	3 0.	062	[g/mi]		[g/mi]	[9]	CERT	STD	CER	r st	D C	ERT	STD	CERT	STD	CERT
		ĝ 50K	0.033	*	0.075	0.7	3.4	0.02	0.0	5	1	15	*	*	0.01	0.07
		@ UL	0.037	*	0.090	0.8	4.2	0.02	0.0	17	1	18	*	*	0.01	0.09
	@ 50°F	& 4K	0.080	*	0.150	1.0	3.4	0.01	0.0	5	1	30	*	*	*	*
CO [g/mi] SFTP 1 = @ 4K (@ 20°F & LEV) or 50		@ 4K (SUL /) or 50K (Ti			Ox [g/mi] CO [g/mi] osite) (composite)			NMHC+NOx [g/mi] [US06]					HC+NOx i] [SC03]		CO [g/mi] [SC03]	
50		SFTP 2 = @ UL (Tièi			CERT	STD	CERT	STD	CERT	STD	CER	T STD	CERT	STD	CERT	STD
CERT	2.7		10.0	SFTP 1	*	*	*	*	0.04	0.14	3.0	8.0	0.02	0.20	0.1	2.7
STD	10.0			SFTP 2	*	*	*	*	*	*	*	*	*	*	*	•
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR				PORATI	VE FAN	IILY 3	E'	EVAPORATIVE FAMILY 4			
W OL	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2 - D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.31	0.35	0.00	0.02	0.24	0.33	0.00	0.02	*	*	*	•	*	*	*	
STD	0.50	0.65	0.05	0.20	0.50	0.65	0.05	0.20	*	*	*	*	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-002-0137-1 dated June 17, 2005.

Executed at El Monte, California on this ______ day of November 2005.

Allen Lyons, Chief

Mobile Source Operations Division