LAND ROVER

EXECUTIVE ORDER A-277-0038

New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

•		•		4					
1	2TWC, 2HAFS	5, 2HO2S, SFI, EGR, OBD(F)	7LRXR0	7LRXR0175001					
No.		SPECIAL FEATURES	EVAPORATIVE		ACEMENT (L)				
		WAS SECTION AND ADDRESS OF THE PROPERTY OF THE	ULEV)	120K	150K	•	*	Unleaded)	
2007	7LRXT04.0001	LDT: 6001-8500# GVW, 5751- 8500# ALVW	"LEV II" Ultra Low Emission Vehicle (LEV II	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2	
MODEL YEAR	TEST GROUP VEHICLE TYPE		EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap. late in-use)	FUEL TYPE	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles



ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVERAG		NMOG (CH4 R	2) RAF=* AF = *	NMOG or	CH4=metha HCHO=form	ne; NMOG= naldehyde; P	non-CH4 org M=particulat	anic gas; N	MHC=non-CH	4 hydrocarb	on; CO=carbo	n monoxide;	NOx=oxides o	f nitrogen;
CERT	STD	NMOG	NMHC	NMHC STD	or HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram ml=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure									
0.054	0.055	CERT [g/mi]	CERT [g/mi]	[g/mi]	<u> </u>	g/mij	NUx	g/mi]	НСНО	mg/mi]		g/mi]	Hwy NO	x [g/mi]
	@ 50K	0.044		 	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
學類類類		0.011		0.040	0.4	1.7	0.02	0.05	0.1	8.		•	0.00	0.07
14. 胸侧点	@ UL	0.012		0.055	0.6	2.1	0.03	0.07	0.1	11.	.		0.00	
- 0	50°F & 4K	0.034	*	0.080	0.5	1.7	0.04	0.05	0.3	16.	+ -		*	0.09
	35	Section Address of the	Transfer Sept.	MANICONIC										

C @ 2	O [g/mi] 0°F & 50K	and seed of his ord		Ox [g/mi] posite)		g/mi] posite)		+NOx [US06]		g/mi] 306]		+NOx [SC03]	CO	g/mi] :031
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	3.8	SFTP @ 4000 miles	•	*	*		0.03	0.60	3.4	11.8	0.01	0.44	0.6	4.0
STD	12.5	SFTP @ * miles	*	•	*	*	•		•	*	*	*	*	*

Evaporative Family	3-Days Diurn (grams/te	al + Hot Soak est) @ UL		ıal + Hot Soak est) @ UL		ng Loss nile) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ L		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
7LRXR0175001	0.40	0.90	0.58	1.15	0.00	0.05	0.01	0.20	
•	*	*	•		*	*		*	
*	*	•	*	*	•	*	*	+	
*	*	*	•	•	•	*			

^{* =} not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=utra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; DGI=direct gasoline fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel;

2007 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E≖ex	MEDIATE USE LIANCE full in-use; n. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
LAND ROVER	LR3	7LRXR0175001	1	4			SFTP	Full