KIA MOTORS CORPORATION

EXECUTIVE ORDER A-314-0088 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light-duty MDV=medium-duty vehicle; LVW=ic vehicle welght; GVW=gross VM	aded L	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles) FUEL TYPE (CNG/LNG=compres liquefied natural g LPG=liquefied petro gas)				
2008		8KMXT02.0KW5				LDT <6,000 pounds GVW (0-3750 # LVW; 3,751-5750 # L	vw) "	"LEV I!" Ultra-Low Emission Vehicle (LEVII ULEV)			120K / 150K	Gasoline (Tier 2 Unleaded)			
No.		EVAPORATIVE No				SPECIAL FEATUREMISSION CONTROL SY		(S)	0	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	8KM	XR012	5PDK		1	WU-TWC, TWO	C, HO2S(2),	- BA	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust						
2		• 2			2		•		g	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFVSFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger					
3		· 3		3		*									
4				4	**	*	٦ď	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVAI No.		ECS No.	ENGII SIZE			VEHICLE MAKES & MODELS			ECT TO SFTP E UNDERLINED	ABE	REVIATIONS:				
1	1 2.0					(LDT1) Kia Sportage 2WD; (LDT2) Kia Sportage 4WD									
					1	***									
		 			╁										

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NOG F	FLEET E (g/mi)		@ RAF= RAF =	NMOG or	Initrogen	HUHU=TOI	maldenvde	e PM≕part	iculate m	natter	RAF≅reactiv	rbon CO=c	ent factor :	DIS D Indes	1=212 day	
STD-L	STD-LDT1 STD-LDT2		NMOG	RT CERT	1 NMHC I	mg=millige	n-soak Ki	ւ լց/ույ≃ռս	nning loss 1000 miles	ORVR	g/gallon	dispensed) ahrenheit	=on-board re SFTP=supp	efueting vap	of recovery	g=gram	
0.04	0.050		CERT [g/mi]				[g/ml]		x [g/mi]		існо [mg/mi]	PM [c		Hwy NO		
ALCOHOLOGICAL CONTRACTOR CONTRACT		a -	[g/ill]			CERT	STD	CERT	STD) C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.026	•	0.040	0.4	1.7	0.005	0.05	i (0.1	8	*	*	0.01	0.07	
		@ UL	0.031	*	0.055	0.6	2.1	0.01	0.07	, ,	0.1	11	•	0.01	0.01	0.09	
3	@	50°F & 4K	0.064	•	0.080	0.5	1.7	0.004	0.05	; (0.2	16	*	*	+	*	
@ 20		LEV)	FTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			Ox [g/mi] Osite)	CO [g/mi] (composite)		NMHC [g/ml]				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2 = (UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT STI			CERT	STD	
CERT	1.1	14.46	s. SF	TP @ 4K	*	+	*	•	0.04	0.14	5.	0 B.0	0.02	0.20	0.7	2.7	
STD	10.0		SF	TP @ UL	*	*	•	•	*	•	*		•	•		•	
@ UL		EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR				ORATI	RATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR	
CERT	0.41	0.50	0.02	0.05	*	•	•	*	*	•	1 •	-	+	•	*		
STD	0.65	0.85	0.05	0.20	• 1	*		•	•	*	·	*		*			

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 7 day of August 20

Annette Hebert, Chief

Mobile Source Operations Division