New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2, and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003,

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mli		IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap. late in-use)	FUEL TYPE		
2010	ANSXT05.6G9A	LDT: 6001-8500# GVW, 5751-	"LEV II" Low Emission Vehicle (LEV II LEV)	EXH / ORVR	EVAP	EXH	EVAP	Gasoline		
		8500# ALVW	, ,	120K	1		•			
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE			DISPLACEMENT (L)				
1	2TWC(2), 2	ANSXRO	ANSXR0132PBA							
*		ANSXRO	ANSXR0174PBA			5.6				
•										
•	·····			•						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-015-0545 dated April 14, 2009.

Executed at El Monte, California on this ______ day of July 2009.

Annette Hebert, Chief

Mobile Source Operations Division



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fue).

NMOG FLEET NMOG @ RAF=" AVERAGE [g/mi] CH4 RAF = "		CH4=metrane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; N0x=oxides of NHCHO=formaldehyde; PM=particulate martier; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diumati-NHMHC hot-soat; RL [g/mi]=nuning loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=millig													
CERT	STD	NMOG NMHC		NMHC STD	mi=mile, K	L [g/mi]≃run ≃1000 miles	ining ioss; (; F≂degree:	DRVR (g/ga s Fahrenhe	lion disper t; \$FTP=s	nsed}≕on-bo :upplementa.	ard refuelii I federal te	ng vapor re- st procedur	e co∧età: č =di	ram; mg=milli	gram
0.051 0.043	0.043	CERT	CERT	[g/ml]		g/mi]	NO	x [g/mi]	HO	CHO [mg/i	ni]	PM [9	/mi]	Hwy NC)x [g/mi]
5.551		[g/mi] [g/mi	[g/mi]		CERT	STD	CERT	STD	CE	RT S	TD	CERT	STD	CERT	STD
	@ 50K	0.036	•	0.075	0.9	3.4	0.03	0.05		1	5.	*	•	0.02	0.07
	@ UL	0.039	*	0.090	1.0	4.2	0.03	0.07	•	1	8.		0.01	0.02	0.09
	@ 50°F & 4K	0.086	*	0.150	0.9	3.4	0.02	0.05	•	3	0.	•	*	*	*
	[g/mi]			NMHC+NC (compo		CO [g (comp		NMHC [g/ml]		co [g/mi] 06]		C+NOx [SC03]		g/mi] :03]
@ 20°	F& 50K	7.17		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	7.3	SFTP @ 4	000 miles	*	*	*	*	0.01	0.60	1.0	11.8	0.01	0.44	0.4	4.0
STD	12.5	SFTP	@ * miles	•	•	*	*	*	*	*	•	*	*		*

Evaporative Family		3-Days Diurnal + Hot Soak (grams/test) @ UL		2-Days Dlurnal + Hot Soak (grams/test) @ UL		ig Loss ille) @ UL	On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
ANSXR0132PBA	0.40	0.65	0.44	0.85	0.00	0.05	0.05	0.20	
ANSXR0174PBA	0.25	0.90	0.26	1.15	0.00	0.05	0.04	0.20	
*	*	*	*		*		*	•	
•	•	* .	•	•	*	**	*	*	

* = not applicable; UL=useful life; PC=passenger car; LDY=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger, CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

2010 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE ("=N/A or full in-use; A/E=exh. / evap, intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		
INFINITI	QX56 2WD	ANSXR0174PBA	1	5.6	*	*	SFTP .	Full
INFINITI	QX56 4WD	ANSXR0174PBA	1	5.6	•	•	SFTP	Full
NISSAN	ARMADA 2WD LE PLATINUM	ANSXR0174PBA	1	5.6	*	*	SFTP	Full
NISSAN	ARMADA 2WD LE TITANIUM	ANSXR0174PBA	1	5.6	•	*	SFTP	Full
NISSAN	ARMADA 2WD SE	ANSXR0174PBA	1	5.6	•	*	SFTP	Full
NISSAN	ARMADA 4WD SE	ANSXR0174PBA	1	5.6	*	*	SFTP	Full
NISSAN	ARMADA 4WD LE PLATINUM	ANSXR0174PBA	1	5.6	*	•	SFTP	Full
NISSAN	ARMADA 4WD LE TITANIUM	ANSXR0174PBA	1	5.6	*	•	SFTP	Full
NISSAN	TITAN 2WD LE SWB	ANSXR0174PBA	1	5.6	*	*	SFTP	Full
NISSAN	TITAN 2WD SE LWB	ANSXR0174PBA	1	5.6		*	SFTP	Full
NISSAN	TITAN 2WD SE SWB	ANSXR0174PBA	1	5.6	*		SFTP	Full
NISSAN	TITAN 2WD XE LWB	ANSXR0174PBA	1	5.6	*	*	SFTP	Full
NISSAN	TITAN 2WD XE SWB	ANSXR0174PBA	1	5.6	*	*	SFTP	Full
NISSAN	TITAN 4WD LE SWB	ANSXR0174PBA	1	5.6	*	•	SFTP	Full
NISSAN	TITAN 4WD PRO-4X SWB	ANSXR0174PBA	1	5.6	*	. *	SFTP	Full
NISSAN	TITAN 4WD SE LWB	ANSXR0174PBA	1	5.6	•	•	SFTP	Full



NISSAN MOTOR COMPANY, LTD.

EXECUTIVE ORDER A-015-0545-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

NISSAN	TITAN 4WD SE SWB	ANSXR0174PBA	1	5.6	*	*	SFTP	Full
NISSAN	TITAN 4WD XE LWB	ANSXR0174PBA	1	5.6	*	*	SFTP	Full
NISSAN	TITAN 4WD XE SWB	ANSXR0174PBA	1	5.6		*	SFTP	Full
NISSAN	PATHFINDER 4WD LE	ANSXR0132PBA	1	5.6	*	*	SFTP	Fuli