

DAIMLER AG

EXECUTIVE ORDER A-003-0414-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP		N	VEHICLE TYPE C=passenger car; LDT=light-duty IDV=medium-duty vehicle; LVW≕l vehicle weight; ALVW=adjusted I	STAND/ (LEV=lov UL	UST EMISSION ARD CATEGORY w emission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVRI EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE					
201	1 1	BMBXJ05.5U2A			PC and LDT > 6,000 pounds ((PC; LDT > 5,750 pounds AL)	L	EV II ULEV	120K / 150K	Gasoline					
No.		EVAPORATIVE FAMILY (EVAF)			SPECIAL FEAT EMISSION CONTROL S	URES & SYSTEMS	S (ECS)	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S #AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust						
1	BMBXR0168LNA				2TWC,2HC	D2S(2),SF	I, AIR,OBD(AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust						
2	2 BMBXR0170LNC			2		*		gas recirculation AIR/PAIR=secondary air injection/pulsed						
3	3 BMBXR0165LNC			3		*			TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
4				4		*		diagnostic prefix 2=paralle	el (2) suffix=series					
EVA No.		ECS ENGINE No. SIZE (L)			VEHICLE VEHICLES SUBJECT TO SFTP MAKES & MODELS STANDARDS ARE UNDERLINED									
1		1	5.5		MERCEDES-BENZ: (PC) SL550									
2		1 4.7			MERCEDES-BENZ: (LDT > 5,750 pounds ALVW) GL 450 4MATIC									
2		1 5.5			MERCEDES-BENZ: (LDT.) 5.750 pounds ALVVV) ML 550 4MATIC / GL 550 4MATIC / G550									
3		1 5.5			MERCEDES-BENZ: (PC) CLS 550 / E 550 / E 550 (coupe) / E 550 (Convertible) / E 550 4MATIC									
*		*	*											
*		*	*											
•		*	*											

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (The STD and CERT in parentheses are those applicable to the LDT2 models, if different.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF = * CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
STD PC/LD		TD T2	NMOG CERT	NMHC CERT	NMHC STD	mg= milli g	ram mi=ı	. [g/mi]=run mile K=1	ning loss 000 miles	F=d	legrees F	hrenheit	on-board r= SFTP=sup	efueling vap plemental fed —	or recovery deral test pr	g=gram ocedure	
0.03	5 0.0	43	[g/mi]	[g/mi]	[g/mi]	CO	[g/mi]	NO	x [g/mi]		НСНО [mg/mi]	PM [g	g/mi]	Hwy NO	x [g/mi]	
0.03	, 0.0	3.043	[9/111]			CERT	STD	CERT	ST	D (CERT	STD	CERT	STD	CERT	STD	
*	@	50K	0.025		0.040	0.5	1.7	0.04	0.0	5	0.4	8	*	*	0.02	0.07	
S .		@ UL	0.042		0.055	0.8	2.1	0.05	0.0	7	1 .	11	*	0.01	0.03	0.09	
	@ 5 0°F	& 4K	*	*	*	*	*	*	*		*	*	*	*	*	*	
CO [@ 20	g/mi]	SFTP 1 =	@ 4K (SULE	EV, ULEV, er 1. TLEV)	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NO [g/mi] [US				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50			@ UL (Tier		CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD	
CERT	3.5	A SYLT		SFTP 1	*	*	*	*	0.11	0.14	4 1.	1 8.0	0.05	0.20	1.8	2.7	
STD	10.0		74	SFTP 2	*	*	*	*	*	*	*	*	*	*	*	*	
@ LII	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVA	EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
@ UL	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	0.45	4	0.00	0.02	0.53	*	0.00	0.08	0.29	*	0.0	0.01	*	*	*	*	
STD	0.50	0.65	0.05	0.20	0.90	1.15	0.05	0.20	0.50	0.65	0.0	5 0.20) *	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).



DAIMLER AG

EXECUTIVE ORDER A-003-0414-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 30 day of April 2010

Annette Hebert, Chief

Mobile Source Operations Division