## CHRYSLER GROUP LLC

EXECUTIVE ORDER A-009-1130 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI						VEHICLE TYPE  C=passenger car; LDT=light-duf  MDV=medium-duty vehicle; LVW=  vehicle weight; GVW=gross \(\begin{align*} \text{V} & \	=loaded	STANI (LEV=low transition	AUST EMISSION DARD CATEGORY emission vehicle; TLEV al LEV; ULEV=ultra LEV LEV=super ULEV)		FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
201	2 CC	CCRXJ02.44P1				C; LDT: ≤ 6000# GVW, 0-375	50 LVW		LEV II LEV	150K / 150K	Gasoline (Tier 2 Unleaded)				
No.		VAPORATIVE AMILY (EVAF)				SPECIAL FEATURES &  EMISSION CONTROL SYSTEMS (ECS)  * = not applicable				WU= warm-up cat. O2S/HO2	t. ADSTWC=adsorbing TWC 2S=oxygen sensor/heated O2S				
1	CCRXR0	CRXR0112PK0				TWC,	HO2S(2), 5	SFI, OBD(P	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsec						
2	*						*		AIR MFI/SFI= multiport fuel injection/sequential MFI						
3	*	*			3		*			TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
4	*				4		*		diagnostic prefix 2=parallel (2) suffix=series						
EVAI No.	ECS No.	ECS EN				VEHICLE MAKES & MODELS			JECT TO SFTP RE UNDERLINED	ABBREVIATIONS: (PC=passenger car; LDT=light-duty truck)					
1	1		2.0				Jeep: Compass 2WD, Patriot 2WD (LDT, 0-3750 LVW)								
1	1		2.0				Dodge Caliber (PC)								
1	1 2.4					Jeep: Compass 2WD, Patriot 2WD (LDT, 0-3750 LVW)									
1	1	1 2.4					Dodge Caliber (PC)								

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *					NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day digmal+bnt-soak RL [a/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram												
CER	CERT		NMO		NMHC CERT	STD [g/mi]	mg=millig		mile K=1	000 miles	F=de	grees F	ahrenheit	SFTP=s	upplemental fe	deral test p	rocedure	
			CERT				CO	[g/mi]	NO	NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
0.03	4	0.035	[g/mi	]	[g/mi]	[g/m]	CERT	STD	CERT	STD	C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	@ 50K 0.029		*	0.075	0.5	3.4	0.01	0.05	*		15 *			0.003	0.07	
		@ UL	0.029	9	*	0.090	0.5	4.2 3.4	0.01	0.07		*	18	*	0.01	0.003	0.09	
L to be	@ 50	°F & 4K	0.072	2	•				0.01	0.05		*	30	*	*			
CO [ @ 20		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)				NMHC+NOx [g/mi] (composite)		ni] CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50						CERT	STD	CERT	STD	CERT	STD	CE	ERT ST	D CE	RT STD	CERT	STD	
CERT	1.3	100	SFTP @ 4K		*	*	*	*	0.02	0.14	0	.4 8.	0 0	.04 0.20	0.6	2.7		
STD	10.0			SFTP @ UL		*	*	*		*						*	*	
1828 NO 650	E	EVAPORA	ATIVE F	AMILY	<b>/1</b>	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3					EVAPORATIVE FAMILY 4			
@ UL	3-D	2-D	F	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	R	L OR\	/R 3-	D 2-D	RL	ORVR	
CERT	0.46	0.50	0.0	000	80.0	*	*	*	*	*	*					*		
STD	0.50	0.6	5 0.	.05	0.20	*	*	*	*	*	*		*		*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

## CHRYSLER GROUP LLC

EXECUTIVE ORDER A-009-1130 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(iii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer,

## BE IT FURTHER RESOLVED:

Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

**Mobile Source Operations Division**