GENERAL MOTORS LLC

EXECUTIVE ORDER A-006-1926

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED:

The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

			TEST	GROUP INFORM	ATION					
MODEL YEAR	TEST GRO	OUP VEHIC	LE CLASS(ES)	FUE	L CATEGORY		FU	EL TYPE		
2015	FGMXV01.8	3031	PC	DEDICA	TED SINGLE FUE VEHICLE	L	G	GASOLINE		
	USEFUL LIF	E (miles)	VEHICLE E	MISSION CATE	GORY	IN	TERIM / INTERME	EDIATE IN-USE STD		
EXH/C	RVR	EVAP	FTP		SFTP		FTP	SFTP		
150,	000	150,000	LEV3 SULEV30	LEV3 C	OMPOSITE	*		NMOG+NOx		
SPECIAL I	FEATURES &	EXHAUST EMISSION O	ONTROL SYSTEMS		OBD STATUS		ENGIN	E DISPLACEMENT (L)		
1	Т	WC(2), HO2S(2), SFI, /	AIR '	FULL	ALL MOI	DELS				
+		*		PARTIAL				1.8		
		•	700	PARTIAL WITH FINES	•					
		E	APORATIVE & REFUEL	ING (EVAP/ORV	R) FAMILY INFOR	MATION				
	EVAP / O	RVR FAMILY	EVAPOR	RATIVE STD CA	TEGORY	E	VAP EMISSION ST	TD VEHICLE CLASS		
	FGMX	R0095700		LEV2			Р	C		
	FGMX	R0117704		LEV2			PC			
	•	*		*			*			
	1.		EMISSIO	N CREDIT INFO	RMATION					
	· A	LLOWANCE FOR TEST	GROUP		G CREDIT FOR	MMOGC	REDIT FOR DOR	OPTIONAL EXH. STD FOR		
BASEL	NE PZEV	AT PZEV	TZEV	NON-	ZEV ZERO-EVAP	NMOG C		WORK TRUCKS		
ALL N	IODELS	•	*		N		N	N ,		
			NMOG AND FL	EET AVERAGE	INFORMATION					
NMOG RAF	CH4 RAF	NMOG/NMHC RATIO	HCHO/NMHC RATIO		OG+NOX FLEET DT (0-3750 LVW) (c	ı/mi)	NMOG+NOX FLEET STD LDT (3751 LVW- 8500 GVWR) + MDPV (g/ml)			
*	*	1.10		STD PC+LDT (0-3750 LVW) (g/mi) 8500 GVW				0.119		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG+NOx Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV, amended December 6, 2012).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT, and MDV, amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the

GENERAL MOTORS LLC

EXECUTIVE ORDER A-006-1926

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of April 2014.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

EXECUTIVE ORDER A-006-1926

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50 °F, 20 °F)

	FUEL TYPE	CH4=methane; NMOG=non-CH4 organic gas; HC=nydrocarbon; NMHC=non-CH4 HC; CU=carbon monoxide; NOX=oxides of nitrogen; HCH0=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2DHS/3DHS [g HC/test]=2/3 days diumal+hot-soak; RL [g HC/m]=running loss; ORVR [g HC/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram; ml=mile; K=1000 miles; F=degrees Fahrenheit; FTP=federal test procedure; SFTP=supplemental FTP										
		NMOG+N	Ox (g/mi)	. CO (g/mi)	HCHO ((mg/mi)	PM (g/mi)	HWY NMOG	+NOx (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP @ 50K	*	*	*	*	*	*	*		ŵ		*	
FTP @ UL	GASOLINE-LEV3 E10	0.018	0.030	0.2	1.0	*	4	*	0.01	0.002	0.030	
20°F @ 50K	GASOLINE-COLD CO LOW OCTANE	•	*	0.6	10.0	*	*	*	*		*	
50°F @ 4K	*		*		*	*	*	*	*	*	*	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	FUEL TYPE		US06 / UC (LA92)				SC03				COMPOSITE					
		NMOG+NOx (g/mi)		CO (CO (g/mi) PM (mg/mi)		ng/mi)	NMOG+NOx (g/mi)		CO (g/mi)		NMOG+NOx (g/mi)		CO (g/mi)		
124		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	BIN	CERT	STD
@ UL	GASOLINE-LEV3 E10	*		*	*	*			*		*	0.018	0.140	0.050	1.1	4.2

WHOLE VEHICLE EVAPORATIVE/ORVR EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	FUEL TYPE	WHOLE VEHICLE EVAPORATIVE TESTING						RUNNING LOSS		ON-BOARD REFUELING	
		3-DAYS DIURNAL + HOT SOAK (g/test) @ UL			2-DAYS DIURNAL + HOT SOAK (g/test) @ UL			(g/mi) @ UL		VAPOR RECOVERY (g/gallon) @ UL	
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD	CERT	STD
	GASOLINE - CA PHASE 2	0.32	0.35	*	0.31	0.35	* .	0.000	0.05	*	*
FGMXR0095700	GASOLINE-TIER2 UNLEADED	*	*	*	*	*	*	*	*	0.01	0.20
FGMXR0117704	GASOLINE - CA PHASE 2	0.32	0.35	*	0.31	0.35	*	0.000	0.05	*	•
	GASOLINE-TIER2 UNLEADED	*	*	*	*	*	*	*	*	0.02	0.20

FUEL ONLY & CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	FUEL TYPE		FUEL ONLY EVAP				
		3-DAYS DIURN/ (g/test		2-DAYS DIURN/ (g/test)	AL + HOT SOAK	CANISTER BLEED (g/test)	
		CERT	STD	CERT	STD	CERT	STD *
FGMXR0095700	GASOLINE - CA PHASE 2	0.04	0.0	*	0.0	*	•
FGMXR0117704	GASOLINE - CA PHASE 2	0.04	0.0	*	0.0	*	* -

*=not applicable; #=pounds; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT≤6000#GVWR,0-3750#LVW; LDT2=LDT≤6000#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#LVW; LDT4=LDT 6001-8500#GVWR,5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-10000#GVWR; MDV5=MDV 10001-14000#GVWR; MDPV=medium-duty passenger vehicle; ECS=emission control system; CERT=certification; STD=standard; FEL=family emission limit; GVWR=gross vehicle weight rating; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; ZEV=zero-emission vehicle; PZEV=partial ZEV; AT PZEV=advanced technology PZEV; TZEV=transitional ZEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; HAC=HC adsorbing catalyst; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3=selective catalytic reduction-urea/ammonia; NH3OC=ammonia oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF=diesel particulate filter (active); GPF=PM filter for spark-ignited engine; HO2S/O2S=heated/oxygen sensor; WR-HO2S or AFS=wide range/linear/heated air-fuel ratio sensor; NOXS=NOx sensor; PMS=PM sensor; RDQS=reductant quality sensor; NH3S=ammonia sensor; EGR=exhaust gas recirculation; DFI/IFI=direct/indirect fuel injection; tipletion; (belt driven)/(electric driven); PAIR=pulsed AIR; SFI/MFI=sequential/multiport fuel injection; DFI/IFI=direct/indirect fuel injection; trap injection (belt driven)/(electric driven); PAIR=pulsed AIR; SFI/MFI=sequential/multiport fuel injection; DR=direct ozone reducing; HCT=hydrocarbon trap; BCAN=bleed carbon canister; prefix 2=parallel; (2) suffix=senes; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85-CARB: 85% ethanol+15% CA Phase2 gasoline; E85-EPA: 85% ethanol+15% Tier2 unleaded gasoline; E10-CARB: 10% ethanol+90% CA Phase2 gasoli

2015 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEHICLE CLASS	ENGINE (L)	TRANSMI SSION	EVAPORATIVE FAMILY	EXHAUST ECS	OBD	PZEV DESIGNATION
CHEVROLET	SONIC	PC	1.8	SA, M	FGMXR0095700	1	F	PZEV

California	Environmental	Protect	ion	Agency
OB Ai	r Resou	rces	B	oard

GENERAL MOTORS LLC

EXECUTIVE ORDER A-006-1926

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

CHEVROLET	SONIC 5	PC	1.8	SA, M	FGMXR0095700	1	F	PZEV
CHEVROLET	CRUZE	PC	1.8	SA, M	FGMXR0117704	1	F	PZEV