

Executive Order: A-015-0806

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP INF	FORM	ATION					
MOD	1 11	TEST GROUP			VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
201	9 KNSKV03.7NAA PC						DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
	USEFUL	LIFE (miles)	VEHICLE EMISSION CATEGOR			ORY	INTERIM / IN	TERM	RMEDIATE IN-USE STD				
EXH/ORVR EVAP				FTP S			SFT	TP FTP			SFTP		
1	50000	150000		LEV3	ULEV125 LEV 3 COM		POSITE *			*			
SPI	ECIAL FE	ATURES & EX	HAUS TEMS	T EMISSIO	ON CONTRO	L		OBD S	EN	ENGINE DISPLACEMENT (L)			
1		2TWC(2), 2H	02S, 2	2WR-HO2S	s, SFI		F	ULL	*	1			
*	*							RTIAL	ALL MODELS	11	3.7		
*	* PARTIAL WITH FINES												
		E	/APOF	RATIVE &	REFUELING	(EVAF	/ORV	R) FAMILY	INFORMATION	V			
EV	AP / ORV	R FAMILY	EVAF	PORATIVE	STD CATE	GORY	RY EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES		
	KNSXR0120MBA				LEV 2			PC			*		
		•		-	EMISSION C	REDIT	INFO	RMATION					
					EDIT FOR NON-PZEV ZERO-EVAP			NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
	И								N		N		
	NMOG AND FLEET AVERAGE INFORMATION												
NMO0 RAF	OG CH4 NMOG/NMHC HCHO/NMHC PC+				PC+LDT (MOG+NOX FLEET STD C+LDT (0-3750 LVW) (g/mi)) LDT	NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	* 1.10 * 0.07						0.083 *					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



Executive Order: A-015-0806

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of January 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-015-0806

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 3 of 4

ATTACHMENT

	EX						IVE EMI									S	
		E	(HAU	STEM	ISSIC	N STAN	IDARDS A	ND CE	RTIFICA	ATION L	EVELS	(FTP, HV	VFET	, 50°F, 20)°F)		
		FUEL TYPE		moi adju OR	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP												
							IOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)			HCHO (mg/mi)			PM (g/mi)
			,	C	ERT	STD	CER	T S	TD	CERT	STD	CEF	ET.	STD	CERT	STD	
FTP@5	0K	*			*	*	*		*	*	*			*	*	+	
FTP@U		LEV3	ASOLINE- EV3 E10 PREM		.046	0.12	5 0.5	2	.1	*		N.		4	*	0.01	
50°F @	GASOLINE-		0.	.086	0.25	0 0.4	2	.1	*				16				
										NI	MOG+NO	Ox (g/mi)			CO (g/m	i)	
						FUEL T	YPE				RT	STD		CER	Т	STD	
HWFE	r@5	50K				*						*		7			
HWFE	Т@	UL		G	SOLI	NE-LEV	3 E10 PR	EM		0.0	013	0,12	5				
20°F	@ 50	K	COLD	CO E	10 P	REMIUM	GASOLIN	E (TIE	ER3)					0.6		10.0	
				SF1	PEX	HAUST	EMISSION	STANI	DARDS	AND C	ERTIFIC	ATION L	EVE	LS			
						US06			SC03				COMPOSI		TE		
	FUE	UEL TYPE		(1)	NMOG+NOx (g/mi)		CO (g/mi)		PM (mg/mi)		NMOG+NOx (g/mi)		NIV	IOG+NO) (g/mi)	CO (g/mi	PM (mg/mi	
@ 4K		*		ERT				-9		,	•	*	· OMG			1	
				TD		*	*			* *					100		
		CE		RT		*	* *		*	1	•	*	0.065		0.5	*	
@ UL	GASOLINE- LEV3 E10 PREM			TD	<u> </u>		. *	. * 1		*		*		0.090	4.2	*	
BIN		BIN	1									0.110		1 = 1			
		1	WHOL	E VEH	IICLE	EVAPO	RATIVE E	MISSIO	N STA	NDARD	S AND C	ERTIFIC	ATIC	N LEVE	_S		
							WHOLE \	/EHICL	E EVAF	PORATI	/E TEST	ING					
EVAPORATIVE		FUEL TYPE			3DHS (g/test) @ UL				2DHS (g/test) @		@ UL		RL (g/mi) @ (D UL		
					CERT		STD	FEL CE		RT STD		FEL		CERT		STD	
KNSXE	0120	OMBA		LINE	1 0 30 1		0.50	*	0.	30	0.65		0.001		01	0.05	



Executive Order: A-015-0806

New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/g	gallon) @) UL	FUEL'TYPE		IG TEST) @ UL	2DHS R (g/test		BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
KNSKR0120MBA	GASOLINE - TIER 2 UNLEADED	0.01 0.20		*	*	*	*	*	*	*		
	EFFECTIVE I	EAK D	IAMET	ER STANDARI	AND CE	RTIFICA	TION LEV	EL (INCH	HES)			
EVAPORATIVE	FAMILY	LEA	K FAMIL	.Υ	CE	RT '			STD			
*		*		*				*				

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1; LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium-duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT; certification; STD: standard; FEL: family emission limit; GWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER; equivalent AER; PHEV; plug-in hybrid electric vehicle

	2019 MODEL	YEAR: VE	HICLE M	ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	OBD
INFINITI	. Q70	PC	3.7	SA7	KNSKR0120MBA	1	P
NISSAN	3702	PC	. 3.7	M6,SA7	KNSKR0120MBA	1	P
NISSAN	370Z ROADSTER	. PC	3.7	SA7	KNSKR0120MBA	1	P