-		
(X)	CALLE	ORNIA RCES BOARD
A	CALIF	ORNIA
ALC INT	AIR RESOU	RCES BOARD

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FOR	ATION	· 7				
MODE		EST GROUP		VEHICI	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2020	LH	NXV02.4LBM			PC		I	DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								CATEGORY INTERIM / INTERMEDIATE IN-USE ST					
EXH/ORVR EVAP FTP							SF	P	SFTP				
15	150000 150000 LEV3 ULEV125 LEV						3 CO	MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS OBD STATUS ENGINE DISPLACEM										IGINE DISPLACEMENT (L)			
1 WU-TWC, TWC, WR-HO2S, HO2S, DFI FULL *													
*			*				P.	ARTIAL	ALL MODELS	State of the	2.4		
* * PARTIAL WITH *													
		EV	APOR	RATIVE &	REFUELING	(EVA	P/OR	R) FAMILY	INFORMATIO	N			
EVA	P / ORV	R FAMILY	EVAF	PORATIVE	STD CATE	GORY			SSION STD E CLASS	SI	PECIAL FEATURES		
I	LHNXR01	21VFA		L	EV 2			F	PC .	8	*		
				E	EMISSION C	REDIT	INFC	RMATION					
								OPTIONAL EXH. STD FOR WORK TRUCKS					
	121	N			N			N N					
				NMOG	AND FLEE	T AVE	RAGE	INFORMA	TION	•			
NMOG RAF	CH4 RAF					0-375					NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		0.05	C	0.065			0.074		*		
	A	16 1/11	1	1.1. 5	C			D' 1		-	ntral Custome Dhase		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)

$\sim$					
A	CA	LI	FO	RNI	A
ME INY	AIRR	ESC	URCE	S BOA	RD

## **BE IT FURTHER RESOLVED:**

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## **BE IT FURTHER RESOLVED:**

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 🥻 day of March 2019.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

														1				
CALIFORNIA AIR RESOURCES BOARD								HONDA MOTOR CO., LTD.				Executive Order: A-023-0740 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4						
							A	ΤΤΑΟ	CHN	IEN	Г							
	EXH	AUS	T AN	D EV	APO	RATIV	EEMIS	SION	STA		RDS AN	D CER						
											LEVELS							
	FU	JEL T		CH4: i monox adjust ORVR	metha kide; N ment f [g H0	ne; NMC NOx: oxic factor; 2I C/gallon	DG: non- des of nit DHS/3DH dispense	CH4 org rogen; H IS [g H0 d]: on-b	anic g ICHO C/test] oard r	gas; H0 : forma  : 2/3 da refuelin	C: hydroca aldehyde; ays diurna ig vapor re cest proce	rbon; NM PM: partic I+hot-soa	HC: r culate k; RL ; gran	non-CH4 matter; [g HC/m	HC; CC RAF: re ni]: runn	activ	ity SS <sup>.</sup>	
				NI	NMOG+NOx (g/mi)			CO g/mi)			NOx (g/mi)		HCHO (mg/mi)			PM (g/mi)		
				CER		STD	CERT		D	CERT		CER		STD	<sup>,</sup> CEF		STD	
FTP@5	0K	*		*		*	*	*		*	*	*		*	*		*	
FTP@l		SOLI EV3 E		0.01	.3	0.125	0.2	2.	1	*	*	0		4	*		0.01	
50°F @	4K	*		*		*	*	*		*	*	*		*				
					FL	JEL TYF	ΡE	NI			NMOG+N				CO (g	CO (g/mi)		
								CE		CERT	STD		CER	रा	STD			
	T @ 50k					*				*	*			2120				
HWFE	T @ UL			Gi	ASOLI	INE-LEV	3 E10 0.0			.005	05 0.125							
20°F	@ 50K	С	OLD C	CO E10	REG	ULAR G	ASOLINE	SOLINE (TIER3)			· ·	0.			4 10.0			
				SFTP	EXHA	USTEM	IISSION	STAND	ARDS	SAND	CERTIFIC	CATION L	EVE	LS				
	e en E			US06						SC0	3	CC		OMPOSITE				
	FUEL	TYPE		NN	lOG+ (g/mi		CO (g/mi)				DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)		)x C (g/	O mi)	PM (mg/mi)	
@ 4K	· *		CER				*			- - -	*							
			STE		*		*				*	*						
	GASOL THE		CER		*		*		*		*	*		0.034	1.	. 4	*	
@ UL	LEV3		STE		*		. *		*		*	*	* 0.083		4	2	*	
			BIN	1044000										0.100		•		
		W	HOLE	VEHIC	LEEV						DS AND		ATIC	N LEVE	LS			
	ORATIV	'E F	UEL .	ТҮРЕ	-		HOLE VE		EVA		RATIVE TESTING 2DHS (g/test) @ UL RL (g/mi) @ UL					UL		
FA	MILY			3	CE				CE	RT	STD	FE						
		ASOLI A PHZ		0.2		.50			.39	0.65	*	×				STD 0.05		
C	RVR / F	UEL	ONLY	/ CAN	ISTER		EVAPC	RATIV	EEMI	SSION	STANDA	RDS AN	D CE	RTIFICA	TION L	EVE	LS	
											NLY EVA							
	ORATIV MILY							3D			G TEST @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
			JEL T		ERT	STD			CE	ERT	STD	CERT		STD	CERI	•	STD	
LHNXR	.0121VF	A	SOLIN TIER NLEAD	2 (	0.02	0.20		*		*	*	*		*	* *		*	
												-						

	FORNIA URCES BOARD		NDA MOTOR CO., LTD.	Executive Order: A-023-0740 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4							
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)											
EVAPORATIVE FAMILY	LEAK FAMILY		CER	Г	STD						
*	*		*		*						
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen secondary air injection (belt direct/indirect fuel injection; fines on-board diagnostic; D suffix: series; CNG/LNG: cor E10: "10%" ethanol ("90%"ga	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: MI ': heavy-duty vehicle; E0 vehicle weight rating; L per ULEV; ZEV: zero-en IAC: HC adsorbing cata : selective catalytic redu izer; DPF: diesel particu HO2S or AFS: wide rang sor; NH3S: ammonia se driven)/(electric driven); TC/SC: turbo/super chan DR: direct ozone reduci npressed/liquefied natu asoline) fuel; A: automa ission; SCV: selectable e transmission: OT: oth	01-850 DV 850 CS: en VW: Ic missio alyst; V uction- ulate fil ge/line ensor; PAIR: rger; C ng; HC ral gas tic (wit contin	00#GVWR,3751-5750 01-10000#GVWR; MI nission control syster paded vehicle weight; n vehicle; TZEV: tran VU: warm-up catalysi urea/ammonia; NH39 lter (active); GPF: PM ar/heated air-fuel rati EGR: exhaust gas re pulsed AIR; SFI/MFI cAC: charge air coole CT: hydrocarbon trap; s; LPG: liquefied petro h lockup); M: manua uously variable trans smission: AER: all-el	J#ALVVV; LD14: DV5: MDV 1000 n; CERT: certific ALVW: adjusted sitional ZEV; TV t; NAC: NOx ads OC: ammonia ov d filter for spark-i o sensor; NOX S circulation; EGR : sequential/mul r; FFH: fuel fired ; BCAN: bleed ca obleum gas; E85: transmission; AM: au ectric range; EA	ignition catalyst, CTOX/PTOX. ignited engine; HO2S/O2S: S: NOx sensor; PMS: PM sensor; RC: EGR cooler; AIR/AIRE: Itiport fuel injection; DFI/IFI: I heater; F/P/\$: full/partial/partial with arbon canister; prefix 2: parallel; (2) "85%" ethanol ("15%"gasoline) fuel; GA: semi-automatic transmission; CV: itomated manual transmission; AMS: VER: equivalent AER; PHEV: plug-in						

## 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE EXH FAMILY ECS		OBD
ACURA	TLX L4 FWD	PC	2.4	AMS8	LHNXR0121VFA	1	P
ACURA	TLX L4 FWD A-SPEC	PC	2.4	AMS8	LHNXR0121VFA	1	P