| and the second | | | |
|----------------|----------------|-------|-------|
| (A) | CALL | LMD | NILA |
| 1 Prod | has good her 1 | 1 1 1 | 1010 |
| ATT | AIR RESO | URCES | BOARD |

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| | | | - | | TEST GRO | UP IN | IFORI | ATION | | | | | |
|--|------------------------|---|----------------|-------------------|--------------------------------------|-------|--------------------|---|--|----------------|--|--|--|
| MODE | | ST GROUP | | VEHICLE CLASS(ES) | | | | FUEL CATEGORY | | | FUEL TYPE | | |
| 2021 | MGMXT06.2375 LDT4 | | | | | | I | DEDICATED SINGLE FUEL VEHICLE | | | GASOLINE | | |
| USEFUL LIFE (miles) VEHICLE EMISSION CATEGORY INTERIM / INTERMEDIATE II | | | | | | | MEDIATE IN-USE STD | | | | | | |
| | /ORVR | EVAP | | | -TP | | SF | ГР | FTP | | SFTP | | |
| 15 | 0000 | 0 150000 LEV3 ULEV125 LEV 3 COMPOSITE * | | | | | * | | PM | | | | |
| SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS | | | | | | L | | OBD STATUS | | | ENGINE DISPLACEMENT (L) | | |
| 1 DFI, 2TWC, 2H02S(2) | | | | | | | | FULL | FULL * | | | | |
| * | * * | | | | | | Р | ARTIAL | ALL MODELS | LL MODELS 6.2 | | | |
| * | * * | | | | | | | TIAL WITH FINES | * | | | | |
| 2000 - 101 - | 20 | E | VAPO | RATIVE & | REFUELING | EVA | P/OR | VR) FAMIL | Y INFORMATIO | N | | | |
| EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR | | | | | | GOR | (| EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATUR | | | PECIAL FEATURES | | |
| M | IGMXR01 | 7350D | L | EV 3 OPTI | ON2 WITH | FEL | LDT4 | | | | HCT | | |
| M | IGMXR02 | 2450C | L | EV 3 OPTI | ON2 WITH | FEL | | LDT4 HCT | | | HCT | | |
| | THE FILE COLOR STUDIES | un sennen und des sone de senen este est | | E | EMISSION C | REDI | TINFO | RMATION | na ing sang tersengan sang ang ang ang ang ang ang ang ang ang | LEGICE VERSION | | | |
| NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY | | | | | NOG CREDIT FOR NON-PZEV ZERO-EVAP | | | NMOG CREDIT FOR DOP | | R | OPTIONAL EXH. STD FOR WORK TRUCKS | | |
| | | N | | | N | | | | N | | N | | |
| | | n a folgan georgene generalen er folgan generalen er folgan generalen er folgan generalen er folgan generalen e | saanan ay saho | NMOG | AND FLEE | t ave | RAG | EINFORMA | TION | | | | |
| NMOG RAF | CH4 RAF | FTP NMOG/NMHO RATIO | нс | HO/NMHC RATIO | PC+LDT | | | V) LDT | i+NOX FLEET S (3751 LVW-850 R) + MDPV (g/n | 0 | NWOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi) | | |
| * | * | 1.10 | | * | (| 0.058 | | | 0.065 | | * | | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)

| CALIFORNIA AIR RESOURCES BOARD | GENERAL MOTORS LLC. | Executive Order: A-006-2246 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4 |
|-----------------------------------|------------------------|---|
|-----------------------------------|------------------------|---|

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this $27 \frac{t0}{10}$ day of February 2020.

Kim Pryce

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

| ATTACHMENT | A | 8 | ΓA | C | Carlos a | Vo | - | | - |
|------------|---|---|----|---|----------|----|---|--|---|
|------------|---|---|----|---|----------|----|---|--|---|

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

| | | | | |)G+NOx g/mi) | | CO (g/mi) | | | lOx /mi) | | HCH mg/n | - | | Piv (g/m | |
|-----------------------------|--|--|-------------------------------|--------------------|-----------------|--------------|-------------------------------------|------------------|-------|---------------|--------------|-------------|------------------|--------|---------------------------------|---------------|
| | | | | CERT | STE | CER | T ST | D | CERT | STD | CER | T | STD | CEF | RT | STD |
| FTP@5 | OK | * | | * | * | * | * | | Ŕ | * | * | | × | * | | * |
| FTP@L | | SOLIN ER3 E | | 0.035 | 0.12 | 25 0.5 | 5 2. | 1 | * | × | × | 4 | | 0.002 | | 0.003 |
| 50°F @ | 4K | * | | * | * | * | * | | * | * | * | | × | | | |
| 14786 C & NOT 2 (C 47 X 14) | | | estanting meriod south Second | | | | and frankriger over 2 city over the | 711478 C.M. 1997 | N | MOG+NC | x (g/mi) | | | CO (9 | g/mi) | |
| | | | | | FUEL | YPE | | | Cł | ERT | STD | | CER | | | STD |
| HWFET @ 50K | | | | | * | | | | | * | × | | | | | |
| HWFE | T @ UL | | | GASOLINE-TIER3 E10 | | | | | | 001 | 0.125 | , | | | | |
| 20°F | @ 50K | © 50K COLD CO E10 REGULAR GASOLINE (TIER3) 1.6 1 | | | | | | | | .2.5 | | | | | | |
| | an de la carde la carde de | alant in outpetion | S | FTP E | XHAUST | EMISSIO | STAND | ARDS | AND C | ERTIFIC | ATION LI | EVEL | .S | | | |
| | | | | | | US06 | | | | SC03 | | | CO | MPO: | SITE | |
| | FUEL | TYPE | | | DG+NOx g/mi) | CO (g/mi) | CO PM (g/mi) (mg/mi) | | | G+NOx /mi) | CO (g/mi) | | OG+NOx (g/mi) | | CO /mi) | PM (mg/mi) |
| @ 4K | * | | CERT | - | * | * | | | | × | * | | | | | |
| | | | STD | | * | * | | | | ŵ | * | | | | | |
| | CERT | | | * | * | | 1 | | * | * | (| 0.025 | C | .5 | * | |
| @ UL | @ UL GASOLINE- STIER3 E10 ST | | | | * | * | | 6 | | * | * | | 0.077 | 4 | . 2 | * |
| | | | BIN | | | | | | | | | (| 0.120 | | N (7) program and an and a star | |
| | | WH | OLE V | EHICL | E EVAPO | DRATIVE I | EMISSION | V STA | NDARE | DS AND C | ERTIFIC | ATIO | N LEVE | _S | | |
| | | | | | | WHOLE | VEHICLE | EVAF | ORAT | IVE TEST | ING | | | | | |
| | ORATIV | E | FUEL T | YPE | 3DH | S (g/test) | @ UL | | 2DH | S (g/test) | @ UL | | R | L (g/n | ni) @ | UL |
| | | | | | CERT | STD | FEL | CE | RT | STD | FEI | L | CEF | T | | STD |
| MGMXI | R017350 | | GASOLI FIER3 | | 0.198 | 0.500 | 0.500 | 0.3 | 200 | 0.500 | 0.50 | 00 | 0.0 | 0 | | 0.05 |
| MGMXI | R022450 | CI | GASOLI TIER3 | | 0.314 | 0.500 | 0.525 | 0.4 | 165 | 0.500 | 0.52 | 25 | 0.00 0.05 | | | 0.05 |

| | CALIF AIR RESOL | FORM urces b | VIA Oard | | GENERAL MOTORS LLC. | | | Executive Order: A-006-2246 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicle: Page 4 of 4 | | | | | |
|--|---|--|---|---|--|---|---|---|---|--|--|--|--|
| ORVR / FU | EL ONLY / (| CANISTER | BLEED | EVAPORATIVE | EMISSION | STANDA | RDS AN | D CERTIFIC | ATION LEV | ELS | | | |
| | | | | | | | | ISTER BLEE | | | | | |
| EVAPORATIVE FAMILY | ORVR (| ORVR (g/gallon) @ UL | | | 3DHS RI (g/test) | | | | | | | | |
| | FUEL TYP | E CERT | STD | | CERT | STD | CERT | STD | CERT | STD | | | |
| MGMXR017350D | GASOLINE TIER3 E1 | 0 02 | 0.20 | GASOLINE- TIER3 E10 | * | * | * | * | 0.008 | 0.020 | | | |
| MGMXR022450C | GASOLINE TIER3 E1 | 1 11 112 | 0.20 | GASOLINE- TIER3 E10 | * | * | * | * | 0.012 | 0.020 | | | |
| | EFFECTIV | E LEAK D | IAMET | ER STANDARI | D AND CE | RTIFICA | TION LE | EVEL (INCH | IES) | | | | |
| EVAPORATIVE FAMILY LEAK FAMIL | | | Y | CERT ST | | | | STD | STD | | | | |
| MGMXR017 | 350D | MGMXR0 | 17350D | -LK1 * | | | | 0.02 | | | | | |
| MGMXR022 | 450C | MGMXR0 | 22450C | -LK1 * | | | | 0.02 | | | | | |
| uty passenger vo mission limit; GV JLEV: ultra LEV; DSTWC: adsorb CRC/SCR-N or ontinuous/period eated/oxygen se RDQS: reductant | ehicle; HDV: /WR: gross v SULEV: supe bing TWC; H/ SCRC-NH3: lic trap oxidiz ensor; WR-H(quality senso er; AIR/AIRE /IFI: direct/in | heavy-duty ehicle weig er ULEV; Z AC: HC ads selective c eer; DPF: di D2S or AFS or; NH3S: a : secondar direct fuel i | vehicle pht rating EV: zero sorbing c atalytic r esel par S: wide r ammonia y air inje niection; | MDV 8501-10000 ; ECS: emission of ; LVW: loaded ve -emission vehicle atalyst; WU: wan eduction-urea/an ticulate filter (acti ange/linear/heate a sensor; EGR: ex ction (belt driven) TC/SC: turbo/su DOR: direct ozone | control syste ehicle weigh a; TZEV: trai m-up cataly monia; NH: ve); GPF: P d air-fuel ra khaust gas r)/(electric dr per charger | em; CERT: t; ALVW: a nsitional ZI st; NAC: N 3OC: amm M filter for tio sensor; recirculatio iven); PAIF ; CAC: cha | certificat djusted l EV; TWC Ox adso onia oxid spark-ig NOXS: n; HP/LF R: pulsed rge air c | ion; STD: sta _VW; LEV: lov ;/OC: 3-way/c rption catalys dation catalys nited engine; NOx sensor; P EGR: High/l AIR; SFI/MF ooler; FFH: ft | ndard; FEL w emission oxidizing cat t; SCR-U or t; CTOX/PT HO2S/O2S PMS: PM sr _ow Pressur 1: sequentia | : family vehicle; alyst; r OX: : ensor; re EGR; | | | |

| MAKE | MODEL | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | EXH ECS | OBD |
|-----------|--------------|-----------|------------|------------|-----------------------|------------|-----|
| CADILLAC | ESCALADE 2WD | LDT4 | 6.2 | A10 | MGMXR017350D | 1 | P |
| CADILLAC | ESCALADE 2WD | LDT4 | 6.2 | A10 | MGMXR022450C | 1 | P |
| CADILLAC | ESCALADE 4WD | LDT4 | 6.2 | A10 | MGMXR017350D | 1 | P |
| CADILLAC | ESCALADE 4WD | LDT4 | 6.2 | A10 | MGMXR022450C | 1 | P |
| CHEVROLET | SUBURBAN 2WD | LDT4 | 6.2 | A10 | MGMXR022450C | 1 | P |
| CHEVROLET | SUBURBAN 4WD | LDT4 | 6.2 | A10 | MGMXR022450C | 1 | P |
| CHEVROLET | TAHOE 2WD | LDT4 | 6.2 | A10 | MGMXR017350D | 1 | P |
| CHEVROLET | TAHOE 4WD | LDT4 | 6.2 | A10 | MGMXR017350D | 1 | P |
| GMC | YUKON 2WD | LDT4 | 6.2 | A10 | MGMXR017350D | 1 | P |
| GMC | YUKON 4WD | LDT4 | 6.2 | A10 | MGMXR017350D | 1 | P |
| GMC | YUKON XL 2WD | LDT4 | 6.2 | A10 | MGMXR022450C | 1 | P |
| GMC | YUKON XL 4WD | LDT4 | 6.2 | A10 | MGMXR022450C | 1 | Р |