

**Initial Statement of Proposed Rulemaking
Amendments to the Low-Emission Vehicle Program**

**Mobile Source Division
Monitoring and Laboratory Division
9528 Telstar Ave.
El Monte, California 91731**

Date of Release: September 25, 1992

I. INTRODUCTION

On September 28, 1990, the California Air Resources Board (ARB or Board) adopted Resolution 90-58, approving the low-emission vehicles and clean fuels regulations. These regulations created four categories of low-emission vehicles which are required to be phased-in beginning in the mid 1990's. Because of the far-reaching, long-term nature of the regulations, the Board approved in Resolution 90-58 a process to periodically review the status of implementation of the regulations and to propose any appropriate regulatory modifications.

At a June 11, 1992 public meeting, the staff provided the Board with a status update of the progress being made by the industry to comply with the low-emission vehicle requirements. At the conclusion of this meeting, the Board adopted Resolution 92-46 which found that the low-emission vehicle standards continue to be technologically feasible within the required timeframes and that no changes to the standards or phase-in schedule are currently needed. However, both the Board and staff recognized that various amendments could be made to augment the regulations, improve their clarity, and ease their implementation. These amendments will be considered at a Board hearing scheduled for November 12-13, 1992 and are the subject of this report.

The amendments proposed by the staff cover a wide range of topics, from providing detailed procedures for certifying hybrid electric vehicles to adding reactivity adjustment factors for Phase 2 gasoline and inserting specific language to set forth penalties for non-compliance. Because many of the amendments concern very detailed aspects of the regulations, only the most important changes proposed by the staff will be described in this report. A detailed description of other changes can be found in Appendix A.

II. SUMMARY OF THE LOW-EMISSION VEHICLE REGULATIONS

For light-duty vehicles, the cornerstone of the low-emission vehicle program is the creation of four new categories of vehicles:

- o Transitional Low-Emission Vehicles (TLEVs)
- o Low-Emission Vehicles (LEVs)
- o Ultra-Low-Emission Vehicles (ULEVs)
- o Zero-Emission Vehicles (ZEVs)

For each category, a set of exhaust emission standards for non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) apply, as listed in Table I. (In this report, the term "low-emission vehicle(s)" is used to refer to any vehicle(s) certified to TLEV, LEV, ULEV, or ZEV standards, not just those certified to low-emission vehicle standards.)

Table I. 50,000 mile and 100,000 mile (in parentheses) exhaust emission standards for light-duty low-emission vehicles, in g/mi.

Passenger Cars and Light-Duty Trucks 0-3750 lbs. LVW

Category	NMOG	CO	NOx	HCHO
TLEV	0.125 (0.156)	3.4 (4.2)	0.4 (0.6)	0.015 (0.018)
LEV	0.075 (0.090)	3.4 (4.2)	0.2 (0.3)	0.015 (0.018)
ULEV	0.040 (0.055)	1.7 (2.1)	0.2 (0.3)	0.008 (0.011)
ZEV	-zero-	-zero-	-zero-	-zero-

Light-Duty Trucks 3751-5750 lbs. LVW

Category	NMOG	CO	NOx	HCHO
TLEV	0.160 (0.200)	4.4 (5.5)	0.7 (0.9)	0.018 (0.023)
LEV	0.100 (0.130)	4.4 (5.5)	0.4 (0.5)	0.018 (0.023)
ULEV	0.050 (0.070)	2.2 (2.8)	0.4 (0.5)	0.009 (0.013)
ZEV	-zero-	-zero-	-zero-	-zero-

LVW: Loaded Vehicle Weight

For comparison, the 50,000 mile federal (Tier I) standards that apply during the same timeframe are, for passenger cars, 0.25 g/mi non-methane hydrocarbons (NMHC), 3.4 g/mi CO, and 0.4 g/mi NOx. There are no federal standards for formaldehyde. (NMOG includes NMHC plus oxygenated compounds, specifically, alcohols and carbonyls.)

a. Phasing-In Low-Emission Vehicles

Rather than require certain percentages of vehicles to be phased-in at specified times, the low-emission vehicle program takes a more market-based approach to implementation. A categorized fleet averaging system has been established whereby vehicles certified to any combination of the low-emission vehicle categories, or to conventional vehicle standards (for example, 0.25 g/mi NMHC for passenger cars), may be produced as long as the overall fleet average requirement is met. Compliance with

fleet average requirements is determined by calculating the average NMOG emission standard to which a manufacturer's fleet of light-duty vehicles is certified. For example, if 50 percent of a manufacturer's fleet is certified to TLEV standards and 50 percent is certified to low-emission vehicle standards, the manufacturer's fleet average value is 0.100 g/mi NMOG ($0.50 \times 0.125 \text{ g/mi NMOG} + 0.50 \times 0.075 \text{ g/mi NMOG}$).

For passenger cars and small light-duty trucks, the fleet average requirements begin in 1994 at 0.25 g/mi NMOG and decline to 0.062 g/mi NMOG in 2003, as illustrated in Figure 1. Similar fleet average requirements have been established for larger light-duty trucks.




Figure 1. Fleet average requirements for passenger cars and light-duty trucks 0-3750 lbs. LVW.

The categorized fleet averaging approach provides considerable flexibility to manufacturers by allowing them to choose the mix of low-emission vehicles they produce in any given year. Additional flexibility is provided through the establishment of a marketable credit system. Manufacturers which produce more low-emission vehicles than needed to meet the fleet average requirements will earn credits. Credits may be banked internally for future use or traded/sold to other manufacturers.

In developing the regulations, an implementation schedule (Table II) was established which sets forth the phase-in percentages of each low-emission vehicle category used to compute the fleet average requirements each year. Manufacturers are not compelled to adhere to this schedule. They may vary the percentages of each vehicle category provided that their weighted average meets the fleet average requirements shown in Figure 1. For example, although ULEVs first appear in the schedule at 2 percent in 1997, no ULEVs have to be certified until the year 2000, when the fleet average requirement first falls below the NMOG standard for LEVs (refer to Figure 1).

Table II. Possible implementation schedule for low-emission vehicles, as percentages of California vehicle sales.

Year	TLEVs	LEVs	ULEVs	ZEVs*
1994	10%			
1995	15			
1996	20			
1997		25%	2%	
1998		48	2	2%
1999		73	2	2
2000		96	2	2
2001		90	5	5
2002		85	10	5
2003+		75	15	10

* Percent requirements for ZEVs are mandatory.

There is, however, one instance where implementation of a specific low-emission vehicle category is required. Beginning in 1998, large manufacturers that sell over 35,000 vehicles per year in California will have to certify specified percentages of their passenger cars and small light-duty trucks as ZEVs. Since ZEVs, by definition, have no tailpipe emissions of any pollutants throughout their lifetimes, widespread penetration of these vehicles is the ultimate goal of the ARB. A regulatory requirement for the production of ZEVs ensures that resources are devoted to the development of battery-powered electric vehicles and other potential ZEV technologies.

b. Reactivity Adjustment Factors

Compliance with the low-emission vehicle standards can be achieved with advanced emission control technology alone or in combination with cleaner-burning fuels. The California low-emission vehicle program is unique in that it considers the vehicle and its fuels as two components of a single system - a vehicle/fuel system.

Consistent with the system concept, the low-emission vehicle program is structured to accommodate a variety of different technologies and fuels. For the first time, the ozone-forming potential, or reactivity, of organic gas emissions will be considered. Use of alternative and reformulated fuels may provide benefits by reducing the ozone reactivity of exhaust emissions which are not properly accounted for under traditional mass-based motor vehicle standards. Therefore, to allow all vehicle/fuel systems to be compared on an equal air quality basis, a so-called "level-playing field," the low-emission vehicle program requires the use of "reactivity adjustment factors" (RAFTs) for vehicles which operate on fuels other than conventional gasoline. In this case, conventional gasoline is defined to be 1989 industry average gasoline (specifically, "reformulated fuel A" used in the Auto/Oil Air Quality Improvement Research Project).

The RAFT for a clean fuel vehicle is calculated by dividing the ozone-forming potential per gram of its NMOG emissions by the ozone-forming potential per gram of the NMOG emissions from a comparable vehicle operated on conventional gasoline:

$$\text{RAFT} = \frac{\text{ozone/gram of clean fuel vehicle emissions}}{\text{ozone/gram of conventional gasoline vehicle emissions}}$$

The baseline ozone-forming potential per gram for conventional gasoline vehicles in each low-emission vehicle category, the denominator of the RAFT expression, is established by the ARB. At a hearing held on November 14, 1991, the ARB approved a baseline ozone-forming potential of 3.42 for TLEVs, and at the November 12, 1992 hearing, the staff will be proposing a similar value for LEVs.

The ARB also establishes the ozone-forming potential per gram for clean fuel vehicles, the numerator of the expression, although manufacturers are given the option of determining the numerator for individual engine families. This value divided by the baseline ozone-forming potential per gram for conventional gasoline vehicles yields an RAFT for the clean fuel vehicle. Last November, the ARB approved a RAFT of 0.41 for methanol-fueled TLEVs. This November, the staff will be proposing RAFTs for Phase 2 gasoline-fueled TLEVs and LEVs and for various alternate fuel vehicles, pending the receipt of additional data.

Once established, the RAFTs are used to adjust or correct the NMOG emissions from the clean fuel vehicle before the emissions are compared to the NMOG standards. In this way, vehicles powered by alternative fuels or reformulated gasoline are allowed to emit a greater mass of NMOG as long as the total

ozone-forming potential of the emissions, on a g/mi basis, is no greater than emissions from conventional gasoline vehicles that just meet the standard.

III. NEW REQUIREMENTS AND TEST PROCEDURES

a. Hybrid Test Procedures

Background

Hybrid electric vehicles (HEVs) are designed to operate on electric power and/or an auxiliary power unit (APU), which is usually a combustion engine. Some designs rely primarily on the APU to provide motive force for the vehicle, with the electric propulsion system providing minimal assist. Because of tightening emission regulations and impending requirements for improved fuel efficiency, however, most emerging HEV designs rely predominantly on electric operation with the APU taking a secondary role. Although the APU can be coupled to the drive wheels to help power the vehicle, perhaps the most desirable HEV designs from an emission standpoint rely on a small APU only to run an alternator to recharge the batteries during vehicle operation; only the electric motors actually propel the vehicle. Typically, when all-electric driving has depleted the batteries to a moderate level, the APU would energize to slow the rate of battery discharge during driving, thereby extending the range of the HEV. Because these APUs are comparatively small and can operate at their most efficient constant speed and load point, emissions are much easier to control and fuel efficiency can be very high.

Given the wide variety of HEV designs and the generally intermittent pattern of APU operation, developing an appropriate exhaust and evaporative emission test procedure can be challenging. Since the operating range of HEVs will normally exceed 100 miles it would not be practical to measure emissions over the full driving range as the APU cycles on and off in order to determine an average gram per mile emission rate of the HEV. Instead, the staff is proposing to conduct exhaust emission testing of an HEV using the familiar Federal Test Procedure (FTP) driving cycle. To ensure that the APU would be operating during the FTP driving cycle, the HEV batteries would be discharged prior to emission sampling to the point at which APU operation would commence. Emission testing would then begin with the APU in a moderate load operating condition. Although most HEVs will operate for some portion of driving without APU operation, depending on the driving and recharging habits of the operator, measuring emissions under these conditions would ensure that HEV emissions would not exceed emission standards in use. In some instances, for example, operators may neglect recharging the batteries consistently or batteries may not be replaced when they have deteriorated, increasing the proportion of APU operation and

attendant HEV emissions. (By comparison, a worst case emission testing scenario might include complete discharge of the batteries before initiating the test requiring maximum APU output, but this condition would likely be relatively uncharacteristic of HEV operating patterns.)

In order to foster HEV designs which operate long distances on battery power alone, thereby promoting driving in a "zero emission" mode, the low-emission vehicle regulations currently provide credit to HEVs based on their all-electric range. This credit is only provided for the purpose of calculating a manufacturer's NMOG fleet average. An HEV with an all-electric range of 60 miles or greater would be given additional credit equal to one half of the difference between the NMOG level at which the vehicle certifies and the next most stringent emission level. An HEV with a 40 to 59 mile all-electric range would be given additional credit equal to 25 percent of the difference between the NMOG level at which the vehicle certifies and the next most stringent emission level. No additional credit is given to an HEV with an all-electric range of less than 40 miles. As an illustration, the possible NMOG emission levels of an HEV certified as an ULEV to be used in calculating a manufacturer's fleet average for determining compliance with the low-emission vehicle program are presented below.

HEV Type	All-Electric Range (miles)	NMOG level (g/mi)
A	≥ 60	0.02
B	40 - 59	0.03
C	0 - 39	0.04

In contrast, conventional (i.e., non-hybrid electric) ULEVs must use an NMOG value of 0.040 g/mi in calculating the fleet average regardless of the certification emission level the vehicle achieved (the process is called "categorized emission averaging").

In order to ensure that HEVs will perform as expected, a complete HEV certification procedure is being proposed, including a modified evaporative emission determination, as explained below. With this procedure, the important aspects of both the electric operation and APU operation of HEVs will be evaluated.

All Electric Range Test

In order to determine the appropriate HEV certification NMOG level, the all-electric mileage range must be demonstrated. Under the ARB's proposed procedure, the range determination would be based on driving the test vehicle with the batteries initially completely charged over successive, alternating federal highway and urban driving schedules until either the APU is activated by the vehicle's electronic control unit, or the vehicle is unable to maintain the speed versus time trace of the driving schedule.

The mileage accumulated to that point would be considered the all-electric range for the purposes of determining the NMOG level for fleet averaging. Manufacturers would be allowed to use regenerative braking during the range test.

Emission Testing

As mentioned previously, the emission performance of HEVs will be evaluated with the batteries at a state of charge that would initiate APU operation at the beginning of the test. Otherwise, emission testing is conducted similarly to conventional vehicles. During the emission test, the APU controller is allowed to turn the APU on and off according to its normal operational strategy.

Evaporative Emission Testing

Under the proposed test procedures, HEVs would also be tested for evaporative and running loss emissions similarly to conventional vehicles. However, one inherent difference between the vehicle technologies requires special handling of the way running loss emissions are determined. Unlike conventional vehicles, it is possible for HEVs to operate for days at a time without activating the APU. Without APU operation, there would be no opportunity to purge hydrocarbon vapor accumulating in the vehicle's evaporative canister. In order to prevent canister saturation and excessive evaporative emissions, it is expected with most HEV designs that the vehicle's controller will automatically start the APU (even though battery power is adequate) in order to purge vapor into the engine where it would be burned. The staff proposes for such vehicle designs that the emissions generated from this short period of APU operation be converted into a grams per mile per day figure based on the length of APU operation, the average speed of the CVS-75 cycle, and the number of 24 hour diurnals between operation of the APU for evaporative emission control. For certification purposes, the emissions would be added to the running loss emissions to determine compliance with running loss emission standards.

Durability Requirements

Because Type A and Type B HEVs are able to operate on battery power alone for significant distances, the staff believes that it would be appropriate to shorten the mileage accumulation requirements for certification. Light-duty Type A HEVs would therefore only be required to accumulate 50,000 miles, while Type B HEVs would have to accumulate 75,000 miles in order to develop deterioration factors needed for certification. Type C HEVs, which have little or no battery-only range, would be treated similarly to gasoline vehicles, i.e., demonstration of 100,000 mile durability would be required.

Other HEV Test Procedures Considered

In the course of developing the proposed HEV certification procedures, ARB staff received a proposed test procedure from General Motors. After reviewing GM's proposal, staff concluded that its own proposed strategy for HEV testing would better assure testing efficiency and optimum vehicle designs from an emissions viewpoint. Some of the reasons behind staff's determination are set forth below.

Under GM's test procedure, HEV emissions would be calculated based on combining "worst" and "best" case emissions over an urban driving cycle 30 miles in length using assumptions regarding in-use driving and battery recharging patterns. However, this proposal falls short of the ARB staff's goal to keep emissions under the applicable standard under at least moderate case driving and recharging patterns. For example, under GM's proposal, a vehicle with an all electric range of 30 miles could meet the 0.040 g/mi NMOG standard with an APU that emits 0.073 g/mi NMOG. For every day that the vehicle is driven further than its all-electric range, or without adequately charged batteries, emissions could significantly exceed the base standard to which the vehicle is certified.

Because GM proposes that emissions be measured over 30 mile cycles and no test is proposed for an all-electric range determination, no incentive exists under GM's proposal for the development of an HEV with an all-electric range greater than 30 miles. The ARB's proposed procedure offers incentive for up to a 60 mile all electric range, thereby increasing HEV emission benefits because such vehicles will be able to operate further under all-electric conditions. Further, the procedure proposed by GM would not dissuade manufacturers from implementing HEV control strategies that activate the APU under normal highway driving conditions even with fully charged batteries; the ARB staff's proposed requirement for all-electric range testing over a mix of urban and highway driving cycles would effectively limit such designs.

The ARB staff has also followed the work of the Society of Automotive Engineers (SAE) committees involved in developing electric vehicle and hybrid electric vehicle test procedures. At the present time, many aspects of the test procedures do not seem to be sufficiently in line with the ARB's goals concerning HEV testing to justify the incorporation of these procedures into the staff's proposal. For example, the electric vehicle range and energy consumption tests specified by the SAE's latest draft will take as long as 3 days to complete. The staff has determined that the same information can be derived from the single range test it has proposed. One reason for this difference, as well as others, appears to lie in the SAE's desire to keep the testing requirements for electric vehicles as similar as possible to the existing procedures for conventional vehicles. Because the factors of importance vary significantly between the two

technologies with respect to emissions, the staff is not convinced of the need for such consistency and has instead attempted to develop a test procedure that will generate the necessary information while minimizing the testing burden. As another example, the SAE test procedures specify a flat 10% compensation factor for dynamometer load settings for vehicles that will be equipped with air conditioning systems (consistent with the procedure for conventional vehicles). However, because energy consumption is more directly related to in-use emissions of HEVs, staff proposes instead to actually measure the additional loading necessary because of the air conditioning system in order to reward and encourage more efficient air conditioning system designs.

With respect to determining the emission characteristics of HEVs the SAE's most recent draft appears to be similar in concept to GM's proposal and therefore was not more seriously considered for the reasons stated previously. While the SAE procedures are not considered appropriate for HEV certification in their present form, the ARB staff plans to follow and participate to the extent possible in the further development of these procedures in the hope of increasing the consistency between the ARB and SAE procedures in the future.

b. Cold CO Requirements

Despite adoption of increasingly stringent emission standards for new motor vehicles, additional reductions of CO emissions are still needed in some areas of the state to achieve compliance with the National Ambient Air Quality Standard (NAAQS) for CO during winter months. A significant cause of the CO problem is the contribution of motor vehicle emissions which are largely unregulated at cold temperatures. Testing by the ARB and the U.S. Environmental Protection Agency indicates that, oftentimes, vehicles are designed to adequately control CO emissions only within the 68-86°F range specified by the FTP. Comparisons of vehicle operating control strategies have shown that significant changes in air pump and fuel control strategies are often employed at temperatures below 68°F which result in unnecessarily high emissions. In view of this situation, the US EPA recently adopted requirements to ensure adequate control of CO emissions at cold temperatures, and the staff is proposing that consistent requirements be adopted in California.

To ensure adequate control of CO emissions, the staff is proposing CO standards at 20°F and a linear cap on CO emissions between the applicable CO standard at FTP conditions and the proposed emission standard at 20°F. This is identical to the EPA proposal. These requirements will apply to all light- and medium-duty vehicles up to 8,500 lbs. GVW beginning with the 1996 model-year. While EPA's requirements apply only for gasoline vehicles, the ARB proposal would apply to all fuels except natural gas, diesel, and hybrid electric vehicles since

their cold operating characteristics do not depend on fuel enrichment to achieve suitable driveability. Like EPA, compliance with California's cold temperature CO standards would be required up to 50,000 miles in use.

c. ZEV Certification Procedures

ZEVs are defined as vehicles which have no emissions of criteria pollutants under any possible operating condition. Presently only battery-powered electric vehicles which do not use auxiliary fuel-fired heaters are able to qualify as ZEVs. Since the adoption of this definition, however, the staff has been approached by several manufacturers about the marketability of electric vehicles without fuel-fired heaters. These manufacturers voiced concerns that customers may not want to purchase electric vehicles that are unable to heat the passenger cabin during cold winter days. Since high ambient ozone levels are not a concern during the wintertime, the staff has agreed to reexamine the ZEV definition.

The staff is proposing that the current ZEV definition be revised to accommodate electric vehicles with fuel-fired heaters provided that 1) the fuel-fired heaters cannot be operated at ambient temperatures above 40°F and 2) the fuel-fired heaters have no evaporative emissions. With these new criteria in place, the Board can be assured that ZEVs will not have any emissions that may exacerbate ozone levels during the ozone season while still ensuring that electric vehicles are attractive to drivers living in colder climates.

Moreover, the staff is also proposing that ZEV manufacturers supply information about fuel-fired heaters and other vehicle specifications in the certification application. In particular, electric vehicle manufacturers would be required to provide the driving range in miles and the energy usage in kilowatt-hours of the vehicle when operated over the All-Electric Range Test. This information will be used by the staff to properly assess the power plant emissions attributable to electric vehicles.

d. Test Procedures for Ethanol Vehicles

In order to ensure that ethanol is an option for manufacturers to meet the low-emission vehicle requirements, the low-emission vehicle test procedures would be modified to include certification requirements for ethanol-fueled vehicles and test fuel specifications for E100 and E85. In general, the exhaust and evaporative emission standards and test procedures that are proposed for ethanol-fueled vehicles are consistent with those applicable to methanol-fueled vehicles.

The ethanol certification test fuel specifications would be equivalent to the ethanol commercial fuel specifications previously set by the Board on March 12, 1992, with the added requirement that the Reid vapor pressure (RVP) adjustment needed to ensure good vehicle cold starting characteristics be performed using common blending components (such as butane) from refinery feedstocks. Because fuel-flexible vehicles will have varying mixtures of gasoline and E85 in the fuel tank depending on the refueling pattern of the vehicle, the mixture resulting in the highest evaporation rate would be used for evaporative emission testing purposes. For ethanol fuel-flexible vehicles, this would be a blend of 10 percent ethanol and 90 percent certification gasoline.

For non-low emission ethanol vehicles certifying to the exhaust non-methane hydrocarbon (NMHC) emission standards, an Organic Material Non-Methane Hydrocarbon Equivalent ("OMNMHCE") term has been defined that is similar to the one for methanol. OMNMHCE is used as the basis for more equitably comparing mass emissions from ethanol (or methanol) non-low emission vehicles to emissions from gasoline vehicles in the absence of the reactivity adjustment factors developed for low-emission vehicles. Accordingly, the current definition of OMNMHCE for methanol-fueled vehicles would be revised for ethanol-fueled vehicles to include ethanol and acetaldehyde emissions. Ethanol-fueled vehicles would also be required to meet the formaldehyde standards in effect for methanol-fueled vehicles.

IV. MODIFICATIONS AND CLARIFICATIONS TO EXISTING REQUIREMENTS

a. 50°F Requirements

A 50°F testing requirement was adopted in 1990 as a part of the low-emission vehicle regulations in order to ensure that emission control systems are effective even at low temperatures. Testing of some vehicles by the ARB had revealed sharp, discontinuous increases in emissions particularly at temperatures just below the lower bound of current federal test limits. This was attributed to the possible use of defeat strategies such as the deactivation of the air pump below 68°F. The 50°F testing requirement was developed in order to prevent manufacturers from producing designs that could cause unexpected increases in emissions especially during the summer ozone season when it is not unusual for morning temperatures to drop to 50°F.

The existing 50°F test requires manufacturers to demonstrate on a 4000 mile certification vehicle that emissions at 50°F remain below the 50,000 mile certification standards applicable at 68 to 86°F. This requirement is reasonable since no emission deterioration factors are applied to the 50°F test

results and manufacturers generally design vehicles to allow for increases in emissions as vehicles age. Therefore, sufficient margin should be available to account for expected increases in emissions at 50°F on a 4,000 mile certification vehicle.

In developing the 50°F test requirements, however, it was not anticipated that manufacturers would be able to certify to TLEV and LEV standards without the use of more advanced control technologies than they are using. It now appears that the 50°F testing requirement may force the use of additional technologies that would otherwise not be required to meet certification standards. Since the intent was to prevent the use of defeat devices, rather than force the installation of new technology, the staff is recommending a revision to the 50°F test standards.

The staff's current proposal would require manufacturers to demonstrate that NMOG and formaldehyde emissions at 50°F remain below a multiplier times the 50,000 mile certification standards applicable at 68 to 86°F. For TLEVs and LEVs, NMOG and formaldehyde emissions at 50°F would need to remain below 1.75 times the applicable standards. These multipliers were decided upon after consultation with manufacturers and review of the available 50°F test data from TLEV and prototype LEV vehicles (not equipped with electrically heated catalysts). For ULEVs, the multiplier would remain at 1.00 until additional data become available; if necessary, the 1.00 ULEV multiplier can be re-examined at a future review hearing. However, the available data do not support any changes to the existing 50°F requirements for CO and NO_x; accordingly, the staff recommends that the current 50°F CO and NO_x requirement remain unchanged for all low-emission vehicle categories.

b. ZEV Credit System

The staff proposes to add clarifying language to better define the structure of the ZEV credit system. The numerical value of the ZEV credits and debits would be linked to the fleet average requirement for the model year. For example, a manufacturer which produced 1000 extra ZEVs beyond its requirements in 1994 would earn 250 g/mi ZEV credits while a manufacturer which produced 1000 extra ZEVs in 2000 would earn 73 g/mi ZEV credits. (The fleet average requirement is 0.250 g/mi NMOG in 1994 and 0.073 g/mi NMOG in 2000.) This approach provides an incentive for manufacturers to produce extra ZEVs early since more credits would be earned. Similarly, it discourages manufacturers from delaying ZEV implementation.

In the same vein, the staff is proposing a modification to allow manufacturers which produce ZEVs early to use the credits to offset their mandated production requirements. Currently, all ZEV credits earned after 1994 and prior to 1998

are discounted in accordance with the established discounting schedule. The staff proposal would stipulate that any ZEV credits earned prior to 1998 would be treated as if they were earned in 1998 and discounted accordingly. Thus, ZEV credits earned before 1998 would retain full value through the 1999 model year, be discounted by 50 percent in 2000 and to 25 percent of their original value in 2001. This revision would therefore provide an incentive for manufacturers to produce ZEVs prior to the 1998 mandate by allowing them to use accumulated credits to offset potential future shortfalls in ZEV production.

c. Calculation of Penalties for Violations

Health and Safety Code section 43211 authorizes the ARB to impose a civil penalty of up to \$5000 for each sale of a new motor vehicle that does not meet the Board's emission standards. With the fleet averaging and the ZEV credit systems, though, it may not be clear exactly how the sale of a new motor vehicle is determined. Therefore, the staff is proposing to add language to the regulations which explicitly define how penalties will be calculated.

To calculate the number of unlawful sales when the manufacturer has not met the fleet averaging requirement and the period for equalizing debits has passed, the g/mi NMOG debits would be divided by the fleet average requirement for passenger cars and light-duty trucks applicable for the model year in which the debits were first accrued. To calculate the penalty for not producing enough ZEVs, the ZEV shortfall would be multiplied by a maximum of \$5000 per vehicle. Similarly, medium-duty vehicle non-compliance penalties would be proportional to the amount of debits accrued by the manufacturer.

In discussions with manufacturers, the staff has received indication that a \$5000 maximum civil penalty may be insufficient to deter some manufacturers from not meeting their ZEV requirements, that is, some manufacturers may chose to pay the \$5000 penalty rather than comply with the mandate. The staff is sensitive to this concern and will be examining the need to seek legislation to increase the maximum penalty for ZEVs. The purpose of this increased penalty would be to ensure that the ZEV requirements adopted by the Board are actually implemented.

V. REACTIVITY ADJUSTMENT FACTORS

On November 14, 1991, the Board conducted a hearing to consider reactivity adjustment factors for TLEVs. At the hearing the Board approved a baseline ozone per gram value of 3.42 for light-duty TLEVs operated on conventional gasoline (i.e., reformulated fuel A) and a RAF of 0.41 for TLEVs powered by methanol (i.e., M85). The values were established based on speciated emission testing conducted by the ARB. In addition,

the Board approved a procedure whereby manufacturers can establish engine family specific RAFs provided that the RAF is developed based on a representative number of vehicles and a RAF deterioration factor is calculated. In this rulemaking, the staff intends to propose amendments to the RAF regulations that would establish new RAFs for other vehicle/fuel systems and would require the calculation of ozone deterioration factors.

a. New RAFs

This fall the staff is embarking on an extensive test program to develop baseline ozone per gram values for LEVs on conventional gasoline and RAFs for Phase 2 gasoline. The staff has procured several gasoline vehicles that have emissions below the TLEV and LEV standards. The TLEVs are primarily production vehicles leased from rental car agencies, and the LEVs are mainly production vehicles which have been retrofitted with electrically heated catalysts. Some of the test vehicles may be able to meet the LEV standards without electrically heated catalysts. Moreover, the staff has also obtained test fuel that meets the Phase 2 certification fuel specifications approved by the Board on August 14, 1992. A fuel analysis of the properties of the specific batch of Phase 2 gasoline that the staff is using is provided in Table III.

Speciated vehicle testing began in August, 1992, but has not yet been completed. Testing is expected to be completed prior to the Board hearing date, and the full results will be presented at the hearing on November 12, 1992. The staff also intends to provide the data to the public as soon as they become available. Based on the preliminary data obtained thus far (see Appendix B), the staff is able to estimate conservative values for the baseline ozone/gram for LEVs and RAFs for Phase 2 gasoline. These values are

Ozone/gram for LEVs operating on conventional gasoline: 3.25

RAF for Phase 2 gasoline-fueled TLEVs: 1.00

RAF for Phase 2 gasoline-fueled LEVs: 0.95

Again, these values are conservative ones based on very preliminary data, and the staff will be proposing modified values based on the complete test results at the Board hearing.

Additionally, the staff is also planning on testing several alternate fuel vehicles this fall. Arrangements have already been made to procure several CNG, LPG, methanol, and ethanol vehicles for speciated testing. Alternate fuel vehicle

Table III. Analysis of Phase 2 certification fuel used by the
ARB. (Lot R-802)

<u>TESTS</u>	<u>RESULTS</u>	<u>METHOD</u>
Specific Gravity, 60/60	0.7379	ASTM D-4052
API Gravity	60.3	ASTM D-1298
Corrosion	1a	ASTM D-130
Phosphorous	0.004	ASTM D-3231
Sulfur, ppm	37.6	ASTM D-4045
MTBE, LV%	10.8	CHROMATOGRAPHY
Nitrogen	0.0	
Multi-Alkylated Aromatics	12.6	
Reid Vapor Pressure	6.8	ASTM D-4814
TEL (ml/gal)	0.00	ASTM D-3237
Benzene Content, LV%	1.10	
Carbon Wt%	84.7	
Hydrogen Wt%	13.7	
Oxidation Stability (min)	1000+	ASTM D-525
Existant Gums (mg/100mi)	1.32	ASTM D-381
<u>DISTILLATION. °F</u>		
IBP	92	ASTM D-86
5%	119	
10%	133	
20%	146	
30%	161	
40%	180	
50%	200	
60%	219	
70%	236	
80%	258	
90%	292	
95%	320	
EP	381	
Loss	0.7	
Residue	0.7	
<u>HYDROCARBON TYPE, VOL%</u>		
Aromatics	23.3	
Olefins	5.8	
Saturates	remainder	
Research Octane Number	96.7	
Motor Octane Number	88.0	
Antiknock Index	92.4	
Sensitivity	8.7	

testing will begin after the Phase 2 gasoline testing has been completed. If representative data are available by the Board hearing date, the staff will also propose RAFs for these alternate fuels in the TLEV or LEV categories.

b. Ozone Deterioration Factor Calculation Procedures

As part of the November, 1991 rulemaking, the ARB adopted a requirement that manufacturers which develop engine family specific RAFs must also develop a deterioration factor for the RAF. This deterioration factor is determined by speciating the exhaust emissions of a durability-data vehicle at 10,000 mile intervals, calculating the RAF at each mileage interval, and determining the slope of the line formed by plotting the RAFs as a function of mileage. Thus, the RAF deterioration factor indicates only the change in the reactivity per gram of emissions. In addition, manufacturers are required to determine separate NMOG mass deterioration factors. To determine whether the NMOG emissions of an engine family would comply with the NMOG standards, actual NMOG mass emissions would be multiplied by the RAF, the RAF deterioration factor, and the NMOG mass deterioration factor to determine compliance with the NMOG standards. Neither the RAF nor the NMOG mass deterioration factor can be less than 1.00.

After discussing this issue with manufacturers, the staff has determined that it is more scientifically justified to combine the RAF deterioration factor with the NMOG mass deterioration factor to obtain an ozone deterioration factor (note that the value of the RAF itself is not affected by this consolidation of deterioration factors). Such a factor would account for both changes in mass emissions and reactivity with vehicle mileage. Thus, rather than calculate separate NMOG mass and RAF deterioration factors at each mileage interval, manufacturers would determine the ozone-forming potential per mile, plot that value versus mileage, and determine the ozone deterioration factor from the slope of the line. Under this approach, actual NMOG mass emissions would be multiplied by the RAF and the ozone deterioration factor prior to comparing with the NMOG standards.

Because of potential test variability and uncertainties in manufacturers' testing methods, the staff is proposing that the ozone deterioration factor be required to have a value of 1.00 or greater. The initial indication from some manufacturers is that reactivity per gram may actually decrease with mileage, and as such, the ozone deterioration factor may be less than 1.00 for some engine families. However, without more substantive data to support this phenomenon, the staff favors retaining the 1.00 restriction for ozone deterioration factors at the present time to ensure that ozone levels are not exacerbated. If warranted by the data that become available, the staff can reassess the need

to keep the 1.00 limitation for ozone deterioration factors at a later date.

c. Methane RAF

Traditionally, California standards and test procedures for light- and medium-duty vehicles have not regulated the emission of methane because of its low reactivity and because methane mass emissions are very low in conventional gasoline and diesel vehicles comprising the great majority of the vehicle fleet. With the adoption of the low-emission vehicle regulations, and the concomitant increase in manufacturers' interest in producing natural gas vehicles, the effect of disproportionately higher amounts of methane emissions in natural gas vehicles was reviewed. Despite the very low reactivity of the exhaust from natural gas vehicles, emission testing of low emission CNG vehicles reveals that as much as 40 percent of the reactivity can be due to methane emissions. Therefore, to preserve the integrity of the RAF concept, methane emission reactivity should be accounted for in determining the compliance of natural gas vehicles with the low-emission vehicle standards.

The staff is, therefore, proposing an approach that considers the ozone-forming potential of the methane emissions from natural gas vehicles. In addition to the reactivity adjustment factor that is calculated for NMOG, a methane reactivity adjustment factor is being proposed only for natural gas low emission vehicles. A specific methane RAF would be calculated by dividing the maximum incremental reactivity of methane (0.0148) by the ozone-forming potential per gram value of the appropriate emission control technology category. For CNG TLEVs, the RAF for methane would be 0.0043 (0.0148/3.42). For natural gas LEVs, an interim methane RAF of 0.0045 (0.0148/3.25) is being proposed; however, this value will likely be modified at the hearing pending the receipt of additional data. A methane RAF for natural gas ULEVs will be proposed at a future date.

The methane RAF would then be multiplied by the mass of methane emissions to obtain a reactivity adjusted mass value for methane which would be added to the reactivity adjusted NMOG value for the remainder of the exhaust sample. The sum of these two values would then be compared to the NMOG emission standard to determine compliance, as shown in the following equation:

$$RAF_{NMOG} \times Mass_{NMOG} + RAF_{Methane} \times Mass_{Methane} = \text{Reactivity Adjusted NMOG}$$

VI. ENVIRONMENTAL AND ECONOMIC IMPACTS

As noted above, the purpose of the proposed amendments is to build upon and refine the low-emission vehicle regulations by clarifying or expanding various provisions, easing

implementation, and further effectuating the RAF framework. Thus for the purpose of evaluating potential emission impacts, the proposed amendments are appropriately viewed as part of the larger low-emission vehicle regulatory program. In this context, the proposed amendments are not expected to change the emissions reductions that were originally projected to result from the low-emission vehicle regulations.

The establishment of additional RAFs further facilitates the use of cleaner burning fuels in low-emission vehicles. The structure of the reactivity adjustment process is intended to equalize the ozone impact of different vehicle/fuel systems certified to the low-emission vehicle standards. Thus, while the RAFs could allow vehicles operating on nonconventional fuels to emit a greater mass of NMOG, the net effect on ambient ozone should be no different for such a vehicle than for a conventional gasoline vehicle certified to the same low-emission vehicle standard.

The staff also does not expect that the proposed amendments will result in any adverse economic impacts. Several of the modifications should make it somewhat easier and more practical for vehicle manufacturers to meet the requirements of the low-emission vehicle program. These modifications should result in some cost savings. Some of the proposed amendments will create additional certification requirements (e.g., for hybrid electric vehicles). Overall, the staff believes that the proposed modifications would result in no significant cost impacts.

VII. SUMMARY AND CONCLUSIONS

The changes described above and those detailed in Appendix A have been discussed at length with industry in three workshops (February 3 & 4, 1992; August 12, 1992; and September 3, 1992) and in numerous meetings with individual manufacturers. While industry may differ with the Board resolution adopted at the June 12, 1992 hearing concerning the lead time and technological feasibility of the low-emission vehicle requirements, there do not appear to be significant issues of controversy regarding the matters relative to this hearing. This is because the changes being proposed are largely intended to clarify or improve implementation of the low-emission vehicle program in response to industry recommendations and/or staff suggestions. No alternative proposals considered by the staff would be as effective in carrying out the purpose for which the amendments are proposed and less burdensome to affected private persons than the staff proposal contained herein.

Although vehicle testing is not yet complete, ARB staff will be proposing as many RAFs as possible at the hearing to ensure that industry can proceed on schedule with their low-emission vehicle designs. As soon as adequate data become

available, the Executive Officer will establish RAFs for other vehicle and fuel combinations pursuant to the protocol contained in the regulations.

In addition to the issues discussed in this report, the staff is also proposing various amendments to regulations for determining evaporative emissions from HEVs, assembly-line testing, measuring NMOG, certification fuels for diesel vehicles, etc. Interested parties are encouraged to review Appendix A to obtain a summary of all the changes being proposed by the staff.

In conclusion, the staff recommends that the Board adopt the proposed revisions and the RAFs that the staff will be presenting at the Board hearing in November.

APPENDIX A

SUMMARY OF PROPOSED REGULATORY MODIFICATIONS

In reviewing the low-emission vehicle regulations, the staff has identified several areas where regulatory modifications are needed. In general, these modifications are needed to correct errors or to clarify various provisions. In some instances, new or revised regulatory requirements are proposed. Descriptions of the proposed modifications are found in this summary.

A. TITLE 13, CALIFORNIA CODE OF REGULATIONS, SECTION 1960.1

1. In subsection (e)(3), note (6), subsection (g)(1), note (8), and subsection (h)(2), note (13), language stating that hybrid electric, natural gas, and diesel-fueled vehicles would be exempt from 50°F test requirements would be added.
2. In subsection (f)(1), note (7), the existing regulation requires vehicle manufacturers to certify a minimum of 80 percent of their sales to 0.25 g/mi NMHC-level conventional vehicle standards and/or low-emission vehicle standards in the 1994 model year; manufacturers will also have to comply with fleet average requirements for that year. The regulation would be modified to give manufacturers the option of meeting the fleet average requirements only; that is, 80 percent phase-in to the new standards would no longer be required. This change would give manufacturers additional compliance flexibility in the 1994 model year. It is important to note, however, that 100 percent certification of vehicles to 0.25 g/mi NMHC-level or low-emission vehicle standards is required in the 1995 model year, as certification to 0.39 g/mi NMHC-level standards will not be allowed beyond 1994.
3. In subsections (f)(1) and (f)(2), methanol and ethanol vehicles certifying to 0.25 g/mi NMHC-level standards would certify to OMNMHCE standards, rather than to OMHCE standards. (The difference is that OMNMHCE standards exclude methane.) This change to OMNMHCE would make California standards consistent with federal standards for methanol Tier I vehicles. For ethanol vehicles, the OMNMHCE standard would be modified to account for the specific characteristics of ethanol vehicle emissions by adding in ethanol and acetaldehyde.
4. In subsection (f)(2), note (9), 100,000 mile NO_x standards have been added for vehicles certifying to 0.25 g/mi NMHC-level standards. The 100,000 mile NO_x standards are identical to those for federal Tier I

vehicles and would become effective beginning with the 1996 model year (when federal Tier I vehicles are implemented for 100 percent of the fleet). This change would therefore make California 0.25 g/mi NMHC-level standards identical to federal Tier I standards for 1996 and subsequent model-year vehicles.

5. The low-emission vehicle regulations currently require manufacturers to "sell" certain percentages of vehicles to meet specified fleet average, ZEV, or medium-duty vehicle requirements. However, accurate sales information is generally not available to the ARB within the timeframe needed for enforcement, and the staff has historically used production data to represent sales. Production information is submitted to the ARB each calendar quarter as part of manufacturers' assembly-line reporting requirements. Therefore, to reflect actual practice, language throughout subsections (g)(1), (g)(2), and (h)(2) which refer to "sales" would be changed to "production and delivery for sale in California."
6. In subsection (g)(1), notes (3), (4)a., and (6)a. and subsection (h)(2), notes (3), (4)a., and (9)a., language concerning the use of methane reactivity adjustment factors for natural gas vehicles would be added. For natural gas vehicles only, methane mass emissions would be multiplied by the methane reactivity adjustment factor and then added to the reactivity-adjusted NMOG emissions and the compared with the NMOG emission standard.
7. In subsections (g)(1), note (4) and (h)(2), note (4), the language would be revised to allow manufacturers to use Phase 2 gasoline for certifying fuel-flexible and dual-fuel vehicles to emission standards that apply when the vehicles are operated on conventional gasoline. However, since fuel-flexible and dual-fuel vehicles are allowed to certify to numerically higher standards on gasoline, use of reactivity adjustment factors for Phase 2 gasoline would not be allowed.
8. In subsection (g)(1) note (10), language would be added to specify the certification standards that the auxiliary power units of hybrid electric vehicles would need to demonstrate compliance with. The certification mileage limits for the auxiliary power units would be shortened in view of the vehicle's ability to operate on battery power alone. Type A hybrid electric vehicles would need to demonstrate compliance with 50,000 mile standards only; demonstrating compliance with 100,000 mile standards would be waived. To certify a Type B hybrid electric vehicle, deterioration factors would need to be generated at 50,000 miles and at 75,000 miles. Therefore, a Type B hybrid would be required to comply with 50,000 mile standards using 50,000 mile deterioration factors and 100,000 mile standards using 75,000 mile deterioration factors.
9. In subsection (g)(2), note (3)a. and subsection (h)(2), note (11)a., a provision would be added to state that electric vehicles which are not

certified as ZEVs because of the operating characteristics of their fuel fired heaters would be treated as Type A HEV ULEVs for fleet average calculation purposes.

10. In subsection (g)(2), notes (4)c. and (5)c., language would be added to require federal Tier I vehicles certified under the AB 965 program to be added to manufacturers' fleet average calculations beginning in the 1996 model-year.
11. In subsection (g)(2), note (6)d., language would be added to accommodate potential changes in status for small volume manufacturers. Current regulations define small volume manufacturers as having average California sales of less than 3000 new passenger cars, light-duty trucks, and medium-duty vehicles each model year, based on 1989 through 1991 sales. The new language would require that any time a manufacturer exceeds a running average of 3000 units, based on any three consecutive model years, the manufacturer would be required to comply with the fleet average requirements applicable to larger manufacturers four model years later. Conversely, if a manufacturer's three-year running average should fall below 3000, the manufacturer would become subject to small volume manufacturer requirements the next model year. This provision would be added to note (6)e.
12. Because of the difference in NMOG emission standards for (1) passenger cars and light-duty trucks 0-3750 lbs. LVW and (2) light-duty trucks 3751-5750 lbs. LVW, it is necessary to establish separate fleet average requirements for each of the two vehicle classifications. However, because the credit systems have the same structure and units (g/mi NMOG), it is possible for the two classifications to converge through the credit system. This would be accomplished by adding together the amount of g/mi NMOG credits or debits earned in both classifications for each model year; the composite value would constitute the total g/mi NMOG credits or debits earned by the manufacturer for the model year. In this way, bookkeeping requirements would be simplified, and more importantly, situations where manufacturers would benefit by earning credits in one classification while maintaining a deficit in the other classification would be eliminated. The staff's proposed modified language would be made to subsection (g)(2), note (7)a.
13. In subsection (g)(2), notes (4) and (5), the equations for calculating fleet average NMOG values for 1) passenger cars and light-duty trucks 0-3750 lbs. LVW and 2) light-duty trucks 3751-5750 lbs. LVW, respectively, are given. To represent the 1993 model-year phase-in standards, the equation refers only to subsection (f)(2), which references standards applicable to 1995 and subsequent vehicles. However, for the 1994 model year, the standards listed in subsection (f)(1) apply. Therefore, the equations in notes (4) and (5) would be modified to include the standards in (f)(1).

14. In subsection (g)(2), note (7)b., the penalty for non-compliance with fleet average NMOG requirements would be explicitly identified. California Health and Safety Code section 43211 authorizes imposition of a civil penalty of up to \$5000 for each sale of a new motor vehicle that does not meet the Board's emission standards. To calculate the number of unlawful sales when a manufacturer has not met the fleet averaging requirement and the period for equalizing debits has passed, the g/mi NMOG debits would be divided by the fleet average requirement for passenger cars and light-duty trucks 0-3750 lbs. LVW applicable for the model year in which the debits were first accrued. This approach is consistent with the description of calculation of penalties in the August 13, 1990 Technical Support Document, p. I-15.
15. In subsection (g)(2), note (9)a., clarifying language would be added to better define the structure of the ZEV credit system. The amount of g/mi NMOG credits earned by exceeding the ZEV production requirements would be equal to the fleet average NMOG requirement for that year multiplied by the number of excess ZEVs produced. Since the ZEV production requirements apply only to passenger cars and light-duty trucks 0-3750 lbs. LVW, the value of the fleet average requirement for that vehicle classification would be used. Therefore, if 1000 excess ZEVs were produced in 1994, the credits earned would be 250 g/mi NMOG ($0.250 \text{ g/mi NMOG} \times 1000 \text{ ZEVs}$); if 1000 excess ZEVs were produced in 2000, the credits earned would be 73 g/mi NMOG ($0.073 \text{ g/mi NMOG} \times 1000 \text{ ZEVs}$). Also, language would be added to state that discounting of ZEV credits would not begin until the 1998 model year, that is, all ZEV credits earned before the 1998 model year would be considered as earned in 1998 and discounted accordingly.
16. Similarly, the amount of g/mi NMOG credits needed to balance ZEV deficits would be equal to the ZEV shortfall (in numbers of vehicles) multiplied by the fleet average requirement for passenger cars and light-duty trucks 0-3750 lbs. LVW applicable for that year. The modified language is found in subsection (g)(2), note (9)b.
17. In subsection (g)(2), note (9)e., language would be added to make clear that ZEVs classified by weight as light-duty trucks 3751-5750 lbs. LVW or as medium-duty vehicles may be produced to meet the ZEV production requirement. ZEVs which fall into the light-duty truck 3751-5750 lbs. LVW classification and are used to satisfy the ZEV production requirement would be included in the equation to determine compliance with fleet average requirements for passenger cars and light-duty trucks 0-3750 lbs. LVW (subsection (g)(2), note (4)b.). Only those zero-emission light-duty trucks 3751-5750 lbs. which have not been used to satisfy the ZEV production requirement would be included in the fleet average equation for light-duty trucks 3751-5750 lbs. LVW (subsection (g)(2), note (5)b.). This restriction would be implemented to account for the additional weight of the electric battery, which may place a light-duty truck into the 3751-5750 lbs. LVW classification when its usage is more typical of light-duty trucks 0-3750 lbs. LVW.

To be classified as a medium-duty vehicle, however, a ZEV must have a gross vehicle weight rating of at least 6000 lbs. This suggests that usage of the ZEV would be typical of other medium-duty vehicles. Therefore, medium-duty ZEVs used to satisfy the ZEV production requirement would be counted toward phase-in requirements for low-emission medium-duty vehicles (subsection (h)(2), note (12)f.).

18. In subsection (g)(2), note (9)d., the penalty for non-compliance with ZEV production requirements would be identified. The maximum penalty would be \$5000 multiplied by the shortfall in the number of ZEVs required to be produced less any ZEV credits submitted. However, staff is examining various means by which the monetary penalty for failing to produce ZEVs can be increased significantly beyond \$5000.
19. In subsection (h)(1), notes (3) and (7), special provisions for small volume manufacturers would be added in consideration of their limited product line. The regulations currently require certification of 50 percent of a medium-duty vehicle manufacturer's product line to more stringent medium-duty vehicle standards in 1995, 100 percent in 1996. For small volume manufacturers, the 50 percent requirement would be deleted; 100 percent certification would be required in 1996. Also, small volume manufacturers may utilize alternative in-use compliance for up to 100 percent of their medium-duty fleet through the 1997 model year.
20. In subsection (h)(2), note (4)b.(ii), the 120,000 mile NMOG standard for medium-duty FFVs 0-3750 lbs. TW when certifying on conventional gasoline in the ULEV category would be changed from 0.190 g/mi to 0.180 g/mi. To determine the conventional gasoline standards for low-emission FFVs, the NMOG standard of the next less stringent category was used. In this case, the 120,000 mile NMOG standard for medium-duty LEV FFVs 0-3750 lbs. TW is 0.180 g/mi.
21. In subsection (h)(2), note (12), a 1.4 multiplier had been inadvertently omitted from the equation for calculating compliance with phase-in requirements for medium-duty LEVs and ULEVs. The 1.4 multiplier would be added to the equation just after "(Equivalent No. of ULEVs Required to be Produced)".
22. In subsection (h)(2), note (12)b., the penalty for not producing the required number of medium-duty low-emission vehicles would be specified. The maximum penalty is \$5000 multiplied by the amount of Vehicle-Equivalent Debits (VEDs) incurred.
23. In subsection (h)(2), note (12)e., language would be added stating that any medium-duty vehicle credits earned before the 1998 model year would be treated as earned in 1998 and discounted accordingly. This provision would encourage early introduction of medium-duty low-emission vehicles.

24. In subsection (h)(2) note (15), language would be added to specify the certification standards that the auxiliary power units of hybrid electric vehicles would need to demonstrate compliance with. Type A hybrid electric vehicles would need to demonstrate compliance with 50,000 mile standards only; demonstrating compliance with 120,000 mile standards would be waived. To certify a Type B hybrid electric vehicles, deterioration factors would need to be generated at 50,000 miles and at 90,000 miles. Therefore, a Type B hybrid would be required to comply with 50,000 mile standards using 50,000 mile deterioration factors and 120,000 mile standards using 90,000 mile deterioration factors.
25. In subsection (h)(2), note (16), provisions for small volume manufacturers would be added. Small volume manufacturers would not be required to comply with medium-duty LEV and ULEV requirements until the 2001 model year, when 100 percent of the small volume manufacturer's fleet must be equivalent to LEVs. Similar to the provisions for small volume light-duty vehicle manufacturers, a three-year running average would be established to determine whether a manufacturer would qualify as small volume.
26. A new subsection (p) has been added to set forth the cold temperature CO standards applicable to new 1996 and subsequent passenger cars, light-duty trucks, and medium-duty vehicles (under 8500 lbs. GVWR only).

B. CALIFORNIA EXHAUST EMISSION STANDARDS AND TEST PROCEDURES FOR 1988 AND SUBSEQUENT PASSENGER CARS, LIGHT-DUTY TRUCKS, AND MEDIUM-DUTY VEHICLES

1. Applicability

In a., hybrid electric vehicles will be added to the list of applicable technologies. Also in this section and throughout the document, references to "methanol" have been changed to "alcohol" to include ethanol vehicles.

2. Definitions

- a. The definition of a Zero-Emission Vehicle (ZEV) would be revised to allow the incorporation of a fuel fired heater, provided that the heater cannot be operated at ambient temperatures above 40 degrees Fahrenheit and the heater is demonstrated to have no evaporative emissions.
- b. The definition of conventional gasoline would be revised to refer specifically to Indolene or 7.8 RVP Indolene for certification

purposes, and to industry average gasoline (Auto/Oil Fuel A) for reactivity testing purposes.

- c. The definition of "certification level" would be added to mean the official 4000 mile exhaust or evaporative emission data submitted by a manufacturer to certify an engine family. The term includes the application of mass or ozone deterioration factors.
- d. The definition of "ozone deterioration factor" would be added in order to define a term used in Appendix VIII of the test procedures.
- e. The definition of "Organic Material Non-Methane Hydrocarbon Equivalent" ("OMNMHCE") would be added.
- f. The definitions of "battery pack", "Type A, Type B, and Type C hybrid electric vehicles" (separately), and the "All-Electric Range Test" would be added in order to define terms used in ZEV and hybrid testing.
- g. The definitions of "defeat device", "element of design", and "intermediate temperature cold testing" would be added in order to define terms associated with EPA's cold CO test procedures.
- h. The definitions of "alcohol fuel," "ethanol," "ethanol vehicle," "dedicated ethanol vehicle" would be added in order to define the terms used in the test procedures for the certification of ethanol vehicles.
- i. The definition of "methane reactivity adjustment factor" would be added to define a term applied to the methane emissions from natural gas vehicles.
- j. The definitions of "natural gas" and "natural gas vehicle" would be added in order to include liquefied natural gas as well as compressed natural gas in the test procedures for the certification of natural gas vehicles.

3. Emission Standards

Changes identical to those listed in part A of this document (Title 13, 1960.1) have been made to section 3 of the test procedures.

4. Initial Requirements

- a. In section 4.a.2., the leadtime for submitting sales and fuel economy projections for alternative fuel low-emission vehicles would be changed to 19 months before January 1 of the calendar year which has the same numerical designation as the model year in which the vehicles are certified. Thus, for 1994 models, the deadline for submitting projections would be June 1, 1992.

- b. In section 4.a.3., the information required to be submitted in the application to certify ZEVs and hybrid electric vehicles would be specified. If the ZEV is equipped with a fuel fired heater, a description of how the fuel fired heater operates and an engineering evaluation of whether evaporative emission are possible is required to be submitted with the certification application. If the fuel fired heater is operational at ambient temperatures above 40 degrees F or if the vehicle is capable of having evaporative emissions, the vehicle would not be considered a ZEV. Additionally, energy usage, operating range, safety procedures, and other information would be required.
- c. In section 4.b.1, requirements for calculating NMOG to determine compliance with NMOG standards would be specified. For all TLEVs, LEVs, and ULEVs certifying on a fuel other than conventional gasoline, NMOG results would be multiplied by the applicable reactivity adjustment factor prior to comparing with the NMOG standard. For all TLEVs, LEVs, and ULEVs certifying on natural gas, methane results would be multiplied by the applicable methane reactivity adjustment factor and added to the reactivity-adjusted NMOG emissions; the sum of these two values would be compared to the NMOG standard to determine compliance.
- d. In section 4.b.3, the provision requiring submission of emissions from fuel fired heaters would be deleted. All electric vehicles that utilize fuel fired heaters that are operated above 40 degrees F or that have evaporative emissions and therefore do not qualify as ZEVs would ~~be treated as Type C hybrid ULEVs for fleet averaging purposes (see sections 3.h., note (3) and 3.j., note (11)).~~
- d. In section 4.c.1., a provision would be added to require that beginning with the 1995 model year, all engines classified in the same engine family must be certified to the same exhaust emission standards. This change is needed to ensure effective in-use enforcement of emission standards and will assist in determining compliance with fleet average requirements.

5. Maintenance Requirements

- a. In section 5.a.2, item (10), the maintenance requirements for the battery system of a hybrid electric vehicle would be listed. In particular, manufacturers would be required to equip hybrid electric vehicles with a light that illuminates the first time that the hybrid is unable to achieve at least 75% of the range determined during the All-Electric Range Test.

6. Demonstrating Compliance

- a. In section 6.a.4.(A), the mileage accumulation limits for the auxiliary power units used on hybrid electric vehicles would be provided. For the purpose of developing deterioration factors, the auxiliary power units on light-duty Type A hybrids would have to accumulate 50,000 miles; for light-duty Type B hybrids, 75,000 miles would be required; and for light-duty Type C hybrids, 100,000 miles. For medium-duty hybrid electric vehicles, the mileage limits are 50,000 miles for Type A, 90,000 miles for Type B, and 120,000 miles for Type C. It is important to note, however, all hybrid electric vehicles have full useful lives of 10 years or 100,000 miles (for light-duty vehicles) or 11 years or 120,000 miles (for medium-duty vehicles) (see section 2.q.), and the abbreviated mileage limits are to be used for developing deterioration factors for emissions from auxiliary power units only.
- b. In section 6.a.4.(D), mileage accumulation procedures for fuel-flexible durability vehicles would be clarified. All fuel-flexible vehicles are required to be exhaust emission tested at 5,000 miles, 10,000 miles and at 10,000 mile increments thereafter to the final mileage point using M85 for methanol vehicles and E85 for ethanol vehicles. Exhaust testing on M35 for methanol vehicles or E10 for ethanol vehicles is required at these mileage points only if evaporative emission deterioration factors are also being generated. For 1993 and 1994 fuel-flexible vehicles that are not certifying as TLEVs, LEVs, or ULEVs, emission testing with gasoline is required at 5,000 miles, 50,000 miles, and the final mileage point. However, for all 1995 and subsequent model fuel-flexible vehicles and all fuel-flexible TLEVs, LEVs and ULEVs, emission testing on certification gasoline would be required at 5,000 miles, 10,000 miles, and at 10,000 mile increments thereafter to the final mileage point in order to generate representative deterioration factors. For exhaust emissions, deterioration factors are to be generated for M85 and gasoline or E85 and gasoline. For evaporative emissions, deterioration factors are to be generated for M35 or E10.
- c. In section 6.b.8., subparagraph (a)(4)(iii) of 86.091-28, Code of Federal Regulations, would be amended to require the reporting of emission data to one significant figure beyond the number of significant figures in the emission standard.
- d. A new section 6.c. would be added to prohibit the use of defeat devices on new passenger cars, light-duty trucks, and medium-duty vehicles.

7. Small Volume Manufacturer's Certification Procedures

- a. The references to the CFR would be updated to include the most recent additions made by EPA. However, the EPA provisions revising the definition of small volume manufacturer would not be incorporated.

8. Alternative Procedures for Notification of Additions and Changes

No changes

9. Test Requirements

- a. In section 9.a., section 86.113-94 of the Code of Federal Regulations has been incorporated. Furthermore, a provision would be added to give manufacturers the option of using federal low-sulfur diesel certification fuel for California diesel vehicles beginning with the 1993 model year.
- b. In section 9.a.1.(i) and (ii), language would be added to clarify that both exhaust and evaporative emission testing must be conducted using the same type of gasoline and that the Executive Officer must conduct in-use compliance testing using the same type of gasoline used to certify the engine family.
- c. In section 9.a.10.d.(3) and 9.a.11.e.(3), language would be added to allow the use of alternative mileage accumulation test procedures and/or fuels and alternative evaporative methanol-gasoline or ethanol-gasoline test fuels (in place of M35 or E10) for certifying fuel-flexible vehicles subject to the advance approval of the Executive Officer. Alternative fuels and test procedures would only be approved if demonstrated to result in higher emissions. Use of alternative test procedures and test fuels would also be allowed for gaseous fuel as noted in sections 9.a.12.(7) and (8).
- d. In section 9.a.11.(e), the certification fuel specifications for dedicated ethanol vehicles (E100) and fuel-flexible ethanol vehicles (E85) would be added. The certification fuel would be the same as the commercial fuel specifications with the added requirement that the RVP adjustment be performed using a common blending component of the gasoline stream.
- e. In section 9.b.2.(5), the treatment of electric and hybrid electric vehicles equipped with air conditioners would be specified for the purpose of determining the road load power. For Type A and B hybrid electric vehicles, the incremental road load power that would be added would be determined by measuring the difference in power needed to operate a vehicle with and without air conditioning during the test sequence used to determine the running loss test fuel tank temperature profile. The method for determining the incremental road load power for Type C hybrid electric vehicles would be identical to the method used for non-hybrids that are subject to the running loss standards.
- f. In section 9.c. and 9.d.3, language would be added to require all hybrid electric vehicles and all 1995 and subsequent model-year vehicles certifying to the new high-temp evaporative emission standards

to follow the test and preconditioning procedures specified in the California evaporative test procedures.

- g. A new section 9.f. would be added to set forth the All-Electric Range Test requirements for electric and hybrid electric vehicles. The test cycle consists of alternating Highway Fuel Economy and Urban Dynamometer Driving schedules. The all-electric range would be determined by the distance the vehicle is able to travel, using battery power only, on the test cycle while maintaining the trace to at least ± 5 mph, and ± 2 seconds. Regenerative braking systems may be utilized during the range test. In addition, the energy used by the vehicle during the test would be recorded. For hybrid electric vehicles, manufacturers would have the option of performing the All-Electric Range Test as a stand-alone test or just prior to vehicle preconditioning as part of the exhaust and evaporative emission test sequence.
 - h. A new section 9.g. would be added to define OMNMFCE for ethanol vehicles. For ethanol vehicles, measurement of OMNMFCE would now include ethanol and acetaldehyde in addition to methanol and formaldehyde.
10. Optional 100,000 Mile Certification Procedure
- No change
11. Additional Requirements
- a. In 11.h, language would be added to make clear that the requirement that M35 exhaust emissions remain below the applicable standards would apply to non-low-emission fuel-flexible vehicles. Also, a similar provision for E10 exhaust emissions would be added for non-low-emission ethanol fuel-flexible vehicles.
 - b. In 11.k, the NMOG and formaldehyde limits applicable to low-emission vehicles at 50 °F would be revised. Currently, all TLEVs, LEVs, and ULEVs must demonstrate compliance with the 50,000 mile certification standards at 50 °F. The regulations would be changed to allow TLEVs and LEVs to have 50 °F emissions of NMOG and formaldehyde that are 1.75 times the 50,000 mile certification standards. Also, a provision exempting fuel-flexible vehicles to conduct 50 °F testing when operating on gasoline would be added; fuel-flexible vehicles would have to conduct 50 °F using the alternative fuel. Additionally, a provision would be added which would give the Executive Officer the opportunity to select specific engine families for 50 °F testing in situations where the manufacturer is certifying more than three TLEV, LEV, and ULEV engine families per year. If a manufacturer provides the Executive Officer with a list of the low-emission vehicle engine

families it will certify, together with a description of the emissions-related components, the Executive Officer shall select the three engine families within 30 days after receiving the information.

- c. In 11.m., the provisions regarding the use of NMOG and formaldehyde factors for assembly line testing would be deleted from these test procedures and inserted into the assembly line test procedures.

12. Identification of New Clean Fuels to be Used in Certification Testing

No significant changes

13. Reactivity Adjustment Factors

- a. In 13.a.1, interim reactivity adjustment factors for TLEVs and LEVs operating on Phase 2 gasoline have been added. Based on the initial data, a reactivity adjustment of 1.00 would be added for TLEVs, and a reactivity adjustment factor of 0.95 would be added for LEVs. In 13.a.2, methane reactivity adjustment factors have been added. For natural gas-fueled TLEVs, the methane reactivity adjustment factor would be 0.0043. For natural gas-fueled LEVs, the interim methane reactivity adjustment factor is 0.0045. Pending the receipt of additional data, the staff will propose modified Phase 2 gasoline reactivity adjustment factors and methane reactivity adjustment factors for LEVs at the Board hearing.

14. Cold Temperature Test Procedure

- a. A new section 14 would be added to incorporate the cold temperature test requirements recently adopted by EPA. Revisions to the CFR language would be made to exempt natural gas, diesel-fueled, hybrid, and zero-emission vehicles from cold CO test requirements and to make the requirements applicable to 1996 and subsequent gasoline, methanol, ethanol and LPG vehicles only.

APPENDIX I

Various changes have been made to incorporate the most recent additions made by EPA and to delete sections which are no longer applicable.

APPENDIX VIII

- a. In note (1)c., the language regarding the measurement of 95 percent of NMOG emissions would be deleted. Note (1)d. concerning the definition

of NMOG would be also be deleted. The new language would require speciated vehicle profiles to identify and quantify a list of target NMOG compounds in accordance with the procedures specified in the "California NMOG Test Procedures."

- b. In note (7)b., the procedure for establishing methane reactivity adjustment factors would be established. The methane reactivity adjustment factor would be determined by dividing the maximum incremental reactivity for methane by the baseline ozone per gram value for vehicles operating on conventional gasoline.
- c. In note (8)b., provisions regarding the calculation of 'undeteriorated reactivity adjustment factors' would be deleted, and provisions on the calculation of 'ozone deterioration factors' would be added. An ozone deterioration factor would be calculated by speciating the exhaust emissions of durability-data vehicles at each mileage interval normally used to determine mass deterioration factors. The ozone deterioration factor would account for changes in the ozone-forming potential per mile of the vehicle as it accumulates mileage, and therefore incorporates deterioration in both mass and reactivity.
- d. In note (9), the specifications of industry average gasoline would be added to represent conventional gasoline used in reactivity testing.
- e. In note (10), the list of maximum incremental reactivities would be replaced with a more general list of organic gas compounds. Such a list could be used by any laboratory and would be easier to revise as the reactivities are updated. However, to use the general list, each laboratory would have to assign the appropriate maximum incremental reactivity value to each compound it measures. To ensure that such assignments are made correctly, the list of NMOG compounds and reactivity assignments would have to be submitted to the Executive Officer prior to or with the certification application.

C. TITLE 13, CALIFORNIA CODE OF REGULATIONS, SECTION 1976

- a. In (b)(1), provisions to include hybrid electric vehicles would be added. All 1993 and subsequent hybrid electric vehicles would be subject to the new high-temperature evaporative test procedures.

D. CALIFORNIA EVAPORATIVE EMISSION STANDARDS AND TEST PROCEDURES FOR 1978 AND SUBSEQUENT MODEL MOTOR VEHICLES

- a. In section 1, hybrid electric vehicles would be added to the applicability provisions of the test procedures. All 1993 and subsequent hybrid electric vehicles would be subject to the new high-temperature evaporative test procedures.

- b. In section 4.g.i., the specific aspects of hybrid electric vehicle testing would be added: the All-Electric Range Test may be performed prior to vehicle preconditioning; the battery pack would be discharged to initiate operation of the auxiliary power unit before beginning exhaust emission testing; manufacturers may elect to perform additional 24-hour diurnal tests beyond the required 72-hour diurnal; manufacturers would be required to conduct testing which includes the effects of evaporative purging.
 - c. The procedures for conducting evaporative purge testing would be specified in 4.x.K. The results would be converted into grams/mile per day values and added to the official running loss emission results in order to determine compliance with the running loss emission standard.
 - d. The procedures specified in 4.x and 4.xi would now also be applicable to ethanol vehicles. Whenever methanol is mentioned, ethanol would now be interchangeable.
- E. TITLE 13, CALIFORNIA CODE OF REGULATIONS, SECTION 2061
- a. The language would be changed to incorporate the latest version of the California assembly-line test procedures.
- F. CALIFORNIA ASSEMBLY-LINE TEST PROCEDURES FOR 1983 AND SUBSEQUENT MODEL-YEAR PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES
- a. In Section A.1., the applicability of the test procedures would be expanded to include alternative fuels which may be used as certification fuels, hybrid electric vehicles, and all other low-emission vehicles.
 - b. In Sections A.2. and D.3., the version of the California emission standards and test procedures applicable for 1988 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles would be included as a reference for the quality-audit test.
 - c. In Section D.1., the sample rate for quality-audit testing would be set at not less than 1.0 percent for all engine families certified as fuel-flexible or dual-fuel vehicles. Because fuel-flexible and dual-fuel vehicles must be certified to emission standards using at least two fuels, limiting the sample rate to 1.0 percent would lessen the testing burden on manufacturers of these vehicles.
 - d. In Section D.2(c), a new procedure would be outlined for vehicles that are certified to the running loss and useful life standards set forth in the California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles that would ensure that a vehicle tested under these test procedures would exhibit an interaction

of vapor purge and exhaust emissions which is comparable to that which would occur under the method prescribed in the evaporative test procedures. In section D.2.(c)(1), manufacturers are given three options by which they may satisfy the requirements of the new procedure. The first option represents the original procedures as stipulated in the evaporative emission test procedures, except that alternative methods would be allowed if shown to be comparable. The second option would allow a separate loaded canister to be attached to the vehicle in place of the original canister, and the replacement canister would be loaded at a rate not to exceed 40 grams/hour. Again, alternative methods would be allowed if shown to be comparable. The third option would allow manufacturers to submit data demonstrating that there does not exist a measurable difference in exhaust emissions, for both hydrocarbons and OMHCE, between vehicles possessing a canister(s) loaded to the evaporative test procedure method and vehicles possessing an unloaded canister(s) (i.e., not loaded by the method prescribed by the evaporative test procedures).

- e. In Section D.5., the various types of hydrocarbon standards to which vehicles may be certified would be listed. For engine families certified to OMHCE or OMNMHCE standards, the use of OMHCE or OMNMHCE to NMHC ratios would be allowed. For engine families certified to NMOG standards, the use of NMOG to NMHC ratios would be allowed.
- f. In Section D.6., the requirement for formaldehyde emission measurements would be specified. Similar to OMHCE, OMNMHCE, and NMOG, the use of formaldehyde to NMHC ratios would be allowed.
- g. In Section D.7.(a), a requirement would be added to require the submittal of low-emission vehicle production data in manufacturers' quarterly reports. The additional required data would consist of the total number of vehicles certified to each of the low-emission vehicle categories and produced and delivered for sale in California in each of the three vehicle classifications [1) passenger cars and light-duty trucks 0-3750 lbs. LVW, 2) light-duty trucks 3751-5750 lbs. LVW, and 3) medium-duty vehicles]. Additionally, manufacturers would also be required to report the fuel type and the reactivity adjustment factor, if any, applicable to their vehicles.
- h. In Section D.7.(c), language would be added to require low-emission natural gas vehicles to submit methane data. Also, the number of significant digits to be reported for each emission standard would be clarified. The data reported should be rounded to one significant digit beyond the emission standard.
- i. In Section D.7.(e)(2), the treatment of reactivity adjustment factors and ozone deterioration factors would be specified for the statistical analysis of the quality-audit test results. Reactivity adjustment factors and ozone deterioration factors would be applied prior to computing average and standard deviations.

- j. In Sections D.7(c) and D.7(e)(2) provisions for the measurement of methane would be inserted for natural gas vehicles to reflect the proposed addition of reactivity-adjusted methane exhaust emissions to the calculation of NMOG for natural gas vehicles.

G. CALIFORNIA NON-METHANE ORGANIC GAS TEST PROCEDURES

The California Non-Methane Organic Gas Test Procedures as adopted July 12, 1991 would be superceded by the current revised test procedures in order to simplify the procedures and provide more flexibility for laboratories conducting analyses of non-methane organic gases in motor vehicle exhaust.

1. General Applicability and Requirements. This new document would clarify the applicability of these procedures to low emission vehicles and would update the requirements for measurement of exhaust emissions.

2. Determination of Non-Methane Hydrocarbon Mass Emissions by Flame Ionization Detection. This test procedure would replace the "California Non-Methane Hydrocarbon Test Procedures" amended by the Board on July 12, 1991. This new document would delete the sections outlining the instrumentation, sampling procedures and instrument calibration sections because they have already been detailed in SAE documents incorporated by reference. A procedure for determining FID response to methane would be added, and calculations for NMHC mass emissions would be reorganized for clarity. The criteria for negative NMHC determination would be deleted.

3. Method Nos 1001, 1002, 1003, 1004, 1005. Since standard operating procedures (SOPs) tend to be "living" documents in the laboratory, frequently changing as better techniques and technology used in methods become available, the SOPs would be rewritten as methods. The designation of methods for these regulations would give the user laboratories the flexibility to develop their own SOPs for the determination of the target compounds specified in each method. A new list of target compounds in the methods would be proposed and the "identification of 95% of the compounds" provision of the regulations would be deleted. This new list provides clear guidance to laboratories about the compounds that should be identified. The proposed methods would not require the use of a specific sampling method, although suggestions are provided.

a. SOP No. MLD 101 would be renamed as MLD Method No. 1001 for the determination of alcohols (methanol and ethanol) in motor vehicle exhaust. No major changes would be made. Additional quality control (QC) requirements would be added.

b. SOP No. MLD 102 would be renamed to MLD Method No. 1002 for the determination of the C2 to C5 hydrocarbons in motor vehicle exhaust. A new column material, a list of target compounds to be determined, the use of National Institute of Standards and Technology

(NIST) propane as the primary standard, a method limit of detection (LOD) calculation, and "crossover compound" use and acceptance criteria are specified, and additional QC requirements would be added.

Because of manufacturing changes to the Durapak Phenylisocyanate packed column material, identification of target compounds became difficult. Compound identification required by our SOP became infeasible without the use of other detectors (tandem photoionization and flame ionization detectors) or extraordinary techniques (cryogenic column temperature ramping). Thus the proposed method allows the use of the porous layer open tubular (PLOT) capillary column as an alternative to the packed column. Separation, accuracy, and resolution of the target compounds identified in the current SOP is equal, if not better, with the PLOT column.

The list of target compounds contained in the proposed method would be expanded to include all light hydrocarbons through the pentanes (carbon number 5), including 1,3-butadiene. The list of target compounds proposed for this method is similar to that used for the analyses conducted for the Auto/Oil Study. In addition, the proposed method would designate n-hexane as a "crossover compound" that functions as a quality control indicator. N-hexane could be determined by both the proposed MLD Methods No. 1002 and 1003. The proposed method would include acceptance criteria to judge the agreement between the two determinations.

The current SOP specifies a calibration standard containing a mixture of 11 NIST-traceable compounds, which are not readily available. In response to industry comments, the calibration standard in the proposed method would be designated as NIST-traceable propane. The analyses conducted for the Auto/Oil Study used propane as the calibration standard.

c. SOP No. MLD 103A would be renamed as Method No. 1003 for the determination of the C6 to C12 hydrocarbons in motor vehicle exhaust. A target list of compounds, the use of NIST-traceable benzene as the calibration standard, the designation of the LOD for the method and the procedure for its calculation are specified in the proposal, and some additional QC requirements would be added. The list of target compounds is an expanded version of the proposed "50 compound" list presented by ARB staff at the Spring 1990 workshop. The list of target compounds proposed for this method is similar to that used for the analyses conducted for the Auto/Oil Study.

The ARB staff had initially proposed the use of a calibration standard containing six NIST-traceable compounds which was adopted into the NMOG regulations. However, this calibration standard is specially ordered from NIST by ARB and is not readily available. Industry proposed the use of a NIST-traceable propane standard. After considering industry comments, the use of NIST-traceable benzene would

be proposed as the calibration standard. We do not agree with the use of propane as a calibration standard because it is not determined by this method, and its peak-shape (non-isosceles) makes confirmation tentative.

d. SOP No. MLD 104 would be renamed as MLD Method No. 1004 for the determination of the carbonyls in motor vehicle exhaust. A target list of carbonyls would be added to the proposed method. The 4-carbon compound limitation contained in the current SOP would be replaced with an expanded target list of compounds that reflect technology improvements and method development. The list of target compounds proposed for this method is similar to that used for the analyses conducted for the Auto/Oil Study.

e. MLD Method No. 1005 would be added for the determination of oxygenated compounds in motor vehicle exhaust. Exhaust from motor vehicles tends to reflect the composition of the fuels used. Phase 2 gasoline fuels contain additives that contain oxygenated compounds, such as methyl tertiarybutyl ether (MTBE). Oxygenated compounds in auto exhaust can have a small effect on the Reactivity Adjustment Factors (RAFs). This proposed method would use gas chromatography with a thermionic ionization detector (TID) outfitted with a boiling point capillary column operated at elevated temperatures.

4. Determination of NMOG Mass Emissions. This test procedure would be added to the current procedures because the original SOPs did not include a method for the determination of mass of exhaust. The procedure would be divided into seven subparts: 1) "Determination of NMOG Mass Emissions," 2) "Speciated Hydrocarbon Mass Emissions Calculation," 3) "Alcohol Mass Emissions Calculation," 4) Carbonyl Mass Emissions Calculation," 5) "Dilution Factor Calculation," 6) "Definitions," and 7) "Reference."

APPENDIX B

SUMMARY OF TEST DATA (as of 9/16/92)

Preliminary RAF Determination

RAF for TLEV vehicles operated on Phase 2 gasoline

Vehicle	Phase 2 (Ozone/g)
Camry	3.62
Lexus 300	3.04
Escort	3.45
Average	3.37

Baseline Ozone/g for RF-A = 3.42 (adopted)

Preliminary RAF for TLEV vehicles = $3.37/3.42 = 0.98$

RAF for LEV vehicles operated on Phase 2 gasoline

Vehicle	RF-A (Ozone/g)	Phase 2 (Ozone/g)
Jetta	3.15	2.82
Lexus 400	3.66	3.10
Celica	2.90	NA
Average	3.24	2.96

NA- data not available

Preliminary RAF for LEV vehicles = $2.96/3.24 = 0.91$

Table I
Summary of Test Results of TLEV-level Vehicles
Operated on Phase 2 Certification Fuel

Vehicle	Test #	Species Table #	Test Date	NMOG (g/mi)	CH4 (g/mi)	CO (g/mi)	NOx (g/mi)
1992 Camry 2.2 L	13C9	I-1a	8/20/92	0.085	0.013	1.65	0.161
	13C10	I-1a	8/21/92	0.107	0.015	2.11	0.139
	13C11	I-1b	8/25/92	0.094	0.015	1.68	0.111
			Mean:	0.095	0.014	1.81	0.137
1992 Cougar 4.9 L	36C5	I-2a	8/12/92	0.055	0.030	1.24	0.156
	36C6	I-2a	8/13/92	0.060	0.031	1.17	0.146
	36C7	I-2b	8/14/92	0.055	0.020	0.84	0.178
	36C8	I-2b	8/18/92	0.074	0.031	1.07	0.157
			Mean:	0.061	0.028	1.08	0.159
1993 Escort 1.9 L	41C4	I-3a	8/20/92	0.049	0.010	0.74	0.091
			Mean:				

Table II
Summary of Test Results of LEV-level Vehicles
Operated on RF-A Certification Fuel

Vehicle	Test #	Species Table #	Test Date	NMOG (g/mi)	CH4 (g/mi)	CO (g/mi)	NOx (g/mi)
1991 Jetta 1.8 L	24C5	II-1a	7/16/92	0.049	0.026	1.40	0.148
	24C6	II-1b	7/17/92	0.052	0.025	1.38	0.152
	24C7	II-1b	7/18/92	0.064	0.027	1.44	0.138
			Mean:	0.055	0.026	1.41	0.146
1992 Lexus 400 4.0 L	25C8	II-2a	7/30/92	0.058	0.024	0.29	0.187
	25C9	II-2a	7/31/92	0.064	0.030	0.57	0.215
	25C10	II-2b	8/4/92	0.077	0.029	0.44	0.202
	25C12	II-2b	8/6/92	0.071	0.027	0.42	0.201
			Mean:	0.068	0.028	0.43	0.201
1990 Celica 2.2 L	27C12	II-3a	7/17/92	0.069	0.019	0.61	0.226
	27C14	II-3a	7/22/92	0.062	0.018	0.48	0.240
			Mean:	0.066	0.018	0.55	0.233

Table III
Summary of Test Results of LEV-level Vehicles
Operated on Phase 2 Certification Fuel

Vehicle	Test #	Species Table #	Test Date	NMOG (g/mi)	CH4 (g/mi)	CO (g/mi)	NOx (g/mi)
1991 Jetta 1.8 L	24C10	III-1a	8/27/92	0.035	0.016	1.05	0.083
			Mean:	0.035	0.016	1.05	0.083
1992 Lexus 400 4.0 L	25C13	III-2a	8/11/92	0.041	0.019	0.30	0.139
	25C14	III-2a	8/12/92	0.035	0.017	0.28	0.154
	25C15	III-2b	8/13/92	0.036	0.018	0.28	0.132
	25C16	III-2b	8/14/92	0.052	0.019	0.32	0.140
			Mean:	0.041	0.018	0.30	0.141

Table I-1a
Speciated FTP Results
Toyota Camry, Phase 2

	mg Ozone/ mg NMOG	Test 13C9, 8/20/92		Test 13C10, 8/20/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Light-end Species					
Ethane	0.25	1.90	0.48	2.06	0.52
Ethene	7.29	4.88	35.58	5.75	41.92
Propane	0.48	0.33	0.16	0.03	0.01
Ethyne	0.5	1.84	0.92	2.38	1.19
Methylpropane	1.21	0.72	0.87	0.10	0.12
Butane	1.02	0.50	0.51	0.70	0.71
Propene	9.4	4.15	39.01	4.85	45.59
Methylbutane	1.38	4.85	6.69	5.27	7.27
Pentane	1.04	0.57	0.59	0.64	0.67
1-Butene	8.91	0.45	4.01	0.54	4.81
2-Methylpropene	5.31	4.94	26.23	5.68	30.16
Light-End HC Subtotal	36.79	25.13	115.05	28.00	132.97
	mg Ozone/ mg NMOG	Test 13C9, 8/20/92		Test 13C10, 8/20/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
1,3-Butadiene	10.89	0.32	3.48	0.39	4.25
4-Methyl-1-Pentene	4.42	0.12	0.53	0.17	0.75
2,3-Dimethylbutane	1.07	2.05	2.19	1.86	1.99
2-Methylpentane	1.53	1.57	2.40	2.94	4.50
C6H12 Alkene 2	5.55	0.10	0.56	0.16	0.89
3-Methylpentane	1.52	0.79	1.20	1.30	1.98
C6H12 Alkene 3	5.55	0.10	0.56	0.16	0.89
n-Hexane	0.98	0.47	0.46	0.56	0.55
t-2-Hexene	6.69	0.09	0.60	0.13	0.87
c-2-Hexene	6.69	0.11	0.74	0.17	1.14
Methylcyclopentane	2.82	0.33	0.93	1.19	3.36
C7H16 Alkane	1.4	1.65	2.31	1.96	2.74
Benzene	0.42	3.15	1.32	5.32	2.23
3-Methyl-1-hexene	3.48	0.01	0.03		
Cyclohexane	1.28	0.03	0.04	0.06	0.08
2-Methylhexane + Dimethylpentane	1.4	3.65	5.11	5.32	7.45
3-Methylhexane	1.4	1.07	1.50	1.56	2.18
2,2,4-Trimethylpentane + Alkene	2.59	7.15	18.52	10.49	27.17
n-Heptane	0.81	0.88	0.71	1.34	1.09
Methylcyclohexane	1.85	0.21	0.39	0.32	0.59
Dimethylhexane	1.2	1.76	2.11	2.42	2.90
Toluene + C8H18	2.73	8.11	22.14	12.44	33.96
2,3-Dimethylhexane	1.32	0.77	1.02	1.13	1.49
Methylheptane	1.2	0.76	0.91	1.22	1.46
Dimethylcyclohexane	1.94	0.19	0.37	0.44	0.85
2,2,5-Trimethylhexane	0.97	0.89	0.86	1.31	1.27
n-Octane	0.61	0.50	0.31	0.62	0.38
C9H18 Alkene	3.4	0.14	0.48	0.14	0.48

**Table I-1a
Speciated FTP Results
Toyota Camry, Phase 2**

	mg Ozone/ mg NMOG	Test 13C9, 8/20/92		Test 13C10, 8/20/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
C9H18 Alkene	3.4	0.14	0.48	0.14	0.48
Ethylbenzene	2.7	3.16	8.53	4.05	10.94
m & p-Xylenes	7.38	6.34	46.79	8.42	62.14
C9H20 Alkane	1.14	0.47	0.54	0.55	0.63
Styrene	2.22	0.79	1.75	0.70	1.55
o- Xylene	6.46	2.53	16.34	3.48	22.48
n- Nonane	0.54	0.10	0.05	0.20	0.11
i-Propylbenzene	2.24	0.13	0.29	0.15	0.34
n-Propylbenzene	2.12	0.85	1.80	0.63	1.34
3-Ethyltoluene	7.2	2.29	16.49	1.33	9.58
4-Ethyltoluene + C10cycloalkane	4.49	1.04	4.67	0.49	2.20
1,3,5-Trimethylbenzene	10.12	0.96	9.72	0.70	7.08
2-Ethyltoluene	7.2	0.75	5.40	0.54	3.89
1,2,4-Trimethylbenzene	8.83	1.95	17.22	2.28	20.13
n-Decane	0.47	0.02	0.01	0.08	0.04
n-Undecane	0.42	0.04	0.02		
Mid-Range HC Subtotal		58.53	201.87	78.86	250.39
	mg Ozone/ mg NMOG	Test 13C9, 8/20/92		Test 13C10, 8/20/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates					
Formaldehyde	7.15	0.59	4.22	0.47	3.36
Acetaldehyde	5.52	0.32	1.77	0.32	1.77
Acetone	0.56	0.15	0.08	0.09	0.05
Oxygenates Subtotal		1.06	6.07	0.88	5.18
		Test 13C9, 8/20/92		Test 13C10, 8/20/92	
		NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary					
Light-End Species		25.13	115.05	28.00	132.97
Mid-Range Species		58.53	201.87	78.86	250.39
Oxygenates		1.06	6.07	0.88	5.18
Total		84.72	322.99	107.74	388.54
Ozone/NMOG		3.81		3.61	

**Table I-1b
Speciated FTP Results
Toyota Camry, Phase 2**

	mg Ozone/ mg NMOG	Test 13C11, 8/25/92	
		NMOG	Ozone
Light-end Species	MIR	(mg/mi)	(mg/mi)
Ethane	0.25	2.21	0.55
Ethene	7.29	5.01	36.52
Propane	0.48	0.16	0.08
Ethyne	0.5	1.66	0.83
Methylpropane	1.21	0.14	0.17
Butane	1.02	0.61	0.62
Propene	9.4	3.83	36.00
Methylbutane	1.38	5.33	7.36
Pentane	1.04	0.63	0.66
1-Butene	8.91	0.44	3.92
2-Methylpropene	5.31	4.98	26.44
Light-End HC Subtotal	36.79	25.00	113.15
	mg Ozone/ mg NMOG	Test 13C11, 8/25/92	
		NMOG	Ozone
Mid-Range Species	MIR	(mg/mi)	(mg/mi)
1,3-Butadiene	10.89	0.35	3.81
4-Methyl-1-Pentene	4.42	0.14	0.62
2,3-Dimethylbutane	1.07	1.77	1.89
2-Methylpentane	1.53	2.43	3.72
C6H12 Alkene 2	5.55	0.13	0.72
3-Methylpentane	1.52	1.12	1.70
C6H12 Alkene 3	5.55	0.12	0.67
n-Hexane	0.98	0.64	0.63
t-2-Hexene	6.69	0.10	0.67
c-2-Hexene	6.69	0.13	0.87
Methylcyclopentane	2.82	0.53	1.49
C7H16 Alkane	1.4	2.27	3.18
Benzene	0.42	4.70	1.97
3-Methyl-1-hexene	3.48	0.24	0.84
Cyclohexane	1.28	0.05	0.06
2-Methylhexane + Dimethylpentane	1.4	4.92	6.89
3-Methylhexane	1.4	1.47	2.06
2,2,4-Trimethylpentane + Alkene	2.59	10.09	26.13
n-Heptane	0.81	1.21	0.98
Methylcyclohexane	1.85	0.27	0.50
Dimethylhexane	1.2	2.44	2.93
Toluene + C8H18	2.73	10.52	28.72
2,3-Dimethylhexane	1.32	1.06	1.40
Methylheptane	1.2	1.10	1.32
Dimethylcyclohexane	1.94	0.44	0.85
2,2,5-Trimethylhexane	0.97	1.20	1.16
n-Octane	0.61	0.56	0.34
C9H18 Alkene	3.4	0.13	0.44

Table I-1b
Speciated FTP Results
Toyota Camry, Phase 2

	mg Ozone/ mg NMOG	Test 13C11, 8/25/92	
		NMOG	Ozone
Mid-Range Species	MIR	(mg/mi)	(mg/mi)
Ethylbenzene	2.7	3.05	8.24
m & p-Xylenes	7.38	6.61	48.78
C9H20 Alkane	1.14	0.43	0.49
Styrene	2.22	0.58	1.29
o- Xylene	6.46	2.66	17.18
n- Nonane	0.54	0.17	0.09
i-Propylbenzene	2.24	0.13	0.29
n-Propylbenzene	2.12	0.14	0.30
3-Ethyltoluene	7.2	0.40	2.88
4-Ethyltoluene + C10cycloalkane	4.49		0.00
1,3,5-Trimethylbenzene	10.12	0.62	6.27
2-Ethyltoluene	7.2	0.51	3.67
1,2,4-Trimethylbenzene	8.83	1.73	15.28
n-Decane	0.47	0.07	0.03
n-Undecane	0.42	0.04	0.02
Mid-Range HC Subtotal		67.27	201.38
	mg Ozone/ mg NMOG	Test 13C11, 8/25/92	
		NMOG	Ozone
Oxygenates	MIR	(mg/mi)	(mg/mi)
Formaldehyde	7.15	0.79	5.65
Acetaldehyde	5.52	0.30	1.66
Acetone	0.56	0.25	0.14
Oxygenates Subtotal		1.34	7.44
		Test 13C11, 8/25/92	
		NMOG	Ozone
NMOG Summary		(mg/mi)	(mg/mi)
Light-End Species		25.00	113.15
Mid-Range Species		67.27	201.38
Oxygenates		1.34	7.44
Total		93.61	321.98
Ozone/NMOG		3.44	

Table I-2a
Speciated FTP Results
Mercury Cougar, Phase 2

	mg Ozone/ mg NMOG	Test 36C5, 8/12/92		Test 36C6, 8/13/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Light-end Species					
Ethane	0.25	2.71	0.68	2.54	0.64
Ethene	7.29	3.70	26.97	4.05	29.52
Propane	0.48	0.12	0.06	0.13	0.06
Ethyne	0.50	1.27	0.64	1.49	0.75
Methylpropane	1.21	0.11	0.13	0.11	0.13
Butane	1.02	0.97	0.99	0.82	0.84
Propene	9.40	1.68	15.79	1.78	16.73
Methylbutane	1.38	5.57	7.69	5.30	7.31
Pentane	1.04	0.74	0.77	0.64	0.67
1-Butene	8.91	0.22	1.96	0.23	2.05
2-Methylpropene	5.31	1.53	8.12	1.56	8.28
Light-End HC Subtotal		18.62	63.80	18.65	66.98
	mg Ozone/ mg NMOG	Test 36C5, 8/12/92		Test 36C6, 8/13/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
1,3-Butadiene	10.89	0.12	1.31	0.10	1.09
4-Methyl-1-pentene	4.42	0.18	0.80	0.10	0.44
2,3-Dimethylbutane	1.07	0.69	0.74	2.59	2.77
2-Methylpentane	1.53	2.85	4.36	1.90	2.91
C6H12 Alkene 2	5.55	0.08	0.44	0.08	0.44
3-Methylpentane	1.52	1.91	2.90	0.84	1.28
C6H12 Alkene 3	5.55	0.08	0.44	0.08	0.44
n-Hexane	0.98	0.53	0.52	0.46	0.45
t-2-Hexene	6.69	0.07	0.47	0.06	0.40
c-2-Hexene	6.69	0.08	0.54	0.09	0.60
Methylcyclopentane	2.82	0.41	1.16	0.27	0.76
C7H16 Alkane	1.40	1.38	1.93	1.43	2.00
Benzene	0.42	1.59	0.67	1.91	0.80
3-Methyl-1-hexene	3.48	0.07	0.24	0.03	0.10
Cyclohexane	1.28	0.05	0.06	0.02	0.03
2-Methylhexane + Dimethylpentane	1.40	2.87	4.02	3.04	4.26
3-Methylhexane	1.40	0.84	1.18	0.86	1.20
2,2,4-Trimethylpentane + Alkene	2.59	6.54	16.94	6.02	15.59
n-Heptane	0.81	0.42	0.34	0.64	0.52
Methylcyclohexane	1.85	0.00	0.00	0.16	0.30
Dimethylhexane	1.20	0.85	1.02	1.24	1.49
Toluene + C8H18	2.73	3.71	10.13	4.26	11.63
2,3-Dimethylhexane	1.32	0.38	0.50	0.54	0.71
Methylheptane	1.20	0.40	0.48	0.57	0.68
Dimethylcyclohexane	1.94	0.05	0.10	0.18	0.35
2,2,5-Trimethylhexane	0.97	0.54	0.52	0.60	0.58
n-Octane	0.61	0.25	0.15	0.28	0.17
C9H18 Alkene	3.40	0.07	0.24	0.11	0.37
Ethylbenzene	2.70	0.97	2.62	2.04	5.51

Table I-2a
Speciated FTP Results
Mercury Cougar, Phase 2

	mg Ozone/ mg NMOG	Test 36C5, 8/12/92		Test 36C6, 8/13/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
Ethylbenzene	2.70	0.97	2.62	2.04	5.51
m & p-Xylenes	7.38	2.05	15.13	2.64	19.48
C9H20 Alkane	1.14	0.29	0.33	0.56	0.64
Styrene	2.22	0.26	0.58	0.28	0.62
o-Xylene	6.46	0.79	5.10	0.92	5.94
n-Nonane	0.54	0.11	0.06	0.15	0.08
i-Propylbenzene	2.24	0.07	0.16	0.10	0.22
n-Propylbenzene	2.12	0.18	0.38	0.29	0.61
3-Ethyltoluene	7.20	0.91	6.55	0.32	2.30
4-Ethyltoluene + C10cycloalkane	4.49	0.12	0.54	0.00	0.00
1,3,5-Trimethylbenzene	10.12	0.19	1.92	1.49	15.08
2-Ethyltoluene	7.20	0.27	1.94	0.61	4.39
1,2,4-Trimethylbenzene	8.83	0.00	0.00	0.15	1.32
n-Decane	0.47	0.06	0.03	0.08	0.04
n-Undecane	0.42	0.00	0.00	0.27	0.11
Mid-Range HC Subtotal		34.25	90.15	40.40	114.25
	mg Ozone/ mg NMOG	Test 36C5, 8/12/92		Test 36C6, 8/13/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates					
Formaldehyde	7.15	2.90	20.74	1.97	14.09
Acetaldehyde	5.52	0.35	1.93	0.36	1.99
Acrolein	6.76	0.00	0.00	0.06	0.41
Acetone	0.56	0.22	0.12	0.20	0.11
Oxygenates Subtotal		3.47	22.79	2.59	16.59
		Test 36C5, 8/12/92		Test 36C6, 8/13/92	
		NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary					
Light-End Species		18.62	63.80	18.65	66.98
Mid-Range Species		34.25	90.15	40.40	114.25
Oxygenates		3.47	22.79	2.59	16.59
Total		56.34	176.74	61.64	197.82
Ozone/NMOG		3.14		3.21	

**Table I-2b
Speciated FTP Results
Mercury Cougar, Phase 2**

	mg Ozone/ mg NMOG	Test 36C7, 8/14/92		Test 36C8, 8/18/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Light-end Species					
Ethane	0.25	2.58	0.65	2.66	0.67
Ethene	7.29	4.10	29.89	5.03	36.67
Propane	0.48	0.18	0.09	0.89	0.43
Ethyne	0.50	1.45	0.73	1.60	0.80
Methylpropane	1.21	0.09	0.11	0.37	0.45
Butane	1.02	0.69	0.70	1.69	1.72
Propene	9.40	1.58	14.85	1.83	17.20
Methylbutane	1.38	4.88	6.73	6.37	8.79
Pentane	1.04	0.47	0.49	5.89	6.13
1-Butene	8.91	0.23	2.05	0.37	3.30
2-Methylpropene	5.31	1.33	7.06	2.39	12.69
Light-End HC Subtotal		17.58	63.34	29.09	88.84
	mg Ozone/ mg NMOG	Test 36C7, 8/14/92		Test 36C8, 8/18/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
1,3-Butadiene	10.89	0.09	0.98	0.10	1.09
Cyclopentene	7.66	0.00	0.00	0.15	1.15
4-Methyl-1-pentene	4.42	0.09	0.40	0.08	0.35
2,3-Dimethylbutane	1.07	2.70	2.89	2.44	2.61
2-Methylpentane	1.53	1.82	2.78	2.22	3.40
C6H12 Alkene 2	5.55	0.08	0.44	0.07	0.39
3-Methylpentane	1.52	0.84	1.28	1.16	1.76
C6H12 Alkene 3	5.55	0.20	1.11	0.07	0.39
n-Hexane	0.98	0.47	0.46	0.55	0.54
t-2-Hexene	6.69	0.07	0.47	0.06	0.40
c-2-Hexene	6.69	0.09	0.60	0.08	0.54
Methylcyclopentane	2.82	0.26	0.73	0.34	0.96
C7H16 Alkane	1.40	1.54	2.16	2.00	2.80
Benzene	0.42	1.72	0.72	2.15	0.90
3-Methyl-1-hexene	3.48	0.28	0.97	0.00	0.00
Cyclohexane	1.28	0.02	0.03	0.16	0.20
2-Methylhexane + Dimethylpentane	1.40	3.29	4.61	4.22	5.91
3-Methylhexane	1.40	0.90	1.26	1.16	1.62
2,2,4-Trimethylpentane + Alkene	2.59	6.89	17.85	8.56	22.17
n-Heptane	0.81	0.66	0.53	0.91	0.74
Methylcyclohexane	1.85	0.15	0.28	0.22	0.41
Dimethylhexane	1.20	1.27	1.52	1.78	2.14
Toluene + C8H18	2.73	3.93	10.73	4.93	13.46
2,3-Dimethylhexane	1.32	0.55	0.73	0.74	0.98
Methylheptane	1.20	0.48	0.58	0.74	0.89
Dimethylcyclohexane	1.94	0.11	0.21	0.20	0.39
2,2,5-Trimethylhexane	0.97	0.61	0.59	0.82	0.80
n-Octane	0.61	0.28	0.17	0.43	0.26
C9H18 Alkene	3.40	0.11	0.37	0.13	0.44

**Table I-2b
Speciated FTP Results
Mercury Cougar, Phase 2**

	mg Ozone/ mg NMOG	Test 36C7, 8/14/92		Test 36C8, 8/18/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
C9H18 Alkene	3.40	0.11	0.37	0.13	0.44
Ethylbenzene	2.70	1.37	3.70	0.88	2.38
m & p-Xylenes	7.38	2.14	15.79	2.37	17.49
C9H20 Alkane	1.14	0.24	0.27	0.24	0.27
Styrene	2.22	0.19	0.42	0.20	0.44
o-Xylene	6.46	0.80	5.17	0.92	5.94
n-Nonane	0.54	0.04	0.02	0.13	0.07
i-Propylbenzene	2.24	0.08	0.18	0.10	0.22
n-Propylbenzene	2.12	0.17	0.36	0.11	0.23
3-Ethyltoluene	7.20	0.18	1.30	0.19	1.37
4-Ethyltoluene + C10cycloalkane	4.49	0.00	0.00	0.16	0.72
1,3,5-Trimethylbenzene	10.12	0.23	2.33	0.21	2.13
2-Ethyltoluene	7.20	0.56	4.03	0.16	1.15
1,2,4-Trimethylbenzene	8.83	0.52	4.59	0.04	0.35
n-Decane	0.47	0.08	0.04	0.06	0.03
n-Undecane	0.42	0.04	0.02	0.00	0.00
Mid-Range HC Subtotal		36.25	94.05	42.37	100.92
	mg Ozone/ mg NMOG	Test 36C7, 8/14/92		Test 36C8, 8/18/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates					
Formaldehyde	7.15	0.89	6.36	1.88	13.44
Acetaldehyde	5.52	0.31	1.71	0.43	2.37
Acrolein	6.76	0.06	0.41	0.00	0.00
Acetone	0.56	0.19	0.11	0.15	0.08
Oxygenates Subtotal		1.45	8.59	2.46	15.90
		Test 36C7, 8/14/92		Test 36C8, 8/18/92	
		NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary					
Light-End Species		17.58	63.34	29.09	88.84
Mid-Range Species		36.25	94.05	42.37	100.92
Oxygenates		1.45	8.59	2.46	15.90
Total		55.28	165.98	73.92	205.65
Ozone/NMOG		3.00		2.78	

**Table I-3a
Speciated FTP Results
Ford Escort, Phase 2**

	mg Ozone/	Test 41C4, 8/20/92	
	mg NMOG	NMOG	Ozone
Light-end Species	MIR	(mg/mi)	(mg/mi)
Ethane	0.25	1.87	0.47
Ethene	7.29	3.58	26.10
Propane	0.48	0.09	0.04
Ethyne	0.50	0.62	0.31
Methylpropane	1.21	0.06	0.07
Butane	1.02	0.45	0.46
Propene	9.40	2.63	24.72
Methylbutane	1.38	3.77	5.20
Pentane	1.04	0.38	0.40
1-Butene	8.91	0.35	3.12
2-Methylpropene	5.31	2.83	15.03
Light-End HC Subtotal		16.63	75.92
	mg Ozone/	Test 41C4, 8/20/92	
	mg NMOG	NMOG	Ozone
Mid-Range Species	MIR	(mg/mi)	(mg/mi)
1,3-Butadiene	10.89	0.30	3.27
4-Methyl-1-pentene	4.42	0.07	0.31
2,3-Dimethylbutane	1.07	1.02	1.09
2-Methylpentane	1.53	1.24	1.90
C6H12 Alkene 2	5.55	0.06	0.33
3-Methylpentane	1.52	0.57	0.87
C6H12 Alkene 3	5.55	0.06	0.33
n-Hexane	0.98	0.28	0.27
t-2-Hexene	6.69	0.05	0.33
c-2-Hexene	6.69	0.07	0.47
Methylcyclopentane	2.82	0.18	0.51
C7H16 Alkane	1.40	1.23	1.72
Benzene	0.42	2.00	0.84
Cyclohexane	1.28	0.01	0.01
2-Methylhexane + Dimethylpentane	1.40	2.42	3.39
3-Methylhexane	1.40	0.67	0.94
2,2,4-Trimethylpentane + Alkene	2.59	5.19	13.44
n-Heptane	0.81	0.50	0.41
Methylcyclohexane	1.85	0.15	0.28
Dimethylhexane	1.20	1.16	1.39
Toluene + C8H18	2.73	4.11	11.22
2,3-Dimethylhexane	1.32	0.55	0.73
Methylheptane	1.20	0.47	0.56
Dimethylcyclohexane	1.94	0.21	0.41
2,2,5-Trimethylhexane	0.97	0.61	0.59
n-Octane	0.61	0.33	0.20
C9H18 Alkene	3.40	0.15	0.51
Ethylbenzene	2.70	1.06	2.86
m & p-Xylenes	7.38	2.20	16.24

Table I-3a
Speciated FTP Results
Ford Escort, Phase 2

	mg Ozone/ mg NMOG	Test 41C4, 8/20/92	
		NMOG	Ozone
	MIR	(mg/mi)	(mg/mi)
Mid-Range Species			
C9H20 Alkane	1.14	0.27	0.31
Styrene	2.22	0.49	1.09
o-Xylene	6.46	0.87	5.62
n-Nonane	0.54	0.14	0.08
i-Propylbenzene	2.24	0.11	0.25
n-Propylbenzene	2.12	0.21	0.45
3-Ethyltoluene	7.20	0.61	4.39
4-Ethyltoluene + C10cycloalkane	4.49	0.25	1.12
1,3,5-Trimethylbenzene	10.12	0.25	2.53
2-Ethyltoluene	7.20	0.20	1.44
1,2,4-Trimethylbenzene	8.83	0.48	4.24
n-Decane	0.47	0.03	0.01
n-Undecane	0.42	0.04	0.02
Mid-Range HC Subtotal		30.87	86.96
	mg Ozone/ mg NMOG	Test 41C4, 8/20/92	
		NMOG	Ozone
	MIR	(mg/mi)	(mg/mi)
Oxygenates			
Formaldehyde	7.15	0.66	4.72
Acetaldehyde	5.52	0.30	1.66
Acetone	0.56	0.04	0.02
Oxygenates Subtotal		1.00	6.40
		Test 41C4, 8/20/92	
		NMOG	Ozone
		(mg/mi)	(mg/mi)
NMOG Summary			
Light-End Species		16.63	75.92
Mid-Range Species		30.87	86.96
Oxygenates		1.00	6.40
Total		48.50	169.27
Ozone/NMOG		3.49	

Table II-1a
Speciated FTP Results
VW Jetta, RFA

	mg Ozone/ mg NMOG	Test 24C5, 7/17/92	
		NMOG	Ozone
Light-end Species	MIR	(mg/mi)	(mg/mi)
Ethane	0.25	3.20	0.80
Ethene	7.29	3.21	23.40
Propane	0.48	0.00	0.00
Ethyne	0.50	0.86	0.43
Methylpropane	1.21	0.12	0.15
Butane	1.02	3.05	3.11
Propene	9.40	1.23	11.56
Methylbutane	1.38	3.52	4.86
Pentane	1.04	2.06	2.14
1-Butene	8.91	0.17	1.51
2-Methylpropene	5.31	1.20	6.37
Light-End HC Subtotal		18.62	54.34
	mg Ozone/ mg NMOG	Test 24C5, 7/17/92	
		NMOG	Ozone
Mid-Range Species	MIR	(mg/mi)	(mg/mi)
1,3-Butadiene	10.89	0.22	2.40
t-2-Pentene	8.80	0.16	1.41
2,2-Dimethylbutane	0.82	0.76	0.62
4-Methyl-1-pentene	4.42	0.00	0.00
2,3-Dimethylbutane	1.07	0.87	0.93
2-Methylpentane	1.53	2.27	3.47
C6H12 Alkene 2	5.55	0.08	0.44
3-Methylpentane	1.52	1.25	1.90
C6H12 Alkene 3	5.55	0.05	0.28
n-Hexane	0.98	1.23	1.21
c-2-Hexene	6.69	0.00	0.00
Methylcyclopentane	2.82	0.48	1.35
C7H16 Alkane	1.40	0.42	0.59
Benzene	0.42	2.51	1.05
3-Methyl-1-hexene	3.48	0.00	0.00
Cyclohexane	1.28	0.08	0.10
2-Methylhexane + Dimethylpentane	1.40	1.24	1.74
3-Methylhexane	1.40	0.64	0.90
2,2,4-Trimethylpentane + Alkene	2.59	1.59	4.12
n-Heptane	0.81	0.62	0.50
Methylcyclohexane	1.85	0.27	0.50
Dimethylhexane	1.20	0.60	0.72
2,3,4-Trimethylpentane	1.60	0.35	0.56
Toluene + C8H18	2.73	3.21	8.76
2,3-Dimethylhexane	1.32	0.17	0.22
Methylheptane	1.20	0.41	0.49
Dimethylcyclohexane	1.94	0.49	0.95
2,2,5-Trimethylhexane	0.97	0.17	0.16

**Table II-1a
Speciated FTP Results
VW Jetta, RFA**

	mg Ozone/ mg NMOG	Test 24C5, 7/16/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species			
n-Octane	0.61	0.30	0.18
C9H18 Alkene	3.40	0.05	0.17
Ethylbenzene	2.70	1.09	2.94
m & p-Xylenes	7.38	3.47	25.61
C9H20 Alkane	1.14	0.13	0.15
Styrene	2.22	0.30	0.67
o-Xylene	6.46	1.04	6.72
n-Nonane	0.54	0.09	0.05
i-Propylbenzene	2.24	0.04	0.09
n-Propylbenzene	2.12	0.24	0.51
3-Ethyltoluene	7.20	0.61	4.39
4-Ethyltoluene + C10cycloalkane	4.49	0.32	1.44
1,3,5-Trimethylbenzene	10.12	0.44	4.45
2-Ethyltoluene	7.20	0.17	1.22
1,2,4-Trimethylbenzene	8.83	1.26	11.13
n-Decane	0.47	0.00	0.00
n-Undecane	0.42	0.10	0.04
Mid-Range HC Subtotal		29.79	95.14
	mg Ozone/ mg NMOG	Test 24C5, 7/17/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates			
Formaldehyde	7.15	0.45	3.22
Acetaldehyde	5.52	0.15	0.83
Acetone	0.56	0.18	0.10
Oxygenates Subtotal		0.78	4.15
		Test 24C5, 7/17/92	
		NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary			
Light-End Species		18.62	54.34
Mid-Range Species		29.79	95.14
Oxygenates		0.78	4.15
Total		49.19	153.62
Ozone/NMOG		3.12	

Table II-1b
Speciated FTP Results
VW Jetta, RFA

	mg Ozone/ mg NMOG	Test 24C6, 7/17/92		Test 24C7, 7/18/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Light-end Species					
Ethane	0.25	3.04	0.76	3.31	0.83
Ethene	7.29	3.04	22.16	2.71	19.76
Propane	0.48	0.09	0.04	0.25	0.12
Ethyne	0.50	0.73	0.37	0.81	0.41
Methylpropane	1.21	0.08	0.10	0.09	0.11
Butane	1.02	2.70	2.75	3.33	3.40
Propene	9.40	1.16	10.90	1.27	11.94
Methylbutane	1.38	2.68	3.70	2.79	3.85
Pentane	1.04	1.83	1.90	1.64	1.71
1-Butene	8.91	0.17	1.51	0.18	1.60
2-Methylpropene	5.31	1.10	5.84	0.45	2.39
Light-End HC Subtotal		16.62	50.04	16.83	46.10
	mg Ozone/ mg NMOG	Test 24C6, 7/17/92		Test 24C7, 7/18/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
1,3-Butadiene	10.89	0.23	2.50	0.18	1.96
t-2-Pentene	8.80	0.10	0.88	0.00	0.00
C6H12 Alkene	5.55	0.00	0.00	0.04	0.22
2,2-Dimethylbutane	0.82	0.89	0.73	0.00	0.00
4-Methyl-1-pentene	4.42	0.00	0.00	0.11	0.49
2,3-Dimethylbutane	1.07	0.94	1.01	0.86	0.92
2-Methylpentane	1.53	2.65	4.05	2.54	3.89
C6H12 Alkene 2	5.55	0.00	0.00	0.10	0.56
3-Methylpentane	1.52	1.37	2.08	1.18	1.79
C6H12 Alkene 3	5.55	0.07	0.39	0.05	0.28
n-Hexane	0.98	1.44	1.41	1.40	1.37
t-2-Hexene	6.69	0.09	0.60	0.07	0.47
c-2-Hexene	6.69	0.08	0.54	0.08	0.54
Methylcyclopentane	2.82	0.41	1.16	0.49	1.38
C7H16 Alkane	1.40	0.55	0.77	0.37	0.52
Benzene	0.42	3.11	1.31	2.62	1.10
3-Methyl-1-hexene	3.48	0.00	0.00	1.02	3.55
Cyclohexane	1.28	0.07	0.09	0.21	0.27
2-Methylhexane + Dimethylpentane	1.40	1.43	2.00	2.02	2.83
3-Methylhexane	1.40	0.84	1.18	1.06	1.48
2,2,4-Trimethylpentane + Alkene	2.59	2.00	5.18	2.36	6.11
n-Heptane	0.81	0.71	0.58	0.96	0.78
Methylcyclohexane	1.85	0.27	0.50	1.06	1.96
Dimethylhexane	1.20	0.59	0.71	2.69	3.23
2,3,4-Trimethylpentane	1.60	0.41	0.66	0.00	0.00
Toluene + C8H18	2.73	3.88	10.59	3.14	8.57
2,3-Dimethylhexane	1.32	0.14	0.18	0.53	0.70
Methylheptane	1.20	0.49	0.59	1.25	1.50

**Table II-1b
Speciated FTP Results
VW Jetta, RFA**

	mg Ozone/ mg NMOG	Test 24C6, 7/17/92		Test 24C7, 7/18/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
Dimethylcyclohexane	1.94	0.57	1.11	0.54	1.05
2,2,5-Trimethylhexane	0.97	0.18	0.17	0.92	0.89
n-Octane	0.61	0.34	0.21	0.75	0.46
C9H18 Alkene	3.40	0.05	0.17	0.40	1.36
Ethylbenzene	2.70	1.31	3.54	1.64	4.43
m & p-Xylenes	7.38	3.99	29.45	2.94	21.70
C9H20 Alkane	1.14	0.14	0.16	0.54	0.62
Styrene	2.22	0.33	0.73	0.60	1.33
o-Xylene	6.46	1.21	7.82	1.14	7.36
n-Nonane	0.54	0.10	0.05	0.23	0.12
i-Propylbenzene	2.24	0.05	0.11	0.31	0.69
n-Propylbenzene	2.12	0.29	0.61	0.00	0.00
3-Ethyltoluene	7.20	1.20	8.64	3.24	23.33
4-Ethyltoluene + C10cycloalkane	4.49	0.37	1.66	1.62	7.27
1,3,5-Trimethylbenzene	10.12	0.49	4.96	1.25	12.65
2-Ethyltoluene	7.20	0.19	1.37	0.94	6.77
1,2,4-Trimethylbenzene	8.83	1.50	13.25	1.10	9.71
n-Decane	0.47	0.00	0.00	0.11	0.05
n-Undecane	0.42	0.00	0.00	1.26	0.53
Mid-Range HC Subtotal		35.07	113.68	45.92	146.78
	mg Ozone/ mg NMOG	Test 24C6, 7/17/92		Test 24C7, 7/18/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates					
Formaldehyde	7.15	0.29	2.07	0.53	3.79
Acetaldehyde	5.52	0.22	1.21	0.18	0.99
Acetone	0.56	0.09	0.05	0.08	0.04
Oxygenates Subtotal		0.60	3.34	0.79	4.83
		Test 24C6, 7/17/92		Test 24C7, 7/18/92	
NMOG Summary		NMOG	Ozone	NMOG	Ozone
		(mg/mi)	(mg/mi)	(mg/mi)	(mg/mi)
Light-End Species		16.62	50.04	16.83	46.10
Mid-Range Species		35.07	113.68	45.92	146.78
Oxygenates		0.60	3.34	0.79	4.83
Total		52.29	167.06	63.54	197.71
Ozone/NMOG		3.19		3.11	

Table II-2a
Speciated FTP Results
Lexus 400, RFA

	mg Ozone/ mg NMOG	Test 25C8, 7/30/92		Test 25C9, 7/31/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Light-end Species					
Ethane	0.25	3.01	0.75	3.41	0.85
Ethene	7.29	2.10	15.31	2.33	16.99
Propane	0.48	0.59	0.28	0.22	0.11
Ethyne	0.50	0.24	0.12	0.59	0.30
Methylpropane	1.21	0.07	0.08	0.08	0.10
Butane	1.02	2.60	2.65	2.62	2.67
Propene	9.40	1.25	11.75	1.41	13.25
Methylbutane	1.38	2.64	3.64	2.60	3.59
Pentane	1.04	1.69	1.76	1.54	1.60
1-Butene	8.91	0.26	2.32	0.28	2.49
2-Methylpropene	5.31	0.42	2.23	0.47	2.50
Light-End HC Subtotal		14.87	40.90	15.55	44.44
	mg Ozone/ mg NMOG	Test 25C8, 7/30/92		Test 25C9, 7/31/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
1,3-Butadiene	10.89	0.17	1.85	0.19	2.07
C6H12 Alkene	5.55	0.04	0.22		0.00
2,2-Dimethylbutane	0.82		0.00	1.20	0.98
Cyclopentene	7.66	0.19	1.46		0.00
4-Methyl-1-pentene	4.42		0.00	0.11	0.49
2,3-Dimethylbutane	1.07	0.94	1.01	0.86	0.92
2-Methylpentane	1.53	3.06	4.68	2.97	4.54
C6H12 Alkene 2	5.55	0.13	0.72	0.13	0.72
3-Methylpentane	1.52	1.49	2.26	1.50	2.28
C6H12 Alkene 3	5.55	0.11	0.61	0.11	0.61
n-Hexane	0.98	1.39	1.36	1.44	1.41
t-2-Hexene	6.69	0.10	0.67	0.11	0.74
c-2-Hexene	6.69	2.60	17.39	0.10	0.67
Methylcyclopentane	2.82	0.60	1.69	0.56	1.58
C7H16 Alkane	1.40	0.58	0.81	0.57	0.80
Benzene	0.42	1.95	0.82	3.00	1.26
3-Methyl-1-hexene	3.48	0.04	0.14	0.02	0.07
Cyclohexane	1.28	0.14	0.18	0.09	0.12
2-Methylhexane + Dimethylpentane	1.40	1.78	2.49	1.83	2.56
3-Methylhexane	1.40	0.91	1.27	0.93	1.30
2,2,4-Trimethylpentane + Alkene	2.59	2.22	5.75	2.39	6.19
n-Heptane	0.81	0.85	0.69	0.87	0.70
Methylcyclohexane	1.85	0.37	0.68	0.35	0.65
Dimethylhexane	1.20	1.02	1.22	0.90	1.08
Toluene + C8H18	2.73	3.82	10.43	4.75	12.97
2,3-Dimethylhexane	1.32	0.37	0.49	0.34	0.45
Methylheptane	1.20	0.84	1.01	0.90	1.08
Dimethylcyclohexane	1.94	0.13	0.25	0.87	1.69

Table II-2a
Speciated FTP Results
Lexus 400, RFA

	mg Ozone/ mg NMOG	Test 25C8, 7/30/92		Test 25C9, 7/31/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
2,2,5-Trimethylhexane	0.97	0.39	0.38	0.34	0.33
n-Octane	0.61	0.53	0.32	0.51	0.31
C9H18 Alkene	3.40	0.16	0.54	0.11	0.37
Ethylbenzene	2.70	1.97	5.32	2.28	6.16
m & p-Xylenes	7.38	4.82	35.57	5.33	39.34
C9H20 Alkane	1.14	0.64	0.73	0.53	0.60
Styrene	2.22	0.46	1.02	0.41	0.91
o- Xylene	6.46	2.04	13.18	2.38	15.37
n- Nonane	0.54	0.25	0.14	0.23	0.12
i-Propylbenzene	2.24	0.12	0.27	0.09	0.20
n-Propylbenzene	2.12	0.47	1.00	0.45	0.95
3-Ethyltoluene	7.20			2.28	16.42
4-Ethyltoluene + C10cycloalkane	4.49			0.74	3.32
1,3,5-Trimethylbenzene	10.12	0.67	6.78	0.73	7.39
2-Ethyltoluene	7.20	1.05	7.56	0.70	5.04
1,2,4-Trimethylbenzene	8.83	2.70	23.84	3.06	27.02
n-Decane	0.47	0.14	0.07	0.08	0.04
n-Undecane	0.42	0.05	0.02	0.05	0.02
Mid-Range HC Subtotal		42.30	156.90	47.39	171.84
	mg Ozone/ mg NMOG	Test 25C8, 7/30/92		Test 25C9, 7/31/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates					
Formaldehyde	7.15	0.51	3.65	0.74	5.29
Acetaldehyde	5.52	0.21	1.16	0.19	1.05
Acetone	0.56	0.09	0.05	0.22	0.12
Oxygenates Subtotal		0.81	4.86	1.15	6.46
		Test 25C8, 7/30/92		Test 25C9, 7/31/92	
		NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary					
Light-End Species		14.87	40.90	15.55	44.44
Mid-Range Species		42.30	156.90	47.39	171.84
Oxygenates		0.81	4.86	1.15	6.46
Total		57.98	202.66	64.09	222.75
Ozone/NMOG		3.50		3.48	

**Table II-2b
Speciated FTP Results
Lexus 400, RFA**

		mg Ozone/ mg NMOG	Test 25C10, 8/4/92		Test 25C12, 8/06/92	
			NMOG	Ozone	NMOG	Ozone
Light-end Species		MIR	(mg/mi)	(mg/mi)	(mg/mi)	(mg/mi)
Ethane		0.25	3.86	0.97	3.17	0.79
Ethene		7.29	4.09	29.82	3.13	22.82
Propane		0.48	0.24	0.12	0.13	0.06
Ethyne		0.50	0.90	0.45	0.41	0.21
Methylpropane		1.21	0.06	0.07	0.06	0.07
Butane		1.02	2.78	2.84	2.57	2.62
Propene		9.40	2.37	22.28	1.79	16.83
Methylbutane		1.38	2.97	4.10	2.81	3.88
Pentane		1.04	1.73	1.80	1.66	1.73
1-Butene		8.91	0.39	3.47	0.34	3.03
2-Methylpropene		5.31	1.03	5.47	0.54	2.87
Light-End HC Subtotal		36.79	20.42	71.37	16.61	54.90
		mg Ozone/ mg NMOG	Test 25C10, 8/4/92		Test 25C12, 8/06/92	
			NMOG	Ozone	NMOG	Ozone
Mid-Range Species		MIR	(mg/mi)	(mg/mi)	(mg/mi)	(mg/mi)
1,3-Butadiene		10.89	0.25	2.72	0.20	2.18
C6H12 Alkene		5.55		0.00		0.00
2,2-Dimethylbutane		0.82		0.00		0.00
Cyclopentene		7.66		0.00	0.05	0.38
4-Methyl-1-pentene		4.42	0.15	0.66	0.13	0.57
2,3-Dimethylbutane		1.07	0.88	0.94	0.89	0.95
2-Methylpentane		1.53	2.99	4.57	2.79	4.27
C6H12 Alkene 2		5.55	0.12	0.67	0.13	0.72
3-Methylpentane		1.52	1.30	1.98	1.42	2.16
C6H12 Alkene 3		5.55	0.09	0.50	0.11	0.61
n-Hexane		0.98	1.41	1.38	1.48	1.45
t-2-Hexene		6.69	0.09	0.60	0.10	0.67
c-2-Hexene		6.69	0.10	0.67	0.12	0.80
Methylcyclopentane		2.82	0.54	1.52	0.59	1.66
C7H16 Alkane		1.40	0.69	0.97	0.61	0.85
Benzene		0.42	3.66	1.54	2.64	1.11
3-Methyl-1-hexene		3.48	0.11	0.38	0.01	0.03
Cyclohexane		1.28	0.13	0.17	0.17	0.22
2-Methylhexane + Dimethylpentane		1.40	1.98	2.77	2.01	2.81
3-Methylhexane		1.40	1.00	1.40	1.01	1.41
2,2,4-Trimethylpentane + Alkene		2.59	2.53	6.55	2.45	6.35
n-Heptane		0.81	0.97	0.79	0.95	0.77
Methylcyclohexane		1.85	0.45	0.83	0.43	0.80
Dimethylhexane		1.20	1.12	1.34	1.04	1.25
Toluene + C8H18		2.73	6.39	17.44	4.66	12.72
2,3-Dimethylhexane		1.32	0.31	0.41	0.45	0.59
Methylheptane		1.20	0.96	1.15	1.10	1.32
Dimethylcyclohexane		1.94	0.12	0.23	0.20	0.39

Table II-2b
Speciated FTP Results
Lexus 400, RFA

			mg Ozone/ mg NMOG	Test 25C10, 8/4/92		Test 25C12, 8/06/92	
			MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species							
2,2,5-Trimethylhexane			0.97	0.40	0.39	0.45	0.44
n-Octane			0.61	0.62	0.38	0.65	0.40
C9H18 Alkene			3.40	0.13	0.44	0.18	0.61
Ethylbenzene			2.70	2.88	7.78	2.68	7.24
m & p-Xylenes			7.38	7.19	53.06	6.13	45.24
C9H20 Alkane			1.14	0.62	0.71	0.68	0.78
Styrene			2.22	0.54	1.20	0.54	1.20
o- Xylene			6.46	3.21	20.74	2.55	16.47
n- Nonane			0.54	0.22	0.12	0.24	0.13
i-Propylbenzene			2.24	0.17	0.38	0.12	0.27
n-Propylbenzene			2.12		0.00	1.21	2.57
3-Ethyltoluene			7.20	3.10	22.32	3.08	22.18
4-Ethyltoluene + C10cycloalkane			4.49	1.19	5.34	1.55	6.96
1,3,5-Trimethylbenzene			10.12	1.67	16.90	1.73	17.51
2-Ethyltoluene			7.20	1.03	7.42	1.06	7.63
1,2,4-Trimethylbenzene			8.83	3.49	30.82	3.57	31.52
n-Decane			0.47	0.09	0.04	0.06	0.03
n-Undecane			0.42	0.08	0.03	0.06	0.03
Mid-Range HC Subtotal				54.97	220.26	52.28	208.24
			mg Ozone/ mg NMOG	Test 25C10, 8/4/92		Test 25C12, 8/06/92	
			MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates							
Formaldehyde			7.15	0.83	5.93	1.31	9.37
Acetaldehyde			5.52	0.30	1.66	0.26	1.44
Acrolein			6.76	0.06	0.41		0.00
Acetone			0.56	0.22	0.12	0.08	0.04
Oxygenates Subtotal				1.41	8.12	1.65	10.85
				Test 25C10, 8/4/92		Test 25C12, 8/06/92	
				NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary							
Light-End Species				20.42	71.37	16.61	54.90
Mid-Range Species				54.97	220.26	52.28	208.24
Oxygenates				1.41	8.12	1.65	10.85
Total				76.80	299.75	70.54	273.99
Ozone/NMOG				3.90		3.88	

**Table II-3a
Speciated FTP Results
Toyota Celica, RF-A**

	mg Ozone/ mg NMOG	Test 27C12, 7/17/92		Test 27C14, 7/22/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Light-end Species					
Ethane	0.25	2.24	0.56	2.13	0.53
Ethene	7.29	3.56	25.95	3.40	24.79
Propane	0.48	0.10	0.05	0.09	0.04
Ethyne	0.50	3.67	1.84	3.62	1.81
Methylpropane	1.21	0.07	0.08	0.09	0.11
Butane	1.02	3.92	4.00	4.08	4.16
Propene	9.40	1.72	16.17	1.42	13.35
Methylbutane	1.38	3.86	5.33	3.89	5.37
Pentane	1.04	2.35	2.44	2.39	2.49
1-Butene	8.91	0.23	2.05	0.20	1.78
2-Methylpropene	5.31	0.53	2.81	0.45	2.39
Light-End HC Subtotal		22.25	61.28	21.76	56.82
	mg Ozone/ mg NMOG	Test 27C12, 7/17/92		Test 27C14, 7/22/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
2-Methyl-1-butene	4.90	0.00	0.00	0.09	0.44
1,3-Butadiene	10.89	0.16	1.74	0.11	1.20
t-2-Pentene	8.80	0.00	0.00	0.40	3.52
C6H12 Alkene	5.55	0.26	1.44	0.00	0.00
2,2-Dimethylbutane	0.82	0.00	0.00	0.82	0.67
2,3-Dimethylbutane	1.07	1.49	1.59	1.38	1.48
C6H12 Alkene 1	5.55	0.04	0.22	0.00	0.00
2-Methylpentane	1.53	4.56	6.98	3.77	5.77
3-Methylpentane	1.52	2.11	3.21	1.96	2.98
n-Hexane	0.98	2.19	2.15	1.96	1.92
t-2-Hexene	6.69	0.03	0.20	0.21	1.40
C6H12 Alkene 4	5.55	0.00	0.00	0.14	0.78
c-2-Hexene	6.69	0.19	1.27	0.16	1.07
C6H12 Alkene 5	5.55	0.00	0.00	0.11	0.61
Methylcyclopentane	2.82	0.86	2.43	0.78	2.20
2,4-Dimethylpentane	1.78	0.00	0.00	0.12	0.21
C7H16 Alkane	1.40	0.08	0.11	0.67	0.94
Benzene	0.42	4.34	1.82	3.49	1.47
3-Methyl-1-hexene	3.48	0.01	0.03	0.04	0.14
Cyclohexane	1.28	0.15	0.19	0.13	0.17
2-Methylhexane + Dimethylpentane	1.40	1.29	1.81	2.06	2.88
3-Methylhexane	1.40	0.13	0.18	1.09	1.53
2,2,4-Trimethylpentane + Alkene	2.59	3.16	8.18	2.72	7.04
n-Heptane	0.81	1.39	1.13	0.87	0.70
Methylcyclohexane	1.85	0.53	0.98	0.39	0.72
Dimethylhexane	1.20	1.34	1.61	0.76	0.91
2,3,4-Trimethylpentane	1.60	0.00	0.00	0.45	0.72
Toluene + C8H18	2.73	5.61	15.32	4.24	11.58
2,3-Dimethylhexane	1.32	0.48	0.63	0.27	0.36

Table II-3a
Speciated FTP Results
Toyota Celica, RF-A

	mg Ozone/ mg NMOG	Test 27C12, 7/17/92		Test 27C14, 7/22/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
2,3-Dimethylhexane	1.32	0.48	0.63	0.27	0.36
Methylheptane	1.20	1.06	1.27	0.48	0.58
Dimethylcyclohexane	1.94	0.24	0.47	0.61	1.18
2,2,5-Trimethylhexane	0.97	0.45	0.44	0.25	0.24
n-Octane	0.61	0.63	0.38	0.36	0.22
C9H18 Alkene	3.40	0.03	0.10	0.05	0.17
Ethylbenzene	2.70	2.32	6.26	1.34	3.62
m & p-Xylenes	7.38	4.44	32.77	3.69	27.23
C9H20 Alkane	1.14	0.51	0.58	0.18	0.21
Styrene	2.22	0.00	0.00	0.17	0.38
o-Xylene	6.46	2.36	15.25	1.02	6.59
n-Nonane	0.54	0.18	0.10	0.12	0.06
i-Propylbenzene	2.24	0.00	0.00	0.06	0.13
n-Propylbenzene	2.12	0.00	0.00	0.16	0.34
3-Ethyltoluene	7.20	1.13	8.14	0.63	4.54
4-Ethyltoluene + C10cycloalkane	4.49	0.37	1.66	0.26	1.17
1,3,5-Trimethylbenzene	10.12	0.87	8.80	0.37	3.74
2-Ethyltoluene	7.20	0.07	0.50	0.19	1.37
1,2,4-Trimethylbenzene	8.83	1.38	12.19	1.00	8.83
n-Decane	0.47	0.04	0.02	0.00	0.00
n-Undecane	0.42	0.09	0.04	0.09	0.04
Mid-Range HC Subtotal		47.05	142.82	40.49	114.40
	mg Ozone/ mg NMOG	Test 27C12, 7/17/92		Test 27C14, 7/22/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates					
Formaldehyde	7.15	0.39	2.79	0.14	1.00
Acetaldehyde	5.52	0.09	0.50	0.19	1.05
Acetone	0.56	0.05	0.03	0.13	0.07
Oxygenates Subtotal		0.53	3.31	0.46	2.12
		Test 27C12, 7/17/92		Test 27C14, 7/22/92	
		NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary					
Light-End Species		22.25	61.28	21.76	56.82
Mid-Range Species		47.05	142.82	40.49	114.40
Oxygenates		0.53	3.31	0.46	2.12
Total		69.83	207.42	62.71	173.34
Ozone/NMOG		2.97		2.76	

**Table III-1a
Speciated FTP Results
VW Jetta, Phase 2**

	mg Ozone/ mg NMOG	Test 24C10, 8/27/92	
		NMOG	Ozone
Light-end Species	MIR	(mg/mi)	(mg/mi)
Ethane	0.25	2.25	0.56
Ethene	7.29	1.44	10.50
Propane	0.48	4.18	2.01
Ethyne	0.50	0.92	0.46
Methylpropane	1.21	0.05	0.06
Butane	1.02	0.44	0.45
Propene	9.40	1.03	9.68
Methylbutane	1.38	2.66	3.67
Pentane	1.04	0.34	0.35
1-Butene	8.91	0.07	0.62
2-Methylpropene	5.31	1.19	6.32
Light-End HC Subtotal		14.57	34.68
	mg Ozone/ mg NMOG	Test 24C10, 8/27/92	
		NMOG	Ozone
Mid-Range Species	MIR	(mg/mi)	(mg/mi)
1,3-Butadiene	10.89	0.14	1.52
t-2-Pentene	8.80	0.00	0.00
2,2-Dimethylbutane	0.82	0.00	0.00
4-Methyl-1-pentene	4.42	0.04	0.18
2,3-Dimethylbutane	1.07	0.90	0.96
2-Methylpentane	1.53	1.20	1.84
C6H12 Alkene 2	5.55	0.03	0.17
3-Methylpentane	1.52	0.53	0.81
C6H12 Alkene 3	5.55	0.03	0.17
n-Hexane	0.98	0.31	0.30
c-2-Hexene	6.69	0.03	0.20
Methylcyclopentane	2.82	0.13	0.37
C7H16 Alkane	1.40	0.92	1.29
Benzene	0.42	0.94	0.39
3-Methyl-1-hexene	3.48	0.01	0.03
Cyclohexane	1.28	0.04	0.05
2-Methylhexane + Dimethylpentane	1.40	1.81	2.53
3-Methylhexane	1.40	0.60	0.84
2,2,4-Trimethylpentane + Alkene	2.59	3.59	9.30
n-Heptane	0.81	0.46	0.37
Methylcyclohexane	1.85	0.15	0.28
Dimethylhexane	1.20	0.80	0.96
2,3,4-Trimethylpentane	1.60	0.00	0.00
Toluene + C8H18	2.73	2.26	6.17
2,3-Dimethylhexane	1.32	0.32	0.42
Methylheptane	1.20	0.35	0.42
Dimethylcyclohexane	1.94	0.13	0.25
2,2,5-Trimethylhexane	0.97	0.37	0.36

Table III-1a
Speciated FTP Results
VW Jetta, Phase 2

	mg Ozone/	Test 24C10, 8/27/92	
	mg NMOG	NMOG	Ozone
Mid-Range Species	MIR	(mg/mi)	(mg/mi)
2,2,5-Trimethylhexane	0.97	0.37	0.36
n-Octane	0.61	0.20	0.12
C9H18 Alkene	3.40	0.03	0.10
Ethylbenzene	2.70	0.69	1.86
m & p-Xylenes	7.38	1.43	10.55
C9H20 Alkane	1.14	0.12	0.14
Styrene	2.22	0.18	0.40
o-Xylene	6.46	0.50	3.23
n-Nonane	0.54	0.00	0.00
i-Propylbenzene	2.24	0.04	0.09
n-Propylbenzene	2.12	0.10	0.21
3-Ethyltoluene	7.20	0.23	1.66
4-Ethyltoluene + C10cycloalkane	4.49	0.00	0.00
1,3,5-Trimethylbenzene	10.12	0.16	1.62
2-Ethyltoluene	7.20	0.12	0.86
1,2,4-Trimethylbenzene	8.83	0.34	3.00
n-Decane	0.47	0.04	0.02
n-Undecane	0.42	0.00	0.00
Mid-Range HC Subtotal		20.64	54.41
	mg Ozone/	Test 24C10, 8/27/92	
	mg NMOG	NMOG	Ozone
Oxygenates	MIR	(mg/mi)	(mg/mi)
Formaldehyde	7.15	0.23	1.64
Acetaldehyde	5.52	0.12	0.66
Acetone	0.56	0.14	0.08
Oxygenates Subtotal		0.49	2.39
		Test 24C10, 8/27/92	
		NMOG	Ozone
NMOG Summary		(mg/mi)	(mg/mi)
Light-End Species		14.57	34.68
Mid-Range Species		20.64	54.41
Oxygenates		0.49	2.39
Total		35.70	91.48
Ozone/NMOG		2.56	

Table III-2a
Speciated FTP Results
Lexus 400, Phase 2

	mg Ozone/ mg NMOG	Test 25C13, 8/11/92		Test 25C14, 8/12/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Light-end Species					
Ethane	0.25	2.19	0.55	2.16	0.54
Ethene	7.29	1.38	10.06	1.30	9.48
Propane	0.48	0.36	0.17	0.18	0.09
Ethyne	0.50	0.82	0.41	1.04	0.52
Methylpropane	1.21	0.31	0.38	0.10	0.12
Butane	1.02	0.93	0.95	0.76	0.78
Propene	9.40	1.07	10.06	1.03	9.68
Methylbutane	1.38	4.28	5.91	2.95	4.07
Pentane	1.04	0.57	0.59	0.31	0.32
1-Butene	8.91	0.16	1.43	0.12	1.07
2-Methylpropene	5.31	1.09	5.79	0.97	5.15
Light-End HC Subtotal		13.16	36.28	10.92	31.81
	mg Ozone/ mg NMOG	Test 25C13, 8/11/92		Test 25C14, 8/12/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
1,3-Butadiene	10.89	0.10	1.09	0.11	1.20
4-Methyl-1-pentene	4.42	0.08	0.35	0.06	0.27
2,3-Dimethylbutane	1.07	1.93	2.07	1.40	1.50
2-Methylpentane	1.53	1.61	2.46	1.06	1.62
C6H12 Alkene 2	5.55	0.09	0.50	0.05	0.28
3-Methylpentane	1.52	0.77	1.17	0.46	0.70
C6H12 Alkene 3	5.55	0.07	0.39	0.05	0.28
n-Hexane	0.98	0.49	0.48	0.26	0.25
t-2-Hexene	6.69	0.06	0.40	0.05	0.33
c-2-Hexene	6.69	0.07	0.47	0.05	0.33
Methylcyclopentane	2.82	0.31	0.87	0.16	0.45
C7H16 Alkane	1.40	1.11	1.55	0.84	1.18
Benzene	0.42	0.86	0.36	0.68	0.29
3-Methyl-1-hexene	3.48	0.03	0.10	0.02	0.07
Cyclohexane	1.28	0.05	0.06	0.02	0.03
2-Methylhexane + Dimethylpentane	1.40	1.79	2.51	1.33	1.86
3-Methylhexane	1.40	0.73	1.02	0.52	0.73
2,2,4-Trimethylpentane + Alkene	2.59	4.37	11.32	3.51	9.09
n-Heptane	0.81	0.57	0.46	0.44	0.36
Methylcyclohexane	1.85	0.14	0.26	0.09	0.17
Dimethylhexane	1.20	0.98	1.18	0.74	0.89
Toluene + C8H18	2.73	2.94	8.03	2.60	7.10
2,3-Dimethylhexane	1.32	0.39	0.51	0.31	0.41
Methylheptane	1.20	0.45	0.54	0.30	0.36
Dimethylcyclohexane	1.94	0.10	0.19	0.07	0.14
2,2,5-Trimethylhexane	0.97	0.45	0.44	0.37	0.36
n-Octane	0.61	0.26	0.16	0.20	0.12
C9H18 Alkene	3.40	0.08	0.27	0.01	0.03
Ethylbenzene	2.70	1.03	2.78	1.29	3.48

Table III-2a
Speciated FTP Results
Lexus 400, Phase 2

	mg Ozone/ mg NMOG	Test 25C13, 8/11/92		Test 25C14, 8/12/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
m & p-Xylenes	7.38	2.29	16.90	1.79	13.21
C9H20 Alkane	1.14	0.25	0.29	0.16	0.18
Styrene	2.22	0.21	0.47	0.14	0.31
o-Xylene	6.46	0.96	6.20	0.68	4.39
n-Nonane	0.54	0.05	0.03	0.00	0.00
i-Propylbenzene	2.24	0.08	0.18	0.05	0.11
n-Propylbenzene	2.12	0.20	0.42	0.13	0.28
3-Ethyltoluene	7.20	0.16	1.15	0.78	5.62
4-Ethyltoluene + C10cycloalkane	4.49	0.00	0.00	0.24	1.08
1,3,5-Trimethylbenzene	10.12	0.39	3.95	0.38	3.85
2-Ethyltoluene	7.20	0.26	1.87	0.35	2.52
1,2,4-Trimethylbenzene	8.83	0.01	0.09	0.57	5.03
n-Decane	0.47	0.06	0.03	0.00	0.00
n-Undecane	0.42	0.04	0.02	0.05	0.02
Mid-Range HC Subtotal		26.87	73.59	22.37	70.46
	mg Ozone/ mg NMOG	Test 25C13, 8/11/92		Test 25C14, 8/12/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates					
Formaldehyde	7.15	0.89	6.36	1.55	11.08
Acetaldehyde	5.52	0.11	0.61	0.10	0.55
Acetone	0.56	0.03	0.02	0.05	0.03
Oxygenates Subtotal		1.03	6.99	1.70	11.66
		Test 25C13, 8/11/92		Test 25C14, 8/12/92	
		NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary					
Light-End Species		13.16	36.28	10.92	31.81
Mid-Range Species		26.87	73.59	22.37	70.46
Oxygenates		1.03	6.99	1.70	11.66
Total		41.06	116.86	34.99	113.94
Ozone/NMOG		2.85		3.26	

Table III-2b
Speciated FTP Results
Lexus 400, Phase 2

	mg Ozone/ mg NMOG	Test 25C15, 8/13/92		Test 25C16, 8/14/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Light-end Species					
Ethane	0.25	2.19	0.55	2.26	0.57
Ethene	7.29	1.57	11.45	1.53	11.15
Propane	0.48	0.10	0.05	1.48	0.71
Ethyne	0.50	1.03	0.52	1.15	0.58
Methylpropane	1.21	0.06	0.07	0.07	0.08
Butane	1.02	0.28	0.29	0.61	0.62
Propene	9.40	1.27	11.94	1.17	11.00
Methylbutane	1.38	3.30	4.55	4.02	5.55
Pentane	1.04	0.35	0.36	0.46	0.48
1-Butene	8.91	0.15	1.34	0.15	1.34
2-Methylpropene	5.31	1.16	6.16	1.23	6.53
Light-End HC Subtotal		11.46	37.27	14.13	38.60
	mg Ozone/ mg NMOG	Test 25C15, 8/13/92		Test 25C16, 8/14/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
1,3-Butadiene	10.89	0.11	1.20	0.11	1.20
4-Methyl-1-pentene	4.42	0.06	0.27	0.08	0.35
2,3-Dimethylbutane	1.07	1.42	1.52	2.86	3.06
2-Methylpentane	1.53	0.97	1.48	1.55	2.37
C6H12 Alkene 2	5.55	0.06	0.33	0.09	0.50
3-Methylpentane	1.52	0.38	0.58	0.74	1.12
C6H12 Alkene 3	5.55	0.05	0.28	0.08	0.44
n-Hexane	0.98	0.21	0.21	0.45	0.44
t-2-Hexene	6.69	0.05	0.33	0.07	0.47
c-2-Hexene	6.69	0.05	0.33	0.08	0.54
Methylcyclopentane	2.82	0.10	0.28	0.34	0.96
C7H16 Alkane	1.40	0.76	1.06	1.33	1.86
Benzene	0.42	0.65	0.27	1.14	0.48
3-Methyl-1-hexene	3.48	0.00	0.00	0.11	0.38
Cyclohexane	1.28	0.01	0.01	0.06	0.08
2-Methylhexane + Dimethylpentane	1.40	1.63	2.28	2.27	3.18
3-Methylhexane	1.40	0.45	0.63	0.88	1.23
2,2,4-Trimethylpentane + Alkene	2.59	3.17	8.21	5.57	14.43
n-Heptane	0.81	0.45	0.36	0.78	0.63
Methylcyclohexane	1.85	0.10	0.19	0.25	0.46
Dimethylhexane	1.20	0.77	0.92	1.41	1.69
Toluene + C8H18	2.73	2.38	6.50	4.05	11.06
2,3-Dimethylhexane	1.32	0.28	0.37	0.54	0.71
Methylheptane	1.20	0.44	0.53	0.73	0.88
Dimethylcyclohexane	1.94	0.08	0.16	0.29	0.56
2,2,5-Trimethylhexane	0.97	0.34	0.33	0.62	0.60
n-Octane	0.61	0.15	0.09	0.37	0.23
C9H18 Alkene	3.40	0.06	0.20	0.10	0.34
Ethylbenzene	2.70	1.15	3.11	1.65	4.46

Table III-2b
Speciated FTP Results
Lexus 400, Phase 2

	mg Ozone/ mg NMOG	25C15, 8/13/92		25C16, 8/14/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Mid-Range Species					
Ethylbenzene	2.70	1.15	3.11	1.65	4.46
m & p-Xylenes	7.38	1.85	13.65	3.30	24.35
C9H20 Alkane	1.14	0.17	0.19	0.37	0.42
Styrene	2.22	0.17	0.38	0.34	0.75
o-Xylene	6.46	0.75	4.85	1.45	9.37
n-Nonane	0.54	0.02	0.01	0.12	0.06
i-Propylbenzene	2.24	0.04	0.09	0.12	0.27
n-Propylbenzene	2.12	0.00	0.00	0.26	0.55
3-Ethyltoluene	7.20	1.09	7.85	1.07	7.70
4-Ethyltoluene + C10cycloalkane	4.49	0.37	1.66	0.40	1.80
1,3,5-Trimethylbenzene	10.12	0.32	3.24	0.42	4.25
2-Ethyltoluene	7.20	0.24	1.73	0.34	2.45
1,2,4-Trimethylbenzene	8.83	0.86	7.59	0.02	0.18
n-Decane	0.47	0.00	0.00	0.06	0.03
n-Undecane	0.42	0.12	0.05	0.04	0.02
Mid-Range HC Subtotal		23.48	76.43	38.56	111.37
	mg Ozone/ mg NMOG	Test 25C15, 8/13/92		Test 25C16, 8/14/92	
	MIR	NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
Oxygenates					
Formaldehyde	7.15	1.55	11.08	0.59	4.22
Acetaldehyde	5.52	0.12	0.66	0.16	0.88
Acetone	0.56	0.08	0.04	0.13	0.07
Oxygenates Subtotal		1.75	11.79	0.88	5.17
		Test 25C15, 8/13/92		Test 25C16, 8/14/92	
		NMOG (mg/mi)	Ozone (mg/mi)	NMOG (mg/mi)	Ozone (mg/mi)
NMOG Summary					
Light-End Species		11.46	37.27	14.13	38.60
Mid-Range Species		23.48	76.43	38.56	111.37
Oxygenates		1.75	11.79	0.88	5.17
Total		36.69	125.49	53.57	155.14
Ozone/NMOG		3.42		2.90	

AIR RESOURCES BOARD

HAAGEN-SMIT LABORATORY
9528 TELSTAR AVENUE
EL MONTE, CA 91731-2990
PHONE: (818) 575-6800



MAIL-OUT #92-59

DATE: November 13, 1992

TO: Light-Duty Vehicle Manufacturers
Fuel Suppliers
Other Interested Parties

RE: Availability of Supplement to the Staff Report for the Low-Emission Vehicle Regulatory Review Hearing

By notice issued on November 4, 1992, the Air Resources Board (ARB or Board) announced that it will postpone the public hearing to consider the adoption of amendments to California regulations for certifying low-emission vehicles. The hearing, which was originally scheduled for November 12-13, 1992, is now scheduled to take place on December 10, 1992 at the following location:

Air Resources Board
Board Hearing Room, Lower Level
2020 "L" Street
Sacramento, CA 95814

This item will be considered at a two-day meeting of the Board, which will commence at 9:30 a.m. on December 10, 1992, and will continue at 8:30 a.m. on December 11, 1992. Although the item is currently scheduled for December 10th, interested parties are advised to consult the agenda for the meeting, which will be available at least ten days before December 10, 1992, to determine if a change has been made to the day on which this item will be considered.

Among the issues to be considered at the hearing is the establishment of reactivity adjustment factors (RAFTs) for Phase 2 gasoline transitional low-emission vehicles (TLEVs) and low-emission vehicles (LEVs). In the original staff report for the item, which was released to the public on September 25, 1992, only preliminary RAFTs were proposed. Since that time, the ARB staff has finished collecting the data needed to establish the factors and is now able to determine the final values based on the emission data. These values are described in the enclosed supplemental report. Pending the results of the airshed modeling now being conducted to confirm the representativeness of the RAFTs, the factors described in the report may be adjusted prior to the December hearing. Information about the modeling adjustment factors may

be requested by completing the form attached as the last page of the supplemental report and returning it to the ARB.

If you have any questions concerning this matter, please contact Steve Albu, Chief of the Engineering Studies Branch, at (818) 575-7010.

Sincerely,



K.D. Drachand, Chief
Mobile Source Division

Supplement to
Initial Statement of Proposed Rulemaking (Staff Report)
Amendments to the Low-Emission Vehicle Program

Establishment of Reactivity Adjustment Factors

Mobile Source Division
Monitoring and Laboratory Division
Research Division

Date of Release of Staff Report: September 25, 1992
Date of Release of Supplement: November 13, 1992
Board Hearing Date: December 10-11, 1992

I. INTRODUCTION

This report is a supplement to the initial statement of proposed rulemaking (staff report) for amendments to certification requirements and test procedures for low-emission passenger cars, light-duty trucks and medium-duty vehicles. The hearing in this rulemaking was originally scheduled for November 12, 1992, and has now been postponed to December 10, 1992. The rulemaking covers a wide variety of topics, including certification requirements for hybrid electric vehicles, penalty provisions for failing to comply with the low-emission vehicle requirements, and adjustments to 50 degree Fahrenheit test results. The original staff report released on September 25, 1992 contained an extensive discussion of the proposed amendments. This supplement provides additional data and analysis, in large part developed since release of the original rulemaking materials, pertaining to the proposed reactivity adjustment factors (RAFTs) for transitional low-emission vehicles (TLEVs) and low-emission vehicles (LEVs).

The September 25 staff report identified interim proposed RAFTs for TLEVs and LEVs operating on Phase 2 reformulated gasoline (Phase 2 gasoline). The staff report also included an interim proposed ozone per gram, or "specific reactivity," value for base gasoline-fueled LEVs. Only interim values were proposed because the ARB's testing of Phase 2 gasoline TLEVs and LEVs had not been completed when the staff report was released. The final data are now available, and the staff is proposing the following modified reactivity values for approval at the December, 1992 hearing:

RAFT for Phase 2 gasoline TLEVs:	1.00
RAFT for Phase 2 gasoline LEVs:	0.98
Specific Reactivity of Base Gasoline LEVs:	3.16
Specific Reactivity of Base Gasoline ULEVs:	3.16

The proposed RAFTs identified above do not include adjustment by a modeling correction factor. The airshed modeling to verify that these RAFTs do not exacerbate ozone levels even under worst case ozone scenarios has not yet been completed. Therefore, if warranted by the results of the airshed modeling, prior to the December hearing the staff may propose additional adjustments to the RAFT values. The modeling results, which will be available after November 20th, and a complete set of the speciated data, will be available to any party requesting these data. Such requests may be made by completing the form attached as the last page of this document and returning it to Donna Barragan of the ARB (telephone: 818-575-7010).

II. PROCEDURE FOR ESTABLISHING REACTIVITY ADJUSTMENT FACTORS

A. Calculating RAFTs

Under the low-emission vehicle regulations, a reactivity adjustment factor or RAFT is to be established for TLEVs, LEVs, and

ultra-low-emission vehicles (ULEVs) operating on each type of fuel other than conventional gasoline. The RAF for a given fuel is the ratio of the ozone formed by one gram of exhaust emissions from a vehicle operated on that fuel to the ozone formed by one gram of exhaust emissions from a vehicle operated on conventional (base) gasoline. The amount of ozone formed per gram of emissions is also called the specific reactivity. The calculation of a RAF may be expressed as follows:

$$\text{RAF} = \frac{\text{specific reactivity of emissions with fuel being evaluated}}{\text{baseline specific reactivity}}$$

In order to determine the specific reactivity, the NMOG exhaust emissions of a vehicle is speciated into roughly 50 component compounds. The mass emission per mile of each compound is multiplied by its maximum incremental reactivity (MIR) value to determine the amount of ozone formed by that compound. These ozone values are then added together and divided by the total mass of exhaust to determine the specific reactivity of the NMOG emissions from that vehicle.

The ARB intends to establish the baseline specific reactivity (the denominator of the RAF ratio) for each low-emission vehicle category, as well as generic RAFs for Phase 2 gasoline and alternative fuels. Pursuant to existing regulations, manufacturers will have the option of using the generic RAFs or calculating a specific reactivity for a certain engine family (the numerator of the RAF ratio). In the latter case, the engine family's specific reactivity is then divided by the baseline specific reactivity in order to determine the RAF applicable to the engine family.

B. Vehicle Selection Criteria

In order to establish the specific reactivities for the base gasoline and the fuel being evaluated, it is important to obtain speciated emission data that are representative of the vehicles that manufacturers will actually produce. Accordingly, the ARB selects for testing only those vehicles that are able to meet all of the emission standards for the category and that are equipped with the technologies that could be used in that category. For example, all gasoline TLEVs must have NMOG emissions between 0.075 and 0.125 g/mi and NOx emissions below 0.4 g/mi.

While these criteria must be followed in order to develop representative specific reactivities, it is very difficult to find very many of today's vehicles that meet future emission standards. Thus the number of vehicles that the ARB has been able to procure for testing is fairly limited. To illustrate this point, of the 68 vehicles tested by the ARB to develop the specific reactivities in this rulemaking, only 17 qualifying vehicles were found. Because it is important that the RAFs reflect the in-use emission characteristics of production low-emission vehicles, the staff has considered only TLEV test vehicles that had NMOG emissions between 0.075

and 0.125 g/mi and LEV test vehicles that had NMOG emissions below 0.075 g/mi.

III. BASELINE SPECIFIC REACTIVITY FOR LEVS AND ULEVS

Following the November 14, 1991 hearing, the ARB adopted a baseline specific reactivity (the denominator of the RAF ratio) of 3.42 for TLEVs. The amendments adopted after the November 1991 hearing have now been approved by the Office of Administrative Law. At the December 10, 1992 hearing, the Board will consider baseline specific reactivities for LEVs and ULEVs. Based on the data now available, the staff is proposing a baseline specific reactivity of 3.16 for both LEVs and ULEVs. In all cases, the fuel used to develop the baseline specific reactivity was industry average gasoline, also known as "RF-A."

A. Baseline Specific Reactivity for LEVs

In order to establish the baseline specific reactivity for LEVs, the ARB staff equipped and tested six late-model passenger cars with electrically-heated catalysts (EHCs). When the low-emission vehicle regulations were approved in September, 1990, the ARB staff identified EHCs as the primary technology needed by base gasoline vehicles to meet the LEV and ULEV mass emission standards, and used EHC-derived data to support these standards. A side-by-side comparison of four vehicles equipped with and without EHCs clearly shows that the use of an EHC is effective in reducing specific reactivity (see Table I).

Table I - Effect of EHC on Exhaust Emissions

		FTP Results				
Vehicle		NMOG (g/mi)	CO (g/mi)	NOx (g/mi)	Ozone/ mile	Ozone/ gram
Phase 2						
1991 Jetta	w/o ehc	0.111	1.89	0.089	0.406	3.681
	w/ehc	0.037	1.20	0.114	0.109	2.946
	% diff.	67%	36%	-28%	73%	20%
1990 Celica	w/o ehc	0.096	1.06	0.111	0.308	3.222
	w/ ehc	0.071	0.74	0.151	0.212	2.978
	% diff	26%	30%	-36%	31%	8%
RF-A						
1990 Buick	w/o ehc	0.127	1.56	0.423	0.477	3.760
	w/ ehc	0.062	0.48	0.168	0.198	3.234
	% diff.	51%	69%	60%	58%	14%
1990 Celica	w/o ehc	0.094	0.84	0.154	0.297	3.160
	w/ ehc	0.062	0.51	0.241	0.172	2.787
	% diff.	34%	39%	-56%	42%	12%

Although manufacturers are allowed to utilize any technology to meet the LEV emission standards, use of a technology less effective than EHCs at reducing specific reactivity to establish the baseline would have the effect of relaxing the stringency of the adopted LEV NMOG standard. A less effective technology would yield a higher baseline specific reactivity, thus resulting in lower RAFs for all fuels other than conventional gasoline, and thus allowing higher mass emissions when these fuels are used.

Based on the test results of the six EHC-equipped vehicles, the ARB staff is proposing that a baseline specific reactivity of 3.16 be adopted for LEVs, as shown in Table II. Although some may argue that the six vehicles do not represent a statistically valid data set, the staff believes that a value of 3.16 makes sense from an engineering standpoint because of the effectiveness of EHCs in reducing specific reactivity. Thus the specific reactivity of EHC-equipped LEVs should be numerically lower than the specific reactivity of TLEVs which do not utilize EHCs. Accordingly, the proposed LEV specific reactivity of 3.16 is lower than the corresponding 3.42 baseline value for TLEVs previously adopted by the Board. It is also important to recognize that all fuels other than conventional gasoline will be compared to the same baseline specific reactivity.

Table II - RF-A LEV Specific Reactivity

Vehicle	NMOG (g/mi)	CO (g/mi)	NOx (g/mi)	Ozone/ mile	Ozone/ gram
Jetta	0.056	1.42	0.146	0.175	3.122
Lexus 400	0.067	0.43	0.201	0.246	3.654
Celica	0.062	0.51	0.241	0.172	2.787
LeSabre '90	0.062	0.48	0.168	0.198	3.234
T-bird	0.050	1.17	0.180	0.150	3.021
Tempo	0.065	1.02	0.151	0.203	3.137
Cum. Avg.	0.060	0.84	0.181	0.191	3.159

B. Baseline Specific Reactivity for ULEVs

Since EHCs were also identified as the primary technology needed to enable gasoline vehicles to meet the ULEV standards, it is appropriate to utilize the data generated for LEVs (see Table II above) to establish the baseline specific reactivity for ULEVs. In spite of the difference in the NMOG mass standards, the baseline specific reactivities of LEVs and ULEVs are not expected to be significantly different because base gasoline vehicles in both categories will use the same basic emission control technologies. We also note that early establishment of the baseline ULEV specific reactivity would give manufacturers more leadtime to begin optimization of the emission strategies needed to meet ULEV standards.

IV. PHASE 2 GASOLINE SPECIFIC REACTIVITY FOR TLEVs AND LEVs

To develop the specific reactivity for TLEVs and LEVs on Phase 2 gasoline (the numerator of the RAF ratio), data from several vehicles which satisfy the criteria outlined in section II.B. have been utilized. Many of these vehicles were tested by the ARB at its Haagen-Smit Laboratory. Additional data were provided by vehicle manufacturers.

A. Phase 2 Gasoline Specific Reactivity for TLEVs

The data set for establishing a Phase 2 gasoline specific reactivity for TLEVs included seven vehicles that were tested an average of four times by the ARB. Data were also supplied by General Motors for five additional vehicles, with two to six repeat tests per vehicle. All of the vehicles utilized multipoint fuel injection, with catalyst location ranging from underfloor to close-coupled configurations. Based on the emission results from these test vehicles (Table III), the staff is proposing a Phase 2 gasoline LEV specific reactivity of 3.44.

Table III - Phase 2 TLEV Specific Reactivity

Vehicle	NMOG (g/mi)	CO (g/mi)	NOx (g/mi)	Ozone/ mile	Ozone/ gram
Camry	0.094	1.88	0.138	0.347	3.703
LeSabre '92	0.114	1.33	0.145	0.371	3.248
Tempo	0.103	1.32	0.177	0.399	3.862
Jetta	0.111	1.89	0.089	0.406	3.681
Celica	0.096	1.06	0.111	0.308	3.222
Pontiac (GM)	0.109	2.09	0.261	0.394	3.625
Regal (GM)	0.123	1.88	0.130	0.408	3.320
Saturn(GM-A)	0.094	2.30	0.221	0.299	3.175
Saturn(GM-M)	0.098	1.51	0.240	0.290	2.965
LeSabre(GM)	0.080	0.89	0.159	0.266	3.330
T-Bird	0.080	0.71	0.255	0.290	3.619
Crown Vic	0.099	1.65	0.313	0.342	3.493
Cum. Avg.	0.100	1.54	0.186	0.343	3.437

B. Phase 2 Gasoline Specific Reactivity for LEVs

The data set for establishing the Phase 2 gasoline specific reactivity for LEVs consists of a total of nine vehicles, eight tested by the ARB and one by Ford Motor Company. The vehicles utilized a mix of EHC and non-EHC systems. With Phase 2 gasoline, the ARB staff expects that most LEVs will not require EHCs to certify to the LEV standards. However, for the most difficult to control engines or to achieve greater in-use compliance margin, some manufacturers will still choose to utilize EHCs.

Therefore, the ARB staff has selected a mix of EHC and non-EHC vehicles to determine the Phase 2 gasoline specific reactivity of 3.10 for LEVs (Table IV).

Table IV - Phase 2 LEV Specific Reactivity

Vehicle	NMOG (g/mi)	CO (g/mi)	NOx (g/mi)	Ozone/ mile	Ozone/ gram
Jetta	0.037	1.20	0.114	0.109	2.946
Lexus 400	0.041	0.30	0.141	0.126	3.112
Celica	0.071	0.74	0.151	0.212	2.978
LeSabre '90	0.054	0.46	0.208	0.164	3.057
Escort (ARB)	0.055	0.80	0.073	0.187	3.446
Cougar	0.059	1.08	0.159	0.180	3.035
Lumina	0.070	1.37	0.122	0.239	3.400
Escort (Ford)	0.059	1.15	0.047	0.180	3.038
T-bird	0.046	0.81	0.170	0.132	2.884
Cum. Avg.	0.055	0.88	0.132	0.170	3.100

C. Specific Reactivity for ULEVs Operated on Phase 2 Gasoline and Alternative Fuels

Due to the lack of currently-available vehicles which are representative of the technologies that will be used to meet the ULEV standards, it is premature to identify the Phase 2 gasoline ULEV specific reactivity at this time. The staff expects that production ULEVs will be better optimized to take advantage of the benefits of Phase 2 gasoline than the test vehicles available to the ARB today (refer to the discussion of the Ford data in section V.B.). As such, it would be more appropriate to establish the Phase 2 ULEV specific reactivities when data from these advanced vehicles become available. By establishing the baseline ULEV specific reactivity of 3.16 at the December hearing, manufacturers have a starting point to begin ULEV optimization on Phase 2 gasoline.

Further, the staff is in the process of procuring alternative fuel vehicles for testing; specific reactivities for compressed natural gas (CNG) and liquified petroleum gas (LPG) TLEVs and/or LEVs are expected to be determined early next year. Any such CNG or LPG specific reactivities determined after the December Board hearing will likely be established by the Executive Officer following an Executive Officer rulemaking hearing in early 1993.

V. REACTIVITY ADJUSTMENT FACTORS FOR PHASE 2 GASOLINE TLEVS AND LEVS

The staff is proposing generic RAFs for Phase 2 gasoline TLEVs and LEVs for approval at the December Board hearing. These proposed RAFs could be used by manufacturers beginning with the 1994 model-year.

Manufacturers may also choose to develop their own RAFs for specific engine families, in accordance with the procedures established in last year's rulemaking on RAFs. As additional data become available, the staff intends to propose revisions to the RAFs as necessary to better reflect the specific reactivity of Phase 2 gasoline production vehicles. That is to say, the numerator of the RAF ratio will be adjusted as warranted by new data, but the denominator (baseline specific reactivity) will remain fixed in order to provide a constant reference point upon which manufacturers can base new emission control strategies. Current regulations require that industry be notified at least three years before any such revised generic RAF becomes effective, although vehicle manufacturers may elect to utilize the revised RAF the following model year.

A. Phase 2 gasoline TLEV and LEV RAFs

Based on a specific reactivity for Phase 2 gasoline TLEVs of 3.44 and a baseline specific reactivity of 3.42, the staff is proposing a Phase 2 gasoline TLEV RAF of 1.00 (3.44/3.42). For LEVs, the staff is proposing a Phase 2 gasoline RAF of 0.98 (3.10/3.16). Although both of these RAFs are approximately one, it is important to note that the RAFs only represent specific reactivity (ozone per gram NMOG). Thus, a RAF of one means that the amount of ozone created by a gram of exhaust from a TLEV or LEV operated on Phase 2 gasoline is roughly equal to the amount of ozone created by a gram of exhaust from a TLEV or LEV operated on base gasoline. However, a RAF of one does not reflect the very significant mass emission reductions that result from the use of Phase 2 gasoline. In order to assess the environmental impact of any vehicle/fuel system, the amount of ozone that is formed each mile that the vehicle travels, or "ozone per mile," must be considered. As discussed below, use of Phase 2 gasoline yields very significant reductions in ozone per mile in low-emission vehicles.

B. Benefits of Phase 2 Gasoline

A comparison of the benefits of Phase 2 gasoline relative to base gasoline can be obtained by examining the test data collected for the 1991 RAF rulemaking and the data described in this report. Of the two data sets, four vehicles were tested on both Phase 2 gasoline and RF-A base gasoline. The emission results listed in Table V showed that Phase 2 gasoline resulted in a reduction in mass NMOG emissions and ozone per mile of approximately 40 percent. Importantly, Phase 2 gasoline also resulted in significant NO_x reductions in three out of the four vehicles. This indicates that Phase 2 gasoline will provide a very substantial emission benefit when used in low-emission vehicles.

Table V - Comparison of Phase 2 vs. RF-A

Vehicle	Fuel	NMOG	CO	NOx	Ozone/mi
Celica	RF-A	0.094	0.84	0.154	0.297
	Phase 2	0.071	0.74	0.151	0.212
	%diff	24%	12%	2%	29%
Cougar	RF-A	0.119	2.43	0.216	0.333
	Phase 2	0.059	1.08	0.159	0.180
	%diff	50%	56%	26%	46%
Jetta	RF-A	0.056	1.42	0.146	0.175
	Phase 2	0.037	1.20	0.114	0.109
	%diff	34%	15%	22%	38%
Lexus 400	RF-A	0.067	0.43	0.201	0.246
	Phase 2	0.041	0.30	0.141	0.126
	%diff	39%	30%	30%	49%
AVERAGE		37%	29%	20%	40%

Another indication of the substantial benefits of Phase 2 gasoline in reducing mass emissions is the fact that two of the ARB's test vehicles which met the TLEV standards on base gasoline qualified as LEVs when operated on Phase 2 gasoline. This phenomenon was observed with the Cougar and Celica, which were used to establish the baseline specific reactivity for TLEVs on RF-A. When operated on Phase 2, the vehicles' mass emission levels fell below the LEV standards, and as a consequence, the data were used to establish the Phase 2 specific reactivity for LEVs.

In light of this situation, the staff expects that many of the vehicles used to establish the specific reactivity for TLEVs on Phase 2 gasoline would likely exceed the TLEV standards on base gasoline. However, in actual production, manufacturers will be certifying TLEVs on Phase 2 gasoline without regard to their emissions on base gasoline. Therefore, in order to develop RAFs that represent actual production vehicles, the staff used data from vehicles that met TLEV standards on Phase 2 gasoline even if their emission control strategies were not as effective as those used to develop the baseline TLEV specific reactivity. This apparent difference in the technologies between the baseline and Phase 2 gasoline test cars may explain why the Phase 2 gasoline RAF for TLEVs is not lower than 1.00.

Additionally, it is important to note that the proposed generic Phase 2 gasoline RAFs represent only a starting point for manufacturers to begin certification, in the case of TLEVs, or to begin vehicle development, in the case of LEVs. As manufacturers begin to optimize their emission control systems to take full advantage of the properties of Phase 2 gasoline, the staff expects that the Phase 2 RAFs will decrease. For example, Ford Motor Company has compiled data from two advanced prototype vehicles, a Fiesta and a Mustang, which had NMOG, CO, and NOx mass emissions

below the LEV standards and which both had specific reactivity values on Phase 2 gasoline of 2.30 grams ozone per gram NMOG. For these two vehicles, the applicable RAF would be 0.73 (2.30/3.16). The staff expects that other manufacturers will be able to match Ford's Phase 2 reactivity levels with further vehicle optimization. If this does occur, the staff will propose a downward revision to the generic Phase 2 gasoline RAFs as warranted by the new data.

C. Modeling Correction Factors

In order to verify that the RAFs calculated above would not exacerbate ozone levels even under worst case conditions, the ARB staff intends to input the RAFs into an airshed model. Prof. Ted Russell of Carnegie Mellon University has been retained to conduct a null test of various ozone parameters to determine the impact of using the RAFs in the South Coast Air Basin during specific ozone episodes. This same procedure performed for the M85 TLEV RAF resulted in an upward adjustment of 10 percent (see Attachment III.A. of Mail-Out #92-23, the 15-day notice for the November, 1991 RAF regulations, released to the public on April 21, 1992). However, the staff will not speculate at this time about what adjustment, if any, would be needed for the Phase 2 gasoline RAFs. The modeling results should be available after November 20, 1992. As indicated in the Introduction to this report, the results will be available to interested parties upon request.

SECTION 1976, TITLE 13, CCR

Amend Title 13, California Code of Regulations, section 1976, to read as follows¹:

1976. Standards and Test Procedures for Motor Vehicle Fuel Evaporative Emissions .

(a) Fuel evaporative emissions from 1970 through 1977 model passenger cars and light-duty trucks are set forth in Title 40, Code of Federal Regulations, Part 86, Subparts A and C, as it existed on June 20, 1973. These standards are enforced in California pursuant to section 43008 of the Health and Safety Code.

(b)(1) Evaporative emissions for 1978 and subsequent model gasoline-fueled, 1983 and subsequent model liquefied petroleum gas-fueled, and 1993 and subsequent model methane~~l~~ alcohol-fueled motor vehicles and hybrid electric vehicles subject to exhaust emission standards under this article, except petroleum-fueled diesel vehicles, hybrid electric vehicles that have sealed fuel systems which can be demonstrated to have no evaporative emissions. and motorcycles, shall not exceed:

<u>Vehicle Type</u>	<u>Model Year</u>	<u>Hydrocarbons or OMHCE (1)</u>	
		<u>Hot Soak + Diurnal (grams per test) 50K Useful Life(2)</u>	<u>Running Loss (grams/mile) Useful Life(2)</u>
Passenger cars Light-duty trucks Medium-duty vehicles Heavy-duty vehicles	1978 and 1979	6.0	
Passenger cars Light-duty trucks Medium-duty vehicles Heavy-duty vehicles	1980 - 1994	2.0	
Passenger cars Light-duty trucks Medium-duty vehicles (6,000-8,500 lbs. GVWR (8,501-14,000 lbs. GVWR) (4) Heavy-duty vehicles	1995 and subsequent (3)	2.0	0.05

1. The regulatory amendments proposed in this rulemaking are shown in underline to indicate additions and ~~strikeout~~ to indicate deletions from existing regulations.

REQUEST FOR SPECIATED VEHICLE DATA OR AIRSHED MODELING RESULTS

Please mail or fax this form to:

California Air Resources Board
9528 Telstar Avenue
El Monte, CA 91731

Attention: Donna Barragan
FAX: 818-575-6818

* * * * *

Please send

- A complete set of the speciated emission profiles used to establish the TLEV and LEV RAFs for Phase 2 gasoline
- A summary of the modeling results and the modeling correction factors that will be applied to the TLEV and LEV RAFs for Phase 2 gasoline (available after November 20, 1992)

to:

Name: _____

Company: _____

Address: _____

**Establishment of Corrections to Reactivity Adjustment Factors for
Transitional Low-Emission Vehicles and Low-Emission Vehicles
Operating on Phase 2 Reformulated Gasoline**

Modeling Protocol and Final Results

California Air Resources Board
Research Division

December 15, 1992

I. Summary

This report presents the complete protocol (or calculation methodology) and results for modeling performed by Professor Armistead Russell and co-workers at Carnegie Mellon University to establish the corrections to reactivity adjustment factors (RAFTs) for Transitional Low-Emission Vehicles (TLEVs) and Low-Emission Vehicles (LEVs) operating on Phase 2 reformulated gasoline. The RAFT corrections are necessary because of differences in spatial and temporal patterns of emissions between vehicle fleets, rather than a problem with the maximum incremental reactivity (MIR) scale used to calculate the RAFTs. The following sections describe the processing of vehicle test data and other details of the emission inputs. Along with pre-existing documents describing other model inputs, the reader should have complete information to evaluate and, if desired, reproduce the modeling simulations. Reactivity adjustment factors of 1.06 and 0.99 are recommended for TLEVs and LEVs, respectively, operating on Phase 2 gasoline. The recommended values reflect improved reactivity assignments for two coeluting pairs of organic gases. The RAFT value for TLEVs operating on Phase 2 gasoline includes a 5 percent increase based on the airshed modeling, but does not yet include data from five vehicles tested by General Motors (GM). The corresponding RAFT for LEVs includes a 4 percent increase, but does not include data from a vehicle tested by Ford. The GM and Ford data are in a much different format than has been received previously, and they will be included in the RAFT calculation when the data is reformatted.

The final 1987 base emission inventory produced by the South Coast Air Quality Management District (SCAQMD) was used, with -4, +19 and +7 percent changes in emissions of nonmethane organic gases (NMOG), oxides of nitrogen (NO_x) and carbon monoxide (CO), respectively, from the draft inventory used in the previous study performed in 1991. The NMOG and CO emissions were doubled to respond to concerns about underestimation of motor vehicle and other emissions, and to provide a more stringent test of the MIR scale, which defines reactivity where hydrocarbon control is most important, i.e., under high NO_x levels. This departs from the 1991 study, which included a doubling of the catalyst exhaust emissions of NMOG and CO, rather than a doubling of the entire inventory. The change in the 1987 inventory necessitated a verification of the correction factor for the 85 percent methanol/15 percent gasoline (M85) case done in 1991. A matrix of two ozone episodes (1987 and 1982) in the South Coast Air Basin (SoCAB), two baseline emission inventories (1987 and 2010), and, in addition to the

conventional fuel, two alternative fuels (Phase 2 gasoline and M85) and a zero motor vehicle hydrocarbon emission case exhaust emissions for two levels of the new standards (TLEV and LEV) was modeled. This results in twenty-four simulations for analysis. The results for M85 show better agreement with the overall equal ozone impacts required by the regulation than those reported in the 1991 study.

II. Calculation Methodology

The CIT airshed model is a three-dimensional, photochemical grid model, based on numerically solving the advection-diffusion equation. The model employs the Lurmann, Coyner and Carter (LCC) lumped molecule mechanism. This family of chemical schemes is now referred to as the SAPRC mechanisms, as Carter is affiliated with the Statewide Air Pollution Research Center at the University of California at Riverside. The LCC mechanism is a predecessor of the SAPRC90 mechanism employed in determining the MIR scale. There are three versions of the LCC mechanism, each using various degrees of lumping to condense the hundreds of organic gases into a manageable number of species for model calculations. The CIT airshed model uses the most condensed version of the LCC, which has been shown previously (ARB 1992) to produce the same RAFs as the SAPRC90 mechanism. The LCC mechanism was extended to include the explicit chemical mechanisms for ethane, propane, methanol, and ethanol, normally lumped with other species in the LCC mechanism, because of the large fractions of these species found in the exhaust for some of the alternative fuels.

The CIT model is used to simulate two three-day ozone episodes in the SoCAB. Both periods are conducive to high ozone formation, although each had different meteorological characteristics, and peak ozone levels occurred in different parts of the Basin during each episode. The August 30 to September 1, 1982 episode had very stagnant meteorological conditions leading to the highest ozone level (0.35 ppm) recorded in the United States in 1982. The August 27 to 29, 1987 episode was an intensive measurement period during the Southern California Air Quality Study (SCAQS) with a peak ozone level of 0.29 ppm. The CIT model has been evaluated for both periods (Russell et al. 1990; Harley et al. 1992). Initial and boundary conditions were derived from measurements, and were unchanged for all calculations. The initial conditions largely influence the model predictions for the first day or two. After that, emissions and boundary conditions predominate. The ideal situation for investigating the effects of different emission inventories is to minimize the influence of initial conditions. As a consequence, only the third day of the simulation is reported. Boundary conditions have a minimal influence on model predictions as determined by sensitivity tests (Russell et al. 1990; Harley et al. 1992).

Emissions of nitrous acid (HONO), an important source of radicals that initiate ozone formation in the morning, were not added to the episodes as was done in the derivation of the MIR scale. The airshed model includes night-time reactions that create HONO levels similar to those observed during SCAQS.

III. Motor Vehicle Data

A. Speciation

Six 1987 and six 2010 inventories were constructed by adjusting the on-road mobile source catalyst emissions to account for changing fuels: a null inventory (NULL) for the case of no catalyst exhaust emissions of NMOG; conventionally-fueled vehicle (CFV) cases, corresponding to industry-average gasoline, termed RF-A in the Auto/Oil Air Quality Improvement Research Program (AQIRP) for TLEVs and LEVs; and alternative fuel inventories for TLEVs and LEVs operated on Phase 2 reformulated gasoline (PH2) and TLEVs operated on M85 with motor vehicle emissions for each alternative fuel increased by the reciprocal of the RAF. Data from testing programs conducted by the California Air Resources Board (ARB), the Auto/Oil AQIRP and Chevron Research & Technology Company were assigned organic gas identifications (OGID) corresponding to the list of species in the MIR scale adopted in the 1991 RAF regulation. (See Appendix A for the OGID assignments and Appendix B for the reactivities.) The vehicle test data were renormalized in terms of weight fractions, and then the weight fractions for each species for all the tests on an individual vehicle were averaged. The composite profiles for each vehicle were averaged to create composite profiles for each fuel. Separate composite profiles were calculated for each bag of the U. S. Environmental Protection Agency's 1975 Federal Test Procedure (FTP).

During the gas chromatographic analysis of vehicle emissions, sometimes two compounds will coelute. Coelution is generally not a problem if both compounds are present in only small amounts or if they have similar reactivities. The testing program conducted by ARB was unable to resolve 2,2,4-trimethylpentane from an unidentified alkene, nor 4-ethyltoluene from a C₁₀ cycloalkane. For lack of better information, a 50/50 split was assumed for both coeluting pairs. Recent gas chromatography/mass spectroscopy analysis reveals that these assumptions are invalid. The first coeluting pair is almost all 2,2,4-trimethylpentane, and the second pair is entirely 4-ethyltoluene. (Appendix A has been updated to reflect this new information.) The composite profiles provided to Professor Russell for the TLEV and LEV vehicles, given in Appendices C and D, respectively, do not include the updated reactivity assignments for the two coeluting pairs. However, the new assignments are not expected to affect the airshed modeling analysis because the mass distributions between the cold start, running, and hot start modes (discussed further below) are independent of the speciation assignments.

The emission inventories for each fuel were adjusted by the calculated RAFs. Table I contains the RAFs provided to Professor Russell, as well as the RAFs from the Initial Statement of Proposed Rulemaking, which includes vehicle test results from Ford and GM not available for this work. Table I also contains RAFs calculated with the Carbon Bond 4 (CB4) chemical mechanism and under maximum ozone incremental reactivity (MOIR) conditions. For these fuels, the RAFs are fairly independent of the chemical mechanism and reactivity scale. Further vehicle testing from ARB, Ford and GM have become available since the composite speciation profiles were provided to Professor Russell. The additional ARB data have been included in the RAF calculation, but the Ford and GM data are in a much different format than has been received previously. They will be included in the RAF calculation when the data is reformatted.

As with the 1991 study, a more realistic distribution of exhaust emissions between the cold start, running, and hot start modes was used. The emission inventories developed for the SoCAB with EMFAC7E have the three phases of the FTP cycle combined according to local information on traffic patterns. Furthermore, different definitions of cold start and hot start emissions are used in the SoCAB inventory and the FTP. In EMFAC7E, the cold and hot starts are represented as an emissions increment due to the actual start. In the FTP, the Bag 1 and Bag 3 measurements reflect the start emissions increment as well as emissions accrued at the cold and hot stabilized rates, respectively. Thus, the Bag 2 result (which represents both cold and hot stabilized emissions) must be subtracted from the Bag 1 and Bag 3 results:

$$\text{Cold Start} = 3.59 * (\text{BAG1} - \text{SCF26} * \text{BAG2}) \quad (1)$$

where Cold Start is the EMFAC7E cold start emissions increment in grams/start, BAG1 is the FTP cold transient emissions in grams/mile, BAG2 is the FTP cold stabilized emissions in grams/mile, 3.59 is the mileage for the FTP cold transient test in miles/start; and SCF26 is the EMFAC7E speed correction factor (0.615 for current vehicles) to adjust the Bag 2 average speed (16 mph) to the Bag 1 average speed (26 mph).

The calculation is performed for each NMOG species in a composite profile, with any negative emissions increments set to zero. The emissions for all species are summed to get the total cold start emissions increment. The calculation of the EMFAC7E hot start emissions increment is done in a similar manner with the substitution of the Bag 3 result in place of the Bag 1 result in Equation 1. The Bag 2 mass emission rate and speciation results are used directly by EMFAC7E to represent the running exhaust emissions.

The three EMFAC7E exhaust emission modes are weighted according to activity data estimated by transportation models. Activity data for both the 1987 and 2010 base years for the SoCAB are given in Table II, with the resulting vehicle mass and reactivity distributions given in Table III. However, it is not known how the mass distributions for the alternatively-fueled vehicles change as a function of temperature or speed.

IV. Baseline Emission Inventory

Both the 1982 and 1987 episodes were simulated with the same two emission inventories: 1) a base year, 1987, with a doubling of NMOG and CO emissions from all sources; and 2) a future year, 2010, with stringent controls. Using the same two inventories for both episodes allows a direct comparison of the effect of meteorological conditions on reactivity. The 2010 time frame is a realistic expectation of when vehicles that meet the requirements of the California LEV/CF regulations will dominate the fleet, but is not considered a stringent test of the RAF approach because the low NMOG to NO_x ratio (3.9) is similar to the high NO_x conditions used to derive the MIR scale. The 1987 inventory with the NMOG and CO exhaust emissions doubled responds to recent studies (Pierson et al. 1990; Fujita et al. 1992; Harley et al. 1992) that organic gas emissions from motor vehicles are underestimated by about a factor of two, and to concerns that a higher NMOG to NO_x ratio (8.4) is needed to provide a stringent test of the MIR scale. This doubling of the entire NMOG and CO emission inventories is consistent with current ARB practices for model sensitivity studies.

The final 1987 base emission inventory produced by the SCAQMD was used, with -4, +19 and +7 percent changes in NMOG, NO_x and CO emissions, respectively, from the draft inventory used in the 1991 study. The major changes from the draft inventory are: 1) motor vehicle emissions of NMOG decreased and of NO_x increased with EMFAC7E; 2) area source evaporative emissions of NMOG increased from floating roof tanks and NO_x emissions increased from locomotives and public utility equipment; 3) biogenic emissions included; and 4) NMOG speciation profiles and assignments updated. The final 1987 base emission inventory is documented in the 1991 Air Quality Management Plan, Technical Report III-C and Appendices III-A, III-B, and III-C.

Due to the large increase in NO_x emissions with the new inventory, it was decided to double the entire NMOG and CO emission inventories, rather than just the catalyst exhaust emissions of NMOG and CO as was done in the 1991 study. The NULL case corresponds to NMOG exhaust emissions for catalyst-equipped vehicles from the base fleet, i.e., without doubling. In the 1991 study, the NULL case was defined as zero NMOG exhaust emissions for catalyst-equipped vehicles. However, the high sensitivity of the Urban Airshed Model to formaldehyde emissions, which are primarily from motor vehicles, created the concern that zeroing emissions would lead to non-linear effects.

Incremental reactivities are, by definition, mathematically additive, but at issue is how large an emission change is considered an "increment". Calculations by Chang and Rudy (1990) with an EKMA-type model indicate that individual emission increments appear to be additive for up to a 30 percent substitution of organic gas emissions in an airshed. In this study, for both the 1987 and 2010 inventories, the speciation for the TLEVs were applied to the entire catalyst motor vehicle fleet. This corresponds to 8 and 22 percent of the NMOG inventory in 1987 and 2010, respectively. This assumption of complete conversion of the fleet to TLEVs is not realistic, but does provide a more stringent test of the RAF approach.

The 1987 base emission inventory represents an average summer weekday with day-specific stationary source emissions for the August 27 to 29 SCAQS episode. Motor vehicle emissions were constructed with the California mobile emissions model, EMFAC7E. Except for the doubling of the NMOG and CO emissions, stationary source, off-road mobile emissions, diesel exhaust, and non-catalyst vehicle emissions were unchanged, as was NO_x. Evaporative emission rates and speciation profiles were not changed from the baseline vehicle fleet. These assumptions are not realistic, but the objective of the study was to test the way the reactivity scale is being applied in the ARB regulations, assuming that all fuels just meet the reactivity-adjusted standards. The 2010 emission inventory is a projection of the draft 1987 base emission inventory. The 2010 inventory was constructed in a similar manner to the 1987 inventory, except that the NMOG and CO emissions were not doubled. The mass emissions are summarized in Table IV and the LCC species emissions are summarized in Table V.

V. Results and Discussion

The CIT airshed model was used to simulate the air quality impacts of the twelve separate emission inventories on both sets of meteorological conditions. A matrix of two ozone episodes (1987 and 1982) in the South Coast Air Basin, two baseline emission inventories (1987 and 2010), and exhaust emissions from three alternative fuels (RF-A, Phase 2 gasoline and M85) for two levels of the new standards (TLEV and LEV) was

modeled. This results in twenty-four simulations for analysis. The ozone predictions for the completed simulations are summarized in Table VI. Four metrics are presented: 1) peak, one-hour average ozone basinwide; 2) spatial ozone exposure showing the number of hours and grids where ozone concentrations are greater than a prescribed value (e.g., the 0.09 ppm California and 0.12 ppm national ambient air quality standards); 3) concentration-weighted spatial ozone dosage; and 4) population- and concentration-weighted ozone dosage. The NULL calculation gives results distinctly different than the CFV and the alternative fuel simulations for each ozone metric other than the peak. If this were not the case, it would be very difficult to assess the impact of the change in organic gas composition and additional emissions of the alternative fuels.

A useful statistic for judging how closely the RAF leads to an equal ozone impact is the "null test", defined as the concentration increment due to the alternative fuel, normalized relative to that of the conventional fuel:

$$\text{Null test result} = \frac{C_{\text{AFV}} - C_{\text{NULL}}}{C_{\text{CFV}} - C_{\text{NULL}}} \quad (2)$$

where C_{AFV} is the concentration (or other metric) for an alternatively-fueled vehicle (AFV) simulation, and C_{CFV} and C_{NULL} are the corresponding metrics for the CFV and NULL simulations, respectively. The closer the null test result is to one, the closer the RAF comes to producing the desired result. If the value found from the multi-day airshed modeling is greater or less than one, the exhaust is greater or less reactive, respectively, than the RAF would imply. The null test results are shown in Table VII.

In general, the null test results for the ozone exposure and dosage metrics are within ± 10 percent of the equal ozone impacts required by the regulation, with much closer agreement in many cases. However, the null test results for some of the ozone peak predictions show large deviations from the desired result. In these cases, the ozone peak is found in a location that is less sensitive to NMOG emissions than much of the urban area, as reflected by the small differences (about 0.01 ppm) between the peak predictions in the CFV and NULL simulations. Thus, small differences in peak concentrations between the conventional- and alternatively-fueled vehicles are magnified in the normalization specified for the null test result in Equation 2. In the one case where there is a large difference (about 0.06 ppm) between the peak ozone predictions for the CFV and NULL simulations, for the 1982 meteorology with the 1987 emission inventory, the null test results are quite reasonable.

The change in the 1987 inventory necessitated a verification of the correction factor for M85 case done in 1991. The results for M85 show better agreement with the overall equal ozone impacts required by the regulation than those reported in the 1991 study.

The only formally adopted RAF to date, a value of 0.41 for M85 vehicles, includes a 10% increase based on the airshed modeling results for the population-weighted dosage statistic for the higher 1982 episode. The corresponding result for TLEVs and LEVs operating on Phase 2 gasoline are 5 and 4 percent increases, respectively.

VII. References

California Air Resources Board (1992) "Proposed Regulations for Low-Emission Vehicles and Clean Fuels--15 Days Notice," State of California, Air Resources Board, April 21.

Chang, T. Y.; Rudy, S. J. (1990) "Ozone-forming potential of organic emissions from alternative-fueled vehicles," *Atmos. Environ.*, **24A**: 2421.

Fujita, E. M.; Croes, B. E.; Bennett, C. L.; Lawson, D. R.; Lurmann, F. W.; Main, H. H. (1992) "Comparison of emission inventory and ambient concentration ratios of CO, NMOG, and NO_x in California's South Coast Air Basin," *J. Air Waste Manage. Assoc.*, **42**: 264.

Harley, R. A.; Russell, A. G.; McRae, G. J.; McNair, L. A.; Winner, D. A.; Odman, M. T.; Dabdub, D.; Cass, C. R.; Seinfeld, J. H. (1992) "Continued Development of a Photochemical Model and Application to the Southern California Air Quality Study (SCAQS) Intensive Monitoring Periods: Phase I," Final Report to the Coordinating Research Council.

Pierson, W. R.; Gertler, A. W.; Bradow, R. L. (1990) "Comparison of the SCAQS tunnel study with other on-road vehicle emission data," *J. Air Waste Manage. Assoc.*, **40**: 1495.

Russell A. G.; St. Pierre, D.; Milford, J. B. (1990) "Ozone control, and methanol fuel use," *Science*, **247**, 201.

Table I. RAFs at various stages of development.

Vehicle Type	Reactivity Adjustment Factors				
	Previous		Current ^c		
	Proposed ^a	CMU ^b	MIR	CB4	MOIR
TLEV PH2	1.00	1.02	1.01	1.01	1.01
TLEV M85	na	0.37	0.38	0.40	0.39
LEV PH2	0.97	0.96	0.95	0.95	0.98

^aFrom Initial Statement of Proposed Rulemaking, which includes vehicle test results from Ford and GM, but not new assignments for coeluting pairs.

^bProvided to Professor Russell of CMU, which does not include some vehicle test results from ARB, any test results from Ford and GM, nor new assignments for coeluting pairs.

^cIncludes new assignments for coeluting pairs, but not vehicle test results from Ford and GM.

na Not applicable.

Table II. Activity data^a for the South Coast Air Basin.

Base Year	Miles per Start	Cold Start Fraction	Hot Start Fraction
1987	8.3	0.58	0.42
2010	9.8	0.60	0.40

^aBased on BURDEN model.

Table III. Exhaust emissions distribution for test data for TLEVs and LEVs.

Vehicle Type	Percent of Mass in Each Exhaust Mode					
	1987 Activity Data			2010 Activity Data		
	Cold	Run	Hot	Cold	Run	Hot
TLEV RFA	72.2	21.9	5.9	70.5	24.3	5.2
TLEV PH2	87.3	9.8	2.9	86.4	11.0	2.6
TLEV M85	95.1	3.7	1.2	94.8	4.2	1.0
LEV RFA	81.6	13.7	4.8	80.5	15.3	4.3
LEV PH2	78.6	17.3	4.1	77.1	19.2	3.6

Table IV. 1987 and 2010 emissions by pollutant and category.

Vehicle Type	Emissions (10 ³ kg/day)					
	1987*			2010		
	NMOG	NO _x	CO	NMOG	NO _x	CO
NULL	3200	1352	12,028	901	967	3571
TLEV RFA	3459	1352	12,028	1150	967	3571
TLEV PH2	3454	1352	12,028	1145	967	3571
TLEV M85	3900	1352	12,028	1574	967	3571
LEV RFA	3459	1352	12,028	1150	967	3571
LEV PH2	3470	1352	12,028	1160	967	3571

*With NMOG and CO emissions doubled.

Table V. LCC species profiles.

LCC Species	Fleet Emissions (kg-moles/day)				
	TLEV			LEV	
	RFA	PH2	M85	RFA	PH2
ETHE	816	512	226	459	501
ALKE	414	634	130	346	574
ALKA	1183	1071	377	1380	1340
TOLU	366	361	156	283	298
AROM	345	319	142	399	246
HCHO	150	393	1318	345	712
ALD2	99	67	46	97	96
MEK	52	8	76	8	13
MEOH	0	0	18,363	0	0

Table VIa. CIT airshed model predictions^a for August 27 to 29, 1987 meteorology and 1987^b inventory.

Ozone Statistic	Ozone Results					
	TLEV			LEV		NULL
	RFA	PH2	M85	RFA	PH2	
basin peak (ppb)	237.6	237.4	238.5	237.3	237.6	229.0
grid-hours ^c > 0.09 ppm	2779	2786	2780	2782	2780	2611
grid-hours ^c > 0.12 ppm	1499	1509	1502	1506	1505	1385
ppm-grid-hours ^d > 0.09 ppm	361	362	362	362	362	336
ppm-grid-hours ^d > 0.12 ppm	229	230	230	230	230	208
10 ³ person-ppm-hours ^e > 0.09 ppm	3891	3902	3900	3883	3900	3236
10 ³ person-ppm-hours ^e > 0.12 ppm	1961	1967	1971	1976	1964	1625

Table VIIb. CIT airshed model predictions^a for August 27 to 29, 1987 meteorology and 2010 inventory.

Ozone Statistic	Ozone Results					
	TLEV			LEV		NULL
	RFA	PH2	M85	RFA	PH2	
basin peak (ppb)	159.7	160.0	159.3	159.8	160.2	151.4
grid-hours ^c > 0.09 ppm	2091	2094	2081	2098	2113	1806
grid-hours ^c > 0.12 ppm	764	756	755	770	787	480
ppm-grid-hours ^d > 0.09 ppm	241	241	240	242	244	200
ppm-grid-hours ^d > 0.12 ppm	101	100	100	102	104	62
10 ³ person-ppm-hours ^e > 0.09 ppm	1605	1611	1583	1617	1641	1059
10 ³ person-ppm-hours ^e > 0.12 ppm	155.7	150.2	152.5	166.6	185.4	67.1

^aResults for third day of simulation.

^bWith NMOG and CO emissions doubled.

^cSummation of the number of grids × hours that any modeling grid experienced an ozone concentration greater than the prescribed value.

^dSummation of the concentration × grids × hours that any modeling grid experienced an ozone concentration greater than the prescribed value.

^eSummation of the population × concentration × hours for any modeling grid that experienced an ozone concentration greater than the prescribed value.

Table VIc. CIT airshed model predictions^a for August 30 to September 1, 1982 meteorology and 1987^b inventory.

Ozone Statistic	Ozone Results					
	TLEV			LEV		NULL
	RFA	PH2	M85	RFA	PH2	
basin peak (ppb)	498.4	498.6	501.0	499.9	501.5	438.2
grid-hours ^c > 0.09 ppm	5976	5957	5969	5984	5968	5667
grid-hours ^c > 0.12 ppm	4677	4686	4686	4677	4675	4383
ppm-grid-hours ^d > 0.09 ppm	1147	1146	1147	1148	1147	1054
ppm-grid-hours ^d > 0.12 ppm	1012	1014	1014	1012	1012	921
10 ⁴ person-ppm-hours ^e > 0.09 ppm	1522	1519	1521	1523	1518	1289
10 ⁴ person-ppm-hours ^e > 0.12 ppm	1336	1340	1340	1339	1336	1110

Table VIId. CIT airshed model predictions^a for August 30 to September 1, 1982 meteorology and 2010 inventory.

Ozone Statistic	Ozone Results					
	TLEV			LEV		NULL
	RFA	PH2	M85	RFA	PH2	
basin peak (ppb)	239.5	241.4	242.5	239.4	240.1	217.7
grid-hours ^c > 0.09 ppm	4270	4305	4321	4309	4330	3581
grid-hours ^c > 0.12 ppm	2415	2448	2467	2435	2463	1894
ppm-grid-hours ^d > 0.09 ppm	583	588	592	588	592	462
ppm-grid-hours ^d > 0.12 ppm	390	395	399	393	398	287
10 ³ person-ppm-hours ^e > 0.09 ppm	5765	5858	5850	5861	5934	3884
10 ³ person-ppm-hours ^e > 0.12 ppm	4233	4312	4330	4311	4378	2745

^aResults for third day of simulation.

^bWith NMOG and CO emissions doubled.

^cSummation of the number of grids × hours that any modeling grid experienced an ozone concentration greater than the prescribed value.

^dSummation of the concentration × grids × hours that any modeling grid experienced an ozone concentration greater than the prescribed value.

^eSummation of the population × concentration × hours for any modeling grid that experienced an ozone concentration greater than the prescribed value.

Table VIIa. Null test results for CIT airshed model simulations of August 27 to 29, 1987 meteorology.

Ozone Statistic	Null Test Result					
	1987 Inventory ^a			2010 Inventory		
	TLEV		LEV	TLEV		LEV
	PH2	M85	PH2	PH2	M85	PH2
basin peak ^b	0.98	1.10	1.04	1.04	0.95	1.05
grid-hours > 0.09 ppm	1.04	1.01	0.99	1.01	0.96	1.05
grid-hours > 0.12 ppm	1.09	1.03	0.99	0.97	0.97	1.06
ppm-grid-hours > 0.09 ppm	1.04	1.04	1.00	1.00	0.98	1.05
ppm-grid-hours > 0.12 ppm	1.05	1.05	1.00	0.97	0.97	1.05
person-ppm-hours > 0.09 ppm	1.02	1.01	1.03	1.01	0.96	1.04
person-ppm-hours > 0.12 ppm	1.02	1.03	0.97	0.94	0.96	1.19

Table VIIb. Null test results for CIT airshed model simulations of August 30 to September 1, 1982 meteorology.

Ozone Statistic	Null Test Result					
	1987 Inventory ^a			2010 Inventory		
	TLEV		LEV	TLEV		LEV
	PH2	M85	PH2	PH2	M85	PH2
basin peak ^b	1.00	1.04	1.03	1.09	1.14	1.03
grid-hours > 0.09 ppm	0.94	0.98	0.95	1.05	1.07	1.03
grid-hours > 0.12 ppm	1.03	1.03	0.99	1.06	1.10	1.05
ppm-grid-hours > 0.09 ppm	0.99	1.00	0.99	1.04	1.07	1.03
ppm-grid-hours > 0.12 ppm	1.02	1.02	1.00	1.05	1.09	1.05
person-ppm-hours > 0.09 ppm	0.99	1.00	0.98	1.05	1.05	1.04
person-ppm-hours > 0.12 ppm	1.02	1.02	0.99	1.05	1.07	1.04

^aWith NMOG and CO emissions doubled.

^bFar downwind ozone peak. Peak relatively insensitive to NMOG emission changes, so ratio of two small numbers.

Appendix A

Organic Gas Names and OGID Assignments

AOP Organic Gas Names and ID Assignments - 11/13/92

Frac OGID1	Frac OGID2	Frac OGID3	Organic Gas Name
1.00 ETHENE	0.00	0.00	ETHENE
1.00 ETHYNE	0.00	0.00	ETHYNE
1.00 ETHANE	0.00	0.00	ETHANE
1.00 PROPENE	0.00	0.00	PROPENE
1.00 PROPANE	0.00	0.00	PROPANE
1.00 ETHENE	0.00	0.00	PROPADIENE
Assume similar to ethene			
1.00 PROPYNE	0.00	0.00	PROPYNE
1.00 2MC3	0.00	0.00	2M-PROPANE
1.00 2MC3=	0.00	0.00	2M-PROPENE
1.00 1C4=	0.00	0.00	1-BUTENE
1.00 13C4==	0.00	0.00	1,3-BUTADIENE
1.00 BUTANE	0.00	0.00	BUTANE
1.00 T-2C4=	0.00	0.00	T-2-BUTENE
1.00 22DMC3	0.00	0.00	2,2-DM-PROPANE
1.00 1BUTYNE	0.00	0.00	1-BUTYNE
1.00 C-2C4=	0.00	0.00	C-2-BUTENE
1.00 3M1C4=	0.00	0.00	3M-1-BUTENE
1.00 2MC4	0.00	0.00	2M-BUTANE
1.00 1BUTYNE	0.00	0.00	2-BUTYNE
Assume similar to 1-butyne			
1.00 1C5=	0.00	0.00	1-PENTENE
1.00 2M1C4=	0.00	0.00	2M-1-BUTENE
1.00 PENTANE	0.00	0.00	PENTANE
1.00 ISOPRENE	0.00	0.00	2M-1,3-BUTADIENE
1.00 C5OLE2	0.00	0.00	T-2-PENTENE
1.00 C6OLE1	0.00	0.00	3,3-DM-1-BUTENE
1.00 C5OLE2	0.00	0.00	C-2-PENTENE
1.00 2M2C4=	0.00	0.00	2M-2-BUTENE
1.00 C5C5=	0.00	0.00	CYCLOPENTADIENE
Assume similar to cyclopentene			
1.00 22DMC4	0.00	0.00	2,2-DM-BUTANE
1.00 C5C5=	0.00	0.00	CYCLOPENTENE
1.00 C6OLE1	0.00	0.00	4M-1-PENTENE
1.00 C6OLE1	0.00	0.00	3M-1-PENTENE
1.00 C5C5	0.00	0.00	CYCLOPENTANE
1.00 23DMC4	0.00	0.00	2,3-DM-BUTANE
1.00 MTBE	0.00	0.00	MTBE
1.00 C6OLE2	0.00	0.00	4M-C-2-PENTENE
1.00 2MC5	0.00	0.00	2M-PENTANE
1.00 C6OLE2	0.00	0.00	4M-T-2-PENTENE
1.00 3MC5	0.00	0.00	3M-PENTANE
1.00 C6OLE1	0.00	0.00	2M-1-PENTENE

05517

1.00 1C6=	0.00	1.00 HEXENE	1.00 HEXENE
1.00 HEXANE	0.00	HEXANE	HEXANE
1.00 C6OLE2	0.00	T-3-HEXENE	T-3-HEXENE
1.00 C6OLE2	0.00	C-3-HEXENE	C-3-HEXENE
1.00 C6OLE2	0.00	T-2-HEXENE	T-2-HEXENE
1.00 C6OLE2	0.00	3M-T-2-PENTENE	3-METHYL-T-2-PENTENE
1.00 C6OLE2	0.00	2M-2-PENTENE	2-METHYL-2-PENTENE
1.00 CYC6=	0.00	3M-CYCLOPENTENE	3-METHYLCYCLOPENTENE
Assume similar to cyclohexene			
1.00 C6OLE2	0.00	C-2-HEXENE	CIS-2-HEXENE
1.00 ETBE	0.00	ETBE	ETBE
1.00 BRC7PAR	0.00	2,2-DM-PENTANE	2,2-DIMETHYLPENTANE
1.00 MCYC5	0.00	M-CYCLOPENTANE	METHYLCYCLOPENTANE
1.00 24DMC5	0.00	2,4-DM-PENTANE	2,4-DIMETHYLPENTANE
1.00 223TMC4	0.00	2,2,3-TM-BUTANE	2,2,3-TRIMETHYLBUTANE
1.00 BENZENE	0.00	BENZENE	BENZENE
1.00 C7OLE1	0.00	3M-1-HEXENE	3-METHYL-1-HEXENE
1.00 33DMC5	0.00	3,3-DM-PENTANE	3,3-DIMETHYLPENTANE
1.00 CYC6	0.00	CYCLOHEXANE	CYCLOHEXANE
1.00 2MC6	0.00	2M-HEXANE	2-METHYLHEXANE
1.00 23DMC5	0.00	2,3-DM-PENTANE	2,3-DIMETHYLPENTANE
1.00 CYC6=	0.00	CYCLOHEXENE	CYCLOHEXENE
1.00 3MC6	0.00	3M-HEXANE	3-METHYLHEXANE
1.00 13DMCYC5	0.00	C-1,3-DM-CYPENTANE	C-1,3-DIMETHYLCYCLOPENTANE
1.00 CYC7PAR	0.00	T-1,2-DM-CYPENTANE	T-1,2-DIMETHYLCYCLOPENTANE
1.00 C7OLE1	0.00	1-HEPTENE	1-HEPTENE
1.00 224TMC5	0.00	2,2,4-TM-PENTANE	2,2,4-TRIMETHYLPENTANE
1.00 C7OLE2	0.00	T-3-HEPTENE	T-3-HEPTENE
1.00 HEPTANE	0.00	HEPTANE	HEPTANE
1.00 C7OLE2	0.00	2M-2-HEXENE	2-METHYL-2-HEXENE
1.00 C7OLE2	0.00	3M-T-3-HEXENE	3-METHYL-T-3-HEXENE
1.00 C7OLE2	0.00	T-2-HEPTENE	T-2-HEPTENE
1.00 C7OLE2	0.00	3E-C-2-PENTENE	3-ETHYL-C-2-PENTENE
1.00 C8OLE1	0.00	2,4,4-TM-1-PENTENE	2,4,4-TRIMETHYL-1-PENTENE
1.00 C7OLE2	0.00	2,3-DM2,-PENTENE	2,3-DIMETHYL-2-PENTENE
1.00 C7OLE2	0.00	C-2-HEPTENE	C-2-HEPTENE
1.00 MCYC6	0.00	M-CYCLOHEXANE	METHYLCYCLOHEXANE
1.00 BRC8PAR	0.00	2,2-DM-HEXANE	2,2-DIMETHYLHEXANE
1.00 C8OLE2	0.00	2,4,4-TM-2-PENTENE	2,4,4-TRIMETHYL-2-PENTENE
1.00 25DMC6	0.00	2,5-DM-HEXANE	2,5-DIMETHYLHEXANE
1.00 ECYC5	0.00	E-CYCLOPENTANE	ETHYLCYCLOPENTANE
1.00 24DMC6	0.00	2,4-DM-HEXANE	2,4-DIMETHYLHEXANE
1.00 BRC8PAR	0.00	3,3-DM-HEXANE	3,3-DIMETHYLHEXANE
1.00 234TMC5	0.00	2,3,4-TM-PENTANE	2,3,4-TRIMETHYLPENTANE
1.00 TOLUENE	0.00	TOLUENE	METHYLBENZENE (TOLUENE)
1.00 23DMC6	0.00	2,3-DM-HEXANE	2,3-DIMETHYLHEXANE
1.00 2MC7	0.00	2M-HEPTANE	2-METHYLHEPTANE

05518

1.00 4MC7	0.00	4M-HEPTANE	4-METHYLHEPTANE
1.00 3MC7	0.00	3M-HEPTANE	3-METHYLHEPTANE
1.00 CYC8PAR	0.00	1C, 2T, 3-TM-CYCOPENTANE	1C, 2T, 3-TM-TRIMETHYLCYCLOPENTAN
1.00 CYC8PAR	0.00	C-1, 3-DM-CYCHEXANE	C-1, 3-DIMETHYLCYCLOHEXANE
1.00 CYC8PAR	0.00	T-1, 4-DM-CYCHEXANE	T-1, 4-DIMETHYLCYCLOHEXANE
1.00 225TMC6	0.00	2, 2, 5-TM-HEXANE	2, 2, 5-TRIMETHYLHEXANE
1.00 C8OLE1	0.00	1-OCTENE	1-OCTENE
1.00 C8OLE2	0.00	T-4-OCTENE	T-4-OCTENE
1.00 OCTANE	0.00	OCTANE	N-OCTANE
1.00 C8OLE2	0.00	T-2-OCTENE	T-2-OCTENE
1.00 CYC8PAR	0.00	T-1, 3-DM-CYCHEXANE	T-1, 3-DIMETHYLCYCLOHEXANE
1.00 C8OLE2	0.00	C-2-OCTENE	C-2-OCTENE
1.00 BRC9PAR	0.00	2, 3, 5-TM-HEXANE	2, 3, 5-TRIMETHYLHEXANE
1.00 24DMC7	0.00	2, 4-DM-HEPTANE	2, 4-DIMETHYLHEPTANE
1.00 CYC8PAR	0.00	1C-2DM-CYCLOHEXANE	C-1, 2-DIMETHYLCYCLOHEXANE
1.00 ECYC6	0.00	E-CYCHEXANE	ETHYLCYCLOHEXANE
1.00 BRC9PAR	0.00	3, 5-DM-HEPTANE	3, 5-DIMETHYLHEPTANE
1.00 EBEN	0.00	E-BENZENE	ETHYLBENZENE
1.00 BRC9PAR	0.00	2, 3-DM-HEPTANE	2, 3-DIMETHYLHEPTANE
0.50 M-XYL	0.00	M&P-XYLENE	1, 3-DIMETHYLBENZENE (M-XYLEN
0.50 P-XYL	0.00		
Average of m & p-xylenes			
1.00 BRC9PAR	0.00	4M-OCTANE	4-METHYLOCTANE
1.00 BRC9PAR	0.00	3M-OCTANE	3-METHYLOCTANE
1.00 STYRENE	0.00	STYRENE	STYRENE
1.00 O-XYL	0.00	O-XYLENE	1, 2-DIMETHYLBENZENE (O-XYLEN
1.00 C9OLE1	0.00	1-NONENE	1-NONENE
1.00 NONANE	0.00	NONANE	N-NONANE
1.00 I-PBEN	0.00	I-PROPBENZENE	I-PROPYLBENZENE (CUMENE)
1.00 BRC10PAR	0.00	2, 2-DM-OCTANE	2, 2-DIMETHYLOCTANE
1.00 BRC10PAR	0.00	2, 4-DM-OCTANE	2, 4-DIMETHYLOCTANE
1.00 N-PBEN	0.00	N-PROPBENZENE	N-PROPYLBENZENE
1.00 C9BEN2	0.00	1M-3E-BENZENE	1-METHYL-3-ETHYLBENZENE
1.00 C9BEN2	0.00	1M-4E-BENZENE	1-METHYL-4-ETHYLBENZENE
1.00 135TMBEN	0.00	1, 3, 5-TM-BENZENE	1, 3, 5-TRIMETHYLBENZENE
1.00 C9BEN2	0.00	1E-2M-BENZENE	1-ETHYL-2-METHYLBENZENE
1.00 124TMBEN	0.00	1, 2, 4-TM-BENZENE	1, 2, 4-TRIMETHYLBENZENE
1.00 DECANE	0.00	DECANE	N-DECANE
1.00 S-BBEN	0.00	S-BUTBENZENE	S-BUTYLBENZENE
1.00 C11BEN2	0.00	1M-4-I-BUTBENZENE	1-METHYL-4-ISOBUTYLBENZENE
1.00 123TMBEN	0.00	1, 2, 3-TM-BENZENE	1, 2, 3-TRIMETHYLBENZENE
1.00 INDAN	0.00	INDAN	INDAN
1.00 C10BEN2	0.00	1, 3-DE-BENZENE	1, 3-DIETHYLBENZENE
1.00 C10BEN2	0.00	1, 4-DE-BENZENE	1, 4-DIETHYLBENZENE
1.00 C10BEN1	0.00	NBUTBENZENE	N-BUTYLBENZENE
1.00 C10BEN2	0.00	1, 2-DE-BENZENE	1, 2-DIETHYLBENZENE
1.00 UNDECANE	0.00	UNDECANE	N-UNDECANE
1.00 C10BEN4	0.00	1, 2, 4, 5-TETMBENZENE	1, 2, 4, 5-TETRAMETHYLBENZENE

05519

1.00	C10BEN4	0.00	0.00	1,2,3,5-TETMBENZENE
1.00	C10BEN4	0.00	0.00	1,2,3,4-TETMBENZENE
1.00	NAPHTHAL	0.00	0.00	NAPHTHALENE
1.00	DODECANE	0.00	0.00	N-DODECANE
1.00	FORMALD	0.00	0.00	FORMALDEHYDE
1.00	ACETALD	0.00	0.00	ACETALDEHYDE
1.00	ACROLEIN	0.00	0.00	ACROLEIN
1.00	ACETONE	0.00	0.00	ACETONE
1.00	PROPALD	0.00	0.00	PROPIONALDEHYDE
1.00	CROTALD	0.00	0.00	CROTONALDEHYDE
1.00	C4ALD	0.00	0.00	N-BUTYRALDEHYDE
1.00	C4KET	0.00	0.00	BUTANONE
1.00	BENZALD	0.00	0.00	BENZALDEHYDE
1.00	C5ALD	0.00	0.00	PENTANALDEHYDE
1.00	BENZALD	0.00	0.00	P-TOLUALDEHYDE
Assume similar to benzaldehyde				
1.00	C6ALD	0.00	0.00	HEXANALDEHYDE
1.00	METHANOL	0.00	0.00	METHANOL
1.00	UNID	0.00	0.00	UNIDENTIFIED
Unknown reactivity				
TOTAL UNCAL SPECIES				

ARB Organic Gas Names and ID Assignments - 12/15/92

Frac OGID1	Frac OGID2	Frac OGID3	Organic Gas Name	
1.00 ETHANE	0.00	0.00	Ethane	
1.00 ETHENE	0.00	0.00	Ethene	
1.00 PROPANE	0.00	0.00	Propane	
1.00 ETHYNE	0.00	0.00	Ethyne	
1.00 2MC3	0.00	0.00	Methylpropane	
1.00 BUTANE	0.00	0.00	Butane	
1.00 PROPENE	0.00	0.00	Propene	
1.00 2MC4	0.00	0.00	Methylbutane	
1.00 PENTANE	0.00	0.00	Pentane	
1.00 1C4=	0.00	0.00	1-Butene	
1.00 2MC3=	0.00	0.00	2-Methylpropene	
1.00 T-2C4=	0.00	0.00	t-2-Butene	
1.00 1BUTYNE	0.00	0.00	1-Butyne	
1.00 C-2C4=	0.00	0.00	c-2-Butene	
1.00 3M1C4=	0.00	0.00	3-Methyl-1-butene	
1.00 2MC4	0.00	0.00	2-Methylbutane	
1.00 1C5=	0.00	0.00	1-Pentene	
1.00 2M1C4=	0.00	0.00	2-Methyl-1-butene	
1.00 13C4==	0.00	0.00	1,3-butadiene	
1.00 ISOPRENE	0.00	0.00	2-Methyl-1,3-butadiene	
1.00 C5OLE2	0.00	0.00	t-2-Pentene	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene	Average of terminal and internal C6
alkenes				
1.00 C5OLE2	0.00	0.00	c-2-Pentene	
1.00 2M2C4=	0.00	0.00	2-Methyl-2-butene	
1.00 22DMC4	0.00	0.00	2,2-Dimethylbutane	
1.00 CYC5=	0.00	0.00	Cyclopentene	
1.00 C6OLE1	0.00	0.00	4-Methyl-1-pentene	
1.00 CYC5	0.00	0.00	Cyclopentane	
1.00 23DMC4	0.00	0.00	2,3-Dimethylbutane	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene 1	Average of terminal and internal C6
alkenes				
1.00 2MC5	0.00	0.00	2-Methylpentane	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene 2	Average of terminal and internal C6
alkenes				
1.00 3MC5	0.00	0.00	3-Methylpentane	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene 3	Average of terminal and internal C6
alkenes				
1.00 HEXANE	0.00	0.00	n-Hexane	
1.00 C6OLE2	0.00	0.00	3-Hexene	
1.00 C6OLE2	0.00	0.00	t-2-Hexene	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene 4	Average of terminal and internal C6
alkenes				

05521

1.00 C6OLE2	0.00	0.00	0.00
1.00 C6OLE2	0.00		0.00
0.50 C6OLE1	0.50 C6OLE2		0.00
alkenes			
1.00 MCYC5	0.00		0.00
0.50 C6OLE1	0.50 C6OLE2		0.00
alkenes			
1.00 24DMC5	0.00		0.00
1.00 BRC7PAR	0.00		0.00
1.00 BENZENE	0.00		0.00
1.00 C7OLE1	0.00		0.00
1.00 CYC6	0.00		0.00
1.00 C7OLE2	0.00		0.00
1.00 2MC6	0.00		0.00
1.00 BRC7PAR	0.00		0.00
1.00 CYC6=	0.00		0.00
1.00 3MC6	0.00		0.00
0.50 C7OLE1	0.50 C7OLE2		0.00
alkenes			
1.00 CYC7PAR	0.00		0.00
1.00 224TMC5	0.00		0.00
GC/MS			
1.00 HEPTANE	0.00		0.00
1.00 CYC6=	0.00		0.00
1.00 MCYC6	0.00		0.00
1.00 CYC8PAR	0.00		0.00
1.00 BRC8PAR	0.00		0.00
1.00 BRC8PAR	0.00		0.00
1.00 CYC8PAR	0.00		0.00
1.00 234TMC5	0.00		0.00
1.00 TOLUENE	0.00		0.00
1.00 23DMC6	0.00		0.00
1.00 BRC8PAR	0.00		0.00
1.00 UNID	0.00		0.00
1.00 CYC8PAR	0.00		0.00
1.00 225TMC6	0.00		0.00
1.00 CYC8PAR	0.00		0.00
1.00 OCTANE	0.00		0.00
1.00 CYC8PAR	0.00		0.00
1.00 BRC9PAR	0.00		0.00
1.00 UNID	0.00		0.00
1.00 CYC6=	0.00		0.00
1.00 BRC9PAR	0.00		0.00
0.50 C9OLE1	0.50 C9OLE2		0.00
alkenes			
1.00 EBEN	0.00		0.00

05522

c-2-hexene	
c-2-Hexene	
C6H12 Alkene 5	Average of terminal and internal C6
Methylcyclopentane	
C6H12 Alkene 6	Average of terminal and internal C6
2, 4-Dimethylpentane	
C7H16 Alkane	Assume branched C7 alkane
Benzene	
3-Methyl-1-hexene	
Cyclohexane	
2-Methyl-3-hexene	
4-Methyl-2-hexene	
2-Methylhexane	
2-Methylhexane +Dimethylpentane	
C6H10 Cycloalkene	Assume cyclohexene
3-Methylhexane	
C7H14 Alkene	Average of terminal and internal C7
Dimethylcyclopentane	
2,2,4-Trimethylpentane + Alkene	100% 2,2,4-trimethylpentane based on
n-Heptane	
C7H12? Cycloalkene	Assume similar to cyclohexene
Methylcyclohexane	
Trimethylcyclopentane	
Dimethylhexane	
C8H18 Alkane	Assume branched C8 alkane
Trimethylcyclopentane 1	
2,3,4-Trimethylpentane	
Toluene + C8H18	Assume 100% toluene
2,3-Dimethylhexane	
Methylheptane	
Unidentified 1	Unknown reactivity
Dimethylcyclohexane	
2,2,5-Trimethylhexane	
Ethylmethylcyclopentane	
n-Octane	
C8H16 Cycloalkane	
2,3,5-Trimethylhexane	
NNDime-acetamide	
C8H14? Cycloalkene	Unknown reactivity
Dimethylheptane	Assume similar to cyclohexene
C9H18 Alkene	Average of terminal and internal C9
Ethylbenzene	

1.00	CYC9PAR	0.00	Trimethylcyclohexane	
0.50	M-XYL	0.50	m & p-Xylenes	Average of m & p-xylenes
1.00	BRC9PAR	0.00	C9H20 Alkane	Assume branched C9 alkane
1.00	STYRENE	0.00	Styrene	
1.00	BRC10PAR	0.00	Trimethylheptane	
1.00	O-XYL	0.00	o-Xylene	
1.00	BRC10PAR	0.00	C10H22 Alkane 1	Assume branched C10 alkane
0.50	C9OLE1	0.50	C9H18 Alkene 1	Average of terminal and internal C9
	alkenes			
1.00	NONANE	0.00	n-Nonane	
1.00	CYC9PAR	0.00	Ethylmethylcyclohexane	
1.00	I-PBEN	0.00	i-Propylbenzene	
1.00	BRC10PAR	0.00	C10H22 Alkane 2	Assume branched C10 alkane
1.00	BRC10PAR	0.00	Dimethyloctane	
1.00	N-PBEN	0.00	n-Propylbenzene	
1.00	C9BEN2	0.00	3-Ethyltoluene	
1.00	C9BEN2	0.00	4-Ethyltoluene + C10cycloalkane	100% C9 dialkyl benzenes based on GC/MS
1.00	135TMBEN	0.00	1,3,5-Trimethylbenzene	
1.00	BRC10PAR	0.00	C10H22 Alkane 3	Assume branched C10 alkane
1.00	C9BEN2	0.00	2-Ethyltoluene	
1.00	BRC10PAR	0.00	C10H22 Alkane 4	Assume branched C10 alkane
1.00	124TMBEN	0.00	1,2,4-Trimethylbenzene	
1.00	DECANE	0.00	n-Decane	
1.00	UNDECANE	0.00	n-Undecane	
0.50	C10BEN1	0.35	C10H14 Aromatic	Assume 50% C10 monoalkyl, 35% dialkyl
	and 15% trialkyl benzenes			
1.00	METHANOL	0.00	Methanol	
1.00	ETHANOL	0.00	Ethanol	
1.00	FORMALD	0.00	Formaldehyde	
1.00	ACETALD	0.00	Acetaldehyde	
1.00	ACROLEIN	0.00	Acrolein	
1.00	ACETONE	0.00	Acetone	
1.00	PROPALD	0.00	Propionaldehyde	
1.00	C4ALD	0.00	Butylaldehyde	
1.00	BENZALD	0.00	Benzylaldehyde	

ARB92 Organic Gas Names and ID Assignments - 12/15/92

Frac OGID1	Frac OGID2	Frac OGID3	Organic Gas Name	
1.00 ETHANE	0.00	0.00	Ethane	
1.00 ETHENE	0.00	0.00	Ethene	
1.00 PROPANE	0.00	0.00	Propane	
1.00 ETHYNE	0.00	0.00	Ethyne	
1.00 2MC3	0.00	0.00	Methylpropane	
1.00 BUTANE	0.00	0.00	Butane	
1.00 PROPENE	0.00	0.00	Propene	
1.00 2MC4	0.00	0.00	Methylbutane	
1.00 PENTANE	0.00	0.00	Pentane	
1.00 1C4=	0.00	0.00	1-Butene	
1.00 2MC3=	0.00	0.00	2-Methylpropene	
1.00 T-2C4=	0.00	0.00	t-2-Butene	
1.00 1BUTYNE	0.00	0.00	1-Butyne	
1.00 C-2C4=	0.00	0.00	c-2-Butene	
1.00 3M1C4=	0.00	0.00	3-Methyl-1-butene	
1.00 2MC4	0.00	0.00	2-Methylbutane	
1.00 1C5=	0.00	0.00	1-Pentene	
1.00 2M1C4=	0.00	0.00	2-Methyl-1-butene	
1.00 13C4=	0.00	0.00	1-3-Butadiene	
1.00 ISOPRENE	0.00	0.00	2-Methyl-1-3-butadiene	
1.00 C5OLE2	0.00	0.00	t-2-Pentene	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene	Average of terminal and internal C6
alkenes				
1.00 C5OLE2	0.00	0.00	c-2-Pentene	
1.00 2M2C4=	0.00	0.00	2-Methyl-2-butene	
1.00 22DMC4	0.00	0.00	2-2-Dimethylbutane	
1.00 CYC5=	0.00	0.00	Cyclopentene	
1.00 C6OLE1	0.00	0.00	4-Methyl-1-pentene	
1.00 CYC5	0.00	0.00	Cyclopentane	
1.00 23DMC4	0.00	0.00	2-3-Dimethylbutane	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene 1	Average of terminal and internal C6
alkenes				
1.00 2MC5	0.00	0.00	2-Methylpentane	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene 2	Average of terminal and internal C6
alkenes				
1.00 3MC5	0.00	0.00	3-Methylpentane	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene 3	Average of terminal and internal C6
alkenes				
1.00 HEXANE	0.00	0.00	n-Hexane	
1.00 C6OLE2	0.00	0.00	3-Hexene	
1.00 C6OLE2	0.00	0.00	t-2-Hexene	
0.50 C6OLE1	0.50 C6OLE2	0.00	C6H12 Alkene 4	Average of terminal and internal C6
alkenes				

1.00 C6OLE2	0.00	c-2-hexene	Average of terminal and internal C6
1.00 C6OLE2	0.00	c-2-Hexene	
0.50 C6OLE1	0.50 C6OLE2	C6H12 Alkene 5	
alkenes			
1.00 MCYC5	0.00	Methylcyclopentane	Average of terminal and internal C6
0.50 C6OLE1	0.50 C6OLE2	C6H12 Alkene 6	
alkenes			
1.00 24DMC5	0.00	2-4-Dimethylpentane	Assume branched C7 alkane
1.00 BRC7PAR	0.00	C7H16 Alkane	
1.00 BENZENE	0.00	Benzene	
1.00 C7OLE1	0.00	3-Methyl-1-hexene	
1.00 CYC6	0.00	Cyclohexane	
1.00 C7OLE2	0.00	2-Methyl-3-hexene	
1.00 C7OLE2	0.00	4-Methyl-2-hexene	
1.00 2MC6	0.00	2-Methylhexane	
1.00 BRC7PAR	0.00	2-Methylhexane +Dimethylpentane	
1.00 CYC6=	0.00	C6H10 Cycloalkene	Assume cyclohexene
1.00 3MC6	0.00	3-Methylhexane	Average of terminal and internal C7
0.50 C7OLE1	0.50 C7OLE2	C7H14 Alkene	
alkenes			
1.00 CYC7PAR	0.00	Dimethylcyclopentane	
1.00 224TMC5	0.00	2-2-4-Trimethylpentane + Alkene	100% 2,2,4-trimethylpentane based on GC/MS
1.00 HEPTANE	0.00	n-Heptane	
1.00 CYC6=	0.00	C7H12? Cycloalkene	Assume similar to cyclohexene
1.00 MCYC6	0.00	Methylcyclohexane	
1.00 CYC8PAR	0.00	Trimethylcyclopentane	
1.00 BRC8PAR	0.00	Dimethylhexane	
1.00 BRC8PAR	0.00	C8H18 Alkane	Assume branched C8 alkane
1.00 CYC8PAR	0.00	Trimethylcyclopentane 1	
1.00 234TMC5	0.00	2-3-4-Trimethylpentane	
1.00 TOLUENE	0.00	Toluene + C8H18	Assume 100% toluene
1.00 23DMC6	0.00	2-3-Dimethylhexane	
1.00 BRC8PAR	0.00	Methylheptane	Unknown reactivity
1.00 UNID	0.00	Unidentified 1	
1.00 CYC8PAR	0.00	Dimethylcyclohexane	
1.00 225TMC6	0.00	2-2-5-Trimethylhexane	
1.00 CYC8PAR	0.00	Ethylmethylcyclopentane	
1.00 OCTANE	0.00	n-Octane	
1.00 CYC8PAR	0.00	C8H16 Cycloalkane	Unknown reactivity
1.00 BRC9PAR	0.00	2-3-5-Trimethylhexane	Assume similar to cyclohexene
1.00 UNID	0.00	NNDime-acetamide	
1.00 CYC6=	0.00	C8H14? Cycloalkene	
1.00 BRC9PAR	0.00	Dimethylheptane	
0.50 C9OLE1	0.50 C9OLE2	C9H18 Alkene	Average of terminal and internal C9
alkenes			
1.00 EBEN	0.00	Ethylbenzene	

Chevron Organic Gas Names and ID Assignments - 11/13/92

Frac OGID1	Frac OGID2	Frac OGID3	Organic Gas Name
1.00 ETHENE	0.00	0.00	Ethylene
1.00 ETHYNE	0.00	0.00	Acetylene
1.00 ETHANE	0.00	0.00	Ethane
1.00 PROPENE	0.00	0.00	Propylene
1.00 PROPANE	0.00	0.00	Propane
1.00 ETHENE	0.00	0.00	Allene
1.00 PROPYNE	0.00	0.00	Propyne
1.00 2MC3	0.00	0.00	2-Me-Propane
0.50 1C4=	0.50 2MC3=	0.00	1-Butene/i-Butene
1.00 13C4==	0.00	0.00	1,3-Butadiene
1.00 BUTANE	0.00	0.00	n-Butane
1.00 METHANOL	0.00	0.00	Methanol
1.00 T-2C4=	0.00	0.00	t-2-Butene
1.00 C-2C4=	0.00	0.00	c-2-Butene
1.00 ETHANOL	0.00	0.00	Ethanol
1.00 3M1C4=	0.00	0.00	3-Me-1-Butene
1.00 2MC4	0.00	0.00	2-Me-Butane
1.00 1C5=	0.00	0.00	1-Pentene
1.00 2M1C4=	0.00	0.00	2-Me-1-Butene
1.00 PENTANE	0.00	0.00	n-Pentane
1.00 C5OLE2	0.00	0.00	t-2-Pentene
1.00 C5OLE2	0.00	0.00	c-2-Pentene
1.00 2M2C4=	0.00	0.00	2-Me-2-Butene
1.00 22DMC4	0.00	0.00	2,2-Di-Me-Butane
1.00 CYC5=	0.00	0.00	Cyclopentene
1.00 C6OLE1	0.00	0.00	4-Me-1-Pentene/
1.00 CYC5	0.00	0.00	Cyclopentane
1.00 23DMC4	0.00	0.00	2,3-Di-Me-Butane
1.00 MTBE	0.00	0.00	MTBE
1.00 2MC5	0.00	0.00	2-Me-Pentane
1.00 3MC5	0.00	0.00	3-Me-Pentane
1.00 1C6=	0.00	0.00	1-Hexene/
1.00 HEXANE	0.00	0.00	n-Hexane
1.00 C6OLE2	0.00	0.00	t-2-Hexene
1.00 C6OLE2	0.00	0.00	3-Me-t-2-Pentene
1.00 C6OLE2	0.00	0.00	2-Me-2-Pentene
1.00 C6OLE2	0.00	0.00	c-2-Hexene
1.00 C6OLE2	0.00	0.00	3-Me-c-2-Pentene
1.00 MCYC5	0.00	0.00	Me-Cyclopentane
1.00 24DMC5	0.00	0.00	2,4-Di-Me-Pentane
1.00 CYC6=	0.00	0.00	1-Me-Cyclopentene
1.00 BENZENE	0.00	0.00	Benzene
1.00 CYC6	0.00	0.00	Cyclohexane

Assume similar to ethene

Average of 1-butene and 2-methylpropene

Assume similar to cyclohexene

1.00	2MC6	0.00	2-Me-Hexane
1.00	23DMC5	0.00	2,3-Di-Me-Pentane
1.00	3MC6	0.00	3-Me-Hexane
1.00	13DMCYC5	0.00	c-1,3-Di-Me-Cypenta
1.00	13DMCYC5	0.00	t-1,3-Di-Me-Cypenta
1.00	224TMC5	0.00	224-Tri-Me-Pentane
1.00	HEPTANE	0.00	n-Heptane
1.00	MCYC6	0.00	Me-Cyclohexane
1.00	25DMC6	0.00	2,5-Di-Me-Hexane
1.00	24DMC6	0.00	2,4-Di-Me-Hexane
1.00	CYC8PAR	0.00	124-Tri-Me-Cypentan
1.00	234TMC5	0.00	234-Tri-Me-Pentane
1.00	BRC8PAR	0.00	233-Tri-Me-Pentane
1.00	TOLUENE	0.00	Toluene
1.00	23DMC6	0.00	2,3-Di-Me-Hexane
1.00	2MC7	0.00	2-Me-Heptane
1.00	3MC7	0.00	3-Me-Heptane
1.00	225TMC6	0.00	225-Tri-Me-Hexane
1.00	OCTANE	0.00	n-Octane
1.00	BRC9PAR	0.00	244-Tri-Me-Hexane
1.00	BRC9PAR	0.00	235-Tri-Me-Hexane
1.00	24DMC7	0.00	2,4-Di-Me-Heptane
1.00	BRC9PAR	0.00	3,5-Di-Me-Heptane
1.00	EBEN	0.00	Ethyl-Benzene
1.00	M-XYL	0.00	m-Xylene
1.00	P-XYL	0.00	p-Xylene
1.00	BRC9PAR	0.00	2-Me-Octane
1.00	BRC9PAR	0.00	3-Me-Octane
1.00	STYRENE	0.00	Styrene
1.00	O-XYL	0.00	o-Xylene
1.00	NONANE	0.00	n-Nonane
1.00	I-PBEN	0.00	Cumene
1.00	N-PBEN	0.00	n-Propyl Benzene
1.00	C9BEN2	0.00	1-Et-3-Me-Benzene
1.00	C9BEN2	0.00	1-Et-4-Me-Benzene
1.00	135TMBEN	0.00	135-Tri-Me-Benzene
1.00	BRC10PAR	0.00	4-Me-Nonane
1.00	C9BEN2	0.00	1-Et-2-Me-Benzene
1.00	BRC10PAR	0.00	3-Me-Nonane
1.00	124TMBEN	0.00	124-Tri-Me-Benzene
1.00	DECANE	0.00	n-Decane
1.00	123TMBEN	0.00	123-Tri-Me-Benzene
1.00	INDAN	0.00	Indan
1.00	C10BEN2	0.00	1,3-Di-Et-Benzene
1.00	C10BEN2	0.00	1-Me-3-Pr-Benzene
1.00	C10BEN2	0.00	1,2-Di-Et-Benzene
1.00	C10BEN2	0.00	1-Me-2-Pr-Benzene

1.00	C10BEN3	0.00	1, 4-Di-Me-2-Et-Benz	
1.00	C10BEN3	0.00	1, 3-Di-Me-4-Et-Benz	
1.00	C10BEN3	0.00	1, 2-Di-Me-4-Et-Benz	
1.00	C10BEN3	0.00	1, 3-Di-Me-2-Et-Benz	
1.00	UNDECANE	0.00	n-Undecane	
1.00	C10BEN4	0.00	1245-Tet-Me-Benzene	
1.00	C10BEN4	0.00	1235-Tet-Me-Benzene	
1.00	INDAN	0.00	Methyl-Indane A	Assume similar to indan
1.00	INDAN	0.00	Methyl-Indane B	Assume similar to indan
1.00	NAPHTHAL	0.00	Naphthalene	
1.00	DODECANE	0.00	Dodecane	
1.00	UNID	0.00	Unidentified HC	Unknown reactivity
1.00	FORMALD	0.00	Formaldehyde	
1.00	ACETALD	0.00	Acetaldehyde	
1.00	ACROLEIN	0.00	Acrolein	
1.00	ACETONE	0.00	Acetone	
1.00	PROPALD	0.00	Propionaldehyde	
1.00	CROTALD	0.00	Crotonaldehyde	
1.00	C4ALD	0.00	Butyraldehyde	
1.00	C4KET	0.00	Methyl Ethyl Ketone	
1.00	BENZALD	0.00	Benzaldehyde	
1.00	C5ALD	0.00	Pentanaldehyde	
1.00	BENZALD	0.00	Tolualdehyde	
1.00	C6ALD	0.00	Hexanaldehyde	Assume similar to benzaldehyde

Appendix B

OGIDs and Reactivity Assignments

B-3

Appendix C

Transitional Low Emitting Vehicle Profiles

California Air Resources Board Transitional Low Emitting Vehicle (TLEV) Profiles - November 13, 1992

Federal Test Procedure (FTP) weight fractions and mass in grams/mile

All standard deviations (SD) in percent

OGID	SAROAD	U. S. National Average Gasoline (RF-A)			85% Methanol/15% RF-A (M85/RF-A)			Phase 2 Gasoline (Phase 2)		
		Bag 1	SD	Comp	Bag 1	SD	Comp	Bag 1	SD	Comp
MASS		0.3659	6	0.0266	15	0.0549	10	0.1047	6	1.1006
ETHANE	43202	0.0245	10	0.0841	27	0.0874	20	0.0399	14	0.0013
PROPANE	43204	0.0025	50	0.0061	68	0.0053	30	0.0033	37	0.0001
BUTANE	43212	0.0405	7	0.0430	33	0.0692	20	0.0442	10	0.0064
PENTANE	43220	0.0264	9	0.0202	31	0.0345	18	0.0268	12	0.0029
HEXANE	43231	0.0187	26	0.0199	19	0.0183	13	0.0119	31	0.0000
HEPTANE	43232	0.0119	11	0.0168	33	0.0138	20	0.0129	13	0.0008
OCTANE	43233	0.0061	7	0.0010	79	0.0028	38	0.0050	7	0.0001
NONANE	43235	0.0022	55	0.0000	0	0.0006	116	0.0016	50	0.0000
DECANE	43238	0.0004	132	0.0013	136	0.0000	0	0.0006	91	0.0000
UNDECANE	43241	0.0010	38	0.0000	0	0.0000	0	0.0007	38	0.0001
2M3	43214	0.0057	60	0.0024	48	0.0026	30	0.0049	54	0.0000
2M4	98132	0.0378	9	0.0481	25	0.0625	18	0.0429	11	0.0037
2M5	43229	0.0266	17	0.0250	37	0.0364	19	0.0282	18	0.0024
3M5	43230	0.0154	16	0.0194	33	0.0229	18	0.0172	15	0.0012
22DMC4	43291	0.0076	24	0.0026	88	0.0058	45	0.0069	24	0.0005
23DMC4	98001	0.0115	23	0.0086	41	0.0140	28	0.0117	22	0.0004
2M6	43275	0.0037	71	0.0027	104	0.0034	100	0.0036	75	0.0000
3M6	43295	0.0133	9	0.0218	30	0.0198	24	0.0153	11	0.0011
23DMC5	43274	0.0013	100	0.0000	0	0.0000	0	0.0010	100	0.0000
24DMC5	43271	0.0017	64	0.0016	107	0.0012	101	0.0016	66	0.0001
BRCPAR	43106	0.0258	25	0.0372	33	0.0362	26	0.0286	24	0.0024
2M7	98140	0.0014	73	0.0009	101	0.0014	100	0.0014	77	0.0001
3M7	43298	0.0020	66	0.0013	103	0.0015	101	0.0019	67	0.0001
24DMC6	98139	0.0033	15	0.0018	120	0.0020	40	0.0030	18	0.0000
25DMC6	43277	0.0012	66	0.0007	120	0.0008	101	0.0008	66	0.0000
24TMC5	43278	0.0009	66	0.0006	101	0.0007	101	0.0007	67	0.0000
24TMC5	43276	0.0061	66	0.0125	73	0.0108	66	0.0076	66	0.0000
24TMC5	43279	0.0085	11	0.0104	35	0.0137	22	0.0093	11	0.0011
BRCPAR	43107	0.0300	23	0.0399	25	0.0367	23	0.0322	22	0.0021
24DMC7	98142	0.0001	101	0.0001	155	0.0001	101	0.0001	101	0.0000
22TMC6	98033	0.0037	10	0.0005	106	0.0016	60	0.0047	32	0.0000
BRCPAR	43108	0.0040	18	0.0063	121	0.0039	86	0.0047	107	0.0002
BRCPAR	43109	0.0006	107	0.0000	0	0.0000	0	0.0004	107	0.0000
CYC5	43242	0.0010	78	0.0000	0	0.0004	111	0.0009	76	0.0004
CYC5	43248	0.0015	71	0.0115	87	0.0022	114	0.0034	67	0.0000
MCYC5	43262	0.0074	9	0.0037	67	0.0068	27	0.0071	10	0.0007
MCYC6	43261	0.0052	17	0.0039	58	0.0021	48	0.0046	18	0.0001
13DMCYC5	90064	0.0004	100	0.0011	103	0.0007	105	0.0005	100	0.0000
CYC8PAR	43116	0.0072	24	0.0019	67	0.0085	29	0.0067	23	0.0003
CYC10PAR	98066	0.0023	32	0.0009	93	0.0002	88	0.0018	34	0.0002
ETHENE	43203	0.0595	9	0.0303	34	0.0766	26	0.0880	10	0.0084
PROPENE	43205	0.0368	10	0.0078	43	0.0168	17	0.0306	10	0.0045
1C4	43213	0.0063	12	0.0018	37	0.0036	29	0.0053	11	0.0003
2M3	43215	0.0184	20	0.0051	35	0.0096	30	0.0054	18	0.0020
1C5	43224	0.0015	96	0.0016	155	0.0000	0	0.0014	86	0.0000
2M1C4	43225	0.0002	103	0.0000	0	0.0000	0	0.0001	102	0.0000
3M1C4	43223	0.0001	104	0.0000	0	0.0000	0	0.0001	104	0.0000
1C6	43245	0.0002	101	0.0005	124	0.0002	112	0.0002	105	0.0000
C9OLE1	43245	0.0022	46	0.0000	0	0.0009	92	0.0018	45	0.0000
C7OLE1	98005	0.0000	0	0.0000	0	0.0000	0	0.0000	0	0.0000
C9OLE1	43265	0.0070	24	0.0173	27	0.0106	25	0.0088	24	0.0007
C9OLE1	43267	0.0005	40	0.0000	0	0.0000	0	0.0003	39	0.0000

Appendix D

Low Emitting Vehicle Profiles

California Air Resources Board Low Emitting Vehicle (LEV) Profiles - November 13, 1992

Federal Test Procedure (FTP) weight fractions and mass in grams/mile

All standard deviations (SD) in percent

OGID	SAROAD	--- U. S. National Average Gasoline (RF-A)			----			----- Phase 2 Gasoline (Phase 2)			-----						
		Bag 1	SD	Bag 2	SD	Comp	SD	Bag 1	SD	Bag 2	SD	Bag 3	SD	Comp	SD		
MASS		0.2453	10	0.0100	18	0.0252	24	0.0605	5	0.2254	10	0.0120	31	0.0225	19	0.0547	11
ETHANE	43202	0.0316	16	0.0941	30	0.1252	21	0.0450	13	0.0341	16	0.0435	26	0.1151	20	0.0450	14
PROPANE	43204	0.0018	16	0.0068	34	0.0080	82	0.0030	31	0.0104	97	0.0472	82	0.0110	72	0.0121	80
BUTANE	43212	0.0486	11	0.0559	15	0.0651	24	0.0516	11	0.0096	17	0.0303	32	0.0220	32	0.0131	15
PENTANE	43220	0.0302	11	0.0348	19	0.0303	24	0.0312	11	0.0095	10	0.0326	97	0.0071	26	0.0127	36
HEXANE	43231	0.0266	7	0.0198	93	0.0161	38	0.0260	9	0.0090	8	0.0030	88	0.0028	37	0.0083	8
HEPTANE	43232	0.0148	4	0.0045	57	0.0095	31	0.0142	5	0.0115	7	0.0049	48	0.0071	30	0.0115	7
OCTANE	43233	0.0074	10	0.0023	130	0.0056	40	0.0075	9	0.0051	6	0.0000	0	0.0020	55	0.0048	8
NONANE	43235	0.0030	16	0.0000	0	0.0000	0	0.0025	16	0.0015	27	0.0029	117	0.0002	145	0.0016	29
DECANE	43238	0.0008	39	0.0000	0	0.0007	149	0.0008	43	0.0008	22	0.0011	166	0.0002	145	0.0008	21
UNDECANE	43241	0.0010	24	0.0100	122	0.0000	0	0.0024	87	0.0005	77	0.0000	0	0.0000	0	0.0005	78
2MC3	43214	0.0013	12	0.0025	57	0.0016	36	0.0015	15	0.0034	107	0.0065	35	0.0038	41	0.0039	81
2MC4	98132	0.0442	9	0.0932	27	0.0558	28	0.0495	12	0.0792	8	0.0831	34	0.0886	22	0.0856	5
2MC5	43229	0.0524	8	0.0133	50	0.0371	27	0.0500	8	0.0334	8	0.0137	46	0.0172	28	0.0325	8
3MC5	43230	0.0251	8	0.0084	41	0.0218	22	0.0246	9	0.0150	7	0.0088	60	0.0098	34	0.0152	11
22DMC4	43291	0.0087	31	0.0055	91	0.0100	47	0.0091	31	0.0032	55	0.0014	89	0.0024	60	0.0031	54
23DMC4	98001	0.0178	11	0.0058	47	0.0125	36	0.0172	11	0.0375	18	0.0231	38	0.0143	44	0.0360	16
3MC6	43295	0.0150	10	0.0025	53	0.0122	31	0.0144	9	0.0154	5	0.0053	55	0.0097	28	0.0152	5
24DMC5	43271	0.0002	121	0.0000	0	0.0000	0	0.0002	121	0.0002	78	0.0000	0	0.0000	0	0.0001	78
BRC7PAR	43106	0.0400	7	0.0054	60	0.0323	28	0.0383	6	0.0745	5	0.0305	31	0.0549	24	0.0747	5
23DMC6	98139	0.0053	8	0.0015	130	0.0013	93	0.0049	11	0.0083	7	0.0000	0	0.0063	35	0.0080	9
234TMC5	43279	0.0043	41	0.0013	130	0.0038	51	0.0042	41	0.0064	51	0.0038	80	0.0035	68	0.0061	52
BRC8PAR	43107	0.0450	5	0.0363	62	0.0427	17	0.0474	8	0.0772	6	0.0287	30	0.0666	22	0.0780	6
225TMC6	98033	0.0053	9	0.0045	130	0.0043	59	0.0058	17	0.0098	6	0.0011	117	0.0086	28	0.0097	8
BRC9PAR	43108	0.0070	20	0.0007	130	0.0039	50	0.0065	22	0.0047	12	0.0027	94	0.0025	72	0.0048	16
BRC10PAR	43109	0.0000	0	0.0000	0	0.0000	0	0.0000	0	0.0002	79	0.0000	0	0.0003	145	0.0002	82
CYC6	43248	0.0022	9	0.0001	155	0.0008	88	0.0019	11	0.0007	27	0.0035	143	0.0000	179	0.0011	55
MCYC5	43262	0.0095	7	0.0047	70	0.0063	40	0.0091	10	0.0045	10	0.0021	71	0.0009	54	0.0042	12
MCYC6	43261	0.0065	6	0.0057	130	0.0016	64	0.0067	18	0.0029	12	0.0010	127	0.0013	88	0.0028	15
CYC8PAR	43116	0.0074	22	0.0037	83	0.0107	26	0.0082	20	0.0034	26	0.0011	179	0.0054	39	0.0037	19
CYC10PAR	98066	0.0051	30	0.0049	80	0.0033	61	0.0050	28	0.0020	25	0.0024	87	0.0017	103	0.0022	27
ETHENE	43203	0.0519	7	0.0355	30	0.0217	37	0.0490	8	0.0573	14	0.0233	27	0.0220	33	0.0536	13
PROPENE	43205	0.0259	5	0.0121	23	0.0119	41	0.0244	6	0.0367	14	0.0178	26	0.0134	33	0.0345	12
1C4=	43213	0.0042	9	0.0018	49	0.0015	38	0.0039	10	0.0045	19	0.0039	33	0.0017	26	0.0043	16
2MC3=	43215	0.0118	21	0.0080	27	0.0097	40	0.0118	22	0.0364	11	0.0321	43	0.0214	27	0.0367	12
2M1C4=	43225	0.0002	122	0.0000	0	0.0000	0	0.0002	123	0.0000	0	0.0000	0	0.0000	0	0.0000	0
C6OLE1	43245	0.0044	43	0.0000	0	0.0021	97	0.0039	44	0.0031	11	0.0020	126	0.0000	0	0.0028	15

C7OLE1	98005	0.0023	112	0.0003	93	0.0003	155	0.0016	102	0.0002	48	0.0060	142	0.0000	0	0.0005	77
C8OLE1	43265	0.0096	4	0.0039	44	0.0101	31	0.0095	5	0.0241	5	0.0109	30	0.0224	21	0.0247	5
C9OLE1	43267	0.0008	19	0.0010	130	0.0002	130	0.0009	32	0.0008	19	0.0004	117	0.0002	117	0.0008	21
C5OLE2	43226	0.0015	84	0.0000	0	0.0042	155	0.0015	87	0.0000	0	0.0000	0	0.0000	0	0.0000	0
C6OLE2	43246	0.0072	27	0.0000	0	0.0257	142	0.0090	48	0.0045	9	0.0012	179	0.0000	0	0.0000	10
C8OLE2	43266	0.0096	4	0.0039	44	0.0101	31	0.0095	5	0.0241	5	0.0109	30	0.0224	21	0.0247	5
C9OLE2	98042	0.0008	19	0.0010	130	0.0002	130	0.0009	32	0.0008	19	0.0004	117	0.0002	117	0.0008	21
13C4=	43218	0.0034	11	0.0011	69	0.0013	64	0.0031	11	0.0028	16	0.0030	39	0.0017	57	0.0029	19
CYC5=	43292	0.0001	155	0.0000	0	0.0014	121	0.0002	136	0.0000	0	0.0005	179	0.0000	0	0.0001	179
ETHYNE	43206	0.0275	47	0.0117	47	0.0009	61	0.0243	49	0.0236	24	0.0124	31	0.0020	80	0.0220	25
BENZENE	45201	0.0490	8	0.0344	62	0.0674	48	0.0535	10	0.0321	8	0.0443	77	0.0433	38	0.0404	21
TOLUENE	45202	0.0744	5	0.0386	29	0.0538	45	0.0732	7	0.0825	4	0.0168	43	0.0373	31	0.0776	4
EBEN	45203	0.0295	11	0.0148	54	0.0145	38	0.0282	11	0.0250	8	0.0458	43	0.0140	38	0.0274	8
N-PBEN	45209	0.0054	39	0.0018	130	0.0026	78	0.0053	37	0.0046	27	0.0029	99	0.0045	99	0.0047	23
I-PBEN	98043	0.0020	34	0.0000	0	0.0000	0	0.0016	28	0.0018	16	0.0000	0	0.0002	145	0.0016	15
M-XYL	45205	0.0357	10	0.0277	29	0.0203	29	0.0349	10	0.0252	6	0.0120	43	0.0096	49	0.0240	7
O-XYL	45204	0.0282	14	0.0173	58	0.0141	28	0.0269	16	0.0195	6	0.0148	53	0.0078	46	0.0189	7
P-XYL	45206	0.0357	10	0.0277	29	0.0203	29	0.0349	10	0.0252	6	0.0120	43	0.0096	49	0.0240	7
C9BEN2	45104	0.0342	24	0.0408	37	0.0238	38	0.0364	25	0.0168	16	0.0403	51	0.0148	49	0.0205	16
124TMBEN	45208	0.0268	28	0.0491	27	0.0156	26	0.0286	26	0.0079	26	0.0231	52	0.0056	60	0.0092	27
135TMBEN	45207	0.0108	18	0.0161	45	0.0129	66	0.0120	21	0.0056	10	0.0093	103	0.0031	89	0.0064	22
STYRENE	45220	0.0064	23	0.0033	88	0.0035	62	0.0064	24	0.0055	17	0.0025	61	0.0044	39	0.0057	17
FORMALD	43502	0.0191	28	0.1613	37	0.1122	64	0.0107	30	0.0401	20	0.2313	31	0.2562	31	0.0247	21
ACETALD	43503	0.0111	9	0.0590	41	0.0153	70	0.0043	18	0.0120	18	0.0356	30	0.0167	40	0.0042	14
ACETONE	43551	0.0020	24	0.0000	0	0.0000	0	0.0005	22	0.0033	36	0.0000	0	0.0000	0	0.0008	35
ACROLEIN	43505	0.0000	155	0.0000	0	0.0000	0	0.0000	155	0.0001	85	0.0000	0	0.0000	0	0.0000	86

REQUEST FOR TEST PROCEDURES

On November 12-13, 1992, the Air Resources Board will conduct a public hearing to consider amendments to California regulations for certifying light-duty and medium-duty motor vehicles. Included in this mail-out are a staff report which describes the proposed amendments and the revised text of sections 1960.1, 1976, and 2061 of Title 13, California Code of Regulations.

Incorporated by reference in Title 13 are four test procedure documents which would also be modified as part of this rulemaking. These documents contain very specific requirements for certifying low-emission vehicles and may be of limited general interest. Appendix A of the staff report contains a detailed summary of the revisions made to the test procedures. If you are interested in reviewing the proposed regulatory language, please indicate below which procedures you would like to receive and mail or fax this form to:

Attention: Donna Barragan
California Air Resources Board
9528 Telstar Avenue
El Monte, CA 91731

FAX: 818-575-6818

* * * *

- _____ California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Vehicles
- _____ California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Vehicles
- _____ California Assembly-Line Test Procedures for 1983 and Subsequent Model-Year Vehicles
- _____ California NMOG Test Procedures

Name: _____

Company: _____

Address: _____

REQUEST FOR TEST PROCEDURES

On November 12-13, 1992, the Air Resources Board will conduct a public hearing to consider amendments to California regulations for certifying light-duty and medium-duty motor vehicles. Included in this mail-out are a staff report which describes the proposed amendments and the revised text of sections 1960.1, 1976, and 2061 of Title 13, California Code of Regulations.

Incorporated by reference in Title 13 are four test procedure documents which would also be modified as part of this rulemaking. These documents contain very specific requirements for certifying low-emission vehicles and may be of limited general interest. Appendix A of the staff report contains a detailed summary of the revisions made to the test procedures. If you are interested in reviewing the proposed regulatory language, please indicate below which procedures you would like to receive and mail or fax this form to:

Attention: Donna Barragan
California Air Resources Board
9528 Telstar Avenue
El Monte, CA 91731

FAX: 818-575-6818

* * * *

- _____ California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Vehicles
- _____ California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Vehicles
- _____ California Assembly-Line Test Procedures for 1983 and Subsequent Model-Year Vehicles
- _____ California NMOG Test Procedures

Name: _____

Company: _____

Address: _____

PROPOSED

State of California
AIR RESOURCES BOARD

CALIFORNIA EXHAUST EMISSION STANDARDS
AND TEST PROCEDURES FOR 1988
AND SUBSEQUENT MODEL PASSENGER CARS,
LIGHT-DUTY TRUCKS, AND MEDIUM-DUTY VEHICLES

Adopted: May 20, 1987
Amended: December 20, 1989
Amended: January 22, 1990
Amended: December 26, 1990
Amended: July 12, 1991
Amended: August 19, 1992
Amended: [Alt. Fuel Specs Item]
Amended: [Phase 2 Cert Fuel Item]
Amended: []

NOTE: The regulatory amendments proposed in this rulemaking are shown in underline to indicate additions and ~~strikeout~~ to indicate deletions from the version of the test procedures adopted on August 19, 1991. On March 12, 1992 and August 13, 1992, the Air Resources Board approved modifications to these test procedures as part of the alternative fuel and Phase 2 gasoline certification fuel specifications rulemakings, respectively; however, these modifications have not yet been approved by the Office of Administrative Law. For both of these rulemakings, added text are identified herein by *italics*; deletions are shown in [~~italized strikeout in brackets~~].

This document incorporates by reference various sections of the Code of Federal Regulations, some with modifications. In numerous instances, this document states that incorporated federal regulations are to be varied in some way. Where the directions introducing the variation are not entirely underlined, the variation is displayed in an underline and ~~strikeout~~ format showing changes from the referenced federal regulation as previously incorporated in the California test procedures. Where the directions introducing the variation are entirely underlined, the federal language which will be modified is underlined and the modifications are displayed in double underline and ~~strikeout~~ to indicate additions to or deletions from the federal language.

The numbering convention employed in this document, in order of priority, is: 1.a.1.i.A. Any references within specific sections in the Code of Federal Regulations are denoted in order of priority as: (a)(1)(i)(A) - the same numbering system employed in the Code of Federal Regulations.

TABLE OF CONTENTS

Section	Page
1 Applicability	1-1
2 Definitions	2-1
3 Emission Standards	3-1
4 Initial Requirements	4-1
a. Application for Certification	4-1
b. Required Data	4-2
c. Test Vehicles and Engines (Assigned Deterioration factors)	4-4
d. Compliance with the Inspection and Maintenance Program	4-7
5 Maintenance Requirements	5-1
a. Maintenance (50,000 Mile Certification)	5-1
b. Maintenance Instructions	5-5
c. Submission of Maintenance Instructions	5-5
6 Demonstrating Compliance	6-1
a. Mileage and Service Accumulation; Emission Measurements	6-1
b. Compliance with Emission Standards	6-6
c. <u>Prohibition of Defeat Devices</u>	<u>6-10</u>
7 Small-Volume Manufacturer's Certification Procedures	7-1
8 Alternative Procedures for Notification of Additions and Changes	8-1
9 Test Requirements	9-1
a. Fuel Specifications	9-1
b. Road Load Power Test Weight	9-10
c. Test Sequence; General Requirements	9-13
d. Vehicle Preconditioning	9-13
e. Regeneration Recording Requirements	9-14
f. <u>All-Electric Range Test Requirements</u>	<u>9-14</u>
10 Optional 100,000 Mile Certification Procedure	10-1
a. General Guidelines for Implementation	10-1
b. Specific Guidelines for Compliance	10-3
c. Maintenance	10-5
11 Additional Requirements	11-1
a. Alternative Durability Procedures	11-1
b. High Altitude Requirements	11-1
c. Highway Fuel Economy Test	11-2
d. Labeling Requirements	11-2
e. Driveability and Performance Requirements	11-2
f. Malfunction and Diagnostic System Requirements	11-2
g. Methanol and Formaldehyde Emission Testing	11-3
h. FFV Emission Testing	11-3
i. Scope of Certification	11-3
j. Statement on Production Vehicles	11-4
k. 50 Degree F Emission Test Requirement	11-4
l. Emission Control System Continuity at Low Temperature	11-6
m. NMOG and HCHO Factors for Assembly Line Testing	11-6
12 Identification of New Clean Fuels For Certification Testing	12-1
13 Reactivity Adjustment Factors	13-1
14 <u>Cold Temperature Test Procedure</u>	<u>14-1</u>

NOTE: The page numbering convention of this document has been changed from previous versions.

Appendices

I	List of Adopted Sections of Subparts A and B, Part 86 Title 40, Code of Federal Regulations, Incorporated by Reference	I-1
II	Exhaust Emission-Data Vehicle Selection Criteria	II-1
III	Determination of Acceptable Durability Test Schedule	III-1
IV	Determination of Acceptable Exhaust Regeneration Durability Test Schedule	IV-1
V	Pollutant Mass Emissions Calculation Procedures	V-1
VI	"Blanket" Approval of Running Changes and Field Fixes of Production Vehicles	VI-1
VII	California Statistical Outlier Identification Procedure	VII-1
VIII	Procedure for Determining Vehicle Emission Control Technology Category/Fuel Reactivity Adjustment Factors	VIII-1

CALIFORNIA EXHAUST EMISSION
STANDARDS AND TEST PROCEDURES
FOR 1988 AND SUBSEQUENT MODEL
PASSENGER CARS, LIGHT-DUTY TRUCKS
AND MEDIUM-DUTY VEHICLES

The provisions of Subparts A, and B, and C, Part 86, Title 40, Code of Federal Regulations as set forth in Appendix I, to the extent they pertain to Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles, are hereby adopted as the California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, with the following exceptions and additions.

1. Applicability

- a. These test procedures are applicable to 1988 and subsequent model gasoline, gaseous, diesel, and, beginning in 1993, methane~~t~~ alcohol passenger cars, light-duty trucks, and medium-duty vehicles. Procedures specific to transitional low-emission, low-emission, and ultra-low-emission vehicles are applicable to 1992 and subsequent model-year gasoline and diesel, and to 1993 and subsequent model-year alternate fuel and hybrid electric passenger cars, light-duty trucks, and medium-duty vehicles. Procedures specific to zero-emission vehicles are applicable to 1992 and subsequent model-year passenger cars, light-duty trucks and medium-duty vehicles. References to "light-duty trucks" in 40 CFR 86 shall apply both to "light-duty trucks" and "medium-duty vehicles" in these procedures.
- b. Any reference to vehicle sales throughout the United States shall mean vehicle sales in California.
- c. Regulations concerning EPA hearings, EPA inspections, specific language on the Certificate of Conformity, evaporative emissions high-altitude vehicles and testing, particulate and oxides of nitrogen averaging and engine family standards applicable in such averaging, alternative useful life, selective enforcement audit and heavy-duty engines and vehicles shall not be applicable to these procedures, except where specifically noted.
- d. Any reference to gasoline-powered vehicles shall also apply to vehicles powered by gaseous fuels.
- e. Regulations both herein and in Title 40, CFR Part 86, Subparts A, and B, and C, concerning otto-cycle and diesel-cycle vehicles shall be applicable to methane~~t~~ alcohol vehicles, except where specifically noted otherwise.
- f. Regulations concerning methane~~t~~ alcohol vehicles shall also be applicable to fuel-flexible vehicles, except where specifically noted otherwise.

- g. For engines used in medium-duty vehicles which are not distinctly diesel engines nor derived from such, the Executive Officer shall determine whether the engines shall be subject to diesel or otto-cycle engine regulations, in consideration of the relative similarity of the engines' torque-speed characteristics and vehicle applications with those of otto-cycle and diesel engines.

2. Definitions

- a. "Administrator" means the Executive Officer of the Air Resources Board (ARB).
- b. "Certificate of Conformity" means Executive Order certifying vehicles for sale in California.
- c. "Certification" means certification as defined in Section 39018 of the Health and Safety Code.
- d. "Passenger car" means any motor vehicle designed primarily for transportation of persons and having a design capacity of 12 persons or less.
- e. "Heavy-duty engine" means an engine which is used to propel a heavy-duty vehicle.
- f. "Heavy-duty vehicle" means any motor vehicle having a manufacturer's gross vehicle weight rating greater than 6000 pounds, except passenger cars.
- g. "Light-duty truck" means any motor vehicle, rated at 6000 pounds gross vehicle weight or less, which is designed primarily for purposes of transportation of property or is a derivative of such a vehicle, or is available with special features enabling off-street or off-highway operation and use.
- h. "Medium-duty vehicle" means any pre-1995 model year heavy-duty vehicle having a manufacturer's gross vehicle weight rating of 8500 pounds or less and any 1995 and subsequent model year heavy-duty vehicle or any 1992 and subsequent model-year low-emission, ultra-low-emission, or zero-emission vehicle having a manufacturer's gross vehicle rating of 14,000 pounds or less.
- i. "Gaseous fuels" means liquefied petroleum gas, compressed natural gas, or liquefied natural gas fuels for use in motor vehicles.
- j. "Trap oxidizer system" means an emission control system which consists of a trap to collect particulate matter and a mechanism to oxidize the accumulated particulate.
- k. "Regeneration" means the process of oxidizing accumulated particulate matter. It may occur continually or periodically.
- l. "Periodically regenerating trap oxidizer system" means a trap oxidizer system that utilizes, during normal driving conditions for cleaning the trap, an automated regeneration mode which can be easily detected.
- m. "Continually regenerating trap oxidizer system" means a trap oxidizer system that does not utilize an automated regeneration mode during normal driving conditions for cleaning the trap.
- n. "Non-regeneration emission test" means a complete emission test which does not include a regeneration.

- o. "Regeneration emission test" means a complete emission test which includes a regeneration.
- p. "Regeneration interval" means the interval from the start of a regeneration to the start of the next regeneration.
- q. "Useful Life" means a period of use denoted by the emission standards to which a given vehicle is certifying. For those light-duty and medium-duty vehicles certified to optional 100,000 mile standards and those 1993 and subsequent vehicles certified to 100,000 mile emission standards, and those transitional low-emission, low-emission, and ultra-low-emission vehicles, including hybrid electric vehicles, certified to 100,000 mile emission standards, the useful life shall be 10 years or 100,000 miles, whichever first occurs. For 1995 and subsequent medium-duty vehicles and medium-duty low-emission and ultra-low emission vehicles certified to 120,000 mile emission standards, the useful life shall be 11 years or 120,000 miles, whichever first occurs. For light-duty and medium-duty vehicles, certified only to 50,000 miles, the useful life shall be 5 years or 50,000 miles, whichever first occurs.
- r. "Methanol" means any fuel for motor vehicles and motor vehicle engines that is composed of either commercially available or chemically pure methanol (CH_3OH) and gasoline as specified in section 9.a. (Fuel Specifications) of these procedures. The required fuel blend is based on the types of methanol-fueled vehicle being certified and the particular aspect of the certification procedure being conducted.
- s. "Methanol vehicle" means any motor vehicle that is engineered and designed to be operated using methanol as a fuel.
- t. "Fuel-Flexible Vehicle (FFV)" means any methanol-fueled or ethanol-fueled motor vehicle that is engineered and designed to be operated using any gasoline-methanol or gasoline-ethanol fuel mixture or blend.
- u. "Dedicated Methanol Vehicle" means any methanol-fueled motor vehicle that is engineered and designed to be operated solely on methanol.
- v. "Diesel-cycle" means powered by an engine where the primary means of controlling power output is by limiting of the amount of fuel that is injected into the combustion chambers of the engine.
- w. "Otto-cycle" means powered by an engine where the primary means of controlling power output is by limiting the amount of air and fuel which can enter the combustion chambers of the engine. Gasoline-fueled engines are otto-cycle engines.
- x. "Organic Material Hydrocarbon Equivalent" (or "OMHCE") means the sum of the carbon mass contributions of non-oxygenated hydrocarbons, methanol, and formaldehyde as contained in a gas sample, expressed as gasoline-fueled vehicle hydrocarbons. In the case of exhaust emissions, the hydrogen-to-carbon ratio of the equivalent hydrocarbon is 1.85:1. In the case of diurnal and hot-soak

emissions, the hydrogen-to-carbon ratios of the equivalent hydrocarbons are 2.33:1 and 2.2:1, respectively.

- y. "Incomplete vehicle" means any vehicle which does not have the primary load carrying device or container attached. In situations where individual marketing relationships makes the status of the vehicle questionable, the Executive Officer shall determine whether a specific model complies with the definition of incomplete vehicle.
- z. "Non-methane organic gas" (or "NMOG") means the sum of non-oxygenated and oxygenated hydrocarbons contained in a gas sample as measured in accordance with the "California Non-Methane Organic Gas Test Procedures" as adopted July 12, 1991 and last amended including, at a minimum, all oxygenated organic gases containing five or fewer carbon atoms (i.e., aldehydes, ketones, alcohols, ethers, etc.), and all known alkanes, alkenes, alkynes, and aromatics containing twelve or fewer carbon atoms. For diesel-fueled vehicles, non-methane organic gas shall mean the sum of all oxygenated organic gases containing five or fewer carbon atoms and all known alkanes, alkenes, alkynes, and aromatics containing twenty-five or fewer carbon atoms. To demonstrate compliance with an NMOG standard, NMOG emissions shall be measured in accordance with the "California Non-Methane Organic Gas Test Procedures" as adopted July 12, 1991.
- Aa. "Dual-fuel vehicle" means any motor vehicle that is engineered and designed to be capable of operating on gasoline or diesel a petroleum fuel and on compressed natural gas or liquefied petroleum gas another fuel, with stored separately fuel tanks for each fuel on-board the vehicle.
- Ab. "Transitional low-emission vehicle" or "TLEV" means any vehicle certified to transitional low-emission standards.
- Ac. "Low-emission vehicle" or "LEV" means any vehicle certified to low-emission standards.
- Ad. "Ultra-low-emission vehicle" or "ULEV" means any vehicle certified to ultra-low emission standards.
- Ae. "Zero-emission vehicle" or "ZEV" means any vehicle which is certified by the Executive Officer to produces zero emissions of any criteria pollutants under any and all possible operational modes and conditions. Incorporation of a fuel fired heater shall not preclude a vehicle from being certified as a ZEV provided the fuel fire heater cannot be operated at ambient temperatures above 40 degrees Fahrenheit and the heater is demonstrated to have zero evaporative emissions under any and all possible operational modes and conditions.
- Af. "Electric vehicle" means any vehicle which operates solely by use of a battery or battery pack. This definition also includes vehicles which are powered mainly through the use of an electric battery or battery pack, but which use a flywheel that stores energy produced by the electric motor or through regenerative braking to assist in vehicle operation.

- Ag. "Series hybrid electric vehicle" means any vehicle which allows power to be delivered to the driven wheels solely by a battery powered electric motor, but which also incorporates the use of a combustion engine to provide power to the battery and/or electric motor.
- Ah. "Parallel hybrid electric vehicle" means any vehicle which allows power to be delivered to the driven wheels by either a combustion engine and/or by a battery powered electric motor.
- Ai. "Battery assisted combustion engine vehicle" means any vehicle which allows power to be delivered to the driven wheels solely by a combustion engine, but which uses a battery pack to store energy which may be derived through remote charging, regenerative braking, and/or a flywheel energy storage system or other means which will be used by an electric motor to assist in vehicle operation.
- Aj. "Hybrid electric vehicle" means any vehicle which is included in the definition of a "series hybrid electric vehicle", a "parallel hybrid electric vehicle", or a "battery assisted combustion engine vehicle".
- Ak. "Diesel Engine" means any engine powered with diesel fuel, gaseous fuel, ethanol, or methanol for which diesel engine speed/torque characteristics and vehicle applications are retained.
- Al. "Fuel fired heater" means a fuel burning device which creates heat for the purpose of warming the passenger compartment of a vehicle ~~but does not contribute to the propulsion of the vehicle~~.
- Am. "Conventional gasoline" means any certification gasoline which whose specifications are substantially equivalent to gasoline available commercially in the 1989 calendar year, as determined by the Executive Officer meets the specifications of 86.113-90(a), 40 CFR 86, including the specifications of (a)(1)(i) but excluding the specifications of (a)(1)(ii) as amended by Section 9.a.1. of these test procedures. For the purpose of determining the ozone-forming potential of conventional gasoline vehicle exhaust emissions, gasoline meeting the specifications of Appendix VIII, note (9) of these test procedures shall be used.
- An. "Reactivity adjustment factor" means a fraction applied to the mass of NMOG emissions from a vehicle powered by a fuel other than conventional gasoline for the purpose of determining a gasoline-equivalent NMOG emission value. The reactivity adjustment factor is defined as the ozone-forming potential of the exhaust from a vehicle powered by a fuel other than conventional gasoline divided by the ozone-forming potential of conventional gasoline vehicle exhaust.
- Ao. "Intermediate volume manufacturer" is any vehicle manufacturer with California sales between 3,001 and 35,000 new light- and medium-duty vehicles per model year based on the average number of vehicles sold by the manufacturer each year from 1989 to 1993; however, for manufacturers certifying for the first time in California, model-year sales shall be based on projected California sales.

- Ap. "Certification level" means the official exhaust or evaporative emission result from an emission-data vehicle which has been adjusted by the applicable mass deterioration factor and is submitted to the Executive Officer for use in determining compliance with an emission standard for the purpose of certifying a particular engine family. For those engine families which are certified using reactivity adjustment factors developed by the manufacturer pursuant to Appendix VIII of these test procedures, the exhaust NMOG certification level shall include adjustment by the ozone deterioration factor.
- Aq. "Ozone deterioration factor" means a factor applied to the mass of NMOG emissions from TLEVs, LEVs, or ULEVs which accounts for changes in the ozone-forming potential of the NMOG emissions from a vehicle as it accumulates mileage.
- Ar. "Organic material non-methane hydrocarbon equivalent" (or "OMNMHCE") for methanol-fueled vehicles means the sum of the carbon mass contribution of non-oxygenated hydrocarbons (excluding methane), methanol, and formaldehyde as contained in a gas sample, expressed as gasoline-fueled hydrocarbons. For ethanol-fueled vehicles, "organic material non-methane hydrocarbon equivalent" (or "OMNMHCE") means the sum of carbon mass contribution of non-oxygenated hydrocarbons (excluding methane), methanol, ethanol, formaldehyde and acetaldehyde as contained in a gas sample, expressed as gasoline-fueled hydrocarbons.
- As. "Battery pack" means any electrical energy storage device consisting of any number of individual battery modules which is used to propel electric or hybrid electric vehicles.
- At. "Type A hybrid electric vehicle" means a hybrid electric vehicle which achieves a minimum range of 50 miles in the All-Electric Range Test, while maintaining minimal speed and time requirements throughout the test and without use of the auxiliary power unit.
- Au. "Type B hybrid electric vehicle" means a hybrid electric vehicle which achieves a range of 40 to 59 miles in the All-Electric Range Test, while maintaining minimal speed and time requirements throughout the test and without use of the auxiliary power unit.
- Av. "Type C hybrid electric vehicle" means a hybrid electric vehicle which achieves a range of 0 to 39 miles in the All-Electric Range Test, while maintaining minimal speed and time requirements throughout the test and without use of the auxiliary power unit, or which has been designated by the manufacturer as having a range of less than 40 miles without the use of the auxiliary power unit. This definition shall also apply to any hybrid electric vehicle which allows the operator to control the time or mode of operation of the auxiliary power unit either directly or indirectly, to any hybrid electric vehicle which can be operated solely through the use of the auxiliary power unit, to any hybrid electric vehicle which utilizes a climate control system that cannot be operated without using the auxiliary power unit, and all other types of hybrid electric vehicles, excluding Type A and Type B hybrid electric vehicles.

- Aw. "All-Electric Range Test" means a test sequence used to determine the range of an electric vehicle or of a hybrid electric vehicle without the use of its auxiliary power unit. The All-Electric Range Test cycle consists of alternating the Highway Fuel Economy Schedule and the Urban Dynamometer Driving Schedule (see 9.f. of these test procedures).
- Ax. "Defeat Device" means an auxiliary emission control device (AECD) that reduces the effectiveness of the emission control system under conditions which may reasonably be expected to be encountered in normal vehicle operation and use, unless (1) such conditions are substantially included in the Federal emission test procedure, (2) the need for the AECD is justified in terms of protecting the vehicle against damage or accident, or (3) the AECD does not go beyond the requirements of engine starting.
- Av. "Element of Design" means any control system (i.e., computer software, electronic control system, emission control system, computer logic), and/or control system calibrations and/or the results of systems interaction, and/or hardware items on a motor vehicle or motor vehicle engine.
- Az. "Intermediate Temperature Cold Testing" means testing done pursuant to the driving cycle and testing conditions contained in 40 CFR Part 86 Subpart C, at temperatures between 25°F (-4°C) and 68°F (20°C).
- Ba. "Ethanol vehicle" means any motor vehicle that is engineered and designed to be operated using ethanol as a fuel.
- Bb. "Dedicated Ethanol Vehicle" means any ethanol-fueled motor vehicle that is engineered and designed to be operated solely on ethanol.
- Bc. "Ethanol" means any fuel for motor vehicles and motor vehicle engines that is composed of either commercially available or chemically pure ethanol ($\text{CH}_3\text{CH}_2\text{OH}$) and gasoline as specified in section 9.a. (Fuel Specifications) of these test procedures. The required fuel blend is based on the type of ethanol-fueled vehicle being certified and the particular aspect of the certification procedure being conducted.
- Bd. "Alcohol fuel" means either methanol or ethanol as those terms are defined in these test procedures.
- Be. "Methane Reactivity Adjustment Factor" means a factor applied to the mass of methane emissions from natural gas fueled vehicles for the purpose of determining the gasoline equivalent ozone-forming potential of the methane emissions.
- Bf. "Natural gas" means either compressed natural gas or liquefied natural gas.
- Bg. "Natural gas vehicle" means any motor vehicle that is engineered and designed to be operated using either compressed natural gas or liquefied natural gas.

3. Standards

The following standards represent the maximum projected exhaust emissions for the useful life of the vehicle.

a. The exhaust emissions from new 1988 model passenger cars, light-duty trucks, and medium-duty vehicles shall not exceed:

1988 EXHAUST EMISSIONS STANDARDS(5)(6) (grams per mile)

Vehicle Type(1)	Loaded Vehicle Weight (lbs.)	Durability Vehicle Basis (mi)	Non-Methane Hydrocarbons(2)	Carbon Monoxide	Oxides of Nitrogen (3)
PC	All	50,000	0.39 (0.41)	7.0	0.4
PC(4)	All	50,000	0.39 (0.41)	7.0	0.7
PC (Option 1)	All	100,000	0.39 (0.41)	7.0	1.0
PC (Option 2)	All	100,000	0.46	8.3	1.0
LDT,MDV	0-3750	50,000	0.39 (0.41)	9.0	0.4
LDT,MDV (4)	0-3750	50,000	0.39 (0.41)	9.0	1.0
LDT,MDV (Option 1)	0-3750	100,000	0.39 (0.41)	9.0	1.0
LDT,MDV (Option 2)	0-3750	100,000	0.46	10.6	1.0
LDT,MDV	3751-5750	50,000	0.50 (0.50)	9.0	1.0
LDT,MDV (Option 1)	3751-5750	100,000	0.50 (0.50)	9.0	1.5
MDV	5751 & larger	50,000	0.60 (0.60)	9.0	1.5
MDV (Option 1)	5751 & larger	100,000	0.60 (0.60)	9.0	2.0

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
"MDV" means medium-duty vehicles.
- (2) Hydrocarbon standards in parentheses apply to total hydrocarbons. In order to demonstrate compliance with a non-methane hydrocarbon emission standard, hydrocarbon emissions shall be measured in accordance with the "California Non-Methane Hydrocarbon Test Procedures."
- (3) The maximum projected emissions of oxides of nitrogen measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall be not greater than 1.33 times the applicable passenger car standards and 2.00 times the applicable light-duty trucks and medium-duty vehicle standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.
- (4) This set of standards for 1988 and later model vehicles is optional. A manufacturer may choose to certify to these optional standards pursuant to the conditions set forth in Section 1960.1.5 of Title 13, California Code of Regulations.
- (5) Diesel passenger cars, light-duty trucks, and medium-duty vehicles, except those fueled with methanol, are subject to the following particulate exhaust emission standards: 0.2 g/mi for the 1988 model years. The particulate compliance shall be determined on a 50,000 mile durability vehicle basis.

- (6) For gaseous-fueled vehicles the calculation procedures provided in Appendix V shall be used for determining emissions and fuel economy.

b. The exhaust emissions from (i) new 1989 through 1992 model passenger cars and light-duty trucks, except those produced by a small volume manufacturer, (ii) new 1991 through 1994 model passenger cars and light-duty trucks produced by a small volume manufacturer, (iii) new 1989 through 1994 model medium-duty vehicles, except those produced by a small volume manufacturer, and (iv) new 1991 through 1994 model medium-duty vehicles produced by a small volume manufacturer, shall not exceed:

1989 THROUGH 1994 MODEL YEAR
EXHAUST EMISSIONS STANDARDS (5)(6)
(grams per mile)

<u>Vehicle Type(1)</u>	<u>Loaded Vehicle Weight (lbs.)</u>	<u>Durability Vehicle Basis (mi)</u>	<u>Non-Methane Hydro- carbons(2)</u>	<u>Carbon Monoxide</u>	<u>Oxides of Nitrogen (3)(4)</u>
PC	All	50,000	0.39 (0.41)	7.0	0.4
PC(7)	All	50,000	0.39 (0.41)	7.0	0.7
Diesel PC (Option 2)	All	100,000(9)	0.46	8.3	1.0
LDT,MDV	0-3750	50,000	0.39 (0.41)	9.0	0.4
LDT,MDV (7)	0-3750	50,000	0.39 (0.41)	9.0	0.7(8)
Diesel LDT, MDV (Option 2)	0-3750	100,000(9)	0.46	10.6	1.0
LDT,MDV	3751-5750	50,000	0.50 (0.50)	9.0	1.0
LDT,MDV (Option 1)	3751-5750	100,000(9)	0.50 (0.50)	9.0	1.5
MDV	5751 & larger	50,000	0.60 (0.60)	9.0	1.5
MDV (Option 1)	5751 & larger	100,000(9)	0.60 (0.60)	9.0	2.0

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
"MDV" means medium-duty vehicles.
- (2) Hydrocarbon standards in parentheses apply to total hydrocarbons. In order to demonstrate compliance with a non-methane hydrocarbon emission standard, hydrocarbon emissions shall be measured in accordance with the "California Non-Methane Hydrocarbon Test Procedures". For 1993 through 1994 model methanol-fueled vehicles certifying to these standards, including flexible-fueled fuel-flexible vehicles, "Non-Methane Hydrocarbons" shall mean "Organic Material Hydrocarbon Equivalent" (or "OMHCE").
- (3) The maximum projected emissions of oxides of nitrogen measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall be not greater than 1.33 times the applicable passenger car standards and 2.00 times the applicable light-duty trucks and medium-duty vehicle standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.

- (4) The standard for in-use compliance for passenger cars, light-duty trucks and medium-duty vehicles certifying to the 0.4 g/mi NOx standard shall be 0.55 g/mi NOx for 50,000 miles. If the in-use compliance level is above 0.4 g/mi NOx but does not exceed 0.55 g/mi NOx, and based on a review of information derived from a statistically valid and representative sample of vehicles, the Executive Officer determines that a substantial percentage of any class or category of such vehicles exhibits, prior to 50,000 miles or 5 years, whichever occurs first, an identifiable, systematic defect in a component listed in Section 1960.1.5(c)(2), Title 13, California Code of Regulations, which causes a significant increase in emissions above those exhibited by vehicles free of such defects and of the same class or category and having the same period of use and mileage, then the Executive Officer may invoke the enforcement authority under Subchapter 2.5, Title 13, California Code of Regulations, commencing with Section 2111, to require remedial action by the vehicle manufacturer. Such remedial action shall be limited to owner notification and repair or replacement of the defective component. As used in this section, the term "defect" shall not include failures which are the result of abuse, neglect, or improper maintenance. This provision is applicable for the 1989 through 1992 model years only. For small volume manufacturers, this provision is applicable for the 1991 through 1994 model years only.
- (5) Diesel passenger cars, light-duty trucks, and medium-duty vehicles certifying to these standards are subject to a particulate exhaust emission standard of 0.08 g/mi for the 1989 and subsequent model years. The particulate compliance shall be determined on a 50,000 mile durability vehicle basis.
- (6) For gaseous-fueled vehicles certifying to these standards, the calculation procedures provided in Appendix V shall be used for determining emissions and fuel economy.
- (7) This set of standards is optional. A manufacturer may choose to certify to these standards pursuant to the conditions set forth in Section 1960.1.5 of Title 13, California Code of Regulations.
- (8) Pursuant to Section 1960.1.5(a)(1)(B), Title 13, California Code of Regulations the optional standard for 1989 model year light-duty trucks and medium-duty vehicles only is 1.0 g/mi NOx.
- (9) The optional 100,000 mile certification standards and provisions are not applicable to methane+ alcohol vehicles.

c. The exhaust emissions from new 1993 and subsequent model dedicated methanol alcohol vehicles and fuel-flexible vehicles shall meet all the requirements in Sections 3.b., 3.e, and 3.f. of these test procedures with the following modifications and additions:

**1993 AND SUBSEQUENT METHANOL-SPECIFIC AND ETHANOL-SPECIFIC
EXHAUST EMISSION STANDARDS**

<u>Vehicle Type</u>	<u>Loaded Vehicle Weight (lbs.)(3)</u>	<u>Durability Vehicle Basis (mi)</u>	<u>Formaldehyde (mg/mi)</u>	
			<u>Certification</u>	<u>In-Use Compliance (2)</u>
PC	A11	50,000	15	23 (1993-1995) 15 (1996 and later)
LDT,MDV	0-3750	50,000	15	23 (1993-1995) 15 (1996 and later)
LDT,MDV	3751-5750	50,000	18	27 (1993-1995) 18 (1996 and later)
MDV	5751-8500	50,000	22	33 (1993-1995) 22 (1996 and later)
MDV	8501-10,000	50,000	28	36 (1995) 28 (1996 and later)
MDV	10,001-14,000	50,000	36	45 (1995) 36 (1996 and later)

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
"MDV" means medium-duty vehicles.
- (2) If the formaldehyde in-use compliance level is above the respective certification level but does not exceed the in-use compliance level, and based on a review of information derived from a statistically valid and representative sample of vehicles, the Executive Officer determines that a substantial percentage of any class or category of such vehicle exhibits, prior to 50,000 miles or 5 years, whichever occurs first, an identifiable, systematic defect in a component listed in Section 1960.1.5(c)(2), Title 13 California Code of Regulations, which causes a significant increase in emissions above those exhibited by vehicles free of such defects and of the same class or category and having the same period of use and mileage, the Executive Officer may invoke the enforcement authority under subchapter 2.5, Title 13, California Code of Regulations, commencing with Section 2111, to require remedial action by the vehicle manufacturer. Such remedial action shall be limited to owner notification and repair or replacement of the defect component. As used in this section, the term "defect" shall not include failures which are the result of abuse, neglect, or improper maintenance.
- (3) For 1995 and subsequent model year medium-duty vehicles certifying to the standards and test procedures specified in Section 1960.1 (h)(1), Title 13, California Code of Regulations, "Loaded Vehicle Weight" shall mean "Test Weight", which is the average of the vehicle's curb weight and gross vehicle weight.

d. The exhaust emission levels from 1992 and subsequent model-year transitional low-emission vehicles, low-emission vehicles, and ultra-low-emission vehicles, including fuel-flexible and dual-fuel vehicles, shall meet all the requirements of Sections 3.g and 3.j of these test procedures with the following additions:

EXHAUST EMISSION STANDARDS
FOR TRANSITIONAL LOW-EMISSION VEHICLES, LOW-EMISSION VEHICLES,
AND ULTRA-LOW-EMISSION VEHICLES IN THE
LIGHT-DUTY AND MEDIUM-DUTY VEHICLE WEIGHT CLASSES (5)(6)
["milligrams per mile" (or "mg/mi")]

<u>Vehicle Type (1)</u>	<u>Vehicle Weight (lbs.)(2)</u>	<u>Durability Vehicle Basis (mi)</u>	<u>Vehicle Emission Category(3)</u>	<u>Formaldehyde (mg/mi)(4)</u>
PC and LDT	A11 0-3750	50,000	TLEV	15 (23)
			LEV	15 (15)
			ULEV	8 (12)
		100,000	TLEV	18
			LEV	18
			ULEV	11
LDT	3751-5750	50,000	TLEV	18 (27)
			LEV	18 (18)
			ULEV	9 (14)
		100,000	TLEV	23
			LEV	23
			ULEV	13
MDV	0-3750	50,000	LEV	15 (15)
			ULEV	8 (12)
		120,000	LEV	22
			ULEV	12
MDV	3751-5750	50,000	LEV	18 (18)
			ULEV	9 (14)
		120,000	LEV	27
			ULEV	13
MDV	5751-8500	50,000	LEV	22 (22)
			ULEV	11 (17)
		120,000	LEV	32
			ULEV	16
MDV	8501-10,000	50,000	LEV	28 (28)
			ULEV	14 (21)
		120,000	LEV	40
			ULEV	21
MDV	10,001-14,000	50,000	LEV	36 (36)
			ULEV	18 (27)
		120,000	LEV	52
			ULEV	26

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
"MDV" means medium-duty vehicles.
- (2) For light-duty or medium-duty vehicles, Vehicle Weight shall mean "Loaded Vehicle Weight" (or "LVW") or "Test Weight" (or "TW"), respectively.
- (3) "TLEV" means transitional low-emission vehicle.
"LEV" means low-emission vehicle.
"ULEV" means ultra-low-emission vehicle.
- (4) The standards in parentheses are intermediate in-use compliance standards for 50,000 miles.
 - a. For PCs and LDTs from 0-5750 lbs. LVW, including fuel-flexible and dual-fuel vehicles, intermediate in-use compliance standards shall apply to TLEVs through the 1995 model year, and LEVs and ULEVs through the 1998 model year. In-use Gcompliance with standards beyond 50,000 miles shall be waived through the 1995 model year for TLEVs and through the 1998 model year for LEVs and ULEVs.
 - b. For MDVs from 0-14,000 lbs. TW, including fuel-flexible and dual-fuel vehicles, intermediate in-use compliance standards shall apply to LEVs and ULEVs through the 1999 model year. In-use Gcompliance with standards beyond 50,000 miles shall be waived through the 1999 model year for LEVs and ULEVs.
- (5) Manufacturers shall demonstrate compliance with the above standards for formaldehyde at 50 degrees F, according to the procedure specified in Section 11k of these test procedures. Hybrid electric vehicles, natural gas vehicles, and diesel-fueled vehicles shall be exempt from 50 degrees F test requirements. the "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as adopted May 20, 1987, and last amended INSERT.
- (6) In-use compliance testing shall be limited to PCs and LDTs with fewer than 75,000 miles and MDVs with fewer than 90,000 miles.

e. The exhaust emissions from new 1993 and 1994 model passenger cars and light-duty trucks, except those produced by a small volume manufacturer, shall not exceed:

1993 AND 1994 MODEL-YEAR PASSENGER CAR AND
LIGHT-DUTY TRUCK EXHAUST EMISSIONS STANDARDS (5)(6)(10)
(grams per mile)

Vehicle Type(1)	Loaded Vehicle Weight (lbs.)	Durability Vehicle Basis (mi)	Non-Methane Hydrocarbons (2)(8)(9)	Carbon Monoxide (8)(9)	Oxides of Nitrogen (1)(3)(4)
PC	All	50,000	0.39 (0.25)	7.0 (3.4)	0.4
PC(7)	All	50,000	0.39 (0.25)	7.0 (3.4)	0.7
PC	All	100,000	(0.31)	(4.2)	n/a
Diesel PC (Option 2)	All	100,000	0.46 (0.31)	8.3 (4.2)	1.0
LDT	0-3750	50,000	0.39 (0.25)	9.0 (3.4)	0.4
LDT (7)	0-3750	50,000	0.39 (0.25)	9.0 (3.4)	0.7
LDT	0-3750	100,000	(0.31)	(4.2)	n/a
Diesel LDT (Option 2)	0-3750	100,000	0.46 (0.31)	10.6 (4.2)	1.0
LDT	3751-5750	50,000	0.50 (0.32)	9.0 (4.4)	1.0
LDT	3751-5750	100,000	(0.40)	(5.5)	n/a
Diesel LDT (Option 1)	3751-5750	100,000	0.50 (0.40)	9.0 (5.5)	1.5

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
"n/a" means not applicable.
- (2) In order to demonstrate compliance with a non-methane hydrocarbon emission standard, hydrocarbon emissions shall be measured in accordance with the "California Non-Methane Hydrocarbon Test Procedures." For methanol-fueled vehicles certifying to these standards, including fuel-flexible-fueled vehicles when certifying on methanol, "Non-Methane Hydrocarbons" shall mean "Organic Material Hydrocarbon Equivalent" (or "OMHCE"). For alcohol vehicles certifying to the phase-in standards in parenthesis, including fuel-flexible vehicles when certifying on methanol or ethanol, "Non-Methane Hydrocarbons" shall mean "Organic Material Non-Methane Hydrocarbon Equivalent" (or "OMNMHCE").
- (3) The maximum projected emissions of oxides of nitrogen measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall be not greater than 1.33 times the applicable passenger car standards and 2.00 times the applicable light-duty truck and medium-duty vehicle standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.
- (4) The standard for in-use compliance for passenger cars and light-duty trucks certifying to the 0.4 g/mi NO_x standard shall be 0.55 g/mi NO_x for 50,000 miles. If the in-use compliance level is above 0.4 g/mi NO_x but does not exceed 0.55 g/mi NO_x, and based on a review of information derived from a statistically valid and representative sample of vehicles, the Executive Officer determines that a substantial percentage of any class or category of such vehicles exhibits, prior to 50,000

- miles or 5 years, whichever occurs first, an identifiable, systematic defect in a component listed in Section 1960.1.5(c)(2), Title 13 California Code of Regulations, which causes a significant increase in emissions above those exhibited by vehicles free of such defects and of the same class or category and having the same period of use and mileage, then the Executive Officer may invoke the enforcement authority under subchapter 2.5, Title 13, California Code of Regulations, commencing with Section 2111, to require remedial action by the vehicle manufacturer. Such remedial action shall be limited to owner notification and repair or replacement of the defective component. As used in this section, the term "defect" shall not include failures which are the result of abuse, neglect, or improper maintenance. This provision is applicable for the 1993 model year only.
- (5) Diesel passenger cars and light-duty trucks certifying to these standards are subject to a particulate exhaust emission standard of 0.08 g/mi, determined on a 50,000 mile durability vehicle basis.
 - (6) For gaseous-fueled vehicles certifying to these standards, the calculation procedures provided in Appendix V shall be used for determining emissions and fuel economy.
 - (7) This set of standards is optional. A manufacturer may choose to certify to these standards pursuant to the conditions set forth in Section 1960.1.5 of Title 13, California Code of Regulations.
 - (8) The emission standards in parenthesis are phase-in standards. For the 1993 model year, each manufacturer must certify a minimum of 40% of their vehicles to the phase-in standards or to the more stringent standards in Section 3.g of these test procedures. For the 1994 model year, each manufacturer must certify a minimum of 80% of their vehicles to the phase-in standards or to the more stringent standards in Section g of these test procedures. The percentages shall be applied to the manufacturers' total projected sales of California-certified passenger cars and light-duty trucks for the 1993 model year. For 1994 and subsequent model years, manufacturers shall comply with the fleet average requirements specified in Section 3.h. of these test procedures.
 - (9) The following conditions shall apply to the in-use compliance standards of 1993 and 1994 model-year passenger cars and light-duty trucks only.
 - (a) The in-use compliance standards for those passenger cars and light-duty trucks certifying to the 0.25 g/mi non-methane hydrocarbon and 3.4 g/mi carbon monoxide standards shall be 0.32 g/mi non-methane hydrocarbon and 5.2 g/mi carbon monoxide for 50,000 miles.
 - (b) The in-use compliance standards for those light-duty trucks certifying to the 0.32 g/mi non-methane hydrocarbon and 4.4 g/mi carbon monoxide standards shall be 0.41 g/mi non-methane hydrocarbon and 6.7 g/mi carbon monoxide for 50,000 miles.
 - (c) In-use compliance standards shall be waived beyond 50,000 miles.
 - (10) All passenger cars and light-duty trucks, except those diesel vehicles certifying to optional 100,000 mile standards, are subject to non-methane hydrocarbon, carbon monoxide, and oxides of nitrogen standards determined on a 50,000 mile durability basis and non-methane hydrocarbon and carbon monoxide standards determined on a 100,000 mile basis.

f. The exhaust emissions from new 1995 and subsequent model passenger cars and light-duty trucks shall not exceed:

1995 AND SUBSEQUENT MODEL-YEAR PASSENGER CAR AND
LIGHT-DUTY TRUCK EXHAUST EMISSIONS STANDARDS (5)(6)(8)(9)(11)
(grams per mile)

Vehicle Type(1)	Loaded Vehicle Weight (lbs.)	Durability Vehicle Basis (mi)	Non-Methane Hydrocarbons (2)(7)	Carbon Monoxide (7)	Oxides of Nitrogen (1)(3)
PC	All	50,000	0.25	3.4	0.4(4)
PC	All	100,000	0.31	4.2	<u>0.6(10)</u> n/a
Diesel PC (Option 2)	All	100,000	0.31	4.2	1.0
LDT	0-3750	50,000	0.25	3.4	0.4(4)
LDT	0-3750	100,000	0.31	4.2	<u>0.6(10)</u> n/a
Diesel LDT (Option 2)	0-3750	100,000	0.31	4.2	1.0
LDT	3751-5750	50,000	0.32	4.4	0.7
LDT	3751-5750	100,000	0.40	5.5	<u>0.97(10)</u> n/a
Diesel LDT (Option 1)	3751-5750	100,000	0.40	5.5	1.5

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
"n/a" means not applicable.
- (2) In order to demonstrate compliance with a non-methane hydrocarbon emission standard, hydrocarbon emissions shall be measured in accordance with the "California Non-Methane Hydrocarbon Test Procedures." For ~~methanol~~ alcohol-fueled vehicles certifying to these standards, including fuel-flexible-fueled vehicles when certifying on methanol or ethanol, "Non-Methane Hydrocarbons" shall mean "Organic Material Non-Methane Hydrocarbon Equivalent" (or "OMNMHCE").
- (3) The maximum projected emissions of oxides of nitrogen measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall be not greater than 1.33 times the applicable passenger car standards and 2.00 times the applicable light-duty truck standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.
- (4) Small volume manufacturers may choose to certify to an optional 0.7 g/mi NOx standard for the 1995 model year only, pursuant to the conditions set forth in Title 13, California Code of Regulations, Sections 1960.1 (f)(1) and 1960.1.5.
- (5) Diesel passenger cars and light-duty trucks certifying to these standards are subject to a particulate exhaust emission standard of 0.08 g/mi, determined on a 50,000 mile durability vehicle basis.
- (6) For gaseous-fueled vehicles certifying to these standards, the calculation procedures provided in Appendix V shall be used for determining emissions and fuel economy.

- (7) For all vehicles, except those certifying to optional diesel standards, in-use compliance with the exhaust emission standards shall be limited to vehicles with less than 75,000 miles.
- (8) For the 1995 and 1996 model years, all manufacturers, except those certifying to optional diesel standards, are permitted alternative in-use compliance. Alternative in-use compliance is permitted for 60% of a manufacturer's vehicles in the 1995 model year and 20% of a manufacturer's vehicles in the 1996 model year. For the 1995 and 1996 model years, small volume manufacturers only are permitted alternative in-use compliance for 100% of the fleet. The percentages shall be applied to the manufacturers' total projected sales of California-certified passenger cars and light-duty trucks certified to the emission standards in this Section 3.f. of these test procedures for the model year. "Alternative in-use compliance" shall consist of the following:
- a. For all passenger cars and those light-duty trucks from 0-3750 lbs., loaded vehicle weight, except those diesel vehicles certifying to optional 100,000 mile standards, in-use compliance standards shall be 0.32 g/mi non-methane hydrocarbon and 5.2 g/mi carbon monoxide for 50,000 miles.
 - b. For light-duty trucks from 3751-5750 lbs., loaded vehicle weight, except those diesel light-duty trucks certifying to optional 100,000 mile standards, in-use compliance standards shall be 0.41 g/mi non-methane hydrocarbon and 6.7 g/mi carbon monoxide for 50,000 miles.
 - c. In-use compliance standards shall be waived beyond 50,000 miles.
- (9) All passenger cars and light-duty trucks, except those diesel vehicles certifying to optional standards, are subject to non-methane hydrocarbon, carbon monoxide, and oxides of nitrogen standards determined on a 50,000 mile durability basis and non-methane hydrocarbon and carbon monoxide standards determined on a 100,000 mile durability basis.
- (10) All 1996 and subsequent model-year PCs and LDTs shall comply with the applicable 100,000 mile standards for NOx..
- (11) Each manufacturer shall certify PCs or LDTs to the exhaust emission standards of Sections 3.f. and 3.g. of these test procedures, or as Zero-Emission Vehicles, such that the manufacturer's fleet average NMOG values for California-certified PCs and LDTs from 0-3750 lbs. Loaded Vehicle Weight (or "LVW"), and LDTs from 3751-5750 lbs. LVW produced and delivered for sale in California are less than or equal to the requirement for the corresponding Model Year, Vehicle Type, and LVW Class in Section 3.h. of these test procedures.

g. The exhaust emissions from new 1992 and subsequent model-year transitional low-emission vehicles, low-emission vehicles, and ultra-low-emission vehicles shall not exceed:

EXHAUST MASS EMISSION STANDARDS
FOR TRANSITIONAL LOW-EMISSION VEHICLES, LOW-EMISSION VEHICLES,
AND ULTRA-LOW-EMISSION VEHICLES IN PASSENGER CAR
AND LIGHT-DUTY TRUCK VEHICLE CLASSES (6)(7)(8)(9)
["grams per mile" (or "g/mi")]

<u>Vehicle Type</u> (1)	<u>Loaded Vehicle Weight</u> (lbs.)	<u>Durability Vehicle Basis</u> (mi)	<u>Vehicle Emission Category</u> (2)	<u>Non-Methane Organic Gases</u> (3)(4)	<u>Carbon Monoxide</u>	<u>Oxides of Nitrogen</u> (5)
PC and LDT	All 0-3750	50,000	TLEV	0.125 (0.188)	3.4 (3.4)	0.4 (0.4)
			LEV	0.075 (0.100)	3.4 (3.4)	0.2 (0.3)
			ULEV	0.040 (0.058)	1.7 (2.6)	0.2 (0.3)
		100,000	TLEV	0.156	4.2	0.6
			LEV	0.090	4.2	0.3
			ULEV	0.055	2.1	0.3
	LDT 3751-5750	50,000	TLEV	0.160 (0.238)	4.4 (4.4)	0.7 (0.7)
			LEV	0.100 (0.128)	4.4 (4.4)	0.4 (0.5)
			ULEV	0.050 (0.075)	2.2 (3.3)	0.4 (0.5)
		100,000	TLEV	0.200	5.5	0.9
			LEV	0.130	5.5	0.5
			ULEV	0.070	2.8	0.5

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
- (2) "TLEV" means transitional low-emission vehicle.
"LEV" means low-emission vehicle.
"ULEV" means ultra-low-emission vehicle.
- (3) "Non-Methane Organic Gases" (or "NMOG") shall mean the total mass of oxygenated and non-oxygenated hydrocarbon emissions. To demonstrate compliance with an NMOG standard, NMOG emissions shall be measured in accordance with the "California Non-Methane Organic Gas Test Procedures" as adopted July 12, 1991. For TLEVs, LEVs, and ULEVs certified to operate on any fuel other than conventional gasoline, including fuel-flexible and dual-fuel vehicles when certifying on any fuel other than conventional gasoline, manufacturers shall multiply the exhaust NMOG certification levels mass emission levels at 50,000 and 100,000 miles by the applicable reactivity adjustment factor set forth in Section 13 of these test procedures, or established by the Executive Officer pursuant to Appendix VIII of these test procedures. In addition, natural gas (NG) vehicles certifying to TLEV, LEV or ULEV standards shall calculate a reactivity-adjusted methane exhaust emission value by multiplying the methane exhaust certification level

by the applicable methane reactivity adjustment factor set forth in section 13 of these test procedures. The product of the exhaust NMOG certification levels mass emission levels and the reactivity adjustment factor shall be compared with the exhaust NMOG mass emission standards established for the particular vehicle emission category and fuel to determine compliance. For NG vehicles, the reactivity-adjusted NMOG value shall be added to the reactivity-adjusted methane value and then compared to the exhaust NMOG mass emission standards established for the particular vehicle emission category to determine compliance.

- a. Each manufacturer shall certify PCs or LDTs to meet the exhaust mass emission standards for TLEVs, LEVs, ULEVs, or to the exhaust emission standards of Sections 3.b., 3.e., or 3.f. of these test procedures, or as Zero-Emission Vehicles such that the manufacturer's fleet average NMOG values for California-certified PCs and LDTs from 0-3750 lbs. "Loaded Vehicle Weight" (or "LVW"), and LDTs from 3751-5750 lbs. LVW sold produced and delivered for sale in California are less than or equal to the requirement for the corresponding Model Year, Vehicle Type, and LVW Class in Section 3.h. of these test procedures.
- (4) Fuel-flexible and dual-fuel PCs and LDTs from 0-5750 lbs. LVW shall be certified to exhaust mass emission standards for NMOG established for the operation of the vehicle on any available fuel other than ~~conventional~~ gasoline, and ~~conventional~~ gasoline as specified in Section 9.a.1. of these test procedures.
- a. For TLEVs, LEVs, and ULEVs, when certifying for operation on a fuel other than ~~conventional~~ gasoline, manufacturers shall multiply the exhaust NMOG mass certification emission levels by the applicable reactivity adjustment factor. In addition to multiplying the exhaust NMOG certification levels by the applicable reactivity adjustment factor, NG vehicles shall multiply the exhaust methane certification level by the applicable methane reactivity adjustment factor and add that value to the reactivity-adjusted NMOG value. The certification levels for fuel-flexible or dual-fuel vehicles when certifying on gasoline shall not be multiplied by a reactivity adjustment factor.
 - b. For PCs and LDTs from 0-3750 lbs. LVW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on ~~conventional~~ gasoline shall be:
 - (i) For TLEVs, 0.25 g/mi and 0.31 g/mi for 50,000 and 100,000 miles, respectively.
 - (ii) For LEVs, 0.125 g/mi and 0.156 g/mi for 50,000 and 100,000 miles, respectively.
 - (iii) For ULEVs, 0.075 g/mi and 0.090 g/mi for 50,000 and 100,000 miles, respectively.
 - c. For LDTs from 3751-5750 lbs. LVW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on ~~conventional~~ gasoline shall be:
 - (i) For TLEVs, 0.32 g/mi and 0.40 g/mi for 50,000 and 100,000 miles, respectively.
 - (ii) For LEVs, 0.160 g/mi and 0.200 g/mi for 50,000 and 100,000 miles, respectively.
 - (iii) For ULEVs, 0.100 g/mi and 0.130 g/mi for 50,000 and 100,000 miles, respectively.
- (5) The maximum projected emissions of "Oxides of Nitrogen" (or "NO_x") measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR 600

- Subpart B) shall not be greater than 1.33 times the applicable light-duty vehicle standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.
- (6) The standards in parentheses are intermediate in-use compliance standards for 50,000 miles. For PCs and LDTs from 0-5750 lbs. LVW, including fuel-flexible and dual-fuel vehicles when operating on any available fuel other than conventional gasoline, intermediate in-use compliance standards shall apply to TLEVs through the 1995 model year and to LEVs and ULEVs through the 1998 model year. In-use compliance with standards beyond 50,000 miles shall be waived through the 1995 model year for TLEVs, and through the 1998 model year for LEVs and ULEVs.
- For TLEVs, LEVs, and ULEVs designed to operate on any fuel other than conventional gasoline, including fuel-flexible and dual-fuel vehicles when operating on any fuel other than conventional gasoline, exhaust NMOG emission results levels shall be multiplied by the reactivity adjustment factor to determine compliance with intermediate in-use compliance standards for NMOG. In addition to multiplying the exhaust NMOG certification levels by the applicable reactivity adjustment factor, NG vehicles shall multiply the exhaust methane certification level by the applicable methane reactivity adjustment factor and add that value to the reactivity-adjusted NMOG value.
 - For fuel-flexible and dual-fuel PCs and LDTs from 0-3750 lbs. LVW, intermediate in-use compliance standards for NMOG emissions at 50,000 miles, when the vehicle is operated on conventional gasoline, shall be 0.32 g/mi, 0.188 g/mi and 0.100 g/mi for TLEVs, LEVs and ULEVs, respectively.
 - For fuel-flexible and dual-fuel PCs and LDTs from 3751-5750 lbs. LVW, intermediate in-use compliance standards for NMOG emissions at 50,000 miles, when the vehicle is operated on conventional gasoline, shall be 0.41 g/mi, 0.238 g/mi and 0.128 g/mi for TLEVs, LEVs and ULEVs, respectively.
- (7) Manufacturers of diesel vehicles shall also certify to particulate standards at 100,000 miles. For all PCs and LDTs from 0-5750 lbs, the particulate standard is 0.08 g/mi, 0.08 g/mi, and 0.04 g/mi for TLEVs, LEVs, and ULEVs, respectively.
- (8) Manufacturers shall demonstrate compliance with the above standards for NMOG, carbon monoxide and NOx at 50 degrees F, according to the procedure specified in Section 11k of these test procedures. Hybrid electric vehicles, natural gas, and diesel-fueled vehicles shall be exempt for 50 degrees F test requirements. California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as Adopted May 20, 1987, Amended: December 20, 1989, Amended: January 22, 1990, Amended: December 26, 1990, Amended: July 12, 1991 and last amended INSERT. For diesel vehicles, compliance with the particulate standard shall also be demonstrated as specified in Section 11k of the foregoing test procedures.
- (9) In-use compliance testing shall be limited to vehicles with fewer than 75,000 miles.
- (10) Deterioration factors for hybrid electric vehicles shall be based on the emissions and mileage accumulation of the auxiliary power unit. For certification purposes only, Type A hybrid electric vehicles shall

demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors), and demonstrating compliance with 100,000 mile emission standards shall not be required. For certification purposes only, Type B hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors) and 100,000 mile emission standards (using 75,000 mile deterioration factors). For certification purposes only, Type C hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors) and 100,000 mile emission standards (using 100,000 mile deterioration factors).

h. The fleet average non-methane organic gas exhaust mass emission values from the a manufacturer's sales of passenger cars and light-duty trucks produced and delivered for sale in California by a manufacturer each model year shall not exceed:

FLEET AVERAGE NON-METHANE ORGANIC GAS EXHAUST MASS EMISSION REQUIREMENTS FOR
LIGHT-DUTY VEHICLE WEIGHT CLASSES (7)(8)(9)
["grams per mile" (or "g/mi")]

<u>Vehicle</u> <u>Type</u> <u>(1)</u>	<u>Loaded</u> <u>Vehicle</u> <u>Weight</u> <u>(lbs.)</u>	<u>Durability</u> <u>Vehicle</u> <u>Basis</u> <u>(mi)(7)</u>	<u>Model</u> <u>Year</u>	<u>Fleet Average</u> <u>Non-Methane</u> <u>Organic Gases</u> <u>(2)(3)(4)(5)(6)</u>
PC and LDT	All 0-3750	50,000	1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 and subsequent	0.250 0.231 0.225 0.202 0.157 0.113 0.073 0.070 0.068 0.062
LDT	3751-5750	50,000	1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 and subsequent	0.320 0.295 0.287 0.260 0.205 0.150 0.099 0.098 0.095 0.093

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
"MDV" means medium-duty vehicles.
- (2) "Non-Methane Organic Gases" (or "NMOG") shall mean the total mass of oxygenated and non-oxygenated hydrocarbon emissions.
- (3) For the purpose of calculating fleet average NMOG values, vehicles which have no tailpipe emissions but use fuel fired heaters and which are not certified as ZEVs shall be treated as Type A Hybrid Electric Vehicles Ultra-Low-Emission Vehicles (or "Type A HEV ULEVs").
manufacturer may adjust the certification levels of hybrid electric vehicles (or "HEVs") based on the range of the HEV without the use of the engine. For the purpose of calculating the adjusted NMOG emission levels, the following definitions shall apply.
"Type A HEV" shall mean an HEV which achieves a minimum range of 60 miles over the Dynamometer Driving Cycle as defined by the "Federal Highway Fuel Economy Test Procedure" (HWFET; 40 CFR Part 600 Subpart B) without the use of an auxiliary engine. Use of vehicle accessories cannot lower the range below 60 miles. This definition shall also apply to vehicles which have no tailpipe emissions, but

use fuel fired heaters, regardless of the operating range of the vehicle.

"Type B HEV" shall mean an HEV which achieves a range of 40 - 59 miles over the Dynamometer Driving Cycle as defined by the "Federal Highway Fuel Economy Test Procedure" (HWFET; 40 CFR Part 600 Subpart B) without the use of an auxiliary engine. Use of vehicle accessories cannot lower the range below 40 miles.

"Type C HEV" shall mean an HEV which achieves a range of 0 - 39 miles over the Dynamometer Driving Cycle as defined by the "Federal Highway Fuel Economy Test Procedure" (HWFET; 40 CFR Part 600 Subpart B) without the use of an auxiliary engine, an HEV which allows the operators of the vehicle to control the engine time and modes of operation either directly or indirectly, an HEV which can be operated solely through the use of the engine, and all other HEVs excluding "Type A" and "Type B" HEVs.

- (4) Each manufacturer's fleet average NMOG value for the total number of PCs and LDTs from 0-3750 lbs. "Loaded Vehicle Weight" (or "LVW") sold produced and delivered for sale in California shall be calculated in units of g/mi NMOG according to the following equation, where the term "Produced" means produced and delivered for sale in California as:
- $$\frac{\{[(\text{No. of Vehicles Certified to the Exhaust Emission Standards in Section 3.b. of these test procedures and Produced Sold}) \times (0.39)] + [(\text{No. of Vehicles Certified to the Exhaust Emission Standards in Section 3.e. of these test procedures and Produced}) \times (0.25)] + [(\text{No. of Vehicles Certified to the Exhaust Emission Standards in Section 3.f. of these test procedures and Produced Sold}) \times (0.25)] + [(\text{No. of Transitional Low-Emission Vehicles (or "TLEVs") Produced Sold excluding HEVs}) \times (0.125)] + [(\text{No. of Low-Emission Vehicles (or "LEVs") Produced Sold excluding HEVs}) \times (0.075)] + [(\text{No. of Ultra-Low-Emission Vehicles (or "ULEVs") Produced Sold excluding HEVs}) \times (0.040)] + (\text{HEV contribution factor})\}}{[\text{Total No. of Vehicles Produced Sold, Including Zero-Emission Vehicles ("ZEVs") and HEVs}]}$$

- a. "HEV contribution factor" shall mean the NMOG emission contribution of HEVs to a manufacturer's fleet average NMOG value. The HEV contribution factor shall be calculated in units of g/mi as follows, where the term "Produced" means produced and delivered for sale in California:

HEV contribution factor = $\{[\text{No. of "Type A HEV" TLEVs Produced Sold}] \times (0.100) + [\text{No. of "Type B HEV" TLEVs Produced Sold}] \times (0.113) + [\text{No. of "Type C HEV" TLEVs Produced Sold}] \times (0.125)\} + \{[\text{No. of "Type A HEV" LEVs Produced Sold}] \times (0.057) + [\text{No. of "Type B HEV" LEVs Produced Sold}] \times (0.066) + [\text{No. of "Type C HEV" LEVs Produced Sold}] \times (0.075)\} + \{[\text{No. of "Type A HEV" ULEVs Produced Sold}] \times (0.020) + [\text{No. of "Type B HEV" ULEVs Produced Sold}] \times (0.030) + [\text{No. of "Type C HEV" ULEVs Produced Sold}] \times (0.040)\}$

- b. ZEVs classified as LDTs 3751-5750 lbs. LVW which have been counted toward the ZEV requirement for PCs and LDTs 0-3750 lbs. LVW as specified in note (9) shall be included in the above equation of note (4) calculation may not be included in the calculation of vehicle emission credits for medium-duty vehicles in footnote 12 of Section j of these test procedures.
- c. Beginning with the 1996 model year, manufacturers that produce and deliver for sale in California LDTs 0-3750 lbs. LVW that are certified to the Tier I exhaust emission standards in 40 CFR

86.094-8 and 86.094-9 shall add the following term to the numerator of the fleet average NMOG equation in note (4) and calculate their fleet average values accordingly:

[(No. of Vehicles Certified to federal Tier I exhaust emission standards and Produced) x (0.25)].

- (5) Manufacturers that certify LDTs from 3751-5750 lbs. LVW, shall calculate a fleet average NMOG value in units of g/mi NMOG according to the following equation, where the term "Produced" means produced and delivered for sale in California as: [(No. of Vehicles Certified to the Exhaust Emission Standards in Section 3.b. of these test procedures and Produced Sold x (0.50)) + [(No. of Vehicles Certified to the Phase-In Exhaust Emission Standards in Section 3.e. of these test procedures and Produced) x (0.32)] + [(No. of Vehicles Certified to the Exhaust Emission Standards in Section 3.f. of these test procedures and Produced Sold) x (0.32)] + [(No. of TLEVs Produced Sold excluding HEVs) x (0.160)] + [(No. of LEVs Produced Sold excluding HEVs) x (0.100)] + [(No. of ULEVs Produced Sold excluding HEVs) x (0.050)] + (HEV contribution factor)]/(Total No. of Vehicles Produced Sold, Including ZEVs and HEVs).

- a. "HEV contribution factor" shall mean the NMOG emission contribution of HEVs to a manufacturer's fleet average NMOG value. The HEV contribution factor shall be calculated in units of g/mi as follows, where the term "Produced" means produced and delivered for sale in California:

HEV contribution factor = [(No. of "Type A HEV" TLEVs Produced Sold) x (0.130) + [No. of "Type B HEV" TLEVs Produced Sold] x (0.145) + [No. of "Type C HEV" TLEVs Produced Sold] x (0.160)] + [(No. of "Type A HEV" LEVs Produced Sold) x (0.075) + [No. of "Type B HEV" LEVs Produced Sold] x (0.087) + [No. of "Type C HEV" LEVs Produced Sold] x (0.100)] + [(No. of "Type A HEV" ULEVs Produced Sold) x (0.025) + [No. of "Type B HEV" ULEVs Produced Sold] x (0.037) + [No. of "Type C HEV" ULEVs Produced Sold] x (0.050)]

- b. Only ZEVs which have been certified as LDTs 3751-5750 lbs. LVW and which have not been counted toward the ZEV requirements for PCs and LDTs 0-3750 lbs. LVW as specified in note (9) shall be included in the equation of note (5). included in the above calculation or in the calculation of footnote 4 may not be included in the calculation of vehicle emission credits for medium-duty vehicles in footnote 12 of Section j of these test procedures.

- c. Beginning with the 1996 model year, manufacturers that produce and deliver for sale in California LDTs 3751-5850 lbs. LVW that are certified to the Tier I exhaust emission standards in 40 CFR 86.094-9 shall add the following term to the numerator of the fleet average NMOG equation in note (5) and calculate their fleet average NMOG values accordingly:

[(No. of Vehicles Certified to federal Tier I exhaust emission standards and Produced and Delivered for Sale in California) x (0.32)]

- (6) As used in this subsection 3.h. of these test procedures, the term "small volume manufacturer" shall mean any vehicle manufacturer with California sales less than or equal to 3000 new PCs, LDTs, and MDVs light- and medium-duty vehicles per model year based on the average number of vehicles sold by the manufacturer each model year from 1989 to 1991, except as otherwise noted below. For manufacturers certifying

for the first time in California, model-year sales shall be based on projected California sales. In 2000 and subsequent model years, small volume manufacturers shall comply with the fleet average NMOG requirements set forth below.

- a. Prior to the model year 2000, compliance with the specified fleet average NMOG requirements shall be waived.
- b. In 2000 and subsequent model years, small volume manufacturers shall not exceed a fleet average NMOG value of 0.075 g/mi for PCs and LDTs from 0-3750 lbs. LVW calculated in accordance with note (4) for 50,000 miles.
- c. In 2000 and subsequent model years, small volume manufacturers shall not exceed a fleet average NMOG value of 0.100 g/mi for LDTs from 3751-5750 lbs. LVW calculated in accordance with note (5) for 50,000 miles.
- d. If a manufacturer's average California sales exceeds 3000 units of new PCs, LDTs, and MDVs based on the average number of vehicles sold for any three consecutive model years, the manufacturer shall no longer be treated as a small volume manufacturer and shall comply with the fleet average requirements applicable for larger manufacturers as specified in Section 3.h. of these test procedures beginning with the fourth model year after the last of the three consecutive model years.
- e. If a manufacturer's average California sales falls below 3000 units of new PCs, LDTs, and MDVs based on the average number of vehicles sold for any three consecutive model years, the manufacturer shall be treated as a small volume manufacturer and shall be subject to requirements for small volume manufacturers as specified in Section 3.h. of these test procedures beginning with the next model year.

(7) In 1992 4 and subsequent model years, manufacturers that achieve fleet average NMOG values lower than the fleet average NMOG requirement for the corresponding model year shall receive credits in units of g/mi NMOG determined as: $\{[(\text{Fleet Average NMOG Requirement}) - (\text{Manufacturer's Fleet Average NMOG Value})] \times (\text{Total No. of Vehicles Produced and Delivered for Sale in California Sold, Including ZEVs and HEVs})\}$.

- a. Manufacturers with fleet average NMOG values greater than the fleet average requirement for the corresponding model year shall receive debits in units of g/mi NMOG equal to the amount of negative credits determined by the aforementioned equation. For any given model year, the total g/mi NMOG credits or debits earned for PCs and LDTs 0-3750 lbs. LVW and for LDTs 3751-5750 lbs. LVW shall be summed together. The resulting amount shall constitute the g/mi NMOG credits or debits accrued by the manufacturer for the model year.
- b. For the 1994 through 1997 model years, manufacturers shall equalize emission debits within three model years and prior to the end of the 1998 model year by earning g/mi NMOG emission credits in an amount equal to their g/mi NMOG debits, or by submitting a commensurate amount of g/mi NMOG credits to the Executive Officer that were earned previously or acquired from another manufacturer. For 1998 and subsequent model years, manufacturers shall equalize emission debits by the end of the following model year. If emission debits are not equalized within the specified time period, the manufacturer shall be subject to the Health and Safety Code section 43211 civil penalty applicable to a manufacturer which

- sells a new motor vehicle that does not meet the applicable emission standards adopted by the state board. The cause of action shall be deemed to accrue when the emission debits are not equalized by the end of the specified time period. For the purposes of Health and Safety Code section 43211, the number of vehicles not meeting the state board's emission standards shall be determined by dividing the total amount of g/mi NMOG emission debits for the model year by the g/mi NMOG fleet average requirement for PCs and LDTs 0-3750 lbs. LVW applicable for the model year in which the debits were first incurred.
- c. The g/mi NMOG emission credits earned in any given model year shall retain full value through the subsequent model year.
 - d. The g/mi NMOG value of any credits not used to equalize the previous model-year's debit, shall be discounted by 50% at the beginning of second model year after being earned, discounted to 25% of its original value if not used by the beginning of the third model year after being earned, and will have no value if not used by the beginning of the fourth model year after being earned.
 - e. Any g/mi NMOG emission credits earned by a manufacturer may be applied toward either the fleet average requirement for passenger cars and light-duty trucks from 0-3750 lbs. LVW, or to the fleet average requirement for light-duty trucks from 3751-5750 lbs. LVW, at the manufacturer's discretion.
- (8) Manufacturers that sell produce and deliver for sale in California vehicles certified to the phase-in complying with the exhaust emission standards in Section 3.e. of these test procedures or vehicles certified to the exhaust emission standards in Sections 3.f. or 3.g. of these test procedures and/or ZEVs in the 1992 and 1993 model years, shall receive emission credits for the sale of these vehicles as determined by the equations in footnotes (4), or (5), depending upon Vehicle Weight Class, and footnote (7).
- a. For PCs and LDTs from 0-3750 lbs. LVW, the fleet average NMOG requirement for calculating a manufacturer's emission credits shall be 0.390 and 0.334 g/mi NMOG for vehicles certified in the 1992 and 1993 model years, respectively.
 - b. For LDTs from 3751-5750 lbs. LVW, the fleet average NMOG requirement for calculating a manufacturer's emission credits shall be 0.500 and 0.428 g/mi NMOG for vehicles certified in the 1992 and 1993 model years, respectively.
 - c. Emission credits earned prior to the 1994 model year shall be considered as earned in the 1994 model year and discounted in accordance with the schedule specified in footnote (7).
- (9) While meeting the fleet average requirements, each manufacturer shall certify, produce, and deliver for sale in California its sales fleet of passenger cars and light-duty trucks from 0-3750 lbs. LVW shall be composed of at least 2% ZEVs each model year from 1998 through 2000, 5% ZEVs in 2001 and 2002, and 10% ZEVs in 2003 and subsequent model years. These percentages shall be applied to the manufacturer's total production of PCs and LDTs 0-3750 lbs. LVW delivered for sale in California.
- a. Manufacturers which produce for sale in California more ZEVs than required in a given model year shall earn ZEV credits, which shall have units of g/mi NMOG. The amount of ZEV credits earned shall be equal to the number of ZEVs required to be produced and delivered for sale in California for the model year subtracted from the

- number of ZEVs actually produced and delivered for sale in the model year and then multiplied by the fleet average requirement for PCs and LDTs 0-3750 lbs. LVW for that model year. All ZEV credits earned prior to the 1998 model year shall be treated as if earned in the 1998 model year and shall be discounted in accordance with notes (7)c and (7)d.
- a b. A manufacturer may meet the ZEV requirements in any given model year by submitting to the Executive Officer a commensurate amount of ZEV credits, g/mi NMOG emission credits earned exclusively from the sale of ZEVs. These credits may be earned previously by the manufacturer or acquired from another manufacturer. The amount of ZEV credits required to be submitted shall be calculated by subtracting the number of ZEVs produced and delivered for sale in California by the manufacturer for the model year from the number of ZEVs required to be produced by the manufacturer for the model year and then multiplying by the fleet average requirement for PCs and LDTs 0-3750 lbs. LVW for that model year.
 - b c. Manufacturers which sell certify, produce, and deliver for sale in California fewer ZEVs than required in a given model year shall make up the deficit by the end of the next model year, by selling an additional number of ZEVs equal to their deficit or by submitting to the Executive Officer a commensurate amount of ZEV credits, g/mi NMOG credits earned exclusively from the sale of ZEVs. The amount of ZEV credits required to be submitted shall be calculated by subtracting the number of ZEVs actually produced and delivered for sale in California by the manufacturer for the model year from the number of ZEVs required to be produced by the manufacturer for the model year and then multiplying by the fleet average requirements for PCs and LDTs 0-3750 lbs. LVW for the model year in which the deficit is incurred.
 - d. Any manufacturer which fails to produce and deliver for sale in California the required number of ZEVs or submit an appropriate amount of ZEV credits and does not make up ZEV deficits within the specified time period shall be subject to the Health and Safety Code section 43211 civil penalty applicable to a manufacturer which sells a new motor vehicle that does not meet the applicable emission standards adopted by the state board. The cause of action shall be deemed to accrue when the ZEV deficits are not balanced by the end of the specified time period. For the purposes of Health and Safety Code section 43211, the number of vehicles not meeting the state board's standards shall be calculated according to the following equation: (No. of ZEVs required to be produced and delivered for sale in California for the model year) - (No of ZEVs actually produced and delivered for sale in California for the model year) - [(Amount of ZEV credits submitted for the model year) / (the fleet average requirement for PCs and LDTs 0-3750 lbs. LVW for the model year)].
 - e. ZEVs classified as MDVs or as LDTs 3751-5750 lbs. LVW may be counted toward the ZEV requirement for PCs and LDTs 0-3750 lbs. LVW and included in the calculation of ZEV credits as specified in note (9)a., if the manufacturer so designates.
 - e f. Small volume manufacturers shall not be required to meet the percentage ZEV requirements. However, small volume manufacturers may earn and market credits for ZEVs they produce and sell deliver for sale in California.

d g. Intermediate volume manufacturers shall not be required to meet the percentage ZEV requirements before the 2003 model year.

i. The exhaust emissions from new 1995 and subsequent model medium-duty vehicles shall not exceed:

1995 AND SUBSEQUENT MODEL-YEAR
MEDIUM-DUTY VEHICLE EXHAUST EMISSIONS STANDARDS (1)(2)(3)(7)(8)
(grams per mile)

Test Weight(lbs.)	Durability Vehicle Basis(mi)	Non-Methane Hydrocarbons(4)	Carbon Monoxide	Oxides of Nitrogen(5)	Particulates (6)
0-3,750	50,000	0.25	3.4	0.4	n/a
0-3,750	120,000	0.36	5.0	0.55	0.08
3,751-5,750	50,000	0.32	4.4	0.7	n/a
3,751-5,750	120,000	0.46	6.4	0.98	0.10
5,751-8,500	50,000	0.39	5.0	1.1	n/a
5,751-8,500	120,000	0.56	7.3	1.53	0.12
8,501-10,000	50,000	0.46	5.5	1.3	n/a
8,501-10,000	120,000	0.66	8.1	1.81	0.12
10,001-14,000	50,000	0.60	7.0	2.0	n/a
10,001-14,000	120,000	0.86	10.3	2.77	0.12

- (1) "n/a" means not applicable.
"Test Weight" shall mean the average of the vehicle's curb weight and gross vehicle weight.
- (2) Manufacturers have the option of certifying engines used in incomplete and diesel medium-duty vehicles from 8501-14,000 pounds gross vehicle weight to the heavy-duty engine standards and test procedures set forth in Section 1956.8(e), Title 13, California Code of Regulations. Manufacturers certifying incomplete or diesel medium-duty vehicles to the heavy-duty engine standards and test procedures shall specify, in the application for certification, an in-use compliance test procedure, as provided in Sections 2139(c), Title 13, California Code of Regulations.
- (3) For the 1995 model year only, manufacturers of medium-duty vehicles may certify a maximum of 50 percent of their vehicles to the applicable 1994 model year standards and test procedures. The percentage shall be based upon each manufacturer's projected sales of California-certified medium-duty vehicles. For the 1995 model year only, small volume manufacturers may certify 100 percent of their vehicles to the applicable 1994 model-year standards and test procedures.
- (4) For methane+ alcohol-fueled vehicles certifying to these standards, including fuel-flexible-fueled vehicles when certifying on methanol or ethanol, "Non-Methane Hydrocarbons" shall mean "Organic Material Non-Methane Hydrocarbon Equivalent" (or "OMNMHCE").
- (5) The maximum projected emissions of oxides of nitrogen measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall be not greater than 2.00 times the applicable medium-duty vehicle standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.

- (6) Particulate standards are only applicable for diesel vehicles and shall be determined on a 120,000 mile basis.
- (7) In-use compliance testing shall be limited to vehicles with less than 90,000 miles. For the 1995 through 1997 model years, alternative in-use compliance is available for medium-duty vehicle manufacturers. A manufacturer may use alternative in-use compliance for up to 100 percent of its fleet in the 1995 and 1996 model years and up to 50 percent of its fleet in the 1997 model year. Small volume manufacturers only may use alternative in-use compliance for up to 100 percent of their fleet in the 1995 through 1997 model years. The percentages shall be determined only from the manufacturer's projected California sales of medium-duty vehicles. For vehicles certified to the standards and test procedures of this subsection, "alternative in-use compliance" shall consist of an in-use allowance of 25 percent over the applicable 1995 model-year hydrocarbon, carbon monoxide, and oxides of nitrogen 50,000 mile emission standards and a waiver of the emission standards beyond 50,000 miles.
- (8) All medium-duty vehicles, except diesel-fueled vehicles and those incomplete and diesel vehicles certifying to heavy-duty engine test procedures, are subject to 50,000 mile and 120,000 mile non-methane hydrocarbon, carbon monoxide, and oxides of nitrogen standards. Diesel-fueled vehicles shall be subject to 120,000 mile non-methane hydrocarbon, carbon monoxide, oxides of nitrogen, and particulate standards only.

j. The exhaust emission levels from new 1992 and subsequent model-year medium-duty low-emission vehicles and ultra-low-emission vehicles shall not exceed:

**EXHAUST EMISSION STANDARDS FOR LOW-EMISSION VEHICLES
AND ULTRA-LOW-EMISSION VEHICLES IN THE
MEDIUM-DUTY VEHICLE WEIGHT CLASS (8)(9)(10)(11)(12)(13)(14)(15)(16)
[grams per mile (or "g/mi")]**

Test Weight (lbs.) (1)	Durability Vehicle Basis (mi)	Vehicle Emission Category (2)	Non-Methane Organic Gases (3)(4)	Carbon Monoxide	Oxides of Nitrogen (5)	Particulates (6)(7)
0-3750	50,000	LEV	0.125 (0.188)	3.4 (3.4)	0.4 (0.4)	n/a
		ULEV	0.075 (0.100)	1.7 (2.6)	0.2 (0.3)	n/a
	120,000	LEV	0.180	5.0	0.6	0.08
		ULEV	0.107	2.5	0.3	0.04
3751-5750	50,000	LEV	0.160 (0.238)	4.4 (4.4)	0.7 (0.7)	n/a
		ULEV	0.100 (0.128)	2.2 (3.3)	0.4 (0.5)	n/a
	120,000	LEV	0.230	6.4	1.0	0.10
		ULEV	0.143	3.2	0.5	0.05
5751-8500	50,000	LEV	0.195 (0.293)	5.0 (5.0)	1.1 (1.1)	n/a
		ULEV	0.117 (0.156)	2.5 (3.8)	0.6 (0.8)	n/a
	120,000	LEV	0.280	7.3	1.5	0.12
		ULEV	0.167	3.7	0.8	0.06
8501-10000	50,000	LEV	0.230 (0.345)	5.5 (5.5)	1.3 (1.3)	n/a
		ULEV	0.138 (0.184)	2.8 (4.2)	0.7 (1.0)	n/a
	120,000	LEV	0.330	8.1	1.8	0.12
		ULEV	0.197	4.1	0.9	0.06
10,001-14000	50,000	LEV	0.300 (0.450)	7.0 (7.0)	2.0 (2.0)	n/a
		ULEV	0.180 (0.240)	3.5 (5.3)	1.0 (1.5)	n/a
	120,000	LEV	0.430	10.3	2.8	0.12
		ULEV	0.257	5.2	1.4	0.06

- (1) "Test Weight" (or "TW") shall mean the average of the vehicle's curb weight and gross vehicle weight.
- (2) "LEV" means low-emission vehicle.
"ULEV" means ultra-low-emission vehicle.
- (3) "Non-Methane Organic Gases" (or "NMOG") shall mean the total mass of oxygenated and non-oxygenated hydrocarbon emissions. To determine compliance with an NMOG standard, NMOG emissions shall be measured in accordance with "California Non-Methane Organic Gas Test Procedures" as adopted July 12, 1991 and last amended.
 - a. For LEVs and ULEVs certified to operate on any available fuel other than conventional gasoline, including fuel-flexible or dual-fuel vehicles when certifying on a fuel other than conventional gasoline, manufacturers shall multiply the NMOG exhaust mass emission certification levels at 50,000 and 120,000 miles by the applicable reactivity adjustment factor set forth in Section 13 of

these test procedures or established pursuant to Appendix VIII of these test procedures. In addition, NG vehicles certifying to LEV or ULEV standards shall calculate a reactivity-adjusted methane exhaust emission value by multiplying the methane exhaust certification level by the applicable methane reactivity adjustment factor set forth in section 13 of these test procedures. For NG vehicles, the reactivity-adjusted NMOG value shall be added to the reactivity-adjusted methane value and then compared to the exhaust NMOG mass emission standards established for the particular vehicle emission category to determine compliance.

- (4) Fuel-flexible and dual-fuel "Medium-Duty Vehicles" (or "MDVs") from 0-14,000 lbs. TW shall be certified to exhaust mass emission standards for NMOG established for the operation of the vehicle on any fuel other than conventional gasoline, and conventional gasoline.
- a. For LEVs and ULEVs when certifying on the fuel other than gasoline, manufacturers shall multiply the exhaust NMOG certification mass emission levels at 50,000 and 120,000 miles by the applicable reactivity adjustment factor. In addition to multiplying the exhaust NMOG certification levels by the applicable reactivity adjustment factor, NG vehicles shall multiply the exhaust methane certification level by the applicable methane reactivity adjustment factor and add that value to the reactivity-adjusted NMOG value. When certifying on gasoline, the exhaust NMOG certification levels of fuel-flexible and dual-fuel vehicles shall not be multiplied by a reactivity adjustment factor.
 - b. For MDVs from 0-3750 lbs. TW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on conventional gasoline shall be:
 - (i) For LEVs, 0.25 g/mi and 0.36 g/mi for 50,000 and 120,000 miles, respectively.
 - (ii) For ULEVs, 0.125 g/mi and 0.180 g/mi for 50,000 and 120,000 miles, respectively.
 - c. For MDVs from 3751-5750 lbs. TW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on conventional gasoline shall be:
 - (i) For LEVs, 0.32 g/mi and 0.46 g/mi for 50,000 and 120,000 miles, respectively.
 - (ii) For ULEVs, 0.160 g/mi and 0.230 g/mi for 50,000 and 120,000 miles, respectively.
 - d. For MDVs from 5751-8500 lbs. TW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on conventional gasoline shall be:
 - (i) For LEVs, 0.39 g/mi and 0.56 g/mi for 50,000 and 120,000 miles, respectively.
 - (ii) For ULEVs, 0.195 g/mi and 0.280 g/mi for 50,000 and 120,000 miles, respectively.
 - e. For MDVs from 8501-10,000 lbs. TW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on conventional gasoline shall be:
 - (i) For LEVs, 0.46 g/mi and 0.66 g/mi for 50,000 and 120,000 miles, respectively.
 - (ii) For ULEVs, 0.230 g/mi and 0.330 g/mi for 50,000 and 120,000 miles, respectively.

- f. For MDVs from 10,001-14,000 lbs. TW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on conventional gasoline shall be:
- (i) For LEVs, 0.60 g/mi and 0.86 g/mi for 50,000 and 120,000 miles, respectively.
 - (ii) For ULEVs, 0.300 g/mi and 0.430 g/mi for 50,000 and 120,000 miles, respectively.
- (5) The maximum projected emissions of "Oxides of Nitrogen" (or "NOx") measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall not be greater than 2.00 times the applicable MDV standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.
- (6) Particulate standards are only applicable for diesel vehicles and shall be determined on a 120,000 mile basis.
- (7) "n/a" means not applicable.
- (8) Manufacturers have the option of certifying engines used in incomplete and diesel MDVs to the heavy-duty engine standards and test procedures set forth in Section 1956.8(h), Title 13, California Code of Regulations. Manufacturers certifying incomplete or diesel MDVs to the heavy-duty engine standards and test procedures shall specify in the application for certification an in-use compliance procedure as provided in Section 2139(c), Title 13, California Code of Regulations.
- (9) The standards in parenthesis are intermediate in-use compliance standards for 50,000 miles. For MDVs from 0-14,000 lbs. TW, including fuel-flexible and dual-fuel vehicles when operating on any available fuel other than conventional gasoline, intermediate in-use compliance standards shall apply to LEVs and ULEVs through the 1999 model year. In-use compliance with standards beyond 50,000 miles shall be waived through the 1999 model year for LEVs and ULEVs.
- a. For LEVs and ULEVs designed to operate on any available fuel other than conventional gasoline, including fuel-flexible and dual-fuel vehicles when operating on any available fuel other than conventional gasoline, NMOG exhaust mass emission levels results shall be multiplied by the applicable reactivity adjustment factor. In addition to multiplying the exhaust NMOG certification levels by the applicable reactivity adjustment factor, NG vehicles shall multiply the exhaust methane certification level by the applicable methane reactivity adjustment factor and add that value to the reactivity-adjusted NMOG value. For fuel-flexible and dual-fuel vehicles when operating on gasoline, NMOG emission results shall not be multiplied by a reactivity adjustment factor.
 - b. For fuel-flexible and dual-fuel MDVs from 0-3750 lbs. TW, intermediate in-use compliance standards for NMOG emissions at 50,000 miles, when the vehicle is operated on conventional gasoline, shall be 0.32 g/mi and 0.188 g/mi for LEVs and ULEVs, respectively.
 - c. For fuel-flexible and dual-fuel MDVs from 3751-5750 lbs. TW, intermediate in-use compliance standards for NMOG emissions at 50,000 miles, when the vehicle is operated on conventional gasoline, shall be 0.41 g/mi and 0.238 g/mi for LEVs and ULEVs, respectively.
 - d. For fuel-flexible and dual-fuel MDVs from 5751-8500 lbs. TW, intermediate in-use compliance standards for NMOG emissions at

- 50,000 miles, when the vehicle is operated on conventional gasoline, shall be 0.49 g/mi and 0.293 g/mi for LEVs and ULEVs, respectively.
- e. For fuel-flexible and dual-fuel MDVs from 8501-10,000 lbs. TW, intermediate in-use compliance standards for NMOG emissions at 50,000 miles, when the vehicle is operated on conventional gasoline, shall be 0.58 g/mi and 0.345 g/mi for LEVs and ULEVs, respectively.
 - f. For fuel-flexible and dual-fuel MDVs from 10,001-14,000 lbs. TW, intermediate compliance standards for NMOG emissions at 50,000 miles, when the vehicle is operated on conventional gasoline, shall be 0.75 g/mi and 0.450 g/mi for LEVs and ULEVs, respectively.
- (10) Each manufacturer's MDV fleet shall be defined as the total number of California certified MDVs from 0-14,000 lbs. TW sold produced and delivered for sale in California.
- a. Manufacturers of MDVs shall certify an equivalent of 25% of their MDV fleet sales to LEV standards in the 1998 model year, 50% of their MDV fleet sales to LEV standards in the 1999 model year, 75% of their MDV fleet sales to LEV standards in the 2000 model year, 95% of their MDV fleet sales to LEV standards in the 2001 model year, 90% of their MDV fleet sales to LEV standards in the 2002 model year, and 85% of their MDV fleet sales to LEV standards in the 2003 and subsequent model years.
 - b. Manufacturers of MDVs shall certify an equivalent of 2% of their MDV fleet sales to ULEV standards in each model year from 1998 to 2000, 5% of their MDV fleet sales to ULEV standards in the 2001 model year, 10% of their MDV fleet sales to ULEV standards in the 2002 model year, and 15% of their MDV fleet sales to ULEV standards in the 2003 and subsequent model years.
 - c. The percentages shall be applied to the manufacturers' total production sales of California-certified medium-duty vehicles delivered for sale in California.
 - d. These requirements shall not apply to small volume manufacturers. Small volume manufacturers shall comply with the requirements of note (15) below.
- (11) For the purpose of calculating "Vehicle Equivalent Credits" (or "VECs"), vehicles which have no tailpipe emissions but use fuel fired heaters and which are not certified as ZEVs shall be treated as Type A Hybrid Electric Vehicle Ultra-Low-Emission Vehicles (or "Type A HEV ULEVs"). the contribution of hybrid electric vehicles (or "HEVs") will be calculated based on the range of the HEV without the use of the engine. For the purpose of calculating the contribution of HEVs to the VECs, the following definitions shall apply.
- "Type A HEV" shall mean a hybrid electric vehicle (or "HEV") which achieves a minimum range of 60 miles over the Dynamometer Driving Cycle as defined by the "Federal Highway Fuel Economy Test Procedure" (HWFET; 40 CFR Part 600 Subpart B) without the use of the engine. Use of vehicle accessories cannot lower the battery-only range below 60 miles. This definition shall also apply to vehicles which have no tailpipe emissions, but use fuel fired heaters, regardless of the operating range of the vehicle.
- "Type B HEV" shall mean an HEV which achieves a range of 40 - 59 miles over the Dynamometer Driving Cycle as defined by the "Federal Highway Fuel Economy Test Procedure" (HWFET; 40 CFR Part 600

Subpart B) without the use of the engine. Use of vehicle accessories cannot lower the battery-only range below 40 miles. "Type C HEV" shall mean an HEV which achieves a range of 0 - 39 miles over the Dynamometer Driving Cycle as defined by the "Federal Highway Fuel Economy Test Procedure" (HWFET, 40 CFR Part 600 Subpart B) without the use of an auxiliary engine, an HEV which allows the operator of the vehicle to control the engine time and modes of operation either directly or indirectly, an HEV which can be operated solely through the use of the engine, and all other HEVs excluding "Type A" and "Type B" HEVs.

- (12) In 1992 and subsequent model years, manufacturers that produce and deliver for sale in California sell MDVs in excess of the equivalent requirements for LEVs and/or ULEVs, shall receive "Vehicle-Equivalent Credits" (or "VECs") calculated in accordance with the following equation, where the term "Produced" means produced and delivered for sale in California as:
$$\{[(\text{No. of LEVs Produced Sold excluding HEVs}) + (\text{No. of "Type C HEV" LEVs Produced Sold})] + [(\text{No. of "Type A HEV" LEVs Produced Sold}) \times (1.2)] + [(\text{No. of "Type B HEVs" LEVs Produced Sold}) \times (1.1)] - (\text{Equivalent No. of LEVs Required to be Produced Sold})\} + \{[(1.4) \times [(\text{No. of ULEVs Produced Sold excluding HEVs}) + (\text{No. of "Type C HEV" ULEVs Produced Sold})] + [(1.7) \times (\text{No. of "Type A HEV" ULEVs Produced Sold})] + [(1.5) \times (\text{No. of "Type B HEV" ULEVs Produced Sold})] - [(1.4) \times (\text{Equivalent No. of ULEVs Required to be Produced Sold})]\} + [(2.0) \times (\text{No. of ZEVs Certified and Produced Sold as MDVs})]$$
.
- a. Manufacturers which fail to produce and deliver for sale in California sell the equivalent quantity of MDVs certified to LEV and/or ULEV exhaust emission standards, shall receive "Vehicle-Equivalent Debits" (or "VEDs") equal to the amount of negative VECs determined by the aforementioned equation.
 - b. Manufacturers shall equalize emission debits within one model year by earning VECs in an amount equal to their previous model-year's total of VEDs, or by submitting a commensurate amount of VECs to the Executive Officer that were earned previously or acquired from another manufacturer. Any manufacturer which fails to equalize emission debits within the specified time period shall be subject to the Health and Safety Code civil penalty applicable to a manufacturer which sells a new motor vehicle that does not meet the applicable emission standards adopted by the state board. The cause of action shall be deemed to accrue when the emission debits are not equalized by the end of the specified time period. For the purposes of Health and Safety Code section 43211, the number of vehicles not meeting the state board's emission standards shall be equal to the amount of VEDs incurred.
 - c. The VECs earned in any given model year shall retain full value through the subsequent model year.
 - d. The value of any VECs not used to equalize the previous model-year's debit, shall be discounted by 50% at the beginning of second model year after being earned, discounted to 25% of its original value if not used by the beginning of the third model year after being earned, and will have no value if not used by the beginning of the fourth model year after being earned.
 - e. Any VECs earned prior to the 1998 model year shall be treated as earned in the 1998 model year and discounted in accordance with the schedule specified in note (12)(d).

- e f. Only ZEVs certified as MDVs can shall be included in the calculation of VECs.
- (13) Manufacturers shall demonstrate compliance with the above standards for NMOG, carbon monoxide, and oxides of nitrogen at 50 degrees F, according to the procedure specified in Section 11k of these test procedures. Hybrid electric, natural gas, and diesel-fueled vehicles are exempt from 50 degrees F test requirements. "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles as Adopted May 20, 1987, and last amended: INSERT". For diesel vehicles, compliance with the particulate standard shall also be demonstrated as specified in Section 11k of the foregoing test procedures.
- (14) In-use compliance testing shall be limited to vehicles with fewer than 90,000 miles.
- (15) Deterioration factors for hybrid electric vehicles shall be based on the emissions and mileage accumulation of the auxiliary power unit. For certification purposes only, Type A hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors), and demonstrating compliance with 120,000 mile emission standards shall not be required. For certification purposes only, Type B hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors) and 120,000 mile emission standards (using 90,000 mile deterioration factors). For certification purposes only, Type C hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors) and 120,000 mile emission standards (using 120,000 mile deterioration factors).
- (16) As used in this section 3.j. of these test procedures, the term "small volume manufacturer" shall mean any vehicle manufacturer with California sales less than or equal to 3000 new PCs, LDTs, and MDVs per model year based on the average number of vehicles sold by the manufacturer each model year from 1992 to 1994, except as otherwise noted below. For manufacturers certifying for the first time in California, model-year sales shall be based on projected California sales. In 2001 and subsequent model years, small volume manufacturers shall comply with the requirements set forth below.
- a. Prior to the model year 2001, small volume manufacturers shall not be required to certify, produce, or deliver LEVs and ULEVs for sale in California.
- b. In 2001 and subsequent model years, small volume manufacturers shall certify, produce, and deliver for sale in California LEVs in a quantity equivalent to 100% of their MDV fleet.
- c. If a manufacturer's average California sales exceeds 3000 units of new PCs, LDTs, and MDVs based on the average number of vehicles sold for any three consecutive model years, the manufacturer shall no longer be treated as a small volume manufacturer and shall comply with the LEV and ULEV requirements applicable for larger manufacturers as specified in Section 3.j of these test procedures beginning with the fourth model year after the last of the three consecutive model years.
- e. If a manufacturer's average California sales falls below 3000 units of new PCs, LDTs, and MDVs based on the average number of vehicles sold for any three consecutive model years, the

manufacturer shall be treated as a small volume manufacturer and shall be subject to requirements for small volume manufacturers as specified in Section 3.j of these test procedures beginning with the next model year.

k. The cold temperature exhaust carbon monoxide emission levels from new 1996 and subsequent model-year passenger cars, light-duty trucks, and medium-duty vehicles shall not exceed:

1996 AND SUBSEQUENT MODEL-YEAR COLD TEMPERATURE CARBON MONOXIDE
EXHAUST EMISSIONS STANDARDS FOR PASSENGER CARS,
LIGHT-DUTY TRUCKS, AND MEDIUM-DUTY VEHICLES (1)(2)
(grams per mile)

<u>Vehicle Type</u>	<u>Loaded Vehicle Weight (lbs.)</u>	<u>Durability Vehicle Basis (mi)</u>	<u>Carbon Monoxide</u>
<u>Passenger Car</u>	<u>All</u>	<u>50,000</u>	<u>10.0</u>
<u>Light-Duty Truck</u>	<u>0-3750</u>	<u>50,000</u>	<u>10.0</u>
<u>Light-Duty Truck</u>	<u>3751-6750</u>	<u>50,000</u>	<u>12.5</u>
<u>Medium-Duty Vehicle</u>	<u>0-3750</u>	<u>50,000</u>	<u>10.0</u>
<u>Medium-Duty Vehicle</u>	<u>3751-8500 (3)</u>	<u>50,000</u>	<u>12.5</u>

- (1) These standards are applicable to vehicles tested in accordance with 40 CFR Part 86 Subpart C, at a nominal temperature of 20°F (-7°C).
- (2) Natural gas vehicles, diesel-fueled vehicles, hybrid electric vehicles, and zero-emission vehicles are exempt from these standards.
- (3) Medium-duty vehicles with a gross vehicle weight rating greater than 8,500 lbs. are exempt from this standard.

4. Initial Requirements

a. Application for Certification

In paragraph 86.088-21, 86.090-21, and 86.091-21, and 86.094-21:

1. Amend subparagraph (b)(1)(i) to read:

(i) Identification and description of the vehicles (or engines) covered by the application and a description (including a list and part numbers of all major emission control system parts and fuel system components) of their engine (vehicles only) emission control system and fuel system components, including if applicable, the turbocharger and intercooler. This shall include a detailed description of each auxiliary emission control device (AECD) to be installed in or on any certification test vehicle (or certification test engine).

2. Amend subparagraph (b)(2) to read:

(2) For 1992 and subsequent model-year TLEVs, LEVs, and ULEVs not certified powered exclusively by on gasoline, projected California sales data and fuel economy data two years 19 months prior to January 1 of the calendar year with the same numerical designation as the model year for which the vehicles are certified the end of the certification process, and projected California sales data for all vehicles, regardless of operating fuel or vehicle emission category, sufficient to enable the Executive Officer to select a test fleet representative of the vehicles (or engines) for which certification is requested at the time of certification.

3. Add subparagraph (g) which reads:

(1) For ZEVs and hybrid electric vehicles, the certification application shall include the following:

(i) Identification and description of the vehicle(s) covered by the application.

(ii) Identification of the vehicle weight category to which the vehicle is certifying: PC, LDT 0-3750 lbs. LVW, LDT 3751-5750 lbs. LVW, or MDV (state test weight range), and the curb weight and gross vehicle weight rating of the vehicle.

(iii) Identification and description of the propulsion system for the vehicle.

(iv) Identification and description of the climate control system used on the vehicle.

- (v) Projected number of vehicles produced and delivered for sale in California, and projected California sales.
- (vi) For electric and hybrid electric vehicles, identification of the energy usage in kilowatt-hours per mile from the point when electricity is introduced from the electrical outlet and the operating range in miles of the vehicle when tested in accordance with the All-Electric Range Test (see section 9.f. of these test procedures).
- (vii) If the vehicle is equipped with a fuel fired heater, a description of the control system logic of the fuel fired heater, including an evaluation of the conditions under which the fuel fired heater can be operated and an evaluation of the possible operational modes and conditions under which evaporative emissions can exist. Vehicles which utilize fuel fired heaters which can be operated at ambient temperatures above 40 degrees Fahrenheit or which cannot be demonstrated to have zero evaporative emissions under any and all possible operation modes and conditions shall not be certified as ZEVs.
- (viii) All information necessary for proper and safe operation of the vehicle, including information on the safe handling of the battery system, emergency procedures to follow in the event of battery leakage or other malfunctions that may affect the safety of the vehicle operator or laboratory personnel, method for determining battery state-of-charge, battery charging capacity and recharging procedures, and any other relevant information as determined by the Executive Officer.

In paragraph 86.088-21 and 86.090-21:

3. Amend subparagraph (b)(4)(iii)(C)(1) and (C)(2) to read:

(1) A statement of maintenance and procedures consistent with the restrictions imposed under subparagraph 86.085-25(a)(1), necessary to assure that the vehicles (or engines) covered by a certificate of conformity in operation in normal use to conform to the regulations, and a description of the program for training of personnel for such maintenance, and the equipment required.

(2) A statement that the vehicles sold comply with the California high-altitude emission requirements as specified in Section 11.b. (High Altitude Requirements) in these procedures.

b. Required Data

In paragraph 86.085-23, 86.087-23, 86.088-23, and 86.091-23, and 86.094-23:

- 1- Amend subparagraph (a) by adding the following paragraph which reads:

Zero-emission vehicles (including electric vehicles which do not utilize auxiliary fuel fired heaters) shall be exempt from emission testing and durability requirements. All series hybrid electric vehicle emission testing shall be conducted while operating the vehicle's auxiliary engine continuously over the CVS-75 test cycle (as specified in paragraphs 86-135-90 and 86-137-90) at maximum regulated engine speed and load conditions or other operation to be determined by the Executive Officer as resulting in the worst case emissions. All parallel hybrid electric vehicle emission testing shall be conducted while the vehicle is operating solely through use of its combustion engine over the CVS-75 test cycle (as specified in paragraphs 86-135-90 and 86-137-90), or as close to pure engine operation as is feasible. All battery assisted combustion engine vehicles shall be tested in accordance with the test procedures specified (40 CFR Part 86) for vehicles which operate solely by use of a combustion engine. All hybrid electric vehicles shall be tested in accordance with paragraphs 86-129-80.

- 2 1. Amend (c)(1) by adding the following two paragraphs which reads:

In the case of electric vehicles (or other zero-emission vehicles) which use fuel fired heaters, the manufacturer shall determine the exhaust emissions per mile produced by the auxiliary fuel fired heater, when certifying electric vehicles (or other zero-emission vehicles) which utilize this type of heater. This shall be accomplished by determining heater emissions per minute when operating at maximum heating capacity, and multiplying that number by 3.6 minutes per mile (the number of minutes in the CVS-75 test cycle divided by the number of miles in the CVS-75 test cycle.) A statement of the standards to which the vehicle complies based on the emissions from the heater shall be required for vehicle certification.

For all TLEVs, LEVs, and ULEVs certifying on a fuel other than conventional gasoline, manufacturers shall multiply the provide a total NMOG exhaust certification level emission value multiplied for each emission-data vehicle by the appropriate reactivity adjustment factor listed in Section 13.a. of these test procedures or established by the Executive Officer pursuant to Appendix VIII of these test procedures in g/mile to demonstrate compliance with the applicable NMOG emission standards. For all TLEVs, LEVs, and ULEVs certifying on natural gas, manufacturers shall multiply the NMOG exhaust certification level for each emission-data vehicle by the appropriate reactivity

adjustment factor listed in Section 13.a. of these test procedures or established by the Executive Officer pursuant to Appendix VIII of these test procedures and add that value to the product of the methane exhaust certification level for each emission-data vehicle and the appropriate methane reactivity adjustment factor listed in Section 13.a. of these test procedures or established by the Executive Officer pursuant to Appendix VIII of these test procedures to demonstrate compliance with the applicable NMOG emission standard. Manufacturers requesting to certify to existing standards utilizing an adjustment factor unique to its vehicle/fuel system must follow the data requirements described in Appendix VIII of these test procedures. A separate formaldehyde exhaust certification level emission value in mg/mile shall also be provided for demonstrating compliance with emission standards for formaldehyde.

c. Test Vehicles and Test Engines; Assigned Deterioration Factors (DFs)

In paragraphs 86.085-24, and 86.090-24, 86.092-24, and 86.095-24:

1. Amend subparagraph (a)(1) by adding the following additional statement:

(a)(1) The vehicles or engines covered by an application for certification will be divided into groupings of engines which are expected to have similar emission characteristics throughout their useful life. Each group of engines with similar emission characteristics shall be defined as a separate engine family. For 1995 and subsequent model-year vehicles or engines, all engines classified in the same engine family shall be certified to identical exhaust emission standards.

- ± 2. Delete subparagraph (b) (Emission-data vehicle selection provisions)

REPLACE WITH:

(b) Emission-data vehicles shall be selected according to the provisions of Appendix II. Selection shall be based on highest sales volume and will require only two emission-data vehicles for certification testing per engine family. (For fifty-state families, the reference in the federal procedures to configuration or sales shall mean California configurations and sales rather than total family configurations and sales.) The Executive Officer will accept data from California (or fifty-state) configuration vehicles or from federal vehicles which meet the requirements of subparagraph 4.b.4. Federal vehicles may be reconfigured to California versions and tested to show compliance with California emission standards. The Executive Officer will also allow the manufacturer to reconfigure California vehicles.

- 2 3. Delete subparagraph (e)(1) (Reduced number of test vehicles)

REPLACE WITH:

(1) Any manufacturer whose projected California annual sales for the model year in which certification is sought is less than a combined total of 3,000 passenger cars, light-duty trucks, medium-duty vehicles, and heavy-duty engines may request a reduction in the number of test vehicles determined in accordance with the foregoing provisions of this paragraph. The Executive Officer may agree to such lesser numbers as he or she determines would meet the objectives of this procedure.

- 3 4. Delete subparagraph (e)(2) (Assigned deterioration factors)

REPLACE WITH:

(2)(i) Any manufacturer may request to certify engine families using assigned DFs for a combined total of 3,000 projected annual California sales of passenger cars, light-duty trucks, medium-duty vehicles, and heavy-duty engines per manufacturer regardless of total sales.

(2)(ii) Assigned DFs shall be used only where specific mileage accumulation data do not exist (i.e., if a vehicle manufacturer uses an engine/system combination where DFs derived from exhaust emission testing exist, then the assigned factors cannot be used).

Assigned DFs shall be used in lieu of data from durability vehicle(s) only when a manufacturer demonstrates that it has control over design specifications, can provide development data, has in-house testing capabilities including accelerated aging of components/systems, and has evaluation criteria to ensure emission control system (ECS) durability for the vehicle's useful life. The applying manufacturer must demonstrate engine durability and that the emission control system(s) developed or adapted for the particular engine will be durable and comply with the applicable emission standards for the engine's or vehicle's useful life. In evaluating any information provided, all relevant test data and design factors shall be considered, including but not limited to: vehicle application, engine design, catalyst loading and volume, space velocity in the catalyst, engine exhaust gas concentrations and catalyst temperatures for various operating modes, and the durability of any emission control system components which may have been used in other vehicle applications. The assigned DFs shall be applied only to entire families.

If emission control parts from other certified vehicles are utilized, then parameter comparisons of the above data must also be provided including part numbers where applicable.

Emission control durability may include special in-house specifications.

(2)(iii) The criteria for evaluating assigned DFs for evaporative families are the same as those for exhaust families. However, in determining evaporative family DFs the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Liquefied Petroleum Gas- or Gasoline- or Methanol-Fueled Motor Vehicles" require that an evaporative family DF be determined by averaging DFs obtained from durability vehicle testing and from bench testing. Therefore, if a manufacturer meets the criteria as specified above in (e)(2)(i) and (e)(2)(ii), the Executive Officer may grant assigned DFs for either (or both) the durability vehicle DF or the bench DF.

Assigned DFs for bench test requirements do not depend upon the 3,000 maximum sales limit. The assigned bench DF is applicable only to evaporative emission control systems which are similar to those used by the manufacturer for 1980 or later model-year vehicles and where an evaporative vehicle DF was determined. In evaluating a request for an assigned bench DF, all relevant information shall be considered, including but not limited to: fuel tank capacity, fuel tank temperatures, carburetor bowl "capacity", underhood temperatures, canister capacity and location, and any other comparisons to the certified application.

- 4 5. Amend subparagraph (f) and (h)(1)(v) by adding the following additional requirement which reads:

The durability or emission data submitted may be from vehicles previously certified by ARB. For 1993 through 1996 model-year passenger cars and light-duty trucks and 1995 through 1997 model-year medium-duty vehicles, the manufacturer shall submit durability data from only California (or fifty-state) configuration vehicles unless the durability data was generated from a vehicle certified by EPA or ARB prior to the 1993 model year (1995 for medium-duty vehicles). For 1997 (1998 for medium-duty vehicles) and subsequent model-year vehicles, durability data shall be submitted from only California (or fifty-state) configuration vehicles. For 1993 and (1995 for medium-duty vehicles) subsequent model-year vehicles, the Executive Officer shall permit the use of federal durability data vehicles if he or she determines that the federal data will adequately represent the durability characteristics of the California configuration. This determination shall be based upon similarity of catalyst location and configuration; similarity of fuel metering system; similarity of major features of emission control system logic and design; and similarity of any other features determined by the Executive Officer to be likely to affect durability. If data from a federal durability data vehicle is used, the requirements of subparagraph 6.b.5. (durability vehicles must meet emission

standards) will refer to the federal emissions standards in effect for the model year for which the durability data was generated.

d. Compliance with the Inspection and Maintenance Program

All 1993 and subsequent model-year emission-data vehicles shall be required to be tail-pipe tested at 4,000 miles and demonstrate compliance with the California Inspection and Maintenance emission standards in place at the time of certification as specified in the "Mandatory Exhaust Emissions Inspection Standards and Test Procedures", Title 16, California Code of Regulations, Section 3340.42. Test vehicles shall undergo preconditioning procedures prior to the tail-pipe test which consist of idle conditions for a minimum period of ten minutes after the thermostat is open. Preconditioning and test procedures shall be conducted at an ambient temperature from 68 to 86 degrees, Fahrenheit. The manufacturer shall, in accordance with good engineering practice, attest that such test vehicles will meet the requirements of this section when preconditioned and tested at ambient temperatures from 35 to 68 degrees Fahrenheit.

5. Maintenance Requirements

a. Maintenance¹

Delete paragraph 86.090-25.

Delete paragraph 86.088-25.

Delete paragraph 86.087-25.

In paragraph 86.085-25:

1. Amend the title and first sentence of subparagraph (a) to read:

(a) Light-duty vehicles. Paragraph (a) of this section applies to passenger cars, light-duty trucks, and medium-duty vehicles.

2. Amend subparagraph (a)(1) to read:

(1) Scheduled maintenance on the engine, emission control system, and fuel system of durability vehicles shall, unless otherwise provided pursuant to paragraph (a)(5)(iii), be restricted as set forth in the following provisions. If a manufacturer must revise the maintenance schedule, prior approval by the Executive Officer is required. Unscheduled maintenance must not render a durability vehicle nonrepresentative of the production vehicles. The unscheduled maintenance must not be likely to be required in the normal use of the vehicle. Unauthorized or unjustifiable unscheduled maintenance may be cause for disqualification of a durability vehicle.

Manufacturers must submit durability maintenance logs to the Executive Officer. The maintenance logs shall include the mileage where maintenance occurred, the nature of the maintenance, and the name and part numbers of all fuel system and emission control parts involved with the maintenance. Manufacturers of series hybrid electric vehicles and parallel hybrid electric vehicles shall be required to incorporate into the vehicles a separate odometer or other device subject to the approval of the Executive Officer which can accurately gauge the mileage accumulation on the engines which are used in these vehicles.

1. These requirements are for vehicles certified to the primary 50,000 mile and 100,000 or 120,000 mile standards. Requirements for the vehicles certified to the optional 100,000 mile standards are found in section 10 (Optional 100,000 Mile Certification Procedure) of these procedures.

(i)(A) For otto-cycle vehicles and hybrid electric vehicles which use otto-cycle engines, maintenance shall be restricted to the inspection, replacement, cleaning, adjustment, and/or service of the following items at intervals no more frequent than indicated:

- (1) Drive belts on engine accessories (tension adjustment only); (30,000 miles of engine operation).
- (2) Valve lash (15,000 miles of engine operation).
- (3) Spark plugs (30,000 miles of engine operation).
- (4) Air filter (30,000 miles of engine operation).
- (5) Exhaust gas sensor (30,000 miles of engine operation).
Provided that:

(a) the manufacturer shall equip the vehicle with a maintenance indicator consisting of a light or flag, which shall be preset to activate automatically by illuminating in the case of a light or by covering the odometer in the case of a flag the first time the minimum maintenance interval established during certification testing is reached and which shall remain activated until reset. After resetting, the maintenance indicator shall activate automatically when the minimum maintenance interval, when added to the vehicle mileage at the time of resetting, is again reached and shall again remain activated until reset. When the maintenance indicator consists of a light, it shall also activate automatically in the engine-run key position before engine cranking to indicate that it is functioning. The maintenance indicator shall be located in the instrument panel and shall, when activated, display the words "oxygen sensor" or may display such other words determined by the Executive Officer to be likely to cause the vehicle owner to seek oxygen sensor replacement. The maintenance indicator shall be separate from the malfunction indicator light required by Section 1968, Title 13, California Code of Regulations;

(b) the manufacturer shall provide free replacement of the oxygen sensor, including both parts and labor, and shall reset the maintenance indicator without any charge, the first time the maintenance interval established during certification testing is reached for vehicles certified with scheduled sensor maintenance before 50,000 miles. If the oxygen sensor is replaced pursuant to the warranty provisions of Section 2037, Title 13, California Code of Regulations, before the first maintenance interval is reached, the manufacturer shall also replace the oxygen sensor and reset the maintenance indicator at the mileage point determined by

adding the maintenance interval to the vehicle's mileage at the time of the warranty replacement. If the calculated mileage point for a second oxygen sensor replacement would exceed 50,000 miles, no free second replacement shall be required;

(c) The maintenance indicator shall be resettable. The maintenance instructions required by section 5.b. of these procedures shall provide instructions for the resetting of the maintenance indicator, and shall specify that the maintenance indicator shall be reset each time the oxygen sensor is replaced; and

(d) Notwithstanding the provisions of Section 2037(c), Title 13, California Code of Regulations; the oxygen sensor, including any replacement required pursuant to this section, shall be warranted for the applicable warranty period of the vehicle or engine in accordance with Section 2037(a), Title 13, California Code of Regulations. If such oxygen sensor fails during this period, it shall be replaced by the manufacturer in accordance with Section 2037(d), Title 13, California Code of Regulations.

- (6) Choke (cleaning or lubrication only); (30,000 miles of engine operation).
- (7) Positive crankcase ventilation valve (50,000 miles of engine operation).
- (8) Ignition wires (50,000 miles of engine operation).
- (9) In addition, adjustment of the engine idle speed (curb idle and fast idle), valve lash, and engine bolt torque may be performed once during the first 5,000 miles of scheduled driving, provided the manufacturer makes a satisfactory showing that the maintenance will be performed on vehicles in use. For hybrid electric vehicles, these adjustments may only be performed once during the first 5,000 miles of engine operation.

(10) Hybrid electric vehicle battery system (manufacturer's established performance limits). Provided that:

(a) The manufacturer shall equip the vehicle with a maintenance indicator consisting of a light which shall activate automatically by illuminating the first time the minimum performance level is observed for all battery system components. Possible battery system components requiring monitoring are:

- i. battery water level
- ii. temperature control
- iii. pressure control

iv. other parameters critical for determining battery condition

(b) The manufacturer shall equip the vehicle with a useful life indicator for the battery system consisting of a light which shall illuminate the first time the battery system is unable to achieve an all-electric operating range (starting from a full state-of-charge) which is at least 75% of the range determined for the vehicle in the All-Electric Range Test (see section 9.f. of these test procedures) and submitted in the certification application.

(i)(B) For diesel vehicles and hybrid electric vehicles which use diesel engines, maintenance shall be restricted to the following items at intervals no more frequently than every 12,500 miles of engine operation, provided that no maintenance may be performed within 5,000 miles of the final test point:

(1) Adjust low idle speed.

(2) Adjust valve lash if required.

(3) Adjust injector timing.

(4) Adjust governor.

~~(5) Clean and service injector tips.~~

(6) Adjust drive belt tension on engine accessories.

(7) Check engine bolt torque and tighten as required.

(ii) Change of engine and transmission oil, change or service of oil filter and, for diesel vehicles only, change or service of fuel filter and air filter, will be allowed at the mileage intervals specified in the manufacturer's maintenance instructions.

(iii) Maintenance shall be conducted in a manner consistent with service instructions and specifications provided by the manufacturer for use by customer service personnel.

3. Delete subparagraph (a)(3) (Service of exhaust gas recirculation system).

4. Delete subparagraph (a)(4) (Service of catalytic converter).

5. Amend subparagraph (a)(5), by adding a new subparagraph (iv) to read:

(iv) When a part has to be replaced while conducting unscheduled maintenance, a similarly aged part shall be used for those parts that affect emissions, unless it is

impractical and unnecessary to age a part and prior approval has been obtained from the Executive Officer for use of the part without aging. In either case, an engineering report on the nature of the problem with the probable cause and corrective action shall be supplied to the Executive Officer.

6. Delete subparagraph (b) (Maintenance of light-duty trucks and heavy-duty engines).

b. Maintenance Instructions

Delete paragraph 86.087-38.

In paragraph 86.085-38:

1. Amend subparagraph (a) to read:

(a) The manufacturer shall furnish or cause to be furnished to the purchaser of each new motor vehicle subject to the standards prescribed in Section 3 of these procedures, written instructions for the maintenance and use of the vehicle by the purchaser as may be reasonable and necessary to assure the proper functioning of emission control systems in normal use. Such instructions shall be consistent with and not require maintenance in excess of the restrictions imposed under subparagraph 86.085-25(a)(1) as amended above, except that the instructions may, subject to approval by the Executive Officer, require additional maintenance for vehicles operated under extreme conditions. In addition, subject to approval by the Executive Officer, the instructions may require inspections necessary to insure safe operation of the vehicle in use.

In addition to any maintenance which may be required pursuant to the preceding paragraph, the instructions may also recommend such inspections, maintenance, and repair as may be reasonable and necessary for the proper functioning of the vehicle and its emission control systems. If the instructions recommend maintenance in addition to that which may be required pursuant to the preceding paragraph, they shall distinguish clearly between required and recommended maintenance.

2. Amend both subparagraphs (c)(1) and (d)(1) to read:

(1) Such instructions shall specify the performance of all scheduled maintenance performed by the manufacturer under subparagraph 86.085-25(a)(1).

c. Submission of Maintenance Instructions

Amend subparagraph 86.079-39(a) to read:

(a) The manufacturer shall provide to the Executive Officer, no later than the time of the submission required by paragraph 86.088-23 or 86.091-23, a copy of the maintenance instructions which the manufacturer proposes to supply to the ultimate purchaser in accordance with subparagraph 86.085-38(a). The Executive Officer will review such instructions to determine whether they are consistent with California requirements, and to determine whether the instructions for required maintenance are consistent with the restrictions imposed under subparagraph 86.085-25(a)(1). The Executive Officer will notify the manufacturer of his or her determinations.

6. Demonstrating Compliance

a. Mileage and Service Accumulation; Emission Measurements

In paragraphs 86.084-26 and 86.090-26:

1. Amend subparagraph (a)(1) to read:

(a)(1) Paragraph (a) of this section applies to light-duty vehicles, except ZEVs which shall be exempt from all mileage and service accumulation, durability-data vehicle, and emission-data vehicle testing requirements.

2. Amend (a)(2) to read:

The procedure for mileage accumulation shall be the Durability Driving Schedule as specified in Appendix IV to Part 86 of the Code of Federal Regulations. A modified procedure may also be used if approved in advance by the Executive Officer. All passenger cars, light-duty trucks, pre-1995 model year medium-duty vehicles, and 1995 model-year vehicles certified to 1994 model-year emission standards shall accumulate mileage at a measured curb weight which is within 100 pounds of the estimated curb weight. All 1995 and subsequent model-year medium-duty vehicles (except those certified to 1994 model-year emission standards) and all 1992 and subsequent medium-duty LEVs and ULEVs shall accumulate mileage at a loaded weight that is within 100 pounds of the average of the vehicle's curb weight and gross vehicle weight. If the vehicle weight is within 100 pounds of being included in the next higher inertia weight class, the manufacturer may elect to conduct the respective emission tests at the higher weight. All mileage accumulation of series hybrid electric vehicles shall be conducted with the battery pack at the manufacturer's indicated lowest state-of-charge at the beginning of the test cycle. At no time throughout mileage accumulation shall the battery pack be charged using any off-board charging source, utilizing constant operation of the auxiliary engines. Parallel hybrid electric vehicles shall accumulate all mileage while operating with as much use of the combustion engine as is possible.

3. Amend (a)(3)(i) and (a)(3)(ii) (Emission-data vehicle mileage accumulation) by adding the following additional requirement which reads:

The Executive Officer will accept the manufacturer's determination of the mileage at which the engine-system combination is stabilized for emission data testing if (prior to testing) a manufacturer determines that the interval chosen yields emissions performance which is stable and representative of design intent. Sufficient mileage should be accumulated to reduce the possible effects of any emissions variability that is the result of insufficient

vehicle operation. Of primary importance in making this determination is the behavior of the catalyst, EGR valve, trap oxidizer or any other part of the ECS which may have non-linear aging characteristics. In the alternative, the manufacturer may elect to accumulate 4,000 mile +/- 250 mile on each test vehicle within an engine family without making a determination.

- 3 4. Amend (a)(4)(i) and (a)(4)(ii) (Durability-data vehicle mileage accumulation) by adding the following new subparagraphs (A), (B), (C), and (D) to read:

(A) For otto-cycle and diesel vehicles and battery assisted combustion engine vehicles which use otto-cycle or diesel engines:

- (1) Passenger cars, light-duty trucks and medium-duty vehicles certifying to exhaust emissions standards only on a 50,000 mile durability basis and selected by the Executive Officer or elected by the manufacturer under 86.085-24(c)(1) or 86.090-24(c)(1) shall be driven, with all emission control systems installed and operating, for 50,000 miles or such lesser distance as the Executive Officer may agree to as meeting the objective of this procedure.
- (2) Prior to initiation of mileage accumulation in a durability-data vehicle, ~~manufacturers must establish~~ the mileage test interval for durability-data vehicle testing of the engine family. Once testing has begun on a durability-data vehicle, the durability test interval for that family may not be changed. At a minimum, multiple tests must be performed at 5,000 miles, 50,000 miles, and the final mileage point as long as they meet the requirements of Appendix III. The Executive Officer will accept durability test interval schedules determined by the manufacturer. The testing must provide a DF confidence level equal to or better than the confidence level using the former fixed mileage test and scheduled maintenance intervals. The procedure for making this determination is also given in Appendix III. The mileage intervals between test points must be approximately of equal length. The +/- 250 mile test point tolerance and the requirement that tests be conducted before and after scheduled maintenance is still mandatory. Emission control systems for otto-cycle engines which have step function changes designed into the control system must use the 5,000 mile test interval schedule.
- (3) Testing before and after scheduled (or unscheduled) maintenance points must be conducted, and these data

are to be included in the deterioration factor calculation.²

The number of tests before and after scheduled maintenance and the mileage intervals between test points should be approximately equal. Durability test interval schedules with multiple testing at test points within 10,000 miles of or at the 50,000 mile and the final mileage test point must be submitted for approval. Multiple testing at maintenance mileage tests points within 10,000 miles of the 50,000 mile and the final mileage test points may be approved if it can be demonstrated by previously generated data that the emission effects of the maintenance are insignificant.

- (4) For engine families which are to be certified to the full useful life emission standards, each exhaust emission durability-data vehicle shall be driven with all emission control systems installed and operating, for the full useful life or such lesser distance as the Executive Officer may agree to as meeting the objective of this procedure. Durability tests shall be at every 5,000 miles, from 5,000 miles to the full useful life, however, the above procedures may be used to determine alternate test intervals subject to the following.

For engine families which are to be certified to the full useful life emission standards, durability vehicles may accumulate less than the full useful life if the manufacturer submits other data or information sufficient to demonstrate that the vehicle is capable of meeting the applicable emission standards for the full useful life. At a minimum, 75% of the full useful life shall be accumulated. For the purpose of conducting mileage accumulation on light-duty hybrid electric vehicles, the full useful life of the auxiliary power unit shall be defined as 50,000 miles for a Type A hybrid electric vehicle, 75,000 miles for a Type B hybrid electric vehicle, and 100,000 miles for a Type C hybrid electric vehicle. For medium-duty hybrid electric vehicles, the full useful life of the auxiliary power unit shall be defined as 60,000 miles for a Type A hybrid electric vehicle, 90,000 miles for a Type B hybrid electric vehicle, and 120,000 miles for a Type C hybrid electric vehicle. Alternative durability plans may also be used if the manufacturer provides a demonstration that the alternative plan provides equal or greater confidence that the vehicles

2. Testing before unscheduled maintenance may be omitted with the prior consent of the Executive Officer when testing would be dangerous to a vehicle or an operator.

will comply in-use with the emission standards. The demonstration shall include, but not be limited to, bench test data and engineering data. A manufacturer's in-use emission data may also be used. All alternative durability plans, including the use of durability vehicles which accumulate less than the full useful life are subject to approval in advance by the Executive Officer.

(B) For diesel vehicles equipped with periodically regenerating trap oxidizer systems, at least four regeneration emission tests (see 86.106 through 86.145) shall be made. With the advance approval of the Executive Officer, the manufacturer may install (1) a manual override switch capable of preventing (i.e. delaying until the switch is turned off) the start of the regeneration process and (2) a light which indicates when the system would initiate regeneration if it had no override switch. Upon activation of the override switch the vehicle will be operated on a dynamometer to precondition it for the regeneration emission test in accordance with section 86.132-82 or 86.132-90 and section 9.b. of these procedures. The Urban Dynamometer Driving Schedule (UDDS) which is in progress at the time when the light comes on shall be completed and the vehicle shall proceed to the prescribed soak period followed by testing. With the advance approval of the Executive Officer, the manual override switch will be turned off at some predetermined point in the testing sequence permitting the regeneration process to proceed without further manual interaction. The mileage intervals between test points shall be approximately equal. The first regeneration emission test shall be made at the 5,000 mile point. The regeneration emission tests must provide a deterioration factor confidence level equal to or better than the confidence level achieved by performing regeneration emission tests at the following mileage point: 5,000; 20,000; 35,000; and 50,000. The procedure for making this determination is shown in Appendix IV.

(C) For gasoline-, gaseous-, and methanol alcohol-fueled vehicles, the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Liquefied Petroleum Gas- or Gasoline- or Methanol-Fueled Motor Vehicles," as incorporated in Title 13, California Code of Regulations, Section 1976, specify evaporative durability testing at 5,000, 10,000, 20,000, 30,000, 40,000 and 50,000 mile test points. These requirements are also applicable to

3. Included in Appendix V are the pollutant mass emission calculation procedures for vehicles equipped with periodically regenerating trap oxidizer systems.

hybrid electric vehicles. With the exception of fuel-flexible vehicles, a manufacturer may conduct evaporative testing at test points used for exhaust emission durability testing provided that the same deterioration confidence level for the evaporative emission DF determination is retained (see Appendix III).

(D) For 1993 and 1994 fuel-flexible vehicles which are not certified to TLEV, LEV, or ULEV standards, the test schedule must include exhaust emission tests at 5,000, 10,000, and every 10,000 miles thereafter to the final mileage point using M85 or E85 for methanol and ethanol fuel-flexible vehicles, respectively. Exhaust emission tests shall also be conducted at 5,000 miles, 50,000 miles, and the final mileage point with certification gasoline. For all 1995 and subsequent fuel-flexible vehicles and all 1992 and subsequent fuel-flexible vehicles certifying to TLEV, LEV, or ULEV standards, the test schedule shall include exhaust emission tests at 5,000 miles, 10,000 miles, and every 10,000 miles thereafter to the final mileage point using M85 or E85 and certification gasoline. For all fuel-flexible vehicles, if evaporative emission testing is conducted, exhaust and evaporative emission tests shall also be conducted using M35 or E10, or another approved fuel, at the mileage points where M85 or E85 testing is conducted. The results of these exhaust and evaporative emission tests will be used by the Executive Officer to evaluate the vehicle's emission control deterioration with various fuels (M85, M35, and unleaded gasoline; See Fuel Specifications, Section 9.a. of these procedures). Only the M85 or E85 and certification gasoline exhaust emission results and the M35 or E10 evaporative emission results will be incorporated with other exhaust emission data in determining used to determine applicable exhaust and evaporative emission deterioration factors, respectively, as required in Section 6.b. (Compliance with Emission Standards) of these procedures.

(E) For series hybrid electric vehicles and parallel hybrid electric vehicles, the manufacturer shall submit a test schedule to the Executive Officer which reflects the operating mileage of the engine over the full useful life of the vehicle. The test schedule shall include exhaust emission tests at 5,000, 10,000, and every 10,000 miles of engine operation thereafter to the final mileage point corresponding to operating mileage of the engine over the full useful life of the vehicles.

(F) (E) The Executive Officer may determine under 86.085-24(f) or 86.090-24(f) that no testing is required.

- 4 5. Amend subparagraph (a)(5)(i) by adding the following requirement which reads:

In addition, the emission tests performed on emission-data vehicles and durability-data vehicles shall be non-regeneration emission tests for diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems. For any of these vehicles equipped with continually regenerating trap oxidizer systems, manufacturers may use the provisions applicable to periodically regenerating trap oxidizer systems as an option.

If such an option is elected, all references in these procedures to vehicles equipped with periodically regenerating trap oxidizer systems shall be applicable to the vehicles equipped with continually regenerating trap oxidizer systems.

- 5 6. Amend subparagraph (a)(8) to read:

(8) Once a manufacturer submits the information required in paragraphs (a)(7) of this section for a durability-data vehicle, the manufacturer shall continue to run the vehicle to 50,000 miles if the family is certified to 50,000 mile emission standards or to the full useful life if it is certified to emission standards beyond 50,000 miles (or to a lesser distance which the Executive Officer may have previously agreed to), and the data from the vehicle will be used in the calculations under 86.088-28, 86.090-28, and 86.091-28. Discontinuation of a durability-data vehicle ~~shall be allowed only with the consent of the Executive Officer.~~

- 6 7. Delete subparagraph (b) (Emission-data and durability-data mileage accumulation for light duty trucks).

b. Compliance with Emission Standards

In paragraph 86.088-28, 86.090-28, and 86.091-28:

1. Amend subparagraph (a)(1) to read:

(1) Paragraph (a) of this section applies to light-duty vehicles { passenger cars, light-duty trucks and medium-duty vehicles }, except ZEVs.

2. Amend Subparagraph (a)(3) to read:

(3) Since it is expected that emission control efficiency will change with mileage accumulation on a vehicle, the emission level of a vehicle which has accumulated 50,000 miles will be used as the basis for determining compliance with the 50,000 mile emission standards.

3. Amend subparagraph (a)(4)(i) to read:

(i) Separate emission deterioration factors shall be determined from the exhaust emission results of the durability-data vehicle(s) for each engine-system combination. A separate factor shall be established for exhaust HC (non-methanol alcohol vehicles, non-TLEVs, non-LEVs, and non-ULEVs), exhaust OMHCE or OMNMHCE (methanol alcohol vehicles that are not TLEVs, LEVs, or ULEVs), exhaust NMOG (all TLEVs, LEVs, and ULEVs), exhaust formaldehyde (methanol alcohol vehicles, TLEVs, LEVs, and ULEVs), exhaust CO, exhaust NOx, and exhaust particulate (diesel vehicles only) for each engine-system combination. A separate evaporative emission deterioration factor shall be determined for each evaporative emission family-evaporative emission control system combination from the testing conducted by the manufacturer (gasoline- and methanol alcohol-fueled vehicles only).

Separate emission correction factors (diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems only) shall be determined from the exhaust emission results of the durability-data vehicle(s) for each engine-system combination. A separate factor shall be established for exhaust HC (non-methanol alcohol vehicles, non-TLEVs, non-LEVs, and non-ULEVs), exhaust OMHCE or OMNMHCE (methanol alcohol vehicles that are not TLEVs, LEVs, or ULEVs), exhaust NMOG (TLEVs, LEVs, and ULEVs), exhaust CO, exhaust NOx, and exhaust particulate for each engine-system combination.

4. Delete subparagraph (a)(4)(i)(A)(4) (Outlier test point procedure).

REPLACE WITH:

(4) The manufacturer must use the California outlier identification procedure entitled "Calculation of t-Statistic for Deterioration Data Outlier Test", dated December 17, 1976 and set forth in Appendix VII, to test for irregular data from a durability-data set. If any data point is identified as a statistical outlier, the Executive Officer shall determine, on the basis of an engineering analysis of the causes of the outlier submitted by the manufacturer, whether the outlier is to be rejected. The outlier shall be rejected only if the Executive Officer determines that the outlier does not reflect representative characteristics of the emission control system i.e., the outlier is a result of an emission control system anomaly, test procedure error, or an extraordinary circumstance not expected to recur. Only the identified outlier shall be eliminated; other data at that test point (i.e., data for other pollutants) shall not be eliminated unless the Executive Officer determines, based on the engineering analysis, that they also do not reflect representative characteristics of the emission control system. Where the

manufacturer chooses to apply both the outlier procedure and averaging (as allowed under 86.084-26(b)(6)(i) and 86.090-26(a)(6)(1) to the same data set, the outlier procedure shall be completed prior to applying the averaging procedure. All durability test data, including any outliers and the manufacturer's engineering analysis, shall be submitted with the final application.

5. Amend subparagraph (a)(4)(i)(B) (durability vehicles must meet emissions standards) to read:

(B). All applicable exhaust emission results shall be plotted as a function of the mileage on the system, rounded to the nearest mile, and the best fit straight lines, fitted by the method of least squares, shall be drawn through all these data points. The emission data will be acceptable for use in the calculation of the deterioration factor only if the interpolated 4,000-mile, 50,000-mile, and full useful life points on this line are within the emission standards given in subparagraph 3. or within the federal emission standards if a federal durability data vehicle is approved in accordance with subparagraph 4.b.4., as applicable. For hybrid electric vehicles, the emission data will be acceptable for use in the calculation of the deterioration factor only if the engine mileage points corresponding to the interpolated 4,000 mile, 50,000 mile, and full useful life points of the vehicle on this line are within the emission standards given in subparagraph 3. or within the ~~federal emission standards if a federal durability data~~ vehicle is approved in accordance with subparagraph 4.b.4., as applicable. The engine mileage points shall be determined based on the test schedule submitted to the Executive Officer as required in paragraphs 86.084-26 and 86.090-26. As an exception, the Executive Officer will review the data on a case-by-case basis and may approve its use in those instances where the best fit straight line crosses an applicable standard but no data point exceeds the standard or when the best fit straight line crosses the applicable standard at the 4,000-mile point but the 5,000-mile actual test point and the 50,000 mile and full useful life interpolated points are both below the standards. A multiplicative exhaust emission deterioration factor shall be calculated for each engine system combination as follows:

- (1) For engine families certified to 50,000 mile emissions standards:

Factor₁ = Exhaust emissions interpolated to 50,000 miles divided by exhaust emissions interpolated to 4,000 miles.

- (2) For engine families certified to full useful life emissions standards beyond 50,000 miles:

Factor₂ = Exhaust emissions interpolated to the full useful life divided by exhaust emissions interpolated to 4,000 miles.

6. Add subparagraph (a)(4)(i)(D) to read:

(D) The regeneration exhaust emission data (diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems only) from the tests required under 86.084-26(a)(4) or 86.090-26(a)(4) shall be used to determine the regeneration exhaust emissions interpolated to the 50,000-mile point. The regeneration exhaust emission results shall be plotted as a function of the mileage on the system, rounded to the nearest mile, and the best fit straight lines, fitted by the method of least squares, shall be drawn through all these data points. The interpolated 50,000-mile point of this line shall be used to calculate the multiplicative exhaust emission correction factor for each engine-system combination as follows:

$$\text{Factor} = 1 + \frac{R-1}{4505} n$$

where, R = the ratio of the regeneration exhaust emissions interpolated to 50,000 miles to the non-regeneration exhaust emissions interpolated to 50,000 miles.

n = the number of complete regenerations which occur during the durability test.

These interpolated values shall be carried out to a minimum of four places to the right of the decimal point before dividing one by the other to determine the correction factor. The results shall be rounded to three places to the right of the decimal point in accordance with ASTM E 29-67. For applicability to gaseous emission standards under the 100,000 mile option, R will be determined based upon projected 100,000 mile emissions.

7. Amend subparagraph (a)(4)(ii)(A) to read:

(A) The official exhaust emission test results for each emission-data vehicle at the 4,000 mile test point shall be multiplied by the appropriate deterioration factor, and correction factor (diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems only): Provided: that if a deterioration factor as computed in paragraph (a)(4)(i)(B) of this section or a correction factor as computed in paragraph (a)(4)(i)(D) of this section is less than one, that deterioration factor or correction factor shall be one for the purposes of this paragraph.

8. Amend subparagraph (a)(4)(iii) to read:

(iii) The emissions to compare with the standard (or the family particulate emission limit, as appropriate) shall be the adjusted emissions of paragraphs (a)(4)(ii)(A) and (B) of this section for each emission-data vehicle. Before any emission value is compared with the standard (or the family particulate limit, as appropriate), it shall be rounded, in accordance with ASTM E29-67 to two one significant figures beyond the number of significant figures contained in the standard (or the family particulate emission limit, as appropriate). The rounded emission values may not exceed the standard (or the family particulate emission limit, as appropriate). Fleet average NMOG value calculations shall be rounded, in accordance with ASTM E29-67, to four significant figures before comparing with fleet average NMOG requirements.

- 8 9. Delete subparagraph (b) (Compliance provisions for light-duty trucks).

c. Prohibition of Defeat Devices

In paragraph 86.094-16:

1. Amend subparagraph (a) to read:

No new passenger car, light-duty truck, or medium-duty vehicle shall be equipped with a defeat device.

7. Small-Volume Manufacturer's Certification Procedures

- a. In paragraphs 86.084-14, and ~~86.088-14~~ 86.090-14, ~~86.02-14~~, and ~~86.095-14~~:

1. Amend subparagraph (b)(1) to read:

(1) The optional small-volume manufacturers certification procedures apply to light-duty vehicles (passenger cars, light-duty trucks, and medium-duty vehicles), produced by manufacturers with California sales (for the model year in which certification is sought) of fewer than 3,000 units (PC, LDT and MDV combined). The optional small-volume manufacturers certification procedures shall not apply to hybrid electric vehicles. All hybrid electric vehicle manufacturers shall be subject to the certification requirements established for hybrid electric vehicles.

2. Delete subparagraphs (b)(2) through (b)(5) (Determining aggregated sales; aggregated sales provisions for small volume manufacturers).

- 2 3. Amend subparagraph (c)(4) to read:

(4) A small-volume manufacturer shall include in its records all of the information that ARB requires in 86.088-21, ~~or 86.091-21, or 86.094-21,~~ including the modifications noted in Section 4.a. of these test procedures. This information will be considered part of the manufacturer's application for certification and must be submitted to the Executive Officer.

4. Delete subparagraph (c)(7)(i)(A) (Worst-case selection of emission-data vehicles).
5. Amend subparagraph (c)(11)(ii)(D)(1) to show the 3,000 total vehicle sales limit applicable to California for determining a small-volume manufacturer.

8. Alternative Procedures for Notification of Additions and Changes

- a. Amend subparagraph 86.082-34(a) by adding the following additional requirements which read:

A manufacturer must notify the Executive Officer within 10 working days of making an addition of a vehicle to a certified engine family or a change in a vehicle previously covered by certification.

The manufacturer shall also submit, upon request of the Executive Officer, the following items:

- (1) service bulletin.
- (2) driveability statement.
- (3) test log.
- (4) maintenance log.

All running changes and field fixes which do not adversely affect the system durability are deemed approved unless disapproved by the Executive Officer within 30 days of the receipt of the running change or field fix request. A change not specifically identified in the manufacturer's application must also be reported to the Executive Officer if the change may adversely affect engine or emission control system durability. Examples of such changes include any change that could affect durability, thermal characteristics, deposit formation, or exhaust product composition i.e., combustion chamber design, cylinder head material, camshaft profile, computer modifications, turbocharger, intercooler wastegate characteristics; and transmission or torque converter specifications. Running changes and field fixes meeting the definitions contained in Appendix VI shall be automatically deemed approved by the Executive Officer, as long as the conditions set forth in Appendix VI are satisfied.

The manufacturer is required to update and submit to the Executive Officer the "supplemental data sheet" for all running changes and field fixes implemented with the change notification. The manufacturer shall submit, on a monthly basis, by engine family, a list of running changes/field fixes giving the document number date submitted and a brief description of the change.

9. Test Requirements

a. Fuel Specifications

In paragraph 86.113-90, 86.113-91, and 86.113-94:

1. Add subparagraphs (a)(1)(i) and (ii) which read[s]:

(i) For 1992-1994 [*and subsequent*] model-year Otto-cycle vehicles, gasoline having the specifications listed below may be used in exhaust and evaporative emission testing as an option to the specifications referred to in subparagraph (a)(1). If a manufacturer elects to utilize this option, both exhaust and evaporative emission testing shall be conducted by the manufacturer with gasoline having the specifications listed below, and the Executive Officer shall conduct exhaust and evaporative emission testing with gasoline having the specifications listed below.

Research Octane, minimum	93
Sensitivity, minimum	7.5
Lead (organic), maximum, g/US gal	0.050
Distillation Range	
IBP, degrees F	75-100
10 pct. point, degrees F	120-140
50 pct. point, degrees F	200-230
90 pct. point, degrees F	300-325
EP, maximum, degrees F	415
Sulfur, maximum weight pct.	0.03
Phosphorous, maximum, g/US gal	0.005
RVP, psi	7.5-8.0
Hydrocarbon composition	
Olefins, maximum pct.	10
Aromatics, maximum pct.	35
Saturates	remainder

(ii) For 1993-1994 model-year Otto-cycle TLEVs, LEVs, and ULEVs and for all 1995 and subsequent model-year Otto-cycle vehicles, gasoline having the specifications listed below may be used in exhaust and evaporative emission testing as an option to the specifications referred to in subparagraph (a)(1). If a manufacturer elects to utilize this option, both exhaust and evaporative emission testing shall be conducted by the manufacturer with gasoline having the specifications listed below, and the Executive Officer shall conduct exhaust and evaporative emission testing with gasoline having the specifications listed below.

Fuel Property a/	Limit	Test Method b/
Octane, (R+M)/2 (min)	91	D 2699-88, D 2700-88
Sensitivity (min)	7.5	D 2699-88, D 2700-88
Lead, g/gal (max) (No lead added)	0-0.01	Title 13 CCR 2253.4(c)
Distillation Range, degrees F		Title 13 CCR 2263 c/
10 pct. point,	130-150	
50 pct. point,	200-210 d/	
90 pct. point,	290-300 e/	
EP, maximum	390	
Residue, vol% (max)	2.0	
Sulfur, ppm by wt.	30-40	Title 13 CCR 2263
Phosphorous, g/gal (max)	0.005	Title 13 CCR 2253.4(c)
RVP, psi	6.7-7.0	Title 13 CCR 2263
Olefins, vol %	4.0-6.0	Title 13 CCR 2263
Total Aromatic	22-25	Title 13 CCR 2263
Hydrocarbons, vol %		
Benzene, vol %	0.8-1.0 f/	Title 13 CCR 2263
Multi-Substituted Alkyl	12-14	g/
Aromatic Hydrocarbons, vol %		
MTBE, vol %	10.8-11.2	Title 13 CCR 2263
Additives	Sufficient to meet requirements of Title 13, Section 2257, of California Code of Regulations	
Copper Corrosion	No. 1	D 130-88
Gum, Washed, mg/100 ml (max)	3.0	D 381-86
Oxidation Stability, minutes (min)	1000	D 525-88
Specific Gravity	Report h/	
Heat of Combustion	Report h/	
Carbon, wt%	Report h/	
Hydrogen, wt%	Report h/	

- a/ The gasoline must be blended from typical refinery feedstocks.
- b/ ASTM specification unless otherwise noted.
- c/ Although Title 13 CCR Section 2263 refers to the temperatures of the 50 and 90 percent points, this procedure can be extended to the 10 percent and end point temperatures, and to the determination of the residue content.
- d/ The range for interlaboratory testing is 195-215 degrees Fahrenheit.
- e/ The range for interlaboratory testing is 285-305 degrees Fahrenheit.
- f/ The range for interlaboratory testing is 0.7-1.1 percent by volume.
- g/ "Detailed Hydrocarbon Analysis of Petroleum Hydrocarbon Distillates, Reformates, and Gasoline by Single Column High Efficiency (Capillary) Column Gas Chromatography," by Neil Johansen, 1992, Boulder, CO.
- h/ The fuel producer should report this fuel property to the fuel purchaser. Any generally accepted test method may be used and shall be identified in the report.

2. Delete subparagraph (a)(3) (Methanol test fuel for otto-cycle vehicles).

3. Delete subparagraph (a)(4) (Alternative methanol test fuels for otto-cycle vehicles).
4. Amend subparagraph (a)(5) to read:

(5) The specification range of the fuels to be used under paragraph (a)(2) of this section shall be reported in accordance with 86.090-21(b)(3) or 86.091-21(b)(3).
5. Amend subparagraph (b)(2) to read:

(2) Except as noted below, petroleum fuel for diesel vehicles meeting the specifications referenced in 86.113-90(b)(2), or substantially equivalent specifications approved by the Executive Officer, shall be used in exhaust emission testing. The grade of petroleum fuel recommended by the engine manufacturer, commercially designated as "Type 2-D" grade diesel shall be used. For 1993 and subsequent model-year diesel vehicles, petroleum fuel meeting the specifications of 86.113-94(b)(2) may be used in exhaust emission testing as an option to the specifications in 86.113-90(b)(2). For 1995 and subsequent model-year diesel-fueled vehicles, the petroleum fuel used in exhaust emission testing may meet the specifications of the general reference fuel in Section 2256(g)(3), Title 13, California Code of Regulations, or substantially equivalent specifications approved by the Executive Officer as an option to the specifications in 86.113-90(b)(2) or 86.113-94(b)(2).
6. Amend subparagraph (b)(3) to read:

(3) Except as noted below, petroleum fuel for diesel vehicles meeting the following specifications, or substantially equivalent specifications approved by the Executive Officer shall be used in service accumulation. The grade of diesel fuel recommended by the engine manufacturer, commercially designated as "Type 2-D" grade diesel fuel, shall be used. For 1993 and subsequent model-year diesel-fueled vehicles, petroleum fuel meeting the specifications of 86.113-94(b)(3) may be used in service accumulation. For 1995 and subsequent model-year diesel-fueled vehicles, diesel fuel representative of commercial diesel fuel which will be generally available through retail outlets shall be used in service accumulation.
7. Delete subparagraph (b)(4) (Methanol test fuel for diesel vehicles).
8. Delete subparagraph (b)(5) (Alternative methanol test fuels for diesel vehicles).
9. Amend subparagraph (b)(6) to read:

(6) The specification range of the fuels to be used under paragraphs (b)(2) and (b)(3) of this section shall be

reported in accordance with 86.090-21(b)(3) or 86.091-21(b)(3).

10. Replace subparagraph (d) with:

(d) Methanol-Gasoline Fuel Specifications[.] for 1993 Model-Year Vehicles.

Various methanol-gasoline fuel blends will be used according to the type of methanol-fueled vehicle being certified and the particular aspect of the certification procedure being conducted, as specified below. Gasoline used for blending fuel for use in mileage accumulation shall be representative of commercial regular unleaded gasoline which will be generally available through retail outlets. Gasoline used for blending fuel for use in emission testing shall conform with the unleaded gasoline specification noted in paragraph (a) above.

Fuel additives and ignition improvers intended for use in methanol test fuels shall be subject to the approval of the Executive Officer. In order for such approval to be granted, a manufacturer must demonstrate that emissions will not be adversely affected by the use of the fuel additive or ignition improver.

- (1) Otto-cycle methanol vehicles and hybrid electric vehicles which use otto-cycle methanol engines

Mileage-accumulation fuel: For methanol vehicles and hybrid electric vehicles which use otto-cycle methanol engines a methanol-gasoline blend composed of 85-percent methanol which is representative of commercially available methanol and 15-percent unleaded gasoline as noted above.

Emission-testing fuel: For vehicles certifying on methanol, a methanol-gasoline blend composed of 85 percent chemical grade methanol and 15-percent unleaded gasoline as noted above.

- (2) Methanol-fueled diesel vehicles and hybrid electric vehicles which use methanol-fueled diesel engines.

Mileage-accumulation fuel: For methanol vehicles and hybrid electric vehicles which use methanol-fueled diesel engines, commercially available methanol fuel.

Emission-testing fuel: chemical grade methanol.

- (3) Fuel-flexible vehicles

Mileage-accumulation fuel: For both durability-data vehicles and emission-data vehicles, mileage accumulation shall be conducted with one fuel. For

vehicles designed to operate on methanol, a methanol-gasoline blend composed of 85-percent methanol and 15-percent unleaded gasoline both of which are representative of commercially available fuels shall be used. Alternative mileage accumulation fuels and procedures may be used if demonstrated to result in equivalent or more severe deterioration of the vehicle's emission control system, subject to the prior approval of the Executive Officer.

Emission-test fuel: Case (1) For regular exhaust only emission testing of emission-data vehicles, a methanol-gasoline blend composed of 85-percent chemical grade methanol and 15-percent unleaded gasoline (M85), and unleaded gasoline shall be used. For evaporative emission testing, a blend of 35-percent chemical grade methanol and 65-percent unleaded gasoline (M35) shall be used.

Case (2) For the testing required under 6.a.4.(D) [2].3-[(D)] of these procedures (of durability-data vehicles), exhaust emission tests (exhaust OMHCE or OMNMHCE for non-TLEVs, non-LEVs, and non-ULEVs, exhaust NMOG for TLEVs, LEVs, and ULEVs, exhaust formaldehyde, exhaust CO, and exhaust NOx) and evaporative emission tests (evaporative OMHCE) shall be conducted at the specified mileage intervals and with the specified fuels using 85-percent chemical grade methanol and 15-percent unleaded gasoline (M85), unleaded gasoline, and/or 35-percent chemical grade methanol and 65-percent unleaded gasoline (M35), as applicable. In addition, complete sets of emission tests shall be conducted at 5,000 miles, 50,000 miles and the final mileage point with unleaded gasoline.

For both Case (1) and (2), alternative methanol-gasoline blends may be used in place of M35 if demonstrated to result in equivalent or higher evaporative emissions, subject to the prior approval of the Executive Officer.

- (4) Other methanol fuels may be used for testing and service accumulation provided: (i) they are commercially available; (ii) information, acceptable to the Executive Officer, is provided to show that only the designated fuel would be used in customer service; (iii) use of a fuel listed in this section would not have a detrimental effect on emissions or durability; (iv) written approval from the Executive Officer of the fuel specifications must be provided prior to the start of testing.
- (5) The specification of the fuels to be used under paragraphs (d)(1), (d)(2), and (d)(3) of this section

shall be reported in accordance with 86.090-21(b)93) or 86.091-21(b)(3).

- (6) The specifications set forth in subparagraph (e) may be used as an option for 1993 model-year vehicles.

11. Add new subparagraph (e) to read:

(e) ~~Methanol~~Alcohol-Gasoline Fuel Specifications for 1994 and Subsequent Model-Year Vehicles

Various ~~methanol~~alcohol-gasoline fuel blends will be used according to the type of ~~methanol~~alcohol-fueled vehicle being certified and the particular aspect of the certification procedure being conducted, as specified below.

Fuel additives and ignition improvers intended for use in ~~methanol~~ alcohol test fuels shall be subject to the approval of the Executive Officer. In order for such approval to be granted, a manufacturer must demonstrate that emissions will not be adversely affected by the use of the fuel additive or ignition improver.

- (1) Otto-cycle ~~methanol~~ alcohol vehicles and hybrid electric vehicles which use otto-cycle ~~methanol~~ alcohol engines

~~Mileage-accumulation fuel:~~ For ~~methanol~~ vehicles ethanol and hybrid electric vehicles which use otto-cycle ~~methanol~~ or ethanol engines, fuel which meets the specifications listed in Title 13, CCR, Section 2292.1, ~~or~~ 2292.2, 2292.3 or 2292.4, as applicable.

~~Emission-testing fuel:~~ For ~~methanol~~ ethanol and hybrid electric vehicles which use otto-cycle ~~methanol~~ or ethanol engines, fuel which meets the specifications listed in Title 13, CCR, Section 2292.1, ~~or~~ 2292.2, 2292.3 or 2292.4, as modified by the following:

The fuel specification for Title 13, CCR, Section 2292.1 shall be modified to: a) require ~~methanol~~ content at 98.0 +/- 0.5 volume percent; b) require ~~ethanol~~ content at 1.0 +/- 0.1 volume percent; c) require certification gasoline as noted in paragraph (a) section 9.a.1. of these test procedures at 1.0 +/- 0.1 volume percent.

The fuel specification for Title 13, CCR, Section 2292.3 shall be modified to: a) require ethanol content at 98.0 +/- 0.5 volume percent; b) require methanol content at 1.0 +/- 0.1 volume percent; c) require certification gasoline conforming with specifications

noted in section 9.a.1. of these test procedures at 1.0 +/- 0.1 volume percent.

The fuel specification for Title 13, CCR, Section 2292.2 and 2292.4 shall be modified to require certification gasoline conforming with specifications noted in paragraph (a) section 9.a.1. of these test procedures as the hydrocarbon fraction. The vapor pressure specification for the emission-testing fuel shall be adjusted to 8.0 - 8.5 psi., using common blending components from the gasoline stream.

- (2) ~~Methanol~~ Alcohol-fueled diesel vehicles and hybrid electric vehicles which use ~~methanol~~ alcohol-fueled diesel engines

Mileage-accumulation fuel: For ~~methanol~~ ethanol and hybrid electric vehicles which use ~~methanol~~ alcohol-fueled diesel engines, fuel which meets the specifications listed in Title 13, CCR, Section 2292.1, or 2292.2, 2292.3 or 2292.4, as applicable.

Emission-testing fuel: For ~~methanol~~ ethanol and hybrid electric vehicles which use otto-cycle ~~methanol~~ alcohol engines, fuel which meets the specifications listed in Title 13, CCR, Section 2292.1, or 2292.2, 2292.3 or 2292.4, as modified by the following:

The fuel specification for Title 13, CCR, Section 2292.1 shall be modified to: a) require methanol content at 98.0 +/- 0.5 volume percent; b) require ethanol content at 1.0 +/- 0.1 volume percent; c) require certification gasoline as noted in paragraph (a) section 9.a.1. of these test procedures at 1.0 +/- 0.1 volume percent.

The fuel specification for Title 13, CCR, Section 2292.3 shall be modified to require ethanol content at 98.0 +/- 0.5 volume percent and require certification gasoline conforming with specifications noted in section 9.a.1. of these test procedures at 1.0 +/- 0.1 volume percent.

The fuel specification for Title 13, CCR, Section 2292.2 and 2292.4 shall be modified to require certification gasoline conforming with specifications noted in paragraph (a) section 9.a.1. of these test procedures as the hydrocarbon fraction. The vapor pressure specification for the emission-testing fuel shall be adjusted to 8.0 - 8.5 psi., using common blending components from the gasoline stream.

- (3) Fuel-flexible vehicles

Mileage-accumulation fuel: For both durability-data vehicles and emission-data vehicles, mileage accumulation shall be conducted with one fuel. For vehicles designed to operate on methanol, a fuel that meets the specifications listed in Title 13, CCR, Section 2292.2 shall be used. For vehicles designed to operate on ethanol, a fuel that meets the specifications listed in Title 13, CCR, Section 2292.4 shall be used. Alternative mileage accumulation fuels and procedures may be used if demonstrated to result in equivalent or more severe deterioration of the vehicle's emission control system, subject to the prior approval of the Executive Officer.

Emission-test fuel: Case (1) For regular exhaust only emission testing of emission-data vehicles, fuel that meets the specifications listed in Title 13, CCR, Section 2292.2 or 2292.4. For evaporative emission testing, a blend of fuel that meets the specifications listed in Title 13, CCR, Section 2292.2 or 2292.4 and gasoline meeting the specifications of section 9.a.1. of these test procedures such that the final blend is composed of either 35 volume percent methanol (plus or minus 1 volume percent of total blend) for methanol-fueled vehicles or 10 volume percent ethanol (plus or minus 1 volume percent of total blend) for ethanol-fueled vehicles shall be used.

Case (2) For the testing required under 6.a.4.(D) 3-(D) of these procedures (of durability-data vehicles), exhaust emission tests (exhaust OMHCE or OMNMHCE for non-TLEVs, non-LEVs, and non-ULEVs, exhaust NMOG for TLEVs, LEVs, and ULEVs, exhaust formaldehyde, exhaust CO, and exhaust NOx) and evaporative emission tests (evaporative OMHCE) shall be conducted at the specified mileage intervals using: (i) emission testing fuel that meets the specifications listed in subparagraph (e)(1) of section 9.a.11. of these test procedures and (ii) a blend of fuel produced by combining emission-testing fuel that meets the specifications in subparagraph (e)(1) of section 9.a.11. of these test procedures and certification gasoline described in paragraph (a) section 9.a.1. of these test procedures such that the final fuel is either 35 volume percent methanol (plus or minus 1 volume percent of total blend) and 65 volume percent certification gasoline for methanol-fueled vehicles or 10 volume percent ethanol (plus or minus 1 volume percent of total blend) and 90 volume percent certification gasoline for ethanol-fueled vehicles. In addition, complete sets of emission tests shall be conducted at 5,000 miles, 50,000 miles and the final

mileage point with commercially available unleaded gasoline-

For both Case (1) and (2), alternative alcohol-gasoline blends may be used in place of M35 or E10 if demonstrated to result in equivalent or higher evaporative emissions, subject to the prior approval of the Executive Officer.

- (4) *The specification of the fuels to be used under paragraphs (e)(1), (e)(2), (e)(3) and (e)(4) of this section shall be reported in accordance with 86.090-21(b)(3) or 86.091-21(b)(3).*

12. Add new subparagraph (ef) to read:

(f) Gaseous Fuel Specifications for 1988 Through 1993 Model Year Vehicles.

(1) Gaseous fuels representative of commercial gaseous fuels which will be generally available through retail outlets in California or liquid petroleum gas having the ASTM D1835 or NGPA HD-5 specification shall be used in service accumulation.

(2) Liquid petroleum gas having the ASTM D1835 or NGPA HD-5 specification shall be used for exhaust and evaporative emission testing.

(3) Natural gas representative of commercial natural gas which will be generally available through retail outlets in California shall be used for exhaust emission testing.

(4) Written approval from the Administrator of the fuel specifications must be provided prior to the start of testing.

(5) For dedicated gaseous- and dual-fueled vehicles and for hybrid electric vehicles which use gaseous-fueled engines, the mileage accumulation fuel for both durability-data vehicles and emission-data vehicles shall be conducted with one fuel. For vehicles designed to operate on natural gas, natural gas which meets the requirements of (3) shall be used. For vehicles designed to operate on liquefied petroleum gas, liquefied petroleum gas which meets the requirements of (2) shall be used.

(6) *The specifications set forth in subparagraph (g) may be used as an option for 1993-model year vehicles.*

(7) Alternative mileage-accumulation fuels and test procedures may be used if demonstrated to result in equivalent or more severe deterioration of the vehicle's emission control system, subject to the prior approval of the Executive Officer.

(8) Alternative emission-test fuels may be used if demonstrated to result in equivalent or higher exhaust emissions, subject to the prior approval of the Executive Officer.

13. Add new subparagraph (g) to read:

(g) Gaseous Fuel Specifications for 1994 and Subsequent Model Year Vehicles.

(1) Dedicated gaseous- and dual-fueled vehicles and hybrid electric vehicles which use liquefied petroleum gas

Mileage accumulation fuel: Liquefied petroleum gas meeting the specifications listed in Title 13, CCR, Section 2292.6 shall be used in service accumulation.

Emission-test fuel: Liquefied petroleum gas meeting the specifications listed in Title 13, CCR, Section 2292.6 shall be used for exhaust and evaporative emission testing with the following exceptions: a) propane content limited to 93.5 +/- 1.0 volume percent; b) propene content limited to 3.8 +/- 0.5 volume percent; c) butane and heavier components limited to 1.9 +/- 0.3 volume percent.

(2) Dedicated gaseous- and dual-fueled vehicles and hybrid electric vehicles which use natural gas

Mileage accumulation fuel: ~~Natural gas meeting the~~ specifications listed in Title 13, CCR, Section 2292.5 shall be used in service accumulation.

Emission-test fuel: Natural gas meeting the specifications listed in Title 13, CCR, Section 2292.5 as modified by the following: a) methane content limited to 90.0 +/- 1.0 mole percent; b) ethane content limited to 4.0 +/- 0.5 mole percent; c) C₃ and higher hydrocarbon content at 2.0 +/- 0.3 mole percent; d) oxygen content at 0.5 +/- 0.1 mole percent; e) inert gases (sum of CO₂ and H₂) content at 3.5 +/- 0.5 mole percent.

b. Road Load Power Test Weight

In paragraph 86.129-80 and 86.129-94:

1. Amend subparagraph (a) to add:

ROAD LOAD POWER TEST WEIGHT AND INERTIA WEIGHT CLASS DETERMINATION

ROAD LOAD POWER AT 50. mi/hr-LIGHT DUTY TRUCKS	LOADED WEIGHT (POUNDS) ⁵	EQUIVA- LENT TEST WEIGHT (POUNDS)	INERTIA WEIGHT CLASS (POUNDS)
	10001 to 10250	10000	10000
	10251 to 10750	10500	10500
	10751 to 11250	11000	11000
	11251 to 11750	11500	11500
	11751 to 12250	12000	12000
	12251 to 12750	12500	12500
	12751 to 13250	13000	13000
	13251 to 13750	13500	13500
	13751 to 14000	14000	14000

⁵ For 1995 and subsequent medium-duty vehicles, "Loaded Weight" shall be the average of the vehicle's curb weight and gross vehicle weight.

2. Add subparagraph (d) to read:

(d) Power absorption unit adjustment- medium-duty vehicles.

(1) The power absorption unit shall be adjusted to reproduce road load power at 50 mph true speed. The dynamometer power absorption shall take into account the dynamometer friction, as discussed in paragraph 86.118-78.

(2) The dynamometer road load setting is determined from the loaded test weight, the reference frontal area, vehicle protuberances, and an aerodynamic drag coefficient as determined appropriate by the Executive Officer. The vehicle manufacturer shall submit the procedure by which the aerodynamic drag coefficient was determined in the test vehicle information section in the certification application. The dynamometer road load setting shall be determined by the following equation.

(i) For medium-duty vehicles to be tested on twin or single, large roll dynamometers.

$$Hp = (0.00182)V((0.015)(W)+(0.0375)(Cd)(A)(V^2)/(32.2ft/s^2))+P$$

where:

Hp=the dynamometer power absorber setting at 50 mph (horsepower).

0.00182=conversion factor to horsepower.

V=velocity in feet/sec.

0.015=coefficient of rolling resistance.

W=loaded vehicle weight in pounds.

0.0375=air density in lbm/cubic ft.

Cd=aerodynamic drag coefficient

A=reference frontal area in square ft.
32.2 ft/s²=gravitational acceleration
P=protuberance power (horsepower)

- (ii) The protuberance power, P shall be determined per subparagraph 86.129-80 (c)(2)(i).
- (iii) The dynamometer power absorber setting for medium-duty vehicles shall be rounded to the nearest 0.1 horsepower.
- (3) The road load power calculated above shall be used or the vehicle manufacturer may determine the road load power by an alternate procedure requested by the manufacturer and approved in advance by the Executive Officer.
- (4) Where it is expected that more than 33 percent of a vehicle line within an engine-system combination will be equipped with air conditioning, per subparagraph 86.090-24(g)(2), 86.092-24(g)(2), or 86.095-24(g)(2), the road load power as determined in paragraph (d) (2) or (3) of this section shall be increased by 10 percent up to a maximum increment of 1.4 horsepower, for testing all test vehicles of that vehicle line within that engine-system combination if those vehicles are intended to be offered with air conditioning in production. This power increment shall be added to the indicated dynamometer power absorption setting prior to rounding off this value.
- (5) For electric and hybrid electric vehicle lines where it is expected that more than 33 percent of a vehicle line will be equipped with air conditioning, per subparagraph 86.090-24(g)(2), 86.092-24(g)(2), or 86.095-24(g)(2), which derives power from the battery pack, the road load shall be increased by the incremental horsepower required to operate the air conditioning unit. The incremental increase shall be determined by recording the difference in energy required for a hybrid electric vehicle under all-electric power to complete the running loss test fuel tank temperature profile test sequence without air conditioning and the same vehicle tested over the running loss test fuel tank temperature profile test sequence with the air conditioning set to the "NORMAL" air conditioning mode and adjusted to the minimum discharge air temperature and high fan speed over the time period needed to perform the test sequence, and converting this value into units of horsepower. Vehicles equipped with automatic temperature controlled air conditioning systems shall be operated in "AUTOMATIC" temperature and fan modes with the system set at 72 degrees Fahrenheit. The running loss test fuel tank temperature profile test sequence is found in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles" as incorporated by reference in section 1976, Title 13, CCR.

c. Test Sequence; General Requirements

Amend paragraph 86.130-78 to read:

The test sequence shown in figure B78-10 shows the steps encountered as the test vehicle undergoes the procedures subsequently described to determine conformity with the standards set forth. Ambient temperature levels shall not be less than 68 degrees F (20 degrees C) nor more than 86 degrees F (30 degrees C) ... For purposes of determining conformity with 50 degrees F test requirements, the procedures set forth in Section 11k of these test procedures shall apply. For all hybrid electric vehicles and all 1995 and subsequent model-year vehicles certifying to running loss and useful life evaporative emission standards, the test sequence specified in "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles" as incorporated by reference in section 1976, Title 13, CCR shall apply.

d. Vehicle Preconditioning

In paragraphs 86.132-82 and 86.132-90:

1. Amend subparagraph (a)(2) to read:

(2) Within one hour of being fueled the vehicle shall be placed, either by being driven or pushed, on a dynamometer and operated through one Urban Dynamometer Driving Schedule (UDDS) test procedure, see 86.115 and Appendix I of the federal procedures.

The UDDS performed prior to a non-regeneration emission test shall not contain a regeneration (diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems only). A gasoline fueled test vehicle may not be used to set dynamometer horsepower.

2. Amend subparagraph (a)(3) to read:

(3) For those unusual circumstances where additional preconditioning is desired by the manufacturer, such preconditioning may be allowed with the advance approval of the Executive Officer. The Executive Officer may also choose to conduct or require the conduct of additional preconditioning to insure that the evaporative emission control system is stabilized in the case of otto-cycle engines, or to insure that the exhaust system is stabilized in the case of diesel engines. The additional preconditioning shall consist of an initial one hour minimum soak and, one, two, or three driving cycles of the UDDS (or more in the case of a diesel vehicle equipped with a periodically regenerating trap oxidizer system, which is being preconditioned for a regeneration emission test), as described in paragraph (a)(2) of this section, each followed by a soak of at least one hour with engine off, engine compartment cover closed and cooling

fan off. The vehicle may be driven off the dynamometer following each UDDS for the soak period.

3. For all hybrid electric vehicles and all 1995 and subsequent model-year vehicles subject to running loss and useful life evaporative emission standards, the preconditioning sequence specified in "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles" as incorporated by reference in section 1976, Title 13, CCR shall apply.

e. Regeneration Recording Requirements

Amend paragraph 86.142-82 by adding the following subparagraph (r) which reads:

(r) The manufacturer shall record in the durability-data vehicle log book, the number of regenerations which occur during the 50,000 mile durability test of each diesel passenger car, light-duty truck and medium-duty vehicle equipped with a periodically regenerating trap oxidizer system. The manufacturer shall include, for each regeneration: the date and time of the start of regeneration, the duration of the regeneration, and the accumulated mileage at the start and the end of regeneration. The number of regenerations will be used in the calculation of the correction factor in 40 CFR Part 86, Section 28.

Amend paragraph 86.142-90 by adding the following subparagraph (s) which reads:

(s) The manufacturer shall record in the durability-data vehicle log book, the number of regenerations which occur during the 50,000 mile durability test of each diesel passenger car, light-duty truck and medium-duty vehicle equipped with a periodically regenerating trap oxidizer system. The manufacturer shall include, for each regeneration: the date and time of the start of regeneration, the duration of the regeneration, and the accumulated mileage at the start and the end of regeneration. The number of regenerations will be used in the calculation of the correction factor in 40 CFR Part 86, Section 28.

f. All-Electric Range Test Requirements

All 1993 and subsequent ZEVs and Type A and Type B hybrid electric vehicles shall be subject to the All-Electric Range Test specified below for the purpose of determining the energy efficiency and operating range of a ZEV or of a hybrid electric vehicle operating without the use of its auxiliary power unit. For hybrid electric vehicles, the manufacturer may elect to conduct the All-Electric Range Test prior to vehicle preconditioning in the exhaust and evaporative emission test sequence specified in "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles" as incorporated by reference in section 1976, Title 13, CCR.

- (1) Cold soak. The vehicle shall be stored at an ambient temperature not less than 68 degrees F (20 degrees C) and not more than 86 degrees F (30 degrees C) for 12 to 36 hours. During this time, the vehicle's battery shall be charged to a full state-of-charge.
- (2) Driving schedule. At the end of the cold soak period, the vehicle shall be placed, either driven or pushed, onto a dynamometer and operated through a Highway Fuel Economy Driving Schedule, found in Part 600, Appendix I of the CFR, followed immediately by an Urban Dynamometer Driving Schedule, found in Part 600, Appendix I of the CFR, followed by another Highway Fuel Economy Driving Schedule and an Urban Dynamometer Driving Schedule. This sequence of driving schedules shall be repeated until the vehicle is no longer able to maintain within 5 miles per hour of the speed requirements or within 2 seconds of the time requirements of the driving schedules in the case of a ZEV, or unable to maintain within 5 miles per hour of the speed requirements or within 2 seconds of the time requirement of the driving schedules without the use of the auxiliary power unit in the case of a hybrid electric vehicle.
- (3) Recording requirements. Once the vehicle is no longer able to maintain the speed and time requirements specified in (2) above, or once the auxiliary power unit turns on, in the case of a hybrid electric vehicle, the accumulated mileage and energy usage of the vehicle from the point where electricity is introduced from the electrical outlet shall be recorded, and the vehicle shall be brought to an immediate stop, thereby concluding the All-Electric Range Test.
- (4) Regenerative braking. Regenerative braking systems may be utilized during the range test. The braking level, if adjustable, shall be set according to the manufacturer's specifications prior to the commencement of the test. The driving schedule speed and time tolerances specified in (2) shall not be exceeded due to the operation of the regenerative braking system.

g. Calculations: exhaust emissions

Amend paragraph 86.144-94 by adding the following subparagraph (b)(10) which reads:

(10) Organic material non-methane hydrocarbon equivalent mass for ethanol vehicles:

$$\begin{aligned} \text{OMNMHCE}_{\text{mass}} = & \text{NMHC}_{\text{mass}} + (13.8756/32.042) \times (\text{CH}_3\text{OH})_{\text{mass}} + \\ & (13.8756/46.064) \times (\text{CH}_3\text{CH}_2\text{OH})_{\text{mass}} + (13.8756/30.0262) \times \\ & (\text{HCHO})_{\text{mass}} + (13.8756/44.048) \times (\text{CH}_3\text{CHO})_{\text{mass}} \end{aligned}$$

the case of a light or by covering the odometer in the case of a flag the first time the minimum maintenance interval established during certification testing is reached and which shall remain activated until reset. After resetting, the maintenance indicator shall activate automatically when the minimum maintenance interval, when added to the vehicle mileage at the time of resetting, is again reached and shall again remain activated until reset. When the maintenance indicator consists of a light, it shall also activate automatically in the engine-run key position before engine cranking to indicate that it is functioning. The maintenance indicator shall be located on the instrument panel and shall, when activated, display the words "oxygen sensor" or may display such other words determined by the Executive Officer to be likely to cause the vehicle owner to seek oxygen sensor replacement. The maintenance indicator shall be separate from the malfunction indicator light required by Section 1968, Title 13, California Code of Regulations;

(b) the manufacturer shall provide free replacement of the oxygen sensor, including both parts and labor, and shall reset the maintenance indicator without any charge, the first time the maintenance interval established during certification testing is reached for vehicles certified with scheduled sensor maintenance before 50,000 miles. If the oxygen sensor is replaced pursuant to the warranty provisions of Section 2037, Title 13, California Code of Regulations, before the first maintenance interval is reached, the manufacturer shall also replace the oxygen sensor and reset the maintenance indicator at the oxygen sensor and reset the maintenance indicator at the mileage point determined by adding the maintenance interval to the vehicle's mileage at the time of the warranty replacement. If the calculated mileage point for a second oxygen sensor replacement would exceed 50,000 miles, no free second replacement shall be required;

(c) the maintenance indicator shall be resettable. The maintenance instructions required by paragraph 5.b. of these procedures shall provide instructions for the resetting of the maintenance indicator, and shall specify that the maintenance indicator shall be reset each time the oxygen sensor is replaced; and

(d) notwithstanding the provisions of Section 2037(c), Title 13, California Code of Regulations, the oxygen sensor, including any replacement required pursuant to this section, shall be warranted for the applicable warranty period of the vehicle or engine in accordance with Section 2037(a), Title 13, California Code of Regulations. If such oxygen sensor fails during this period, it shall be replaced by the manufacturer in accordance with Section 2037(d), Title 13, California Code of Regulations.

- (6) Choke, cleaning or lubrication only (30,000 miles).
- (7) Idle speed (30,000 miles).

correction factor (diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems only). These values shall not exceed the appropriate 100,000 mile oxides of nitrogen standard.

4. Compliance with the particulate standard for options 1 and 2 shall be determined as follows:
 - i. the interpolated 4,000 and 50,000 mile points on the linear regression line in section b.1. shall not exceed the appropriate particulate, except as in ii. below.
 - ii. the linear regression line in section b.1. may exceed the standard provided that no data point exceeds the standard.
 - iii. the particulate data from the 4,000 mile test point of the emission data vehicle shall be multiplied by the deterioration factor computed by dividing the interpolated 50,000 mile point by the interpolated 4,000 mile point, and the appropriate exhaust emission correction factor (diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems only). These values shall not exceed the appropriate particulate standard.
5. All references in these test procedures to "useful life", 5 years, and 50,000 miles shall mean "total life", 10 years, and 100,000 miles, respectively, except in section 10.b.2.

c. Maintenance

Only the following scheduled maintenance shall be allowed under subparagraph 86.085-25 (a)(1)(i).

1. 25(a)(1)(i) Option 1. For 1988 model otto-cycle or diesel vehicles, and 1989 and later model otto-cycle or diesel light-duty trucks and medium-duty vehicles 3751 L.V.W. and greater, and 1993 and subsequent diesel light-duty trucks and medium-duty vehicles 3751 L.V.W. and greater, maintenance shall be restricted to the inspection, replacement, cleaning, adjustment, and/or service of the following items at intervals no more frequent than indicated.
 - (1) Drive belt tension on engine accessories (30,000 miles).
 - (2) Valve lash (15,000 miles).
 - (3) Spark plugs (30,000 miles).
 - (4) Air filter (30,000 miles).
 - (5) Exhaust gas sensor (30,000 miles): Provided that:
 - (a) the manufacturer shall equip the vehicle with a maintenance indicator consisting of a light or flag, which shall be preset to activate automatically by illuminating in

B. The linear regression line in section b.1. may exceed the standard provided that no data point exceeds the standard.

C. The hydrocarbon and carbon monoxide data from the 4,000 mile test point of the emission data vehicle shall be multiplied by the deterioration factor computed by dividing the interpolated 50,000 mile point by the interpolated 4,000 mile point, and the appropriate exhaust emission correction factor (diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems only). These values shall not exceed the appropriate hydrocarbon and carbon monoxide standards.

ii. For Option 2:

A. The interpolated 4,000 and 100,000 mile points on the linear regression line in section b.1. shall not exceed the appropriate hydrocarbon and carbon monoxide standards, except as in 8. below.

B. The linear regression line in section b.1. may exceed the standard provided that no data point exceeds the standard.

C. The hydrocarbon and carbon monoxide data from the 4,000 mile test point of the emission data vehicle shall be multiplied by the deterioration factor computed by dividing the interpolated 100,000 mile point by the interpolated 4,000 mile point, and the appropriate exhaust emission correction factor (diesel passenger cars, light-duty trucks, and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems only). These values shall not exceed the appropriate 100,000 mile hydrocarbon and carbon monoxide standards.

3. Compliance with the oxides of nitrogen standard for Options 1 and 2 shall be determined as follows:

i. the interpolated 4,000 and 100,000 mile points on the linear regression line in section b.1. shall not exceed the appropriate 100,000 mile oxides of nitrogen standard, except as in ii. below.

ii. the linear regression line in section b.1. may exceed the standard provided that no data point exceeds the standard.

iii. the oxides of nitrogen data from the 4,000 mile test point of the emission data vehicle shall be multiplied by the deterioration factor computed by dividing the interpolated 100,000 mile point by the interpolated 4,000 mile point, and the appropriate exhaust emission

performed before and after all unscheduled maintenance and be used in the DF calculation.

5. Evaporative Compliance Criteria

If a manufacturer conducts evaporative emission testing (gasoline- and methanol alcohol-fueled vehicles only) in conjunction with exhaust durability testing, the vehicle manufacturer is required to show compliance with the evaporative emission standard for 50,000 miles. If the manufacturer wishes to conduct testing beyond 50,000 miles, all data must be submitted to the Executive Officer. The Executive Officer will not use any evaporative emission standard. However, the manufacturer must warrant the evaporative emission control system for 10 years or 100,000 miles.

b. Specific Guidelines for Compliance

Each exhaust emission durability data vehicle shall be driven, with all emission control systems installed and operating, for 100,000 miles or such lesser distance as the Executive Officer may agree to as meeting the objectives of this procedure. Emission tests performed on emission-data vehicles and durability-data vehicles (for determination of the deterioration factors) shall be non-regeneration emission tests for diesel passenger cars, light-duty trucks and medium-duty vehicles equipped with periodically regenerating trap oxidizer systems. Compliance with the emission standards shall be established as follows:

1. The linear regression line for all pollutants shall be established by use of all required data from tests of the durability vehicle at every 5,000 mile interval from 5,000 to 100,000 miles. The requirements in subparagraph 86.088-28(a)(4)(i)(B), 86.090-28(a)(4)(i)(B), and 86.091-28(a)(4)(i)(B) (durability vehicles must meet emissions standards) refer, for each pollutant, to the California 100,000 mile emission standards.
2. Compliance with the hydrocarbon and carbon monoxide standards shall be determined as follows:
 - i. For Option 1:
 - A. The interpolated 4,000 and 50,000 mile points on the linear regression line in section b.1. shall not exceed the appropriate hydrocarbon and carbon monoxide standards, except as in B. below.

5. Testing before unscheduled maintenance may be omitted with the prior consent of the Executive Officer when testing would be dangerous to a vehicle or an operator.

the procedures, and (2) the system and engine designs, on the basis of previous engineering experience, would not be expected to exceed the applicable standards after 100,000 miles. For example, a diesel vehicle that shows a flat deterioration curve (D.F. = 1.0) for the first 50,000 miles and which is not equipped with any add-on emission control system (such as EGR) may be eligible for such a waiver. The Executive Officer will evaluate each request on a case-by-case basis. The manufacturer must submit its request to the Executive Officer to stop testing within ten working days after the last emission test.

If a durability vehicle accumulates less than 100,000 miles the manufacturer shall submit evidence that the engine is capable of meeting the applicable emission standards for 100,000 miles. Such evidence shall include engineering data on piston rings, piston, valves, cylinder head, fuel system ignition system, etc., as applicable.

Any decision to stop mileage accumulation before 100,000 miles does not relieve the manufacturer from its warranty and recall obligations.

For the last 50,000 miles, the Executive Officer may, upon the request of the manufacturer, allow driving schedules different from the standard AMA driving cycle for accelerated mileage accumulation and a reduced test frequency. The evaluation of alternate test programs will be based on the type of emission control system involved and the characteristic of the cumulative emission control system deterioration.

3. Scheduled Maintenance

A vehicle manufacturer who initially intends to certify a vehicle to the 50,000 mile procedure may not change to the 100,000 mile option after mileage accumulation unless the manufacturer starts initial mileage accumulation using, for each maintenance item, the most stringent maintenance schedule of either the 100,000 mile option or the 50,000 mile certification requirements.

4. Unscheduled Maintenance

The Executive Officer will follow the provisions of section 5.a of these procedures, in evaluating any manufacturer's request for unscheduled maintenance. Manufacturers shall obtain the Executive Officer's approval before performing any unscheduled emission control component/system maintenance. In all cases, the degree of system degradation must not be improved by any inspection or repairs. Emission tests must be

10. Optional 100,000 Mile Certification Procedure

The following provisions and alternate emission standards shown in section (3) of these procedures shall apply to any engine section family certified to the optional 100,000 mile certification standards.

a. General Guidelines for Implementation

1. Designation

The manufacturer shall designate in the preliminary application for certification those engine families that will be certified to the 100,000 mile procedures. In order to allow the manufacturer as much flexibility as possible, the manufacturer may at any time designate additional engine families or remove any designated engine family. Families originally intended for 50,000 mile certification may be designated as 100,000 mile families after the start of durability testing and vice versa. The Executive Officer must be notified within ten working days of any such changes. Manufacturers are cautioned that any engine family certified to the 100,000 mile certification procedure must comply with the allowable maintenance provisions of section 10.b in these procedures during the engine mileage accumulation.

2. Mileage Accumulation

~~All durability vehicles must be run to at least 50,000 miles~~ for established emission control systems; early termination of mileage accumulation may be requested by the manufacturer if sufficient evidence as described below is provided to satisfy the Executive Officer that further testing is unnecessary.

Testing beyond 50,000 miles must be conducted in accordance with the certification test procedures applicable prior to 50,000 miles. Exhaust emissions tests shall be performed at every 5,000 mile interval starting with the 55,000 mile point and ending with the 100,000 mile point, and before and after all scheduled maintenance.

The Executive Officer may, upon request by the manufacturer waive any exhaust emission testing beyond 50,000 miles, if he or she finds that (1) the extrapolated 100,000 mile points and interpolated 4,000 mile points on the least squares lines comply with the line crossing provisions of section 10.b. of

4. The additional criteria outlined in Section 6.a. (Mileage and Service Accumulation: Emission Measurements) shall be used to determine the durability-data testing schedule and the emission-data 4,000 mile test point.

- (8) Fuel Filter (30,000 miles).
- (9) Injection timing (30,000 miles).

Option 2. For 1981-1988 and later model otto-cycle vehicles or 1988 and later diesel vehicles, maintenance shall be restricted to the inspection, replacement, cleaning, adjustment, and/or service of the following items at intervals no more frequent than indicated:

- (1) Drive belt tension on engine accessories (30,000 miles).
- (2) Valve lash (15,000 miles).
- (3) Spark plugs (30,000 miles).
- (4) Air filter (30,000 miles).
- (5) Fuel Filter (30,000 miles).
- (6) Idle speed (30,000 miles).
- (7) Injection timing (30,000 miles).

- 2. In addition, adjustment of the engine idle speed (curb idle and fast idle), valve lash, and engine bolt torque may be performed once during the first 5,000 miles of scheduled driving, provided the manufacturer makes a satisfactory showing that the maintenance will be performed on vehicles in use.
- d. The manufacturer shall agree to apply to vehicles certified under this paragraph the provision of Section 43204 of the California Health and Safety Code for a period of ten years or 100,000 miles, whichever first occurs.

11. Additional Requirements

- a. In order to qualify for the alternative durability program, in addition to the requirements of paragraph 86.085-13, the algorithm requirements of Appendix III shall be met and only the first 50,000 miles (or 100,000 miles, as applicable) of data or its equivalent shall be used.
- b. For otto-cycle vehicles or hybrid electric vehicles which use otto-cycle engines, evidence shall be supplied showing that the air/fuel metering system or secondary air injection system is capable of providing sufficient oxygen to theoretically allow enough oxidation to attain the CO emission standards at barometric pressures equivalent to those expected at altitudes ranging from sea level to 6000 feet elevations.

A vehicle will be deemed in compliance with the above requirement if the manufacturer demonstrates that the tailpipe air/fuel ratio (TAFR) is, at elevations up to 6000 feet, stoichiometric or leaner in each of several driving modes. However, if a vehicle operates in a given driving mode at sea level with a TAFR richer than stoichiometric, then for that particular driving mode the manufacturer is only required to show that the TAFR is, at elevations up to 6000 feet, no richer than the TAFR at sea level. The driving modes selected for testing shall be representative of the full range of normal driving conditions, and shall include the following three steady-state modes: idle, 30 mph road load cruise, 50 mph road load cruise. Assuming the use of dry air and indolene fuel (hydrogen to carbon atom ratio of 1.85), a TAFR of 14.6 shall be considered a stoichiometric ratio. The vehicle manufacturer may correct this value for different fuels and/or humidity, subject to approval by the Executive Officer.

For fuel injected vehicles or hybrid electric vehicles which use fuel-injected engines, compliance may be demonstrated upon a showing by the manufacturer that the fuel injection system distributes fuel based on air mass flow, rather than volume flow, and is therefore self-compensating. All submitted test proposals will be evaluated on their acceptability by the Executive Officer.

As an alternative to the demonstration described above, a manufacturer may demonstrate compliance by testing California vehicle configurations as part of its federal high altitude certification requirements. Engine families which meet all the applicable California low altitude emission standards when tested at the EPA test elevation are deemed to be in compliance.

Exemptions to the high altitude provisions as allowed by the federal government in 86.087-8, 86.088-9, 86.090-8, 86.090-9, and 86.091-9 shall not be approved.

- c. The exhaust emissions shall be measured from all exhaust emission data vehicles tested in accordance with the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600, Subpart B). The oxides of nitrogen emissions measured during such tests shall be multiplied by the oxides of nitrogen deterioration factor computed in accordance with paragraph 86.088-28, 86.090-28, and 86.091-28, and then rounded and compared with the standard as set forth in section 3 preceding. All data obtained pursuant to this paragraph shall be reported in accordance with procedures applicable to other exhaust emissions data required pursuant to these procedures.

In the event that one or more of the manufacturer's emission data vehicles fail the HWFET standard listed in section 3, the manufacturer may submit to the Executive Officer engineering data or other evidence showing that the system is capable of complying with the standard. If the Executive Officer finds, on the basis of an engineering evaluation, that the system can comply with the HWFET standard, he or she may accept the information supplied by the manufacturer in lieu of vehicle test data.

- d. Labeling required pursuant to paragraph 86.088-35, 86.090-35, and 86.091-35, 86.084-35, and 86.095-35, and Section 1965, Chapter 3, Title 13 of the California Code of Regulations shall conform with the requirements specified in the "California Motor Vehicle Emission Control Label Specifications."

- e. The manufacturer shall submit to the Executive Officer a statement that those vehicles for which certification is requested have driveability and performance characteristics which satisfy that manufacturer's customary driveability and performance requirements for vehicles sold in the United States. This statement shall be based on driveability data and other evidence showing compliance with the manufacturer's performance criteria. This statement shall be supplied with the manufacturer's final application for certification, and with all running changes for which emission testing is required.

If the Executive Officer has evidence to show that in-use vehicles demonstrate poor performance that could result in wide-spread tampering with the emission control systems, he or she may request all driveability data and other evidence used by the manufacturer to justify the performance statement.

- f. For all vehicles subject to the provisions of Section 1968, Title 13, California Code of Regulations, the manufacturer shall submit with its application for certification a description of the malfunction and diagnostic system to be installed on the vehicles. (The vehicles shall not be certified unless the Executive Officer finds that the malfunction and diagnostic system complies with the requirements of Section 1968).

- g. The provisions of the incorporated federal test procedures which allow manufacturers to omit methanol and formaldehyde emission testing of 1990 through 1994 methanol-fueled vehicles shall not be applicable in California.
- h. The following requirements shall apply to methanol and ethanol fuel-flexible vehicles which are not certified to TLEV, LEV, or ULEV emission standards:
The emission testing required under 6.a.24.(D) (Fuel-flexible vehicle special emission testing) shall be made part of the regular certification program and submitted to the Executive Officer for review. Certification for methanol-fueled vehicles shall be denied unless the exhaust emission values resulting from testing with 35-percent methanol and 65-percent unleaded certification gasoline, or another approved methanol-gasoline blend, at the required mileage intervals, and with unleaded certification gasoline at 5,000 miles, 50,000 miles and the final mileage point, comply with the applicable standards. Certification for ethanol-fueled vehicles shall be denied unless the exhaust emission values resulting from testing with 10-percent ethanol and 90-percent certification gasoline, or another approved ethanol-gasoline blend, at the required mileage intervals, and with certification gasoline at 5,000 miles, 50,000 miles and the final mileage point, comply with the applicable standards.
- i. Certification, if granted, is effective only for the vehicle/engine family described in the original manufacturer's certification application. Modifications by a secondary manufacturer to vehicles/engines shall be deemed not to increase emissions above the standards under which those vehicles/engines were certified and to be within the original certification if such modifications do not: (1) increase vehicle weight more than 10 percent above the curb weight, increase frontal area more than 10 percent, or result in a combination increase of weight plus frontal area of more than 14 percent; or (2) include changes in axle ratio, tire size, or tire type resulting in changes in the drive train ratio of more than 5 percent; or (3) include any modification to the emission control system. No originally certified vehicle/engine which is modified by a secondary manufacturer in a manner described in items (1) through (3) of the preceding sentence may be sold to an ultimate purchaser, offered or delivered for sale to an ultimate purchaser, or registered in California unless the modified vehicle/engine is certified by the state board in accordance with applicable test procedures to meet emission standards for the model year for which the vehicle/engine was originally certified.

For the purposes of this subsection, "secondary manufacturer" means any person, other than the original manufacturer, who modifies a new motor vehicle prior to sale to the ultimate purchaser.

- j. A statement must be supplied that the production vehicles shall be in all material respects the same as those for which certification is granted.
- k. Following a 12 to 36 hour cold soak at a nominal temperature of 50 degrees F, emissions of NMOG (multiplied by the reactivity adjustment factor for fuels other than conventional gasoline), CO, and NOx, and formaldehyde measured on the Federal Test Procedure (40 CFR Part 86), conducted at a nominal test temperature of 50 degrees F, shall not exceed the above standards for vehicles of the same emission category and vehicle type subject to a cold soak and emission test at 68 to 86 degrees F. For all TLEVs, emissions of NMOG and formaldehyde at 50 degrees F shall not exceed the 50,000 mile certification standard multiplied by a factor of 1.75. For all LEVs, emissions of NMOG and formaldehyde at 50 degrees F shall not exceed the 50,000 mile certification standard multiplied by a factor of 1.75. For all ULEVs, emissions of NMOG and formaldehyde at 50 degrees F shall not exceed the 50,000 mile certification standard multiplied by a factor of 1.0. Emissions of NMOG shall be multiplied by a reactivity adjustment factor, if any, prior to comparing with the 50,000 certification standard multiplied by the specified factor.

The test vehicles shall not be subject to a diurnal heat build prior to the cold start exhaust test or evaporative emission testing. For diesel vehicles, compliance with the particulate standard applicable to the corresponding vehicle emission category and vehicle type shall also be demonstrated.

i. For the 50 degrees F emission test, the nominal preconditioning, soak, and test temperatures shall be maintained within 3 degrees F of the nominal temperature on an average basis and within 5 degrees F of the nominal temperature on a continuous basis. The temperature shall be sampled at least once every 15 seconds during the preconditioning and test periods and at least once each 5 minutes during the soak period. A continuous strip chart recording of the temperature with these minimum time resolutions is an acceptable alternative to employing a data acquisition system.

ii. The test site temperature shall be measured at the inlet of the vehicle cooling fan used for testing.

iii. The test vehicle may be fueled before the preconditioning procedure in a fueling area maintained within a temperature range of 68 to 86 degrees F. The preconditioning shall be conducted at a nominal temperature of 50 degrees F. The requirement to saturate the evaporative control canister(s) shall not apply.

iv. If a soak area remote from the test site is used, the vehicle may pass through an area maintained within a temperature range of 68 to 86 degrees F during a time

interval not to exceed 10 minutes. In such cases, the vehicle shall be restabilized to 50 degrees F by soaking the vehicle in the nominal 50 degrees F test area for six times as long as the exposure time to the higher temperature area, prior to starting the emission test.

v. The vehicle shall be approximately level during all phases of the test sequence to prevent abnormal fuel distribution.

Manufacturers shall demonstrate compliance with this requirement each year by testing at least three PC or LDT and three MDV emission data and/or engineering development vehicles (with at least 4000 miles) which are representative of the array of technologies available in that model year. Only TLEVs, LEVs, and ULEVs are to be considered for testing at 50 degrees F. It is not necessary to apply deterioration factors (DFs) to the 50 degrees F test results to comply with this requirement. Testing at 50 degrees F shall not be required for fuel-flexible and dual-fuel vehicles when operating on gasoline, natural gas, hybrid electric, and diesel-fueled vehicles shall also be exempt from 50 degrees F testing.

The following schedule outlines the parameters to be considered for vehicle selection:

1. Fuel control system (e.g., multiport fuel injection, throttle body electronic fuel injection, sequential multiport electronic fuel injection, etc.)
2. Catalyst system (e.g., electrically heated catalyst, close-coupled catalyst, underfloor catalyst, etc.)
3. Control system type (e.g., mass-air flow, speed density, etc.)
4. Vehicle category (e.g., TLEV, LEV, ULEV)
5. Fuel type (e.g., gasoline, methanol, GNG, etc.)

The same engine family shall not be selected in the succeeding two years unless the manufacturer produces fewer than three engine families. If the manufacturer produces more than three TLEV, LEV, or ULEV engine families per model year, the Executive Officer may request 50 degrees F testing of specific engine families. If the manufacturer provides a list of the TLEV, LEV, and ULEV engine families that it will certify for a model year and provides a description of the technologies used on each engine family (including the information in items 1 through 5 of the vehicle selection parameters listed above), the Executive Officer shall select the engine families subject to 50 degrees F testing within a 30 day period after receiving such a list and description. The Executive Officer may revise the engine families selected after the 30 day period if the information provided by the manufacturer does not accurately reflect the engine families actually certified by the manufacturer.

1. For each engine family certified to TLEV, LEV, or ULEV standards, manufacturers shall submit with the certification application, an engineering evaluation demonstrating that a discontinuity in emissions of non-methane organic gases, carbon monoxide, oxides of nitrogen and formaldehyde measured on the Federal Test Procedure (40 CFR Part 86) does not occur in the temperature range of 20 to 86 degrees F. For diesel vehicles, the engineering evaluation shall also include particulate emissions.
- m- The Executive Officer may approve, upon submission of supporting data by a manufacturer, an alternative procedure for conducting assembly line quality audit testing for those vehicles certified to non-methane organic gas (NMOG) and formaldehyde (HCHO) standards. In order to use this alternative procedure, the manufacturer shall establish during certification testing the ratio of measured NMOG and HCHO exhaust emissions to measured NMHC exhaust emissions for each certification test data vehicle for the applicable engine family. The average of the individual test ratios of measured NMOG and HCHO emissions to measured NMHC emissions for the family shall be calculated and submitted in the application for certification. Following approval of the application for certification, the manufacturer may conduct quality audit testing on the engine family and measure NMHC exhaust emissions rather than NMOG and HCHO exhaust emissions. The measured NMHC exhaust emissions shall be multiplied by the NMOG to NMHC and HCHO to NMHC ratios submitted in the application for certification for the engine family to determine the equivalent NMOG and equivalent HCHO exhaust emission values for the quality audit test vehicle. The equivalent NMOG exhaust emission values shall be used in place of the measured NMOG exhaust emission value in determining the reactivity adjusted exhaust NMOG emission results. The equivalent reactivity adjusted NMOG and equivalent HCHO exhaust emission values shall be compared to the NMOG and HCHO exhaust emission standard applicable to the vehicle emission category (TLEV, LEV, or ULEV) in which the engine family was certified.

12. Identification of New Clean Fuels to be Used in Certification Testing.

Any person may petition the state board to establish by regulation certification testing specifications for a new clean fuel for which specifications are not specifically set forth in paragraph 86.113-90 as amended herein. Prior to adopting such specifications, the state board shall consider the relative cost-effectiveness of use of the fuel in reducing emissions compared to the use of other fuels. Whenever the state board adopts specifications for a new clean fuel for certification testing, it shall also establish by regulation specifications for the fuel as it is sold commercially to the public.

(a) If the proposed new clean fuel may be used to fuel existing motor vehicles other than low-emission vehicles certified on the primary designated clean fuel, the state board shall not establish certification specifications for the fuel unless the petitioner has demonstrated both of the following:

(1) Use of the new clean fuel in such existing motor vehicles would not increase emissions of NMOG (on a reactivity-adjusted basis), NO_x, CO, and the potential risk ~~asseeation~~ associated with toxic air contaminants as determined pursuant to the procedures set forth in "California Test Procedures for Evaluating the Emission Impacts of Substitute Fuels or New Clean Fuels" as adopted July 12, 1991. In the case of fuel-flexible vehicles or dual-fuel vehicles which were not certified on the new clean fuel but are capable of being operated on it, emissions during operation with the new clean fuel shall not increase compared to emissions during vehicle operation on gasoline.

(2) Use of the new clean fuel in such existing motor vehicles would not result in increased deterioration of the vehicle and would not void the warranties of any such vehicles.

(b) Whenever the state board designates a new clean fuel pursuant to this section, the state board shall also establish by regulation required specifications for the new clean fuel.

13. Reactivity Adjustment Factors

For the purpose of complying with the NMOG exhaust emission standards in Section 1960.1, Title 13, California Code of Regulations, the mass of NMOG emissions from a vehicle certified to operate on a fuel other than conventional gasoline, including fuel-flexible and dual-fuel vehicles when operated on a fuel other than conventional gasoline, shall be multiplied by the reactivity adjustment factor applicable to the vehicle emission control technology category and fuel. The product of the NMOG mass emission value and the reactivity adjustment factor shall be compared to the NMOG exhaust emission standards to determine compliance with the standards. In addition to the above requirements, vehicles operating on natural gas shall add to the product of the NMOG mass emission value and the reactivity adjustment factor, the product of the methane mass emission value and the methane reactivity adjustment factor. This result shall be compared to the NMOG exhaust emission standards to determine compliance with the standards for natural gas-fueled vehicles.

a. The following reactivity adjustment factors have been established pursuant to the criteria in Appendix VIII of these test procedures:

1. Passenger cars and light-duty trucks 0-5750 lbs. LVW

Vehicle Emission Control Technology Category	Fuel	Reactivity Adjustment Factor
1993 and subsequent model-year TLEVs	85% methanol, 15% gasoline blends	0.41
<u>1993 and subsequent model-year TLEVs</u>	<u>gasoline meeting the specifications of section 9.a.1.(ii) of these test procedures</u>	<u>1.00</u>
<u>1993 and subsequent model-year LEVs</u>	<u>gasoline meeting the specifications of section 9.a.1.(ii) of these test procedures</u>	<u>0.95</u>

2. NG passenger cars and light-duty trucks 0-5750 lbs. LVW

<u>Vehicle Emission Control Technology Category</u>	<u>Methane Reactivity Adjustment Factor</u>
<u>1993 and subsequent model-year TLEVs</u>	<u>0.0043</u>
<u>1993 and subsequent model-year LEVs</u>	<u>0.0045</u>

b. The Executive Officer may establish by executive order new reactivity adjustment factors pursuant to Appendix VIII of these test procedures in addition to those listed in Section 13.a. The Executive Officer shall notify manufacturers in writing of the new reactivity adjustment factors within 30 days of their establishment.

c. The Executive Officer may revise any reactivity adjustment factor listed in Section 13.a. or established by the Executive Officer pursuant to Appendix VIII of these test procedures if he or she determines that the revised reactivity adjustment factor is more representative of the ozone-forming potential of vehicle NMOG emissions based on the best available scientific knowledge and sound engineering judgment. The Executive Officer shall notify manufacturers in writing of any such reactivity adjustment factor at least 3 years prior to January 1 of the calendar year which has the same numerical designation as the model year for which the revised reactivity adjustment factor first becomes effective. However, manufacturers may use the revised reactivity adjustment factor in certifying any new engine family whose certification application is submitted following such notification, if they so choose. Manufacturers may also continue to use the original reactivity adjustment factor for any existing engine family previously certified with that reactivity adjustment factor until a new durability-data vehicle is tested for that engine family.

d. Manufacturers may request the use of a unique reactivity adjustment factor for a specific vehicle emission control technology category and fuel. The Executive Officer shall approve such requests in accordance with the conditions and procedures of Appendix VIII of these test procedures. For the purpose of calculating the reactivity adjustment factor as specified in Appendix VIII, the 'g ozone potential per g NMOG' value for the vehicle emission control technology category and fuel system for which the manufacturer is requesting the use of a unique reactivity adjustment factor shall be divided by the 'g ozone potential per g NMOG' value for a conventional gasoline-fueled vehicle established for the vehicle emission control technology category. The following 'g ozone potential per g NMOG' values for conventional gasoline-fueled vehicle emission control technology categories have been established:

1. Passenger cars and light-duty trucks 0-5750 lbs. LVW

Vehicle Emission Control Technology Category	'g ozone potential per g NMOG' for conventional gasoline
All TLEVs	3.42
<u>All LEVs</u>	<u>3.25</u>

14. Cold Temperature Test Procedure.

a. General Applicability

In paragraph 86.201-94:

1. Amend subparagraph (a) to read:

(a) This subpart describes procedures for determining the cold temperature carbon monoxide (CO) emissions from 1994 1996 and later model year new gasoline-fueled light-duty vehicles and passenger cars, light-duty trucks, and medium-duty vehicles (excluding natural gas vehicles, diesel-fueled vehicles, hybrid electric vehicles, and zero-emission vehicles).

b. Equipment Required: Overview

In paragraph 86.206.94:

1. Amend subparagraph (a) to read:

(a) This subpart contains procedures for exhaust emission tests on gasoline-fueled light-duty vehicles and passenger cars, light-duty trucks, and medium-duty vehicles (excluding natural gas vehicles, diesel-fueled vehicles, hybrid electric vehicles, and zero-emission vehicles). Equipment required and specifications are as follows:

2. Amend subparagraph (a)(1) to read:

(a)(1) Exhaust emission tests. Exhaust from gasoline-fueled vehicles (excluding natural gas vehicles, diesel-fueled vehicles, hybrid electric vehicles, and zero-emission vehicles) is tested for gaseous emissions using the Constant Volume Sampler (CVS) concept (Section 86.209). Equipment necessary and specifications appear in 40 CFR Part 86, Sections 86.208 through 86.214.

3. Amend subparagraph (a)(2) to read:

(a)(2) Fuel, analytical gas, and driving schedule specifications. Fuel specifications for exhaust emission testing for gasoline-fueled vehicles are specified in 40 CFR Part 86, Section 86.213. Fuel specifications for exhaust emission testing for alcohol-fueled vehicles and liquefied petroleum gas vehicles are specified in Section 9.a. of these Test Procedures. Analytical gases are specified in 40 CFR Part 86, Section 86.214. The EPA Urban Dynamometer Driving Schedule (UDDS) for use in gasoline-fueled emission tests is specified in 40 CFR Part 86, Section 86.215 and Appendix I.

APPENDIX I

List of Sections of Subparts A, and B, and C, Part 86, Title 40, Code of Federal Regulations, Incorporated by Reference

This Appendix sets forth the sections of Subparts A, and B, and C, Part 86, Title 40, Code of Federal Regulations, as adopted or amended or proposed by the U.S. Environmental Protection Agency (EPA) on the date listed for each section, which are incorporated by reference in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles.

All of the incorporated federal provisions were in effect or proposed as of April 11, 1989. Subpart A - General Provisions for Emission Regulations for 1977 and Later Model Year New Light-Duty Vehicles, Light-Duty Trucks, and Heavy-Duty Engines, and for 1985 and Later Model Year New Gasoline-Fueled and Methanol-Fueled Heavy-Duty Vehicles.

- 86.085-1 General applicability. July 7, 1986.
- 86.082-2 Definition. November 2, 1982.
- 86.084-2 Definition. December 10, 1984.
- 86.085-2 Definition. November 26, 1983.
- 86.088-2 Definition. August 29, 1986.
- 86.078-3 Abbreviations. January 21, 1980.
- 86.084-4 Section numbering; construction. September 25, 1980.
- 86.084-5 General standards; increase in emissions; unsafe conditions.
November 3, 1982.
- 86.090-5 General standards; increase in emissions; unsafe conditions. April
11, 1989.
- 86.078-7 Maintenance of records; submitted information; right of entry.
November 2, 1982.
- 86.087-8 Emission standards for 1987 light-duty vehicles. January 24, 1984.
- 86.090-8 Emission standards for 1990 and later model year light-duty
vehicles. April 11, 1989.
- 86.088-9 Emission standards for 1987 model light-duty trucks. August 29,
1986.
- 86.090-9 Emission standards for 1990 and later model year light-duty trucks.
April 11, 1989.
- 86.091-9 Emission standards for 1991 and later model year light-duty trucks.
April 11, 1989.
- 86.080-12 Alternative certification procedures. April 17, 1980.
- 86.085-13 Alternative durability program. May 19, 1983.
- 86.084-14 Small-volume manufacturers certification procedures. January 31,
1985.
- 86.090-14 Small-volume manufacturer certification procedures. April 11,
1986.
- 86.095-14 Small-volume manufacturer certification procedures. June 5, 1991.
- 86.094-16 Prohibition of defeat devices. July 17, 1992.
- 86.085-20 Incomplete vehicles. January 12, 1983.
- 86.088-21 Application for certification. March 15, 1985.
- 86.090-21 Application for certification. April 11, 1989.
- 86.091-21 Application for certification. April 11, 1989.
- 86.094-21 Application for certification. July 17, 1992.

86.085-22 Approval of application for certification; test fleet selection, etc. July 7, 1986.
 86.090-22 Approval of application for certification; test fleet selection, etc. April 11, 1989.
 86.094-22 Approval of application for certification; test fleet selection, etc. July 17, 1992.
 86.088-23 Required data. August 29, 1986.
 86.091-23 Required data. ~~April 11, 1989~~ July 26, 1990.
 86.094-23 Required data. June 5, 1991.
 86.085-24 Test vehicles and engines. January 31, 1985.
 86.090-24 Test vehicles and engines. April 11, 1989.
 86.092-24 Test vehicles and engines. July 26, 1990.
 86.094-24 Test vehicles and engines. July 17, 1992.
 86.095-24 Test vehicles and engines. July 17, 1992.
 86.085-25 Maintenance. July 7, 1986.
 86.088-25 ~~Maintenance. July 7, 1986.~~
 86.090-25 ~~Maintenance. April 11, 1989.~~
 86.084-26 Mileage and service accumulation; emission measurements. July 7, 1986.
 86.090-26 Mileage and service accumulation; emission requirements. April 11, 1989.
 86.085-27 Special test procedures. January 12, 1983.
 86.090-27 Special test procedures. April 11, 1989.
 86.088-28 Compliance with emission standards. August 29, 1986.
 86.090-28 Compliance with emission standards. April 11, 1989.
 86.091-28 Compliance with emission standards. ~~April 11, 1989~~ July 17, 1992.
 86.088-29 Testing by the Administrator. August 29, 1986.
 86.090-29 Testing by the Administrator. April 11, 1989.
 86.091-29 Testing by the Administrator. April 11, 1989.
 86.088-30 Certification. August 29, 1986.
 86.090-30 Certification. July 26, 1990.
 86.091-30 Certification. July 26, 1990.
 86.094-30 Certification. June 5, 1991.
 86.095-30 Certification. June 5, 1991.
 86.079-31 Separate certification. September 8, 1984.
 86.079-32 Addition of a vehicle or engine after certification. September 8, 1977.
 86.079-33 Changes to a vehicles or engine covered by certification. September 8, 1977.
 86.082-34 Alternative procedures for notification of addition and changes. November 2, 1982.
 86.088-35 Labeling. August 29, 1986.
 86.090-35 Labeling. April 11, 1989.
 86.091-35 Labeling. April 11, 1989.
 86.094-35 Labeling. July 17, 1992.
 86.095-35 Labeling. July 17, 1992.
 86.079-36 Submission of vehicle identification numbers. November 14, 1978.
 86.085-37 Production vehicles and engines. January 12, 1983.
 86.085-38 Maintenance instructions. November 16, 1983.
 86.087-38 Maintenance instructions. July 7, 1986.
 86.079-39 Submission of maintenance instructions. September 8, 1977.
 86.084-40 Automatic expiration of reporting and record keeping requirements. September 25, 1980.

Subpart B-Emission Regulations for 1977 and Later Model Year New Light-Duty Vehicles and New Light-Duty Trucks; Test Procedures.

86.101 General applicability. June 28, 1977.
 86.102 Definitions. March 5, 1980.
 86.103 Abbreviations. March 5, 1980.
 86.104 Section numbering, construction. August 29, 1986.
 86.105 Introduction; structure of subpart. August 29, 1986.
 86.106-82 Equipment required. March 5, 1980.
 86.106-90 Equipment required. April 11, 1989.
 86.106-94 Equipment required. June 5, 1991.
 86.107-78 Sampling and analytical system, evaporative emissions. June 28, 1977.
 86.107-90 Sampling and analytical system, evaporative emissions. April 11, 1989.
 86.108-79 Dynamometer. September 12, 1977.
 86.109-82 Exhaust gas sampling system; gasoline-fueled vehicles. March 5, 1980.
 86.109-90 Exhaust gas sampling system; gasoline-fueled vehicles. April 11, 1989.
 86.109-94 Exhaust gas sampling system; gasoline-fueled vehicles. June 5, 1991.
 86.110-82 Exhaust gas sampling system; diesel vehicles. October 13, 1981.
 86.110-90 Exhaust gas sampling system; diesel vehicles. April 11, 1989.
 86.110-94 Exhaust gas sampling system; diesel vehicles. June 5, 1991.
 86.111-82 Exhaust gas analytical-system. March 5, 1980.
 86.111-90 Exhaust gas analytical-system. April 11, 1980.
 86.111-94 Exhaust gas analytical-system. June 5, 1991.
 86.112-82 Weighing chamber (or room) and microgram balance specifications. March 5, 1980.
 86.112-91 Weighing chamber (or room) and microgram balance specifications. June 5, 1991.
 86.113-90 Fuel Specification. April 11, 1989.
 86.113-91 Fuel Specification. August 21, 1990.
 86.113-94 Fuel Specification. August 21, 1990.
 86.114-79 Analytical gases. November 14, 1978.
 86.114-94 Analytical gases. June 5, 1991.
 86.115-78 EPA urban dynamometer driving schedules. June 28, 1977.
 86.116-82 Calibrations, frequency and overview. March 5, 1980.
 86.117-78 Evaporative emission enclosure calibrations. June 28, 1977.
 86.118-78 Dynamometer calibration. June 28, 1977.
 86.119-78 CVS calibration. June 28, 1977.
 86.120-82 Gas meter or flow instrumentation calibration, particulate measurement. March 5, 1980.
 86.121-82 Hydrocarbon analyzer calibration. March 5, 1980.
 86.122-78 Carbon monoxide analyzer calibration. June 28, 1977.
 86.123-78 Oxides of nitrogen analyzer calibration. September 12, 1977.
 86.124-78 Carbon dioxide analyzer calibration. June 28, 1977.
 86.126-78 Calibration of other equipment. June 28, 1977.
 86.127-82 Test procedures; overview. March 5, 1980.
 86.128-79 Transmission. November 14, 1978.
 86.129-80 Road load power test weight and inertia weight class determination. November 14, 1978.
 86.130-78 Test sequence; general requirements. November 14, 1978.
 86.131-78 Vehicle preparation. June 28, 1977.
 86.132-82 Vehicle preconditioning. March 5, 1980.
 86.132-90 Vehicle preconditioning. April 11, 1989.
 86.133-78 Diurnal breathing loss test. November 16, 1983.
 86.134-78 Running loss test. December 10, 1984.

- 86.135-82 Dynamometer procedure. December 10, 1984.
- 86.135-90 Dynamometer procedure. April 11, 1989.
- 86.136-82 Engine starting and restarting. March 5, 1980.
- 86.137-82 Dynamometer test run, gaseous and particulate emissions. March 5, 1980.
- 86.137-90 Dynamometer test run, gaseous and particulate emissions. April 11, 1989.
- 86.138-78 Hot soak test. June 28, 1977.
- 86.139-82 Diesel particulate filter handling and weighing. March 5, 1980.
- 86.140-82 Exhaust sample analysis. March 5, 1980.
- 86.142-82 Records required. March 5, 1980.
- 86.142-90 Records required. April 11, 1989.
- 86.143-78 Calculations; evaporative emissions. March 15, 1985.
- 86.144-78 Calculations; exhaust emissions. December 10, 1984.
- 86.145-82 Calculations; particulate emissions. October 13, 1981.

Subpart C-Emission Regulations for 1994 and Later Model Year Gasoline-Fueled New Light-Duty Vehicles and New Light-Duty Trucks; Cold Temperature Test Procedures.

- 86.201-94 General applicability. July 17, 1992.
- 86.202-94 Definitions. July 17, 1992.
- 86.203-94 Abbreviations. July 17, 1992.
- 86.204-94 Section number construction. July 17, 1992.
- 86.205-94 Introduction; structure of subpart. July 17, 1992.
- 86.206-94 Equipment required; overview. July 17, 1992.
- 86.208-94 Dynamometer. July 17, 1992.
- 86.209-94 Exhaust gas sampling system; gasoline-fueled vehicles. July 17, 1992.
- 86.211-94 Exhaust gas analytical system. July 17, 1992.
- 86.213-94 Fuel specifications. July 17, 1992.
- 86.214-94 Analytical gases. July 17, 1992.
- 86.215-94 EPA urban dynamometer driving schedule. July 17, 1992.
- 86.216-94 Calibrations, frequency and overview. July 17, 1992.
- 86.218-94 Dynamometer calibration. July 17, 1992.
- 86.219-94 CVS calibration. July 17, 1992.
- 86.221-94 Hydrocarbon analyzer calibration. July 17, 1992.
- 86.222-94 Carbon monoxide analyzer calibration. July 17, 1992.
- 86.223-94 Oxides of nitrogen analyzer calibration. July 17, 1992.
- 86.224-94 Carbon dioxide analyzer calibration. July 17, 1992.
- 86.226-94 Calibration of other equipment. July 17, 1992.
- 86.227-94 Test procedures; overview. July 17, 1992.
- 86.228-94 Transmissions. July 17, 1992.
- 86.229-94 Road load force, test weight, and inertia weight class determination. July 17, 1992.
- 86.230-94 Test Sequence; general requirements. July 17, 1992.
- 86.231-94 Vehicle Preparation. July 17, 1992.
- 86.232-94 Vehicle Preconditioning. July 17, 1992.
- 86.235-94 Dynamometer procedure. July 17, 1992.
- 86.236-94 Engine starting and restarting. July 17, 1992.
- 86.237-94 Dynamometer test run, gaseous emissions. July 17, 1992.
- 86.240-94 Exhaust sample analysis. July 17, 1992.
- 86.242-94 Records required. July 17, 1992.
- 86.244-94 Calculations; exhaust emissions. July 17, 1992.
- 86.246-94 Intermediate temperature testing. July 17, 1992.

PPENDIX II

Exhaust Emission-Data Vehicle Selection Criteria For Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

I. Selection of Exhaust Emission-Data Vehicles (see flow diagram on page II-4)

A. Item 1 of the attached emission-data vehicle selection worksheet (page II-5) shall be prepared with the highest projected sales engine displacement-system combination first and the remainder in order of decreasing projected sales volume.

B. For engine families with a single engine displacement-exhaust emission control system combination representing 70 percent or more of the projected sales.

1. The first vehicle selection will be determined as follows:

a. The engine displacement-exhaust emission control system combination shall be the one with the highest projected sales. (Item 1, on worksheet.)

b. Using the data entered in Item 2 of the worksheet and the formula shown below, the equivalent test weight of the vehicle is determined from the calculated sales weighted equivalent test weight for that engine displacement-exhaust emission control system combination.

Sales Weighted Test Weight

Determine the sales weighted test weight as follows:

T_i = Test weight of i'th class

S_i = Sales volume of i'th class

N = Number of test weight classes

SWTW = Sales Weighted Test Weight

$$SWTW = \frac{\sum_{i=1}^N S_i T_i}{\sum_{i=1}^N S_i}$$

Select the equivalent test weight that includes the calculated SWTW. If the SWTW is exactly between two equivalent test weights, select the higher equivalent test weight. Similarly, if there are no vehicles with the desired displacement-exhaust emission control system combination in the same equivalent test weight that includes the calculated SWTW, the next higher equivalent test weight that contains such a vehicle will be specified.

c. The transmission will be the class with the highest sales for the engine displacement-exhaust emission control system combination (Item 3, worksheet). If the highest sales transmission class is not available in the equivalent test weight determined in (b), above, the next higher equivalent test weight with the highest sales transmission class will be selected. If manual transmissions are the highest selling class, the transmission configuration with the highest sales should generally be selected (Item 4, worksheet). If the manufacturer wishes to test a vehicle with an M-4 transmission both as an M-4 vehicle and an M-3 vehicle, use of the vehicle with an M-4 transmission will be allowed provided the first three gear ratios are identical in both transmissions. Similarly, use of an M-5 will be allowed to represent both an M-5 vehicle and an M-4 vehicle, providing the first four gear ratios are identical in both transmissions.

d. The highest selling engine code within the engine displacement-exhaust emission control system-equivalent test weight-transmission class combination will be specified (Item 5, worksheet).

e. The highest selling body style within the engine displacement-exhaust emission control system-equivalent test weight-transmission class-engine code combination will be specified (Item 6, worksheet.)

f. The N/V ratio will be the standard ratio (standard tire and axle ratio combination) for the vehicle selected (Item 7, worksheet).

g. Standard or optional equipment that can reasonably be expected to influence emissions (Item 8, worksheet) and is expected to be ~~installed on more than 33 percent of the vehicles in the car line within the~~ engine-system combination shall be specified (and the full estimated weight of those items should be included in the curb weight computation) unless an item is not available on the particular vehicle specified. Other standard or optional equipment expected to be installed on more than 33 percent of the vehicles in the car line within the engine-system combination shall have their full estimated weight included in the curb weight computation and be included in the specified vehicle's weight. Overdrive units are considered transmission configurations and not items of optional equipment. The weight of an overdrive unit should be included in the curb weight computation of vehicles with such units. (In other words, the weight of overdrive units should not be disregarded when car line sales of such items are 33 percent or less.)

2. The second vehicle will be determined as follows.


a. The transmission class, from Item 3 of worksheet, with the second highest sales will be specified if this transmission class has projected sales of more than 30 percent of the engine displacement-exhaust emission control system combination. The equivalent test weight, engine code body style, N/V ratio, and optional equipment specified for the second vehicle are determined by criteria in Section 1.

b. If the second transmission class does not meet the criteria of 2.a. above, the second vehicle will be the worst case vehicle selected from the family.

c. For engine families with multiple displacement-emission control system combinations, the first vehicle selection will be highest sales combination, and the second vehicle selection will be second highest sales combination. Other vehicle configuration details will be as in Section B.1.b. through B.1.g.

d. An exception to the two maximum emission-data vehicles may occur for engine families with vehicles in multiple standard classifications, i.e., loaded vehicle weight classifications for light-duty trucks and/or medium-duty vehicles. The first vehicle selection will be determined as above in B.1. in the highest sales loaded vehicle weight classification, and the subsequent vehicle selection(s) will be a worst case vehicle(s) in the other loaded vehicle weight classification(s).

FLOW DIAGRAMS FOR SELECTING ARB PC, LDT AND MDV EXHAUST EMISSION-DATA VEHICLES



Emission-Data Vehicle Selection Worksheet

Manufacturer _____ Date _____

Engine Family _____

1. Engine Displacement	Emission Control System	Unit	Percent	Cumulative%
a) _____	_____	_____	_____	_____
b) _____	_____	_____	_____	_____
c) _____	_____	_____	_____	_____
d) _____	_____	_____	_____	_____

2. Sales Weighted Test Weight

Total projected sales _____

Test Weight - lb.

Sales Volume

a) _____	_____
b) _____	_____
c) _____	_____
d) _____	_____

Calculated SWTW _____ lbs.

Equivalent Test Weight _____ lbs.

3. Transmission Selection

<u>Class</u>	<u>Sales Volumes</u>	<u>Percentage Sales</u>	<u>High Sales</u>
a) _____	_____	_____	_____
b) _____	_____	_____	_____

4. Transmission Configuration

<u>Configuration</u>	<u>Sales Volumes</u>	<u>High Sales</u>
a) _____	_____	_____
b) _____	_____	_____
c) _____	_____	_____

5. <u>Engine Code (within 1, 2, 3, and 4 above)</u>	<u>Sales Volumes</u>	<u>High Sales</u>
a) _____	_____	_____
b) _____	_____	_____
c) _____	_____	_____
d) _____	_____	_____

6. <u>Body Style (within 1, 2, 3, 4, and 5 above)</u>	<u>Sales Volumes</u>	<u>High Sales</u>
a) _____	_____	_____
b) _____	_____	_____
c) _____	_____	_____
d) _____	_____	_____
e) _____	_____	_____
f) _____	_____	_____

7. STD Axle _____ STD N/V _____

8. Options over 33 percent

9. Second and Subsequent Selections Vehicles

a) High Sales Engine Displacement-Exhaust Emission Control System _____

b) Second-Highest Selling Transmission Class _____

Designated Second and Subsequent Selections Vehicles

<u>Disp.</u>	<u>Eng. Code</u>	<u>Evap. Code</u>	<u>Model</u>	<u>Trans.</u>	<u>ETW</u>	<u>Axle</u>	<u>N/V</u>
--------------	----------------------	-----------------------	--------------	---------------	------------	-------------	------------

APPENDIX III

Determination of Acceptable Durability Test Schedule*

A manufacturer may determine mileage test intervals for durability-data vehicles subject to the conditions specified in 40 CFR 86.084-26 or 86.09088-26. The following procedure shall be used to determine if the schedule is acceptable to the Executive Officer.

1. Select exhaust system mileage test points and maintenance mileage test points for proposed (prop) schedule.
2. Calculate the sums of the squares corrected to the mean of the system mileages at the proposed test points:

$$A_{\text{prop}} = \frac{[\sum (X_p)^2] - (\sum X_p)^2 / N_p}{p_{\text{prop}}}$$

Where:

X = Individual mileages at which the vehicle will be tested.

N = Total number of tests (including before and after maintenance tests).

(Subscript "p" refers to proposed test schedule).

3. Determine exhaust system mileage test points and maintenance mileage test points based on testing at five thousand mile intervals from 5,000 miles through the final testing point and maintenance mileage test points selected for the proposed schedule in section 1. This schedule will be designated as the standard (std) test schedule.
4. Calculate the sums of squares corrected to the mean of the standard schedule.

$$B_{\text{std}} = \frac{[\sum (X_s)^2] - (\sum X_s)^2 / N_s}{s_{\text{std}}}$$

* For diesel vehicles equipped with periodically regenerating trap oxidizer systems (or those with continuously regenerating trap oxidizer systems elected to be certified to the provisions of diesel vehicles with periodically regenerating trap oxidizer systems), additional test schedule requirements for regeneration tests must be met as outlined in subparagraphs 6.a.4.(B) and 6.b.7.(D) 6-a-2- and 6-b-3- in these procedures.

Where:

X_i = Individual mileages at which the vehicle will be tested.

N = Total number of tests (including before and after maintenance).

(Subscript "s" refers to standard test schedule).

5. Refer to Table I and determine t_p at $(N_p-2)_{prop}$ degrees of freedom and t_s at $(N_s-2)_{std}$:

$$\text{If } \frac{A}{1/2} \geq \frac{t}{t_s} \times B^{1/2}$$

prop std

the proposed plan is acceptable.

Table I

Degrees of freedom <u>N-2</u>	<u>t</u>
1	6.314
2	2.920
3	2.353
4	2.132
5	2.015
6	1.943
7	1.895
8	1.860
9	1.833
10	1.812
11	1.796
12	1.782
13	1.771
14	1.761
15	1.753
16	1.746
17	1.740
18	1.734
19	1.729
20	1.725
21	1.721
22	1.717
23	1.714
24	1.711
25	1.708

APPENDIX IV

Procedure for Determining An Acceptable Exhaust Regeneration Durability-Data Test Schedule for Diesel Cycle Vehicles, Equipped with Periodically Regenerating Traps Oxidizer Systems.

1. Select exhaust system mileage test points for proposed (prop) schedule.
2. Calculate the sums of the squares corrected to the mean of the system mileages at the proposed test points:

$$A_{prop} = \left[\frac{\sum (X_p)^2}{p} - \frac{(\sum X_p)^2}{N_p} \right]$$

Where:

X = Individual mileages at which the vehicle will be tested.

N = Total number of tests (including before and after maintenance tests).

(Subscript "p" refers to proposed test schedule).

3. The exhaust system mileage tests points at 5,000, 20,000, 35,000 and 50,000 miles will be designated as the standard (std) test schedule.
4. Calculate the sums of square corrected to the mean of the standard tests schedule.

$$B_{std} = \left[\frac{\sum (X_s)^2}{s} - \frac{(\sum X_s)^2}{N_s} \right]$$

Where:

X = Individual mileages at which the vehicle will be tested.

N = Total number of regeneration emission tests.

(Subscript "s" refers to standard test schedule)

5. Refer to Table I and determine t_p at (N_p-2) degrees of freedom and t_s at (N_s-2) degrees of freedom.

$$\text{If } \frac{A_{prop}}{t_p} > \frac{B_{std}}{t_s}$$

the proposed plan is acceptable.

Table I

Degrees of freedom <u>N-2</u>	<u>t</u>
1	6.314
2	2.920
3	2.353
4	2.132
5	2.015
6	1.943
7	1.895
8	1.860
9	1.833
10	1.812
11	1.796
12	1.782
13	1.771
14	1.761
15	1.753

APPENDIX V

Pollutant Mass Emissions Calculation Procedure for Gaseous-Fueled Vehicles and for Vehicles Equipped with Periodically Regenerating Trap Oxidizer Systems *

I. Gaseous-Fueled Vehicle Pollutant Mass Emission Calculation Procedure

For 1988 through 1990 model-year gaseous-fueled vehicles, these calculation procedures are to be used in lieu of those in subparagraph 86.144-878, and 86.144-90 Part 86, Title 40, Code of Federal Regulations (CFR) when calculating the mass emissions from vehicles fueled with either liquefied petroleum gas or compressed natural gas. This calculation procedure is based on the "Positive Displacement Pump- Constant Volume Sampler (PDP-CVS)" exhaust sampling system. For 1991 and subsequent model-year gaseous-fueled vehicles, the calculation procedures specified in "California Non-Methane Hydrocarbon Test Procedures" shall apply to all vehicles certified to the emission standards of section 3.b., 3.e. and 3.f. of these test procedures. For all TLEVs, LEVs, and ULEVs, the calculation procedures specified in "California Non-Methane Organic Gas Test Procedures" shall apply.

The reported test results shall be computed by use of the following formulas:

CO_{conc}	=	Carbon monoxide concentration of the dilute exhaust sample corrected for background, water vapor, and CO_2 extraction in ppm.
CO_{dm}	=	Carbon monoxide concentration of the dilution air sample as measured, in ppm.
CO_d	=	Carbon monoxide concentration of the dilution air corrected for water vapor extraction, in ppm.
CO_e	=	Carbon monoxide concentrations of the dilute exhaust sample volume corrected for water vapor and carbon dioxide extraction, in ppm. The calculation assumes the carbon to hydrogen ratio of the fuel to be 1:3.802 for natural gas and 1:2.658 for LPG.
CO_{em}	=	Carbon monoxide concentration of the dilute exhaust sample as measured, in ppm.
CO_{mass}	=	Carbon monoxide emissions, in grams per test phase.
CO_{2conc}	=	Carbon dioxide concentration of the dilute exhaust sample corrected for background and water vapor, in percent.
CO_{2e}	=	Carbon dioxide concentration of the dilute exhaust sample, in percent.

* These calculation procedures are based on the Federal CVS-1975 Test Procedure.

$CO_{2\text{mass}}$	=	Carbon dioxide emissions, in grams per test phase.
$Density_{CO}$	=	Density of carbon monoxide is 32.97 g/ft ³ at 68°F and 760 mm. Hg pressure.
$Density_{CO_2}$	=	Density of carbon dioxide is 51.81 g/ft ³ 68°F and 760 mm. Hg pressure.
$Density_{HC}$	=	Density of hydrocarbons is 18.64 g/ft ³ for natural gas and 17.28 g/ft ³ for LPG assuming an average carbon to hydrogen ratio of 1:3.802 for natural gas and 1:2.658 for LPG, at 68°F and 760 mm Hg pressure.
$Density_{NO_2}$	=	Density of oxides of nitrogen is 54.16 g/ft ³ assuming they are in the form of nitrogen dioxide, at 68°F and 760 mm Hg pressure.
DF	=	Dilution Factor
H	=	Absolute humidity in grains of water per pound of dry air.
HC_{conc}	=	Hydrocarbon concentration for the dilute exhaust sample corrected for background, in ppm carbon equivalent, i.e. equivalent propane X 3.
HC_d	=	Hydrocarbon concentration of the dilution air as measured, in ppm carbon equivalent.
HC_e	=	Hydrocarbon concentration of the dilute exhaust sample, in ppm carbon equivalent.
HC_{mass}	=	Hydrocarbon emissions, in grams per test phase.
K_H	=	Humidity correction factor
N	=	Number of revolutions of the positive displacement pump during the test phase while samples are being collected.
NO_{xconc}	=	Oxides of nitrogen concentration of the dilute exhaust sample corrected for background, in ppm.
NO_d	=	Oxides of nitrogen concentration of the dilute air as measured, in ppm.
NO_{xe}	=	Oxides of nitrogen concentration of the dilute exhaust sample as measured, in ppm.
NO_{xmass}	=	Oxides of nitrogen emissions, in grams per test phase.
P_B	=	Barometric pressure, in mm. Hg.

P_d	=	Saturated vapor pressure, in mm. Hg at ambient dry bulb temp.
P_i	=	Pressure depression below atmospheric measured at the inlet to the positive displacement pump.
T_p	=	Average temperature of dilute exhaust entering positive displacement pump during test while samples are being collected, in degrees Rankine.
R_a	=	Relative humidity of the ambient air, in percent.
V_{mix}	=	Total dilute exhaust volume in cubic feet per test phase corrected to standard conditions (528°R and 760 mm. Hg).
V_o	=	Volume of gas pumped by the positive displacement pump, in cubic feet per revolution. This volume is dependent on the pressure differential across the positive displacement pump.
Y_{ct}	=	Mass emissions as calculated from the "transient" phase of the cold start test, in grams per test phase.
Y_{ht}	=	Mass emissions as calculated from the "transient" phase of the hot start test, in grams per test phase.
Y_s	=	Mass emissions as calculated from the "stabilized" phase of the cold start test, in grams test phase.
Y_{wm}	=	Weighted mass emissions of each pollutant, i.e., HC, CO, or NOx, in grams per vehicle mile.
D_{ct}	=	The measured driving distance from the "transient" phase of the cold start test, in miles.
D_{ht}	=	The measured distance from the "transient" phase of the hot start test, in miles.
D_s	=	The measured driving distance from the "stabilized" phase of the cold start test, in miles.

For passenger cars, light duty trucks, and medium duty vehicles:

- (a) The mass emissions of each pollutant in grams per mile is

$$Y_{wm} = \frac{0.43 ((Y_{ct} + Y_s)/(D_{ct} + D_s)) + 0.57 ((Y_{ht} + Y_s)/(D_{ht} + D_s))}{1}$$

- (b) The mass of each pollutant for each phase of both the cold start test and the hot start test is determined from the following:

- (1) Hydrocarbon mass:

$$HC_{mass} = V_{mix} \times \text{Density}_{HC} \times (HC_{conc}/1,000,000)$$

(2) Oxides of nitrogen mass:

$$\text{NOx}_{\text{mass}} = V_{\text{mix}} \times \text{Density}_{\text{NO}} \times \frac{K_H}{2} \times (\text{NOx}_{\text{conc}}/1,000,000)$$

K_H = humidity correction factor

(3) Carbon monoxide mass:

$$\text{CO}_{\text{mass}} = V_{\text{mix}} \times \text{Density}_{\text{CO}} \times (\text{CO}_{\text{conc}}/1,000,000)$$

(4) Carbon dioxide mass:

$$\text{CO}_{2\text{mass}} = V_{\text{mix}} \times \text{Density}_{\text{CO}_2} \times (\text{CO}_{2\text{conc}}/100)$$

$$V_{\text{mix}} = \frac{V_o \times N \times (P_b - P_i) \times 528}{(760) (T_p)}$$

$$\text{HC}_{\text{conc}} = \text{HC}_e - \text{HC}_d (1-1/\text{DF})$$

$$\text{NOx}_{\text{conc}} = \text{NOx}_e - \text{NOx}_d (1-1/\text{DF})$$

$$\text{CO}_{\text{conc}} = \text{CO}_e - \text{CO}_d (1-1/\text{DF})$$

$$\text{CO}_e = (1-0.02901 \text{ CO}_{2e} - 0.000323 R_a) \text{ CO}_{\text{em}} \text{ for natural gas}$$

$$\text{CO}_e = (1-0.02328 \text{ CO}_{2e} - 0.000323 R_a) \text{ CO}_{\text{em}} \text{ for LPG}$$

$$\text{CO}_d = (1-0.000323 R_a) \text{ CO}_{\text{dm}}$$

$$K_H = \frac{1}{1-0.0047(H-75)}$$

$$H = \frac{(43.478R) (P_d)}{P_B - \frac{P_d \times R_a}{1}}$$

$$\text{DF} = \frac{9.77}{\text{CO}_{2e} + (\text{HC}_e + \text{CO}_e) \times 10^{-4}} \quad \text{for natural gas}$$

$$\text{DF} = \frac{11.7}{\text{CO}_{2e} + (\text{HC}_e + \text{CO}_e) \times 10^{-4}} \quad \text{for LPG}$$

II. Pollutant Mass Emissions Calculation Procedure for Vehicles Equipped with Periodically Regenerating Trap Oxidizer Systems

Exhaust Emissions

Amend-subparagraph 86.144-88(a) in Part 86, Title 40, Code of Federal Regulations (CFR) to read:

The final reported test results shall be computed by the use of the following formula:

(a) For light-duty vehicles and light-duty trucks:

$$Y_{wm} = 0.43 ((Y_{ct} + Y_s)/(D_{ct} + D_s)) + 0.57 ((Y_{ht} + Y_s)/(D_{ht} + D_s))$$

For purposes of adjusting emissions for regeneration:

$$R_e = ((Y_{r1} - Y_{ct}) + (Y_{r2} - Y_s) + (Y_{r3} - Y_{ht}))/ (D_{ct} + D_s + D_{ht})$$

$$Y_r = Y_{wm}^* + R_e$$

Where:

Y_{wm} = Weighted mass emissions of each pollutant, i.e., HC, CO, NO_x or CO₂, in grams per vehicle mile.*

Y_{ct} = Mass emissions as calculated from the "transient" phase of the cold start test, in grams per test phase.

Y_{ht} = Mass emissions as calculated from the "transient" phase of the hot start test in grams per test phase.

Y_s = Mass emissions as calculated from the "stabilized" phase of the cold start test, in grams per test phase.

D_{ct} = The measured driving distance from the "transient" phase of the cold start test, in miles.

D_{ht} = The measured distance from the "transient" phase of the hot start test, in miles.

D_s = The measured driving distance from the "stabilized" phase of the cold start test, in miles.

Y_r = Regeneration emission test.

R_e = Mass emissions of each pollutant attributable to regeneration in grams per mile.

* Y_{wm} is derived using the emission data from a test with no regeneration.

Yr1 = Mass emissions, during a regeneration emission test, as calculated from the "transient" phase of the cold start test, in grams per test phase.

Yr2 = Mass emissions, during a regeneration emission test, as calculated from the "stabilized" phase of the cold start test, in grams per test phase.

Yr3 = Mass emissions, during a regeneration emission test, as calculated from the "transient" phase of the hot start test in grams per test phase.

Particulate Emissions

Amend subparagraph 86.145-82(a) in Part 86, Title 40, Code of Federal Regulations (CFR) to read:

(a) The final reported test results for the mass particulate (Mp) in grams/mile shall be computed as follows.

For purposes of adjusting emissions for regeneration:

$$Mp = 0.43(Mp1 + Mp2)/(Dct + Ds) + 0.57 (Mp3 + Mp2/(Dht + Ds))$$

$$Re = ((Mpr1 - Mp1) + (Mpr2 - Mp2) + (Mpr3 - Mp3))/(Dct+Ds+Dht)$$

$$Mpr = Mp* + Re$$

Where:

- (1) Mp1 = Mass of particulate determined from the "transient" phase of the cold start test, in grams per test phase. (See 86.110-82(c)(1) and 86.110-88(d)(1) for determination.)
- (2) Mp2 = Mass of particulate determined from the "stabilized" phase of the cold start test, in grams per test phase. (See 86.110-82(c)(1) and 86.110-88(d)(1) for determination.)
- (3) Mp3 = Mass of particulate determined from the "transient" phase of the hot start test, in grams per test phase. (See 86.110-82(c)(1) and 86.110-88(d)(1) for determination.)
- (4) Dct = The measured driving distance from the "transient" phase of the cold start test, in miles.
- (5) Ds = The measured driving distance from the "stabilized" phase of the cold start test, in miles.
- (6) Dht = The measured driving distance from the "transient" phase of the hot start test, in miles.
- (7) Mpr = Regeneration emission test
- (8) Re = Mass of particulate attributable to regeneration in grams/mile.

* Mp is derived using the emission data from a test with no regeneration.

- (9) Mpr1 = Mass of particulate determined, during a regeneration emission test, from the "transient" phase of the cold start test in grams per test phase.
(See 86.110-82(c)(1) and 86.110-88(d)(1) for determination.)
- (10) Mpr2 = Mass of particulate determined, during a regeneration emission test, from "stabilized" phase of the cold start test, in grams per test phase.
(See 86.110-82(c)(1) and 86.110-88(d)(1) for determination.)
- (11) Mpr3 = Mass of particulate determined, during a regeneration emission test, from the "transient" phase of the hot start test, in grams per test phase.
(See 86.110-82(c)(1) and 86.110-88(d)(1) for determination.)

III. Fuel Economy Calculations for Gaseous Fuels Based on the Cold Start CVS-1975 Federal Test Procedure

Assume the fuel meets HD-5 specifications (95% C₃H₈, 5% nC₄H₁₀, by volume)

1. Physical constants of Propane and Normal Butane

<u>Component</u>	<u>Mol. Wt.</u>	<u>Sp. Gr.</u>	<u>Liquid Density</u> <u>lb/gal @ 60°F</u>	<u>Liquid</u> <u>Density of HD-5</u> <u>lb/gal at 60°F</u>
C ₃ H ₈	44.094	0.508	4.235 x (0.95) =	4.0233
nC ₄ H ₁₀	58.12	0.584	4.868 x (0.05) =	<u>.2434</u> 4.2667

2. Density of the HD-5 fuel

$$(0.95 \times 4.235) + (0.05 \times 4.868) = 4.267 \text{ lb/gal @ } 60^{\circ}\text{F}$$

3. Molecular Weights

<u>Species</u>	<u>Mol. Wt.</u>
C	12.01115
H	1.00797
O	15.9994
CO	28.01055
CO ₂	44.00995
*CH ₂	14.6903
2.658	

*Average ratio of Hydrogen to carbon atoms in HD-5 fuel.

$$\text{C}_3\text{H}_8 \quad \frac{8}{3} = 2.666 \times 0.95 (\% \text{ propane}) = 2.533$$

$$\text{nC}_4\text{H}_{10} \quad \frac{10}{4} = 2.5 \times 0.05 (\% \text{ Butane}) = \frac{.125}{2.658}$$

4. Weight of Carbon in:

$$\text{CO} = \text{wt. of CO} \times (12.01115/28.01055) = \text{wt CO} \times (0.429)$$

$$\text{CO}_2 = \text{wt. of CO}_2 \times (12.01115/44.00995) \text{ wt CO}_2 \times (0.273)$$

$$\text{CH}_{2.658} = \text{wt. of CH}_{2.658} \times (12.01115/14.6903) = \text{wt CH}_{2.658} \times (0.818)$$

5. Wt. of Carbon per gallon of LPG

$$\text{wt. of carbon} = 4.2667 \text{ lbs/gal} \times 453.59 \text{ gms/lb} \times 0.818 = 1583 \text{ grams C/gal HD-5}$$

6. Fuel economy:

$$\frac{\text{grams C/gal}}{\text{grams C in exhaust/mi}} = \text{miles/gal.}$$

$$\text{LPG} = \frac{1583 \text{ gms C/gal}}{(0.818)(\text{HC}) + (0.429)(\text{CO}) + (0.273)(\text{CO}_2)}$$

$$\begin{aligned} \text{HC} &= \text{CVS HC in grams/mile} \\ \text{CO} &= \text{CVS CO in grams/mile} \\ \text{CO}_2 &= \text{CVS CO}_2 \text{ in grams/mile} \end{aligned}$$

$$\text{For gasoline} = \frac{2421}{(0.866) \text{ HC} + (0.429) \text{ CO} + (0.273) \text{ CO}_2}$$

$$\text{For Natural Gas} = \frac{1535}{(0.759) \text{ HC} + (0.429) \text{ CO} + (0.273) \text{ CO}_2}$$

APPENDIX VI

Blanket Approval of Running Changes and Field Fixes

Running changes and field fixes meeting the following definitions shall be granted automatic or "blanket" approval by the Executive Officer provided that notification of changes listed in paragraph 1. below are received by the ARB at least five working days before implementation, and notification of changes listed in 2. through 13. below are received by the ARB within two working days after implementation. Such automatic approvals shall be effective when they are approved by EPA.

For passenger cars, light-duty trucks and medium-duty vehicles:

1. The addition of new models to an engine family where the new models differ from previously certified models only in model name and curb weight (same inertia weight class), and where the exhaust, evaporative and fill pipe emission control system specifications do not change.
2. Changes in axle ratio, tire size or tire type, providing that changes to the N/V ratio and/or load horsepower are within 5% of the originally certified values. This includes re-classification of base and optional axle ratios or tires.
3. The deletion of models or vehicle configurations.
4. Changes in fuel tank capacity of less than 10 percent of the originally certified capacity, providing there is no other modification of the evaporative emission control system.
5. Changes to the fuel filler system leaded fuel nozzle restrictor, where EPA preemption is involved.
6. Advance certification of models in the next higher inertia weight class, for use if needed later.
7. Changes in tailpipe length of less than ten inches.
8. The following changes involving spark plugs:
 - a. The addition of resistor-type spark plugs if nonresistor spark plugs are standard, or vice-versa, providing the secondary circuit resistance changes less than 5 percent.
 - b. The addition of alternate heat ranges within one range of the originally certified spark plugs.
 - c. The change of spark plug gap within 15 percent of originally certified spark plug gap.

9. Changes to component part numbers when there are no changes in the materials used or to the performance specifications (e.g. distributor advance curves, carburetor flow curves, fuel pump supply pressure, etc.). These changes may be the result of parts consolidation, changes in supplier, addition/deletion of peripheral items such as brackets, and minor dimensional changes where the durability and performance are not affected.
10. Changes in the crankcase emission control system where EPA preemption is involved, excluding revisions that could have an interaction effect on exhaust emissions (e.g., PCV purge flow changes).
11. Changes submitted under the alternate or concurrent notification procedure in 40 CFR 86 which would otherwise qualify for automatic or "blanket" status.
12. Changes in the physical location of a vacuum hose connection with no change in the relationship between vacuum, speed, load, or any other vacuum-related parameter, provided that the changes do not render the vacuum hose routing diagram unrepresentative.
13. Changes in exhaust system cross sectional area, if this area equals or exceeds the minimum area in the system.

APPENDIX VII

Calculation of t-Statistic for Deterioration Data Outlier Test

Residual normal deviates to indicate outliers are used routinely and usefully in analyzing regression data, but suffer theoretical deficiencies if statistical significance tests are required. Consequently, the procedure for testing for outliers outlined by Snedecor and Cochran, 6th ed., Statistical Methods, pp. 157-158, will be used. The method will be described generally, then by appropriate formulae, and finally a numerical example will be given.

Linearity is assumed (as in the rest of the deterioration factor calculation procedure), and each contaminant is treated separately. The procedure is as follows:

Calculate the deterioration factor regression as usual, and determine the largest residual in absolute value. Then recalculate the regression with the suspected outlier omitted. From the new regression line calculate the residual at the deleted point, denoted as $(y_i - y_i')$. Obtain a statistic by dividing $(y_i - y_i')$ by the square root of the estimated variance of $(y_i - y_i')$. Find the tailed probability, p , from the t-distribution corresponding to the quotient (double-tailed), with $n-3$ degrees of freedom, with n the original sample size.

This probability, p , assumes the suspected outlier is randomly selected, which is not true. Therefore, the outlier will be rejected only if $1 - (1-p)^n \leq .05$.

The procedure will be repeated for each contaminant individually until the above procedure indicates no outliers are present.

When an outlier is found, the vehicle test-log will be examined. If an unusual vehicle malfunction is indicated, data for all contaminants at that test-point will be rejected; otherwise, only the identified outlier will be omitted in calculating the deterioration factor.

Procedure for the calculation of the t-Statistic for Deterioration Data Outlier Test.

Given a set of n points, $(x_1, y_1), (x_2, y_2) \dots (x_n, y_n)$.

where

x_i is the mileage of the i^{th} data point.
 y_i is the emission of the i^{th} data point.

Assume model:

$$y = \alpha + \beta(x - \bar{x}) + \epsilon$$

I.

- i) Calculate the regression line,

$$\hat{y} = a + b (x - \bar{x})$$

- ii) Suppose the absolute value of the i^{th} residual $(y_i - \hat{y}_i)$ is the largest.

II.

- i) Calculate the regression line with the i^{th} point deleted.

$$\hat{y}' = a' + b' (x - \bar{x})$$

- ii) Let $t = (y_i - \hat{y}_i') / \hat{\text{var}}(y_i - \hat{y}_i')$

where y_i is the observed suspected outlier.

$\hat{y}_i'$ is the predicted value with the suspected outlier deleted.

$$\hat{\text{var}}(y_i - \hat{y}_i') = s^2 \left(1 + \frac{1}{n-1} + \frac{x_i - \bar{x}}{\sum_{\substack{j=1 \\ j \neq i}}^n (x_j - \bar{x})^2} \right)^2$$

($\bar{x}$ is calculated without the suspected outlier)

$$s^2 = \frac{\sum_{\substack{j=1 \\ j \neq i}}^n (y_j - \hat{y}_j')^2}{n-3}$$

- iii) Find p from the t -statistic table

where

$p = \text{prob}(|t(n-3)| \geq t)$
 $t(n-3)$ is a t -distributed variable with $n-3$ degrees of freedom.

- iv) y_i is an outlier if $1 - (1-p)^n < .05$

Example:

x	y	$\hat{y}$	$y - \hat{y}$
8	59	56.14	2.86
6	58	58.17	-0.17
11	56	53.10	2.90
-22	53	41.96	11.04
14	50	50.06	-0.06
17	45	47.03	-2.03
18	43	46.01	-3.01
24	42	39.94	2.06
19	39	45.00	-6.00
23	38	40.95	-2.95
26	30	37.91	-7.91
40	27	23.73	3.27

Assume model:

$$y = \alpha + \beta(x - \bar{x}) + \epsilon$$

$$\hat{y} = 45 - 1.013 (x - \bar{x})$$

Suspected outlier

Suspected point out of regression:

$$\hat{y}' = 44.273 - 1.053 (x - \bar{x})$$

$$\hat{y}_i' = 44.273 - 1.053 (22 - 18.727) = 40.827$$

$$y_i - \hat{y}_i' = 12.173$$

$$\widehat{\text{var}}(y_i - \hat{y}_i') = s^2 \left(1 + \frac{1}{11} + \frac{10.711}{914.182} \right)$$

APPENDIX VIII

Procedure for Determining Vehicle Emission Control Technology Category/Fuel Reactivity Adjustment Factors

The following procedure shall be used by the Executive Officer to establish the reactivity adjustment factor for exhaust emissions of non-methane organic gases (NMOG) and establish the 'methane reactivity adjustment factor' for exhaust methane emissions from CNG vehicles, for the purpose of certifying a vehicle of specific emission control technology category and fuel for sale in California. The NMOG emissions results from Transitional Low-Emission Vehicles (TLEVs), Low-Emission Vehicles (LEVs), and Ultra-Low-Emission Vehicles (ULEVs) designed to operate on any available fuel other than conventional gasoline, including fuel-flexible and dual-fuel vehicles when operating on any available fuel other than conventional gasoline, shall be numerically-adjusted to establish a NMOG exhaust mass emission value equivalent, in terms of ozone-forming potential, to the NMOG exhaust mass emissions from conventional gasoline-fueled vehicles of the same vehicle emission control technology category.

- (1) The Executive Officer shall determine the representative speciated NMOG exhaust emission profiles for all light- and medium-duty conventional gasoline-fueled TLEVs, LEVs, and ULEVs according to the following conditions.
 - a. All testing will be conducted using a specified gasoline blend representative of commercial gasoline and having the specifications listed in (9).
 - b. The speciated NMOG profiles shall be calculated obtained from a statistically valid number of TLEVs, LEVs, and ULEVs.
 - c. The speciated NMOG profiles shall identify and quantify, in units of g/mile or mg/mile, as many constituents as possible in accordance with the procedures specified in "California Non-Methane Organic Gas Test Procedures.", such that a minimum of 95% of the total g/mile of NMOG emissions measured is identified, and shall be provided in units of g/mile or mg/mile.
 - d. The speciated NMOG profile shall include at a minimum, the g/mile NMOG emission values of all oxygenated organic gases containing five or fewer carbon atoms (i.e., aldehydes, ketones, alcohols, ethers, etc.), and all known alkanes, alkenes, alkynes and aromatics containing twelve or fewer carbon atoms.
- (2) The 'g ozone potential per mile' of each NMOG identified in the speciated profile shall be determined by multiplying the 'g/mile NMOG' emission value of the constituent NMOG by its maximum incremental reactivity given in step (10) (9).
- (3) The 'total g ozone potential per mile' of NMOG exhaust emissions from the vehicle/fuel system shall be the sum of all the constituent NMOG 'g ozone potential per mile' values calculated in step (2).
- (4) The 'g ozone potential per g NMOG' for the vehicle/fuel system shall be determined by dividing the 'total g ozone potential per mile' value calculated in step (3) by the 'total g/mile of NMOG emissions'.

- (5) For light- and medium-duty candidate vehicle/fuel systems not powered by conventional gasoline, the Executive Officer shall establish 'reactivity adjustment factors' calculated from exhaust emission profiles derived according to the same conditions specified in parts b, c, and d of step (1).
- (6) The 'g ozone potential per g NMOG' for candidate vehicle/fuel systems not powered by conventional gasoline shall be determined according to steps (2), (3), and (4).
- (7) (a) The candidate vehicle/fuel 'reactivity adjustment factor' shall be determined by dividing the 'g ozone potential per g NMOG' calculated in step (6) by the 'g ozone potential per g NMOG' value for the vehicle in the same emission control technology category operated on the specified conventional gasoline blend. The 'g ozone potential per g NMOG' values for conventional gasoline vehicles are listed in Section 13.d. of these test procedures or shall be established by the Executive Officer pursuant to Appendix VIII of these test procedures. For candidate vehicle/fuel systems powered by methanol or liquified petroleum gas, the quotient calculated above shall be multiplied by 1.1. The resulting value shall constitute the 'reactivity adjustment factor' for the methanol or liquified petroleum gas-powered vehicle/fuel system.
- (b) For candidate vehicle/fuel systems operating on natural gas, a 'methane reactivity adjustment factor' shall be calculated by dividing the maximum incremental reactivity value for methane given in (10) by the 'g ozone potential per g NMOG' value for the vehicle in the same emission control technology category operated on conventional gasoline as listed in Section 13.d. of these test procedures or established by the Executive Officer pursuant to Appendix VIII of these test procedures.
- (8) The Executive Officer shall assign a reactivity adjustment factor unique to a specific engine family at the request of a vehicle manufacturer provided that each of the following occurs:
- a. The manufacturer submits speciated NMOG exhaust emission profiles to the Executive Officer obtained from emission testing a minimum of four different vehicles representative of vehicles that will be certified in the engine family. The test vehicles shall include the official emission-data vehicle(s) for the engine family, and the mileage accumulation of each vehicle shall be at or greater than 4000 miles. One speciated profile shall be submitted for each test vehicle. Emission levels of each constituent NMOG shall be measured according to the "California Non-Methane Organic Gas Test Procedures" as adopted July 12, 1991. For the emission-data vehicle(s), the speciated profile(s) shall be obtained from the same test used to obtain the official exhaust emission test results for the emission-data vehicle at the 4,000 mile test point. The manufacturer shall calculate 'g ozone potential per g NMOG' values for each speciated NMOG exhaust emission profile in accordance with the procedures specified in steps (2), (3), and (4) above. By using these 'g ozone potential per g NMOG' values, the manufacturer shall calculate an 'undeteriorated reactivity adjustment factor' for each test vehicle in accordance with the procedure for calculating the 'reactivity adjustment factor' specified in step

(7) above. An 'undeteriorated reactivity adjustment factor' for the engine family shall be calculated by taking the arithmetic mean of the 'undeteriorated reactivity adjustment factor' obtained for each test vehicle. The 95 percent upper confidence bound (95% UCB) shall be calculated according to the equation:

$$95\% \text{ UCB} = \text{RAF}_m + 1.96 \times \left[\frac{1}{n-1} (\text{RAF}_i - \text{RAF}_m)^2 \right]^{1/2}$$

where RAF_m = mean 'undeteriorated reactivity adjustment factor' calculated for the engine family
 RAF_i = 'undeteriorated reactivity adjustment factor' calculated for the i th test vehicle
 n = number of test vehicles

The 95 percent upper confidence bound of the 'undeteriorated reactivity adjustment factor' for the engine family shall be less than or equal to 115 percent of the engine family 'undeteriorated reactivity adjustment factor.'

- b. The manufacturer submits an 'reactivity ozone deterioration factor' for the 'undeteriorated reactivity adjustment factor' calculated for the engine family. To determine the 'reactivity ozone deterioration factor', the manufacturer shall perform two tests at each mileage interval for one or more durability vehicle(s) tested in accordance with the procedures and conditions specified in Sections 6 and 10 of these test procedures for calculating mass deterioration factors. The Executive Officer shall approve the use of other mileage intervals and procedures if the manufacturer can demonstrate that equivalently representative 'reactivity ozone deterioration factors' are obtained. One speciated profile shall be submitted for each test. Emission levels of each constituent NMOG shall be measured according to the "California Non-Methane Organic Gas Test Procedures" as adopted July 12, 1991. A mean g/mi NMOG mass value and a mean 'g ozone per g NMOG' value shall be calculated by taking the arithmetic mean of each measurement from the speciated profiles. These results shall be multiplied together to obtain a mean 'total g ozone potential per mile' value at each mileage interval. A mean 'undeteriorated reactivity adjustment ozone deterioration factor' shall be calculated in accordance with the procedures in Sections 6, 10, and Appendix VIII of these test procedures except that the mean 'undeteriorated reactivity adjustment factor' 'total g ozone potential per mile' value determined at each mileage interval shall be used in place of measured mass emissions. If the 'reactivity ozone deterioration factor' is determined to be less than 1.00, the 'reactivity ozone deterioration factor' shall be assigned a value of 1.00. The 'reactivity ozone deterioration factor' shall be multiplied to the product of the official exhaust NMOG mass emission results at the 4000 mile test point and the mean 'undeteriorated reactivity adjustment factor' for the engine family to obtain the NMOG certification levels 'reactivity adjustment factor' used to determine compliance with the NMOG emission standards.
- c. The speciated profiles, mean 'undeteriorated reactivity adjustment factor' for the engine family, and 'reactivity ozone

deterioration factor' are provided to the Executive Officer with the certification application for the engine family.

- (9) Gasoline meeting the specifications listed below shall be used to determine the 'g ozone potential per g NMOG' of conventional gasoline:

<u>Fuel Property</u>	<u>Limit</u>
<u>Sulfur, ppm by weight</u>	<u>300 +/- 50</u>
<u>Benzene, volume percent</u>	<u>1.6 +/- 0.3</u>
<u>Reid vapor pressure, psi</u>	<u>8.7 +/- 0.3</u>
<u>Distillation, D-86 degrees F</u>	
<u>10%</u>	<u>115-135</u>
<u>50%, maximum</u>	<u>240</u>
<u>90%</u>	<u>323-333</u>
<u>EP, maximum</u>	<u>420</u>
<u>Hydrocarbon Type, volume percent</u>	
<u>Total Aromatics</u>	<u>32 +/- 3.0</u>
<u>Multi-substituted alkyl aromatics</u>	<u>21 +/- 3.0</u>
<u>Olefins</u>	<u>12 +/- 3.0</u>
<u>Saturates</u>	<u>remainder</u>

(The test methods used for each fuel property shall be the same as the test method for the identical fuel property listed in section 9.a.(1) of these test procedures.)

- (109) Table of The maximum incremental reactivities to be used in step (2) are provided in the table below. + Any manufacturer which intends to use the table shall submit to the Executive Officer a list which provides the specific organic gases measured by the manufacturer and the maximum incremental reactivity value assigned to each organic gas prior to or with the submittal of a request for the use of a reactivity adjustment factor unique to a specific engine family. The Executive Officer may deny such requests if he or she determines that the maximum incremental reactivity value assignments are made incorrectly.

Maximum Incremental Reactivity (MIR) Values
(Units: grams ozone/gram organic gas)

<u>Organic Gas Name</u>	<u>MIR</u>
<u>Methane</u>	<u>0.0148</u>
<u>Ethane</u>	<u>0.25</u>
<u>Propane</u>	<u>0.48</u>
<u>n-Butane</u>	<u>1.02</u>
<u>n-Pentane</u>	<u>1.04</u>
<u>n-Hexane</u>	<u>0.98</u>
<u>n-Heptane</u>	<u>0.81</u>
<u>n-Octane</u>	<u>0.61</u>
<u>n-Nonane</u>	<u>0.54</u>
<u>n-Decane</u>	<u>0.47</u>
<u>n-Undecane</u>	<u>0.42</u>
<u>n-Dodecane</u>	<u>0.38</u>

<u>n-Tridecane</u>	<u>0.35</u>
<u>n-Tetradecane</u>	<u>0.32</u>
<u>n-Pentadecane</u>	<u>0.29</u>
<u>2-Methylpropane</u>	<u>1.21</u>
<u>2-Methylbutane</u>	<u>1.38</u>
<u>2,2-Dimethylpropane</u>	<u>0.37</u>
<u>Branched C5 Alkanes</u>	<u>1.38</u>
<u>2-Methylpentane</u>	<u>1.53</u>
<u>3-Methylpentane</u>	<u>1.52</u>
<u>2,2-Dimethylbutane</u>	<u>0.82</u>
<u>2,3-Dimethylbutane</u>	<u>1.07</u>
<u>Branched C6 Alkanes</u>	<u>1.53</u>
<u>2-Methylhexane</u>	<u>1.08</u>
<u>3-Methylhexane</u>	<u>1.40</u>
<u>2,3-Dimethylpentane</u>	<u>1.51</u>
<u>2,4-Dimethylpentane</u>	<u>1.78</u>
<u>3,3-Dimethylpentane</u>	<u>0.71</u>
<u>2,2,3-Trimethylbutane</u>	<u>1.32</u>
<u>Branched C7 Alkanes</u>	<u>1.40</u>
<u>2-Methylheptane</u>	<u>0.96</u>
<u>3-Methylheptane</u>	<u>0.99</u>
<u>4-Methylheptane</u>	<u>1.20</u>
<u>2,3-Dimethylhexane</u>	<u>1.32</u>
<u>2,4-Dimethylhexane</u>	<u>1.50</u>
<u>2,5-Dimethylhexane</u>	<u>1.63</u>
<u>2,2,4-Trimethylpentane</u>	<u>0.93</u>
<u>2,3,4-Trimethylpentane</u>	<u>1.60</u>
<u>Branched C8 Alkanes</u>	<u>1.20</u>
<u>4-Ethylheptane</u>	<u>1.14</u>
<u>2,4-Dimethylheptane</u>	<u>1.34</u>
<u>2,2,5-Trimethylhexane</u>	<u>0.97</u>
<u>Branched C9 Alkanes</u>	<u>1.14</u>
<u>4-Propylheptane</u>	<u>1.01</u>
<u>Branched C10 Alkanes</u>	<u>1.01</u>
<u>Branched C11 Alkanes</u>	<u>1.17</u>
<u>Branched C12 Alkanes</u>	<u>1.23</u>
<u>Branched C13 Alkanes</u>	<u>0.96</u>
<u>Branched C14 Alkanes</u>	<u>0.76</u>
<u>Branched C15 Alkanes</u>	<u>0.70</u>
<u>Cyclopentane</u>	<u>2.38</u>
<u>Cyclohexane</u>	<u>1.28</u>
<u>Methylcyclopentane</u>	<u>2.82</u>
<u>C6 Cycloalkanes</u>	<u>1.28</u>
<u>Methylcyclohexane</u>	<u>1.85</u>
<u>Ethylcyclopentane</u>	<u>2.31</u>
<u>1,3-Dimethylcyclopentane</u>	<u>2.55</u>
<u>C7 Cycloalkanes</u>	<u>1.85</u>
<u>Ethylcyclohexane</u>	<u>1.94</u>
<u>C8 Cycloalkanes</u>	<u>1.94</u>
<u>C9 Cycloalkanes</u>	<u>2.30</u>
<u>C10 Cycloalkanes</u>	<u>1.78</u>
<u>C11 Cycloalkanes</u>	<u>1.91</u>
<u>C12 Cycloalkanes</u>	<u>1.68</u>
<u>C13 Cycloalkanes</u>	<u>1.42</u>
<u>C14 Cycloalkanes</u>	<u>1.22</u>
<u>C15 Cycloalkanes</u>	<u>1.07</u>

<u>Ethene</u>	<u>7.29</u>
<u>Propene</u>	<u>9.40</u>
<u>1-Butene</u>	<u>8.91</u>
<u>2-Methylpropene</u>	<u>5.31</u>
<u>1-Pentene</u>	<u>6.22</u>
<u>2-Methyl-1-Butene</u>	<u>4.90</u>
<u>3-Methyl-1-Butene</u>	<u>6.22</u>
<u>1-Hexene</u>	<u>4.42</u>
<u>C6 Terminal Alkenes</u>	<u>4.42</u>
<u>C7 Terminal Alkenes</u>	<u>3.48</u>
<u>C8 Terminal Alkenes</u>	<u>2.69</u>
<u>C9 Terminal Alkenes</u>	<u>2.23</u>
<u>C10 Terminal Alkenes</u>	<u>1.91</u>
<u>C11 Terminal Alkenes</u>	<u>1.67</u>
<u>C12 Terminal Alkenes</u>	<u>1.52</u>
<u>C13 Terminal Alkenes</u>	<u>1.36</u>
<u>cis-2-Butene</u>	<u>9.94</u>
<u>trans-2-Butene</u>	<u>9.94</u>
<u>2-Methyl-2-Butene</u>	<u>6.41</u>
<u>C5 Internal Alkenes</u>	<u>8.80</u>
<u>C6 Internal Alkenes</u>	<u>6.69</u>
<u>C7 Internal Alkenes</u>	<u>5.53</u>
<u>C8 Internal Alkenes</u>	<u>5.29</u>
<u>C9 Internal Alkenes</u>	<u>4.58</u>
<u>C10 Internal Alkenes</u>	<u>4.05</u>
<u>C11 Internal Alkenes</u>	<u>3.63</u>
<u>C12 Internal Alkenes</u>	<u>3.32</u>
<u>C13 Internal Alkenes</u>	<u>3.03</u>
<u>1,3-Butadiene</u>	<u>10.89</u>
<u>2-Methyl-1,3-Butadiene</u>	<u>9.08</u>
<u>Cyclopentene</u>	<u>7.66</u>
<u>Cyclohexene</u>	<u>5.67</u>
<u>a-Pinene</u>	<u>3.28</u>
<u>b-Pinene</u>	<u>4.41</u>
<u>Ethyne</u>	<u>0.50</u>
<u>Propyne</u>	<u>4.10</u>
<u>1-Butyne</u>	<u>9.24</u>
<u>Benzene</u>	<u>0.42</u>
<u>Toluene</u>	<u>2.73</u>
<u>Ethylbenzene</u>	<u>2.70</u>
<u>n-Propylbenzene</u>	<u>2.12</u>
<u>Isopropylbenzene</u>	<u>2.24</u>
<u>s-Butylbenzene</u>	<u>1.89</u>
<u>C10 Monoalkyl Benzenes</u>	<u>1.87</u>
<u>C11 Monoalkyl Benzenes</u>	<u>1.70</u>
<u>C12 Monoalkyl Benzenes</u>	<u>1.55</u>
<u>m-Xylene</u>	<u>8.16</u>
<u>o-Xylene</u>	<u>6.46</u>
<u>p-Xylene</u>	<u>6.60</u>
<u>C9 Dialkyl Benzenes</u>	<u>7.20</u>
<u>C10 Dialkyl Benzenes</u>	<u>6.45</u>
<u>C11 Dialkyl Benzenes</u>	<u>5.84</u>
<u>C12 Dialkyl Benzenes</u>	<u>5.34</u>
<u>1,2,3-Trimethylbenzene</u>	<u>8.85</u>
<u>1,2,4-Trimethylbenzene</u>	<u>8.83</u>
<u>1,3,5-Trimethylbenzene</u>	<u>10.12</u>

<u>C10 Trialkyl Benzenes</u>	9.07
<u>C11 Trialkyl Benzenes</u>	8.21
<u>C12 Trialkyl Benzenes</u>	7.50
<u>C10 Tetraalkyl Benzenes</u>	9.07
<u>Styrene</u>	2.22
<u>Indan</u>	1.06
<u>Tetralin</u>	0.95
<u>Naphthalene</u>	1.18
<u>Methyl Naphthalenes</u>	3.27
<u>2,3-Dimethylnaphthalene</u>	5.13
<u>Phenol</u>	1.13
<u>Cresols</u>	2.31
<u>Methanol</u>	0.56
<u>Ethanol</u>	1.34
<u>n-Propyl Alcohol</u>	2.26
<u>Isopropyl Alcohol</u>	0.54
<u>n-Butyl Alcohol</u>	2.69
<u>Isobutyl Alcohol</u>	1.92
<u>t-Butyl Alcohol</u>	0.42
<u>Formaldehyde</u>	7.15
<u>Acetaldehyde</u>	5.52
<u>Propionaldehyde</u>	6.53
<u>C4 Aldehydes</u>	5.26
<u>C5 Aldehydes</u>	4.41
<u>C6 Aldehydes</u>	3.79
<u>C7 Aldehydes</u>	3.32
<u>Crotonaldehyde</u>	5.42
<u>Benzaldehyde</u>	-0.55
<u>Methyl t-Butyl Ether</u>	0.62
<u>Ethyl t-Butyl Ether</u>	1.98
<u>Acetone</u>	0.56
<u>C4 Ketones</u>	1.18
<u>Acrolein</u>	6.77

NMOG
Constituent

Maximum
Incremental
Reactivity
(g O / g NMOG)

Alkanes

Methane 0.0102
Ethane 0.147
Propane 0.33
n-Butane 0.64
n-Pentane 0.64
n-Hexane 0.61
n-Heptane 0.48
n-Octane 0.41
n-Nonane 0.29
n-Decane 0.26
n-Undecane 0.21
n-Dodecane 0.19
n-Tridecane 0.17
n-Tetradecane 0.16
n-Pentadecane 0.144

Isobutane 0.85
Lumped G4-G5 Alkanes 0.78
Branched G5 Alkanes 0.88
Iso-Pentane 0.88
Neopentane 0.19
2-Methylpentane 0.91
3-Methylpentane 0.95
Branched G6 Alkanes 0.91
2,3-Dimethyl Butane 0.74
2,2-Dimethyl Butane 0.41
Lumped G6+ Alkanes 0.70
2,4-Dimethyl Pentane 1.07
3-Methyl Hexane 0.85
4-Methyl Hexane 0.85

NMOG
Constituent

Maximum
Incremental
Reactivity
(g O / g₃NMOG)

Branched G7 Alkanes 0.85
2,3-Dimethyl Pentane 0.96
Iso-Octane 0.70
4-Methyl Heptane 0.72
Branched G8 Alkanes 0.72
Branched G9 Alkanes 0.68
4-Ethyl Heptane 0.68
Branched G10 Alkanes 0.60
4-Propyl Heptane 0.60
Branched G11 Alkanes 0.72
Branched G12 Alkanes 0.75
Branched G13 Alkanes 0.57
Branched G14 Alkanes 0.44
Branched G15 Alkanes 0.41

Cyclopentane 1.6
Methylecyclopentane 1.7
G6 Cycloalkanes 0.84
Cyclohexane 0.84
G7 Cycloalkanes 1.17
Methylecyclohexane 1.17
Ethylecyclohexane 1.36
G8 Cycloalkanes 1.36
G9 Cycloalkanes 1.6
G10 Cycloalkanes 1.31
G11 Cycloalkanes 1.23
G12 Cycloalkanes 1.20
G13 Cycloalkanes 0.94
G14 Cycloalkanes 0.88
G15 Cycloalkanes 0.85

NMOG Constituent	Maximum Incremental Reactivity (g O / g NMOG)
---------------------	--

Aromatic Hydrocarbons

Benzene	0.28
---------	------

Toluene	1.9
---------	-----

Ethyl Benzene	1.9
---------------	-----

n-Propyl Benzene	1.44
------------------	------

Isopropyl Benzene	1.5
-------------------	-----

s-Butyl Benzene	1.29
-----------------	------

C10 Monoalkyl Benzenes	1.28
------------------------	------

C11 Monoalkyl Benzenes	1.16
------------------------	------

C12 Monoalkyl Benzenes	1.06
------------------------	------

m-Xylene	6.0
----------	-----

o-Xylene	5.2
----------	-----

p-Xylene	5.2
----------	-----

C9 Dialkyl Benzenes	5.3
---------------------	-----

C10 Dialkyl Benzenes	4.8
----------------------	-----

C11 Dialkyl Benzenes	4.3
----------------------	-----

C12 Dialkyl Benzenes	3.9
----------------------	-----

NMOG Constituent	Maximum Incremental Reactivity (g O / g ₃ NMOG)
---------------------	---

Ethers

Methyl t-Butyl Ether	0.47
----------------------	------

Ethyl t-Butyl Ether	1.33
---------------------	------

NMOG Constituent	Maximum Incremental Reactivity (g O ₃ /g NMOG)	NMOG Constituent	Maximum Incremental Reactivity (g O ₃ /g ₃ NMOG)
Alkenes		1,3,5-Trimethyl Benzene	7.5
Ethene	5.3	1,2,3-Trimethyl Benzene	7.4
Propene	6.6	1,2,4-Trimethyl Benzene	7.4
1-Butene	6.1	G10 Trialkyl Benzenes	6.7
1-Pentene	4.2	G11 Trialkyl Benzenes	6.1
3-Methyl-1-Butene	4.2	G12 Trialkyl Benzenes	5.6
1-Hexene	3.0	Tetralin	0.73
G6 Terminal Alkenes	3.0	Naphthalene	0.87
G7 Terminal Alkenes	2.4	Methyl Naphthalene	2.4
G8 Terminal Alkenes	1.9	2,3-Dimethyl Naphthalene	3.7
G9 Terminal Alkenes	1.6	Alkynes	
G10 Terminal Alkenes	1.32	Acetylene	0.37
G11 Terminal Alkenes	1.15	Alcohols	
G12 Terminal Alkenes	1.03	Methanol	0.40
G13 Terminal Alkenes	0.93	Ethanol	0.79
G14 Terminal Alkenes	0.86	n-Propyl Alcohol	1.33
G15 Terminal Alkenes	0.80	Isopropyl Alcohol	0.37
Isobutene	4.2	Isobutyl Alcohol	0.72
2-Methyl-1-Butene	3.7	n-Butyl Alcohol	1.6
trans-2-Butene	7.3	t-Butyl Alcohol	0.29
cis-2-Butene	7.3	Ethylene Glycol	1.13
2-Methyl-2-Butene	5.0	Propylene Glycol	0.92
G5 Internal Alkenes	6.2	Aldehydes	
2,3-Dimethyl-2-Butene	3.7	Formaldehyde	6.2
G6 Internal Alkenes	5.3	Acetaldehyde	3.8
G7 Internal Alkenes	4.4	Propionaldehyde	4.6
G8 Internal Alkenes	3.6	Ketones	
G9 Internal Alkenes	3.2	Acetone	0.39
G10 Internal Alkenes	2.8	G4 Ketones	0.76
G11 Internal Alkenes	2.5	Aromatic Oxygenates	
G12 Internal Alkenes	2.3	Benzaldehyde	- 0.54
G13 Internal Alkenes	2.1	Phenol	0.79
G14 Internal Alkenes	1.9	Cresols	1.6
G15 Internal Alkenes	1.8		
1,3-Butadiene	7.7		
Isoprene	6.5		
Cyclopentene	4.0		
Cyclohexane	3.3		
a-Pinene	1.9		
b-Pinene	1.9		

PROPOSED

State of California
AIR RESOURCES BOARD

CALIFORNIA ASSEMBLY-LINE TEST PROCEDURES FOR 1983
AND SUBSEQUENT MODEL-YEAR PASSENGER CARS,
LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Adopted: November 24, 1981
Amended: March 9, 1983
Amended: May 25, 1983
Amended: August 21, 1984
Amended: _____

State of California
AIR RESOURCES BOARD

CALIFORNIA ASSEMBLY-LINE TEST PROCEDURES FOR 1983
AND SUBSEQUENT MODEL-YEAR PASSENGER CARS,
LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

A. GENERAL PROVISIONS

1. APPLICABILITY

These test procedures, adopted pursuant to Section 43210 of the California Health and Safety Code (H & SC), are applicable to vehicle manufacturers of 1983 and subsequent model-year liquefied petroleum gas, compressed or liquefied natural gas, methanol, ethanol, hybrid electric, gasoline, and diesel-powered passenger cars, light-duty trucks, and medium-duty vehicles having an engine displacement of 50 cubic inches (820 cubic centimeters) or greater, except motorcycles, including all Transitional Low-Emission Vehicles (TLEVs), Low-Emission Vehicles (LEVs), and Ultra-Low-Emission Vehicles (ULEVs), subject to registration and manufactured for sale in California.

2. COMPLIANCE

The procedures specify two types of tests: (1) an inspection test to be applied to every vehicle before sale; and (2) a quality-audit test according to the "CALIFORNIA EXHAUST EMISSION STANDARDS AND TEST PROCEDURES FOR 1981 AND SUBSEQUENT MODEL PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES" or "CALIFORNIA EXHAUST EMISSION STANDARDS AND TEST PROCEDURES FOR 1988 AND SUBSEQUENT MODEL PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES", as applicable. Demonstration of compliance with cold temperature carbon monoxide standards shall be exempt from quality-audit testing. A vehicle is in compliance with these assembly-line standards and test procedures when that vehicle is in compliance with the inspection test requirements and that vehicle's engine family is in compliance with the quality-audit test requirements. Since quality-audit evaluations occur less frequently than the inspection tests, a vehicle which passes the inspection test may be presumed to be in compliance with the full assembly-line procedures pending meeting the quality-audit evaluation of that vehicle's engine family.

3. ACCESS

Air Resources Board (ARB) personnel and mobile laboratories shall have access to vehicle assembly plants, distribution facilities, and test facilities for the purpose of vehicle selection, testing, and observation. Scheduling of access shall be arranged with the designated manufacturer's representative and shall not unreasonably disturb normal operations.

4. VARIATIONS AND EXEMPTIONS

Variations from these procedures which produce substantially equivalent results may be authorized by the Executive Officer. In extraordinary circumstances where compliance with these procedures is not possible or practicable, a manufacturer may appeal to the Air Resources Board for a temporary exemption.

5. COMMUNICATIONS

All reports required by these procedures shall be sent to:

Chief, Mobile Source Division
California Air Resources Board
9528 Telstar Avenue
El Monte, CA 91731

Two copies of the report shall be submitted.

B. INSPECTION TEST PROCEDURES -- 1983 AND 1984 MODEL-YEAR VEHICLES

This inspection test shall be performed on all 1983 and 1984 model-year passenger cars, light-duty trucks and medium-duty vehicles subject to these test procedures.

1. INSPECTION TEST PROCEDURES

(a) Functional Test

Functional test of the engine components and control systems which affect emissions shall be made prior to the steady-state emissions tests. If a vehicle fails one or more functional tests, it must be repaired and pass a functional retest before it can be emissions tested.

A list of the items to be functionally checked and a procedure for performing these checks shall be maintained by the manufacturer and may be requested for review at any time after production start-up by the chief, Mobile Source Division. When requested, the manufacturer has up to 30 days to submit a copy of these procedures. Within 60 days of receipt, the Chief, Mobile Source Division, may require revisions.

(b) Steady-State Emissions Test

The vehicle engine shall be adjusted to the manufacturer's specifications for delivery to the customer prior to the steady-state emissions test. This test shall consist of a determination of hydrocarbon (HC) and carbon monoxide (CO) exhaust concentrations with the engine operating in a normal idle condition. All tests, including those of control limit test vehicles, shall be conducted as follows:

(1) Vehicles shall be tested in the normal "warmed-up" operating temperature range, i.e., after the choke is fully open and the engine is at curb idle speed, but before thermal override devices are actuated to prevent overheating. The test may be performed in any transmission gear; however the same gear shall be used for control limit test vehicles and production vehicles. For each engine family, the idle test may be performed without the air injection system (AIR) instead of with AIR, provided that the control limit vehicles are tested both with and without AIR. The requirements of section B (3)(g) must be met with AIR. The control limit test vehicles and all production vehicles should be warmed-up and tested in the same manner.

(2) The sampling probes of the analytical system shall be inserted into the exhaust outlets far enough to avoid dilution with the outside air. When this is not possible, a tailpipe extension shall be used.

(3) A vehicle which fails a steady-state emissions test shall be retested or repaired and shall pass on retest prior to sale.

2. EVALUATION

Any vehicle tested by the steady-state emissions test showing emissions less than the control limits established for its engine family or subgroup and which had previously passed the functional tests will be considered to be in compliance with the inspection test requirements.

3. CONTROL LIMITS

The control limits for each engine family or subgroup at the start of a model year will be determined as follows:

(a) Measure the emissions from the first 100 vehicles of each engine family or subgroup tested by the steady-state assembly-line inspection test.

(b) Determine the mean emission level and standard deviation for each pollutant (HC and CO).

(c) The control limit for each pollutant is the sum of the mean plus two times the standard deviation for that pollutant.

(d) Until the first control limits are established, the manufacturer shall use temporary control limits based on the first ten tests. These ten vehicles are deemed to meet the control limits so established.

(e) (i) For control systems that do not use catalytic converters -- If the HC control limit value is determined in subparagraph (c) is less than 100 ppm, the HC control value may be increased by up to 50 ppm, not to exceed 100 ppm. If the CO control limit determined in

subparagraph (c) is less than 1.0 percent, the CO control limit may be increased by up to 0.5 percent, not to exceed 1.0 percent.

(ii) For control systems that use catalytic converters -- If the HC control limit value determined in subparagraph (c) is less than 50 ppm, the control limit value may be increased by up to 30 ppm, not to exceed 50 ppm.

If the CO control limit determined in subparagraph (c) is less than 0.5 percent, the CO control limit may be increased by up to 0.3 percent, not to exceed 0.5 percent.

(f) Idle control limit values may be rounded to the nearest 10 ppm HC and 0.1 percent CO in conformance to ASTM E29-67, except where this would result in a zero value.

(g) The maximum allowable steady-state control limits for HC and CO are those values used as the idle mode standard shown in Title 13, California Administrative Code of Regulations (~~G.A.G.~~) (C.C.R.) Section 2176 for the applicable model-year or, where applicable model-year standards are not yet adopted, the latest previous model-year values in effect at the time the vehicle is manufactured. An exemption to this requirement will be granted providing the manufacturer submits emission data with each quarterly report listed in one of the following options:

(1) Submit with each quarterly assembly-line report HC and CO emission values measured at engine idle speed for each quality audit ~~vehicle tested and the computed mean and standard deviation of HC and CO~~ emission results for the total number of vehicles tested, by engine family. Measurements of HC and CO shall be conducted immediately following completion of the dynamometer run and vehicles shall be in a state described under B.1 (b)(1) above. If less than 30 vehicles were quality-audit tested during the reporting quarter, the computation of the means and standard deviations are not required.

(2) Submit quarterly HC and CO emission values measured at engine idle speed for a minimum of 30 vehicles in the engine family or sub-group immediately after these vehicles have complied with the assembly-line inspection procedures and have either been run-in a distance of 50 miles (on the road or dynamometer) or after other appropriate engine break-in has been performed and the engine is operating at a fully warmed-up condition as described in B.1 (b)(1) above. In addition to emission results of individual vehicles, the mean and standard deviation shall be computed and submitted.

(3) The manufacturer may propose other methods to achieve results equivalent to the two operations above. These emission data shall be obtained from stabilized vehicles which have emission control systems with no defects and are properly adjusted to manufacturer's specifications.

(h) Control limits with AIR operating shall be calculated and reported for information purposes for those engine families that are tested without AIR in operation.

Control limit values shall be recalculated for each production quarter based on the measured emissions from at least 100 vehicles produced during the last half of the preceeding quarter of production for each engine family or subgroup tested by the steady-state emissions test. When production levels do not permit compliance with the above, data from vehicles produced during the first half of the preceeding quarter may be used. If the quarterly production of any engine family is less than 100 vehicles, the manufacturer shall use the test results from all vehicles produced during that quarter in determining the control limit values for the next quarter.

The Executive officer shall be notified within one week if control limit values are recalculated following running changes which affect idle emissions levels. The new control limit values and the date they first went into effect shall be part of the notification.

All testing, reports, evaluations, etc., shall be by engine family except when the Executive Officer has approved a breakdown by subgroups (e.g., different carburetors, engine displacements, control systems, transmissions, and inertia weights), by assembly plant, or both.

Note:

Data from any vehicle indicating gross engine malfunction, and/or failure or disconnection of any emission control component, shall be excluded from that used for generating control limits. Retest data on vehicles exceeding the control limits shall not be used in determining control limits for subsequent quarters.

4. REPORTS

Reports shall be submitted to the Air Resources Board within 45 calendar days of the end of each calendar quarter and within 45 calendar days of the end of the manufacturer's model production year. Results for two different model-years shall not be combined statistically.

The report shall include:

(a) The temporary quarterly control limit values obtained for the first quarter of production.

(b) The mean and standard deviation of the steady-state emissions test used to determine the quarterly control limits.

(c) The steady-state control limit values for the next quarter's production.

(d) From a representative sample of vehicles approved by the Executive Officer, the number and percentage of vehicles:

- (1) failing the test
- (2) repaired or adjusted

All HC values should be stated as hexane equivalents for NDIR measurement and ppm carbon if a flame ionization detector is used. The hexane equivalent conversion value shall be supplied for each different model of flame ionization detector used and for each engine family.

C. INSPECTION TEST PROCEDURES -- 1985 AND SUBSEQUENT MODEL-YEAR VEHICLES

This Inspection Test shall be performed on all 1985 and subsequent model-year passenger cars, light-duty trucks and medium-duty vehicles subject to these Test Procedures. However, for 1985 model-year vehicles only, the Inspection Test Procedures set forth in Section B. of these Test Procedures may be performed in lieu of the Inspection Test Procedures set forth in this Section C. In such a case, a manufacturer may change to the Procedures set forth in this Section C. at the start of any calendar quarter in which the manufacturer starts performing the Inspection Test set forth in this Section C.

1. INSPECTION TEST PROCEDURES

Functional tests of the emission control components and systems used on the vehicle shall be conducted in accordance with a plan approved by the Executive Officer. At least 90 days prior to the start of production, the manufacturer shall submit to the Executive Officer a plan for functional testing which lists the emission control components and systems to be tested and specifies the testing procedures to be used. Appendix B sets forth typical types of components and systems for inclusion in the functional test plan. If an on-board emission control diagnostic system of any type, either completely self-contained or requiring external peripheral equipment, is installed on a vehicle, it must be included in the components to be functionally tested and the on-board diagnostic system must be used in functionally testing the vehicle emission control system. In appropriate instances, functional tests may be conducted during the vehicle assembly process before the end of the assembly line. For components which cannot practically be functionally checked on every vehicle, a statistically valid sampling test may be used as the functional tests. The Executive Officer shall approve the plan unless he or she determines that the tests are not designated for the appropriate control components and systems or that the tests will be inadequate to reasonably assure that the components and systems are correctly installed and are functioning properly. The manufacturer may at any time submit proposed changes to the plan for functional testing. Once a plan is approved, for subsequent model-years, a manufacturer must submit a plan only if changes are made to the emission control components or systems on the vehicle, or to the proposed functional

test. In the case of such changes, only the portion of the plan covering the changed components or systems, or changes in tests, must be submitted for approval. In order for a vehicle to satisfy the inspection test requirements, each of the emission control components and systems identified in the approved plan for testing must be found, pursuant to the specified approved plan for testing must be found, pursuant to the specified approved test, to be correctly installed and functioning properly.

2. EVALUATION

Any vehicle which passes the approved functional test will be considered to be in compliance with the inspection test requirements.

3. REPORTING

Each manufacturer shall submit quarterly a statement that the functional tests included in the approved test plan have been conducted on all vehicles produced for sale in California. The statement shall be signed by an official of the manufacturer who has verified the accuracy of the statement and shall accompany the assembly-line quality audit test report for each production quarter.

D. QUALITY-AUDIT TEST PROCEDURES

1. VEHICLE SAMPLE SELECTION

The vehicle manufacturer shall randomly select vehicles from each engine family for quality-audit testing. Each selected vehicle for quality-audit testing must pass the inspection test, be equipped with emission control systems certified by the ARB, and be representative of the manufacturer's California sales. The procedure for randomly selecting vehicles must be submitted to the Chief, Mobile Source Division, El Monte, CA prior to production.

A continuous sample rate shall be chosen by the manufacturer to provide a sample which is representative of the total production. The manufacturer shall select a sample rate which he or she determines will be satisfactory for use by the ARB in determining the number of vehicles in the entire population of a particular engine family which do not meet Board-established emission standards by extrapolation from the percentage of the sample not meeting the standards. The results from the sample may be extrapolated to the entire population subject to the provisions relating to vehicle exclusion contained in paragraph 3 which follows. The sample rate so chosen shall not be less than 2.0 percent except for fuel-flexible and dual-fuel vehicles where the sample rate chosen shall not be less than 1.0 percent. The manufacturer shall notify the Executive Officer of any change to the sample rate. The date of such change shall be reported in accordance with paragraph 6 which follows.

A vehicle manufacturer may use, as an alternate to the above vehicle selection procedure, the optional procedure outlined in Appendix A.

Four-wheel drive vehicles which can be manually shifted to a two-wheel drive mode will be tested in the normal on-highway two-wheel drive mode of operation. If full-time four-wheel drive vehicles are selected, substitutions may be made with comparable two-wheel drive vehicles of the same engine family. If comparable two-wheel drive vehicles are not available, selected full-time four-wheel vehicles will be tested after having the front wheels temporarily disengaged or the front end of the vehicle elevated.

The Executive Officer may, upon notice to the manufacturer, require the sample rate to be increased to a maximum of ten percent of production (not to exceed 30 additional vehicles) of the calendar quarterly production of any engine family by invoking Section 2110, Chapter 3, Title 13 of the G.A.G. C.C.R.

2. VEHICLE PREPARATION AND PRECONDITIONING

(a) After the inspection tests, no emissions tests may be performed on a quality-audit vehicle prior to the first quality-audit test, except where such tests are run on all vehicles manufactured for sale in California.

(b) The vehicle shall begin the test sequence as received from the inspection test, except for mileage accumulation or engine run-in. The schedule for mileage accumulation or engine run-in and any changes to the schedule must be submitted to the Executive Officer with each quarterly report. This schedule must be adhered to for all quality-audit testing within an engine family and subgroup or engine family and assembly plant as appropriate.

(c)(1) For vehicles which are certified to the running loss and useful life standards for evaporative emissions contained in Title 13, California Code of Regulations, Section 1976(b)(1), and the incorporated "California Evaporative Emissions Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," last amended November 20, 1991, the vehicle preparation and preconditioning procedure shall be conducted in accordance with the evaporative emissions test procedures contained in section 4.g.i., "Test Procedure, General Requirements," subsections A.-F., as codified in subsections 4.g.ii.(c), 4.g.ii.(d), and 4.g.iii., with the exception that: (1) the cold soak prior to the preconditioning, and the fuel drain and fuel fill following the vehicle preconditioning, as described in subsections 4.g.i.B. and 4.g.i.C., respectively, may be omitted at the discretion of the manufacturer and (2) the vehicle canister loading procedure contained in subsection 4.g.iii. shall be conducted using one of the following options:

(i) The vehicle canister loading procedure shall be conducted in accordance with subsections 4.g.iii.C. and 4.g.iii.D. Alternative methods of loading the original canister may be used, provided such a method is approved in advance by the Executive Officer on the basis of achieving canister loading comparable to the prescribed method.

OR

(ii) The vehicle canister loading procedure described in subsections 4.g.iii.C. and 4.g.iii.D. shall be employed for a canister which is loaded separate from the vehicle, and then attached prior to the exhaust tests, with the original canister disabled. Such a canister loaded separate from the vehicle shall be identical in nominal working bed capacity, charcoal bed volume and configuration to the original canister present on the vehicle. The loading procedure for this canister shall be as described in subsections 4.g.iii.C. and 4.g.iii.D., except that the rate of butane loading shall not exceed 40 grams/hour. An alternative to this option may be used provided such a method is approved in advance by the Executive Officer on the basis of whether the flow or vapor from the canister to the engine is comparable to the prescribed method.

OR

(iii) Data shall be submitted to the Executive Officer demonstrating that there does not exist a measurable difference in exhaust emissions, for both hydrocarbons and OMHCE, between vehicles possessing a canister(s) loaded in accordance with subsections 4.g.iii.C. and 4.g.iii.D. and vehicles possessing an unloaded canister(s). For the purposes of this section, the preparation and preconditioning of vehicles with an unloaded canister shall be conducted in an identical manner as described in 2.(c)(1) for vehicles equipped with a loaded canister, except that canister loading requirements contained in subsections 4.g.iii.C. and 4.g.iii.D. shall be omitted.

(c)(2) For all other vehicles, the following procedure shall apply. A new carbon canister may be installed on the vehicle at the start of the test sequence. The test sequence shall consist of one Urban Dynamometer Driving Schedule (UDDS) test procedure, followed by a cold soak and constant volume volume sample (CVS) test. The federal test procedure requirement, consisting of heating the fuel before the CVS test, is to be omitted. The manufacturer may request permission to use an alternate preconditioning procedure provided the manufacturer demonstrates that it will not affect the loading of the carbon canister when compared with the UDDS.

(d) Except as provided in paragraph D.2.(f) below, no vehicle selected for quality-audit testing shall be repaired or adjusted after passing the inspection test, except for a vehicle that: (1) is not testable, e.g., cannot be started, transmission or brakes lock-up; (2) is not reasonably operative, e.g., some transmission gears not functioning; (3) is unsafe to test; or (4) would be damaged by testing.

(e) If a vehicle is shipped to a remote facility for quality-audit testing, correction of damage or maladjustment, which is found to have resulted from shipment of the vehicle, is permitted only after the initial test of the vehicle, except as provided in paragraph (d) above.

All adjustments or repairs performed on vehicles prior to each test shall be reported to the Executive Officer by inclusion in the quarterly report. The vehicle condition and symptoms and reason(s) for each repair or adjustment shall be listed. In the event a retest is performed, application may be made to the Executive Officer for permission to substitute the after-repair test results for the original test results. The Executive Officer will either affirm or deny the application. When requested by the manufacturer, no more than ten days after the production quarter, response from the Executive Officer will be within ten working days.

(f) If a vehicle is shipped to a remote facility for quality-audit testing, no pre-delivery type inspection, adjustment, or repair of vehicles selected for quality-audit is allowed, except as follows: if subsequent to shipping from the assembly-line, the manufacturer performs the particular inspection and correction of damage or maladjustment at designated preparation facility locations for all vehicles produced and the manufacturer's written specific inspections and corrections will be allowed prior to testing quality-audit vehicles.

(g) If the emission test results of a vehicle are determined to be invalid by the manufacturer, the vehicle must be retested. Emission results from all tests shall be reported. A detailed report on the reasons for each invalid test shall be included in the quarterly report.

3. STANDARDS AND TEST PROCEDURES

The emission standards and the exhaust sampling analytical ~~procedures shall be those described in the~~ "CALIFORNIA EXHAUST EMISSION STANDARDS AND TEST PROCEDURES FOR 1981 AND SUBSEQUENT MODEL PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES" or in "CALIFORNIA EXHAUST EMISSION STANDARDS AND TEST PROCEDURES FOR 1988 AND SUBSEQUENT MODEL PASSENGER CARS, LIGHT-DUTY TRUCKS, AND MEDIUM-DUTY VEHICLES", as applicable, ~~for the~~ vehicles tested for exhaust emissions only, with exceptions or additions as shown in paragraph D.2.

4. EVALUATION

The evaluation shall be performed on sample sizes containing 30 or more vehicles. If a sample size for a particular production quarter is less than 30 vehicles, the data from that quarter shall be combined with all the data from each successive quarter until data from at least 30 vehicles have been quality-audit tested is included in the quarterly evaluation. If the sample size for the last final quarter's production for a model year does not contain at least 30 vehicles, the data from the last final quarter shall be combined with all the data from each preceding quarter until the sample size contains at least 30 vehicles. For an engine family which contains both light-duty trucks and medium-duty vehicles, all references in this test procedure to engine family shall mean light-duty truck subgroup or medium-duty vehicle subgroup.

Based upon additional information submitted by a manufacturer, the Executive Officer may allow rejection of any data from vehicles if they are considered to be not representative of production.

For each production quarter, if 30 or more vehicles are tested, the ARB shall consider that probable cause exists for finding a violation by any engine family if the average emissions of any pollutant, after multiplying the emission data of each vehicle by the appropriate certification deterioration factor (DF), exceed the applicable year exhaust emission standards, when rounded to the same number of significant digits as the standard.

The Executive Officer may invoke Section 2109, Chapter 3, Title 13 of the G-A-G- C.C.R., if probable cause is found for a full or combined production quarter. The Executive Officer may invoke Section 2110, Chapter 3, Title 13 of the G-A-G- C.C.R., if probable cause is found for a short start-up production period (less than a full calendar quarter), for the first 30 vehicles quality-audit tested during any production quarter or from the start of production, or for vehicles evaluated in accordance with the monthly evaluation required by paragraph 6 below. In addition, the ARB may seek statutory penalties pursuant to H & SC Sections 43211 and 43212 at the end of each full or combined calendar quarter of production. If the Executive Officer invokes G-A-G- C.C.R. Section 2109 or 2110, an evaluation will be made on vehicles produced subsequent to the invocation of a plan adopted pursuant to Section 2109 or 2110 as long as the sample size contains at least 30 vehicles.

If more than 1.0 percent (at least 2 vehicles) of the sample within an engine family has projected emissions which exceed the applicable standards by more than 2.33 standard deviations at the time of any evaluation of that family's average emissions, within 30 working days, the manufacturer shall submit: (a) an analysis of the projected average emissions for each engine code/transmission type/inertia weight combination within that family; (b) an engineering evaluation of the cause of failure for each vehicle which exceeded the standard by more than 2.33 standard deviations; (c) the manufacturer's opinion as to the nature of the problem; and (d) any corrective action proposed by the manufacturer.

The Executive Officer shall review the report, and may require that the proposed corrective action be taken. If, after review of the report, the Executive Officer finds the proposed corrective action inadequate, the Executive Officer may invoke Section 2109 or 2110, as appropriate.

5. NON-METHANE (NMHC) OR TOTAL HYDROCARBON (THC) MEASUREMENTS

(a) For an engine family certified to the non-methane hydrocarbon (NMHC) standards, the manufacturer shall measure the NMHC content which shall be multiplied by the NMHC DF.

(b) For an engine family certified to the total hydrocarbon (THC) standards, the measured THC values shall be multiplied by the THC DF.

(c) For an engine family certified to organic material hydrocarbon equivalent (OMHCE) or organic material non-methane hydrocarbon equivalent (OMNMHCE) standards, the manufacturer shall measure the OMHCE or OMNMHCE content which shall be multiplied by the OMHCE or OMNMHCE DF. As an alternative to measuring the OMHCE or OMNMHCE content, the Executive Officer may approve, upon submission of supporting data by a manufacturer, the use of OMHCE or OMNMHCE to NMHC ratios. To request the use of OMHCE or OMNMHCE to NMHC ratios, the manufacturer shall establish during certification testing the ratio of measured OMHCE or OMNMHCE exhaust emissions to measured NMHC exhaust emissions for each certification test data vehicle for the applicable engine family. The average of the individual test ratios of measured OMHCE or OMNMHCE to NMHC emissions for the engine family shall be submitted to the Executive Officer in the application for certification. Following approval of the application for certification, the manufacturer may conduct quality-audit testing on the engine family by measuring NMHC exhaust emissions rather than OMHCE or OMNMHCE exhaust emissions. The measured NMHC exhaust emissions shall be multiplied by the OMHCE or OMNMHCE to NMHC ratio submitted in the application for certification for the engine family to determine the equivalent OMHCE or OMNMHCE exhaust emission values for the quality audit test vehicle. The equivalent OMHCE or OMNMHCE exhaust emission values shall be compared to the OMHCE or OMNMHCE exhaust emission standard applicable to the engine family.

(d) For an engine family certified to non-methane organic gas (NMOG) standards, the manufacturer shall measure the NMOG content which shall be multiplied by the NMOG DF and the reactivity adjustment factor and ozone DF, if applicable. As an alternative to measuring the NMOG content, the Executive Officer may approve, upon submission of supporting data by a manufacturer, the use of NMOG to NMHC ratios. To request the use of NMOG to NMHC ratios, the manufacturer shall establish during certification testing the ratio of measured NMOG exhaust emissions to measured NMHC exhaust emissions for each certification test data vehicle for the applicable engine family. The average of the individual test ratios of measured NMOG to NMHC emissions for the engine family shall be submitted to the Executive Officer in the application for certification. Following approval of the application for certification, the manufacturer may conduct quality-audit testing on the engine family by measuring NMHC exhaust emissions rather than NMOG exhaust emissions. The measured NMHC exhaust emissions shall be multiplied by the NMOG to NMHC ratio submitted in the application for certification for the engine family to determine the equivalent NMOG exhaust emission values for the quality audit test vehicle. The equivalent NMOG exhaust emission value shall be used in place of the measured NMOG exhaust emission value in determining the reactivity adjusted exhaust NMOG results. The equivalent reactivity adjusted NMOG exhaust emission values shall be compared to the NMOG exhaust emission standard applicable to the vehicle emission category (TLEV, LEV, or ULEV) in which the engine family was certified.

6. FORMALDEHYDE (HCHO) MEASUREMENTS

For an engine family certified to HCHO standards, the manufacturer shall measure the HCHO content which shall be multiplied by the

HCHO DF. As an alternative to measuring the HCHO content, the Executive Officer may approve, upon submission of supporting data by a manufacturer, the use of HCHO to NMHC ratios. To request the use of HCHO to NMHC ratios, the manufacturer shall establish during certification testing the ratio of measured HCHO exhaust emissions to measured NMHC exhaust emissions for each certification test data vehicle for the applicable engine family. The average of the individual test ratios of measured HCHO to NMHC emissions for the engine family shall be submitted to the Executive Officer in the application for certification. Following approval of the application for certification, the manufacturer may conduct quality-audit testing on the engine family by measuring NMHC exhaust emissions rather than HCHO exhaust emissions. The measured NMHC exhaust emissions shall be multiplied by the HCHO to NMHC ratio submitted in the application for certification for the engine family to determine the equivalent HCHO exhaust emission values for the quality audit test vehicle. The equivalent HCHO exhaust emission values shall be compared to the HCHO exhaust emission standard applicable to the engine family.

6 7. REPORTS

Each vehicle manufacturer shall submit a report to the ARB within 45 calendar days after the end of each calendar quarter and 45 calendar days after the end of the production year. More frequent reports may be required if the Executive Officer invokes 6-A-6- C.C.R. Section 2109 or 2110, Chapter 3, Title 13. Each vehicle manufacturer shall review the test results of the first 30 test vehicles of each engine family for each calendar quarter of production or from the start of production, and the quarter's cumulative test results of each engine family at the end of each month. If the sample size is 30 or more vehicles, the Chief, Mobile Source Division, shall be notified in writing within ten working days whenever an engine family exceeds an emission standard.

The quarterly report shall include the following:

(a) The total production and sample size for each engine family, and the total number of vehicles certified to each of the TLEV, LEV, ULEV and zero-emission vehicle (ZEV) standards and produced and delivered for sale in California in each of the following vehicle classifications: 1) passenger cars and light-duty trucks 0-3750 lbs. loaded vehicle weight, 2) light-duty trucks 3751-5750 lbs. loaded vehicle weight, 3) medium-duty vehicles 0-3750 lbs. test weight, 4) medium-duty vehicles 3751-5750 lbs. test weight, 5) medium-duty vehicles 5751-8500 lbs. test weight, 6) medium-duty vehicles 8501-10,000 lbs. test weight, and 7) medium-duty vehicles 10,001-14,000 lbs. test weight.

(b) A description of each test vehicle ((i.e., date of test, engine family, engine size, vehicle identification number, fuel system (e.g., number of venturi, fuel injection, etc.), transmission type, test weight used, dynamometer power absorber setting in horsepower, engine code or calibration number, and test location)).

(c) The CVS exhaust emission data and carbon dioxide data for each test vehicle. For methanol or ethanol vehicles not certified as TLEVs, LEVs, or ULEVs, OMHCE or OMNMHCE data shall be substituted for NMHC or THC data, and formaldehyde (HCHO) data shall also be submitted. For vehicles certified as TLEVs, LEVs, or ULEVs, NMOG data shall be substituted for NMHC or THC data, and HCHO data shall also be submitted. For natural gas vehicles certifying as TLEVs, LEVs and ULEVs, methane emission data shall also be submitted.

The data reported shall be rounded to one significant figure beyond the number of significant figures in the applicable standard. DF's shall be stated, then applied to the data. The data reported after the DF's are applied shall be rounded using the "rounding off method" specified in ASTM: E29-67 to the number of places to the right of the decimal point indicated below, follows for all in accordance with the emission standards to which the vehicles was certified:

<u>THC, NMHC,</u>					
<u>OMHCE or OMNMHCE</u>	<u>NMOG</u>	<u>CO</u>	<u>NOx</u>	<u>HCHO</u>	<u>CO₂</u>
.XXX	.XXXX	.XX	.XX or .XXX	.XXXX	.X

(d) The retest emissions data, as described in paragraph (c) above, for any vehicle failing the initial test, and description of the corrective measures taken, including specific components replaced or adjusted.

(e) A statistical analysis of the quality-audit test results for each engine family stating:

(1) Number of vehicles tested.

(2) Average emissions and standard deviations of the sample for HC, methane, or OMHCE or OMNMHCE or NMOG, as applicable, CO, and NOx, and HCHO, as applicable, both before and after applying DF's, reactivity adjustment factors, and ozone DF's, as applicable. In the latter case, the individual test points shall be multiplied by the DF's, reactivity adjustment factors, and ozone DF's, as applicable, prior to computing the average and standard deviation. The average emissions and standard deviation of the sample for carbon dioxide shall also be listed.

(3) The applicable exhaust emission standards to be met by listing specific options selected, designating when 100,000 mile standards apply, and designation where NMHC, or THC, OMHCE, OMNMHCE, or NMOG standards apply.

(f) Every aborted test and reason for abort shall be reported.

(g) If both four-wheel and two-wheel drive vehicles are included in a light-duty truck engine family under 4,000 pounds inertia weight, the

quality-audit test data from four-wheel drive vehicles shall be distinguished from and summarized separately from two-wheel drive vehicles.

(h) The final report shall include the date of the end of the manufacturer's model production year for each engine family.

(i) If vehicles from different model-years are produced in any production quarter, separate reports shall be submitted for each model-year.

(j) For federally certified light-duty vehicles produced under the provisions of H & SC 43102(b), the emissions data and other information required in the quarterly reports shall be included in a separate section of the report. Where such federally certified light-duty vehicles are in the same engine family as medium-duty vehicles, all data from these medium-duty vehicles shall be deleted from the separate section. The separate section shall include the statistical summary required by Section (e)(2). The separate section of the report shall also include identical data for California engine families used for offsetting emissions of federally certified light-duty vehicles.

7 8. SPECIAL REQUIREMENTS FOR SMALL VOLUME MANUFACTURERS

The following requirements apply only to those vehicle manufacturers who were granted relief by the Executive Officer under Title 13, ~~G-A-G~~ C.C.R., Section 1960.4, Special Standards for 1982 and Subsequent Model Passenger Cars and 1983 and Subsequent Model Light-Duty Trucks and Medium-Duty Vehicles, 0-3999 Pound Equivalent Inertia Weight.

The requirements listed below are to be followed as supplemental to and when contrary to other requirements specified in part D. "Quality-Audit test Procedures", Sections "4. Evaluation", and "6. Reports". These requirements are listed to implement, define, and clarify the Board requirements of ~~G-G-R~~ C.C.R., Section 1960.4.

(a) Additional Reporting Requirements for NOx Emissions

(1) The cumulative average of NOx emissions from the entire quality-audit light-duty trucks (LDT) plus medium-duty vehicles (MDV) 0-3999 lbs. equivalent inertia weight, shall be reported both before and after applying DF's for the 1983 model-year to:

- (i) All 1983 models tested during each calendar quarter.
- (ii) All 1983 models tested to date by the end of each calendar quarter.
- (iii) All 1983 models tested to date by December 31, 1982, by June 30, 1983, and by December 31, 1983.

(2) The combined averages from the entire passenger car (PC) line and, separately, LDT and MDV lines, 0-3999 lbs. equivalent inertia weight, shall be reported both before and after applying DF's for:

- (i) All 1983 model PC's tested during each calendar quarter.
- (ii) All 1984 model PC's and, separately, LDT's plus MDV's tested during each calendar quarter.
- (iii) All 1985 model LDT's plus MDV's tested during each calendar quarter.

(3) Subgroups

The NOx emission results shall be averaged and reported by engine family subgroup in each regular quarterly assembly-line report.

(b) Semi-Annual Evaluations

Joint ARB - manufacturer evaluations will be made each six months to determine compliance with the 0.7 gm/mi NOx production level based on test results by engine families separately for 1983 and 1984 model PC's and 1984 and 1985 model LDT's plus MDV's tested and on a cumulative basis for 1983 model LDT's plus MDV's. The first evaluation will be made based on averaged NOx test data accumulated through December 31, 1982. ~~Subsequent evaluations will be made semiannually for data accumulated through each June 30 and December 31 periods until December 31, 1984 for PC's and December 31, 1985, for LDT's plus MDV's model year productions.~~

If the NOx value exceeds the 0.7 gm/mi level, but the manufacturer shows that unanticipated technical problems caused the 0.7 gm/mi NOx production average to be exceeded, then appropriate relief will be made available. The relief will be made provided the manufacturer shows reasonable effort was made and will continue to be made towards meeting the 0.7 gm/mi NOx levels for future production periods. This includes incorporating into production improved technology as soon as it becomes available.

After the evaluation, the Executive Officer can revoke Section 2109, Title 13 of the G.A.-G. C.C.R., if combined test results exceed the 0.7 gm/mi NOx level separately for 1983 and 1984 model PC's and 1984 and 1985 model LDT's plus MDV's, and on a cumulative basis for 1983 model LDT's plus MDV's provided that the manufacturer has not taken appropriate action.

DEFINITIONS

The definitions in Section 1900 (b), Chapter 3, Title 13 of the California Administrative Code Code of Regulations, shall apply with the following additions:

1. Calendar Quarter is defined as those three month period of time which start on the first days of January, April, July and October.
2. First or Final Calendar Quarter Production is defined as the calendar quarter in which the production of an engine family begins or ends.
3. End of Assembly-Line is defined as that place where the final inspection test or quality-audit test is performed.
4. Assembly-Line Tests are those tests or inspections which are performed on or at the end of the assembly-line.
5. Assembly-Line Quality Audit-Test is defined as the test performed on a minimum sample of 2.0 percent (or other approved sample) of the production vehicles for sale in California.
6. Assembly-Line Inspection Tests are those tests performed pursuant to Sections B or C of these procedures.
7. Functional Test is defined as a type of test or inspection which is performed on engines or vehicles to detect if the emission control system is operating properly.
8. Gross Engine Malfunction is defined as one yielding an emission value greater than the sum of the mean plus three (3) times the standard deviation. This definition shall apply only for determination of control limits.

APPENDIX A

Alternate Quality-Audit Vehicle Selection Criteria

This appendix sets forth the alternative procedure for selection of Quality-Audit vehicles. It includes the flow diagram in Figure A-1.

1. Vehicles shall be randomly selected at a rate of 2.0 percent of engine family production at the beginning of production. When test results of 30 vehicles have been accumulated, an evaluation as indicated below shall be made.
2. Calculate the family mean and standard deviation of each pollutant (HC, CO, NOx). Identify vehicles which have emission levels greater than three standard deviations above the mean. Eliminate these emission data points and recalculate the mean and standard deviation. Continue the calculation until there are no values greater than three standard deviations above the mean. Count the number of these data points greater than the standard (outliers). If the number of outliers is equal to or less than the allowable number in Table A-1 for each pollutant, the engine family is eligible to continue to a second evaluation shown in paragraph 3 below. Otherwise, sampling must continue at a rate of 2.0 percent of production for the rest of the month.
3. If the allowable outlier criteria is met, the family mean, standard deviation, and sample size determined for each contaminant before excluding any outliers, is substituted in the following expression:

$$\frac{(\text{emission standard} - \text{mean}) ((N^{1/2}))}{(\text{standard deviation})}$$

If the expression is greater than C in Table A-2 below, and the manufacturer reasonably estimates that the quarterly engine family production will exceed 5,000 vehicles, the sampling rate for the remaining portion of the calendar month following the date of selection of the last of the 30 vehicles shall be 30 per month, applied on a prorated basis. If the expression is greater than C in Table A-2 below, and the manufacturer reasonably estimates that the quarterly engine family production will be 5,000 vehicles or less, the sampling rate for the remaining portion of the calendar month following the date of selection of the last of the 30 vehicles shall be 17 per month, applied on a prorated basis. If the expression is equal to or less than C in Table A-2, the sampling rate shall continue to be

2.0 percent of production for the remaining portion of the month in which selection of the 30 vehicles is completed. The value of C is a function of the coefficient of variation (standard deviation/mean). The coefficient of variation and "C" shall be rounded to the number of decimal places shown in Table A-2.

Table A-1

Sample Size	Allowable Outliers	Sample size	Allowable Outliers
1- 32	1	430-478	11
33- 68	2	479-528	12
69-107	3	529-578	13
108-149	4	579-629	14
150-193	5	630-680	15
194-238	6	681-731	16
239-285	7	732-783	17
286-332	8	784-835	18
333-380	9	836-887	19
381-429	10	888-939	20

Table A-2

Coefficient of Variation	C
0.1	0.5
0.2	1.2
0.3	1.8
0.4	2.5
0.5	3.1
0.6	3.8
0.7	4.4
0.8	5.1
0.9	5.7

4. For each remaining calendar month in the quarter, both mathematical procedures set forth in paragraph 2 and 3 shall be repeated at the end of the preceding month, using all of the test data accumulated in the quarter. The sampling rate for each remaining calendar month in the quarter shall be 30 vehicles per month, 17 vehicles per month, or 2.0 percent of the production as determined under the standards in paragraph 3.
5. At the end of the quarter, all of the data accumulated during the quarter is evaluated, and the compliance of the family with emission standards is determined.

6. For each subsequent quarter, the preceding sample selection method shall be followed. The sample rate determination for the first month of each subsequent quarter shall be based on the accumulated data from the previous quarter. The sample rate for the succeeding months of the quarter shall be determined as previously set forth.
7. If the start of production does not coincide with the first of a quarter, the sequence for sample rate determination shall be followed, but references to remaining calendar months may not be appropriate.
8. Where a manufacturer has sampled vehicles at a rate of 17 per month following a reasonable estimate that the quarterly engine family production will be 5,000 vehicles or less, and subsequently determines, or reasonably should determine based on information available to the manufacturer, that the quarterly engine family production will exceed 5,000 vehicles, the manufacturer shall increase the sampling rate for the quarter such that the requirements of paragraph 3 applicable to families reasonably estimated to exceed a quarterly production of 5,000 vehicles are satisfied.

FIGURE A-1


FIRST QUARTER OF PROD.

FIGURE A-1

SUBSEQUENT QUARTERS




FIGURE A-1

OUTLIER CALCULATION PROCEDURE

1. CALCULATE THE MEAN AND STANDARD DEVIATION FOR EACH POLLUTANT WITH DF APPLIED.
2. CALCULATE THE MEAN PLUS THREE STANDARD DEVIATIONS.
3. IDENTIFY ALL EMISSION DATA GREATER THAN $\bar{X} + 3\sigma$ STANDARD DEVIATIONS.
4. REMOVE THE OUTLIERS FROM THE DATA AND RECALCULATE THE MEAN AND STANDARD DEVIATION.
5. REPEAT STEPS 2, 3, 8, 4.
6. REPEAT STEPS 2, 8, 3
7. IDENTIFY ALL OUTLIERS THAT EXCEED APPLICABLE CERTIFICATION STANDARD AND COUNT THE NUMBER.
8. COMPARE THE NUMBER OF OUTLIERS WITH THE MAXIMUM ALLOWED BY THE OUTLIER TABLE. IF THE NUMBER OF OUTLIERS EXCEEDS THE MAXIMUM, SAMPLE RATE IS 2.0% OF PRODUCTION. IF THE NUMBER IS LESS THAN THE MAXIMUM ALLOWED, CALCULATE "C".

APPENDIX B

Air/Fuel Control System
Carburetor or Fuel Injection System
Air Injection Pump
Air Injection Control Valves
Positive Crankcase Ventilation
EGR Control System Components
Controlled Air Intake System
Distributor
Ignition Coil & Wires
Ignition Control Module
Electronic (Computer) Control System
On-Board Diagnostic System
Emissions Related Hoses, Tubing, Clamps, Belts, Fittings, Wiring,
Connectors, Sensors and Switches.
Oxygen Sensor
Coolant Temperature Sensor
Catalyst
Diesel Particulate Control System
Exhaust Gas Recirculation
Choke
Air Diverter Valve
Vacuum Hose Connections

PROPOSED

State of California
AIR RESOURCES BOARD

CALIFORNIA EVAPORATIVE EMISSION STANDARDS AND TEST PROCEDURES
FOR 1978 AND SUBSEQUENT MODEL MOTOR VEHICLES

ADOPTED: April 16, 1975
AMENDED: May 14, 1975
AMENDED: March 31, 1976
AMENDED: October 5, 1976
AMENDED: November 23, 1976
AMENDED: June 8, 1977
AMENDED: December 19, 1977
AMENDED: October 12, 1979
AMENDED: April 23, 1980
AMENDED: June 26, 1980
AMENDED: June 8, 1981
AMENDED: March 9, 1983
AMENDED: October 30, 1985
AMENDED: January 22, 1990
AMENDED: May 15, 1990; effective July 15, 1990
AMENDED: November 20, 1991; effective January 16, 1992
AMENDED:

Note: These procedures are printed in a style to indicate the amendments to the standards and test procedures as amended November 20, 1991 effective January 16, 1992. Proposed new text is underlined and proposed deletions are indicated by ~~strikeouts~~.

CALIFORNIA EVAPORATIVE EMISSION STANDARDS AND TEST PROCEDURES
FOR 1978 AND SUBSEQUENT MODEL MOTOR VEHICLES

The provisions of Title 40, Code of Federal Regulations (CFR), Part 86, Subparts A and B, as they pertain to evaporative emission standards and test procedures and as they were amended or adopted as of July 1, 1989 are hereby adopted as the California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles, with the following exceptions and additions:

1. These standards and test procedures are applicable to all new 1978 and subsequent model gasoline-fueled, 1983 and subsequent model liquefied petroleum gas (LPG)-fueled, and 1993 and subsequent model ~~methanol~~ alcohol-fueled passenger cars, light-duty trucks, medium-duty vehicles, heavy-duty vehicles, hybrid electric vehicles, and motorcycles. These standards and test procedures do not apply to motor vehicles which are exempt from exhaust emission certification or petroleum-fueled diesel vehicles or hybrid electric vehicles that have sealed fuel systems which can be demonstrated to have no evaporative emissions.

a. The evaporative emission standards for vehicles subject to these procedures, except motorcycles, are:

<u>Class of Vehicle</u>	<u>Model Year</u>	Hydrocarbons or OMHCE (1)	
		Diurnal + Hot Soak (grams per test) <u>50K miles Useful Life(2)</u>	Running Loss (grams/mile) <u>Useful life(2)</u>
Passenger Car Light-Duty Trucks Medium-Duty Vehicles Heavy-Duty Vehicles	1978 and 1979	6.0	
Passenger Car Light-Duty Trucks Medium-Duty Vehicles Heavy-Duty Vehicles	1980 - 1994	2.0	
Passenger Car Light-Duty Trucks Medium-Duty Vehicles (6,000 - 8,500 lbs. GVWR) (8,501 - 14,000 lbs. GVWR) (4) Heavy-Duty Vehicles (over 14,000 lbs. GVWR)	1995 and subsequent (3)	2.0	0.05

Hybrid Electric Passenger Car 1993 and
Hybrid Electric Light-Duty subsequent (5)
Trucks
Hybrid Electric Medium-Duty
Vehicles

2.0

0.05

- (1) The applicable evaporative emission standards for methane+
alcohol vehicles are expressed as organic material hydrocarbon
equivalent (OMHCE). These evaporative standards are effective in
the 1993 model year.
- (2) For purposes of this paragraph, "useful life" shall have the same
meaning as provided in section 2112, Title 13, California Code of
Regulations. Approval of vehicles which are not exhaust emission
tested using a chassis dynamometer pursuant to section 1960.1,
Title 13, California Code of Regulations shall be based on an
engineering evaluation of the system and data submitted by the
applicant.
- (3) The running loss and useful life diurnal plus hot soak evaporative
emission standards (hereinafter "running loss and useful life
standards") shall be phased in beginning with the 1995 model year.
Each manufacturer, except small volume manufacturers, shall
certify the specified percent of passenger cars and of light-duty
trucks, medium-duty vehicles and heavy-duty vehicles to the
running loss and useful life standards according to the following
schedule:

<u>Model Year</u>	<u>Number of Vehicles Certified to Running Loss and Useful Life Standards*</u>
1995	10 percent
1996	30 percent
1997	50 percent

*. The number of motor vehicles in each vehicle type required
to be certified to the running loss and useful life standards
shall be determined by applying the specified percentage to
the manufacturer's projected California model-year sales of
passenger cars and of light-duty trucks, medium-duty vehicles
and heavy-duty vehicles.

Beginning with the 1998 model year, all motor vehicles subject to
the running loss and useful life standards, including those
produced by small volume manufacturers, shall be certified to the
specified standards.

All 1995 through 1997 model-year motor vehicles which are not
subject to running loss and useful life standards pursuant to the

phase-in schedule shall comply with the 50,000-mile standards in effect for 1980 through 1994 model-year vehicles.

- (4) Compliance with the evaporative emission standards for complete vehicles in this weight range shall be based on the Sealed Housing for Evaporative Determination (SHED) conducted in accordance with the procedures set forth in Title 40, Code of Federal Regulations, sections 86.130-78 through 86.143-90 as they existed July 1, 1989.
- (5) The running loss and useful life diurnal plus hot soak evaporative emission standards (hereinafter "running loss and useful life standards") for all hybrid electric vehicles shall be effective in the 1993 and subsequent model years.

b. Evaporative emission standards for gasoline-fueled motorcycles are:

<u>Motorcycle Class</u>	<u>Model Year</u>	<u>Hydrocarbons (grams per test)</u>
Class I and Class II (50-279 cc)	1983 - 1984	6.0
	1985 and subsequent	2.0
Class III (280 cc and greater)	1984 - 1985	6.0
	1986 and subsequent	2.0
Class III (280cc and greater) (Optional Standard for Small-Volume Manufacturers)	1986 - 1988	6.0

2. The definitions in section 1900, Title 13, California Code of Regulations, and in the applicable model-year California exhaust emission standards and test procedures, are hereby incorporated into this test procedure by reference.
3. Approval of medium-duty vehicles shall be based on the same standards and test procedures as light-duty trucks. In selecting medium-duty test vehicles, the Executive Officer shall consider the availability of test data from comparably equipped light-duty vehicles and the size of medium-duty vehicles as it relates to the practicability of evaporative emission testing.
4. For all motor vehicles subject to these test procedures, except complete medium-duty vehicles 8,501 to 14,000 lbs GVWR (see footnote 4 to Table 1.a. above), heavy-duty vehicles over 14,000 lbs GVWR (see paragraph 5. below) and motorcycles (see paragraphs 7. and 8. below)

Demonstration of system durability and determination of an evaporative emission (diurnal and hot soak) and running loss emission deterioration factor (DF) for each evaporative emission engine family shall be based on tests of representative vehicles and/or systems. For purposes of evaporative emission durability testing, a representative vehicle is

one which, with the possible exception of the engine and drive train, was built at least three months prior to the commencement of evaporative emission testing, or is one which the manufacturer demonstrates has stabilized non-fuel-related evaporative emissions.

- a. For 1978 model evaporative emission engine families which require durability testing for exhaust emissions certification, either
 - i. Evaporative emission testing shall be conducted on all durability vehicles at the 5,000, 10,000, 20,000, 30,000, 40,000, and 50,000 mile test points. Testing may be performed at more frequent intervals with advance written approval from the Executive Officer. The results of all valid evaporative emission tests within each evaporative emission engine family shall be plotted as a function of mileage, and a least-squares-fit straight line shall be drawn through the data. The evaporative emission DF is defined as the interpolated 50,000 mile value on that line minus the interpolated 4,000 mile value on that line, but in no case shall the factor be less than zero. The interpolated 4,000 and 50,000 mile points on this line must be within the standards of paragraph 1. of these test procedures or the data will not be acceptable for use in the calculation of a DF, unless no applicable data point exceeded the standard.

OR

- ii. The manufacturer shall propose in his preliminary application for certification a method for durability testing and for determination of a DF for each evaporative emission engine family. The 4,000 and 50,000 mile test points (or their equivalent) used in determining the DF must be within the standards of paragraph 1. or data will not be acceptable for use in the calculation of a DF. The Executive Officer shall review the method, and shall approve it if it meets the following requirements:
 - A. The method must cycle and test the complete evaporative emission control system for the equivalent of at least 50,000 miles of typical customer use.
 - B. The method must reflect the flow of liquid and gaseous fuel through the evaporative emission control system, and the exposure (both peak and cyclical) to heat, vibration, and ozone expected through 50,000 miles of typical customer use.
 - C. The method must have the specifications for acceptable system performance, including maximum allowable leakage after 50,000 miles of typical customer use.

No evaporative emission control system durability testing shall be required for 1978 model-year vehicles which do not require exhaust emission control system durability testing, unless the Executive Officer determines that durability performance is likely to be significantly inferior to 1977 model-year systems.

- b. For 1979 through 1994 evaporative emission engine families and 1995 and subsequent evaporative emission engine families which are not subject to the running loss and useful life standards specified in paragraph 1. of this test procedure, both paragraphs 4.a.i. and 4.a.ii. shall apply to all families selected for exhaust emission durability testing, and paragraph 4.a.ii. shall apply to those evaporative emission engine families which are not subject to testing for exhaust emission durability. The DFs determined under paragraph 4.a.i., if any, shall be averaged with the DFs determined under paragraph 4.a.ii. to determine a single evaporative emission deterioration factor for each evaporative emission engine family.
- c. Engine families subject to the running loss and useful life standards specified in paragraph 1. of this test procedure shall demonstrate compliance with durability requirements using one of the following:
 - i. Evaporative emission testing shall be conducted on all durability vehicles at 5,000 and 10,000 miles, and at every 10,000 mile test point interval thereafter to the applicable final test point. Testing may be performed at more frequent intervals with advance written approval from the Executive Officer. Compliance with the running loss and evaporative emission standards shall be demonstrated as follows: The results of all valid evaporative emission and running loss emission tests within each evaporative emission engine family shall be plotted as a function of mileage, and a least-squares-fit straight line shall be drawn through the data. The evaporative emission and running loss emission DFs shall be defined as the interpolated value at the applicable useful life mileage on that line, minus the interpolated 4,000 mile value on that line, but in no case shall the factor be less than zero. The interpolated 4,000 and 100,000 mile points (for passenger cars and light-duty trucks), or 4,000 and 120,000 mile points (for medium-duty vehicles and heavy-duty vehicles) on this line must be within the standards of paragraph 1. or the data will not be acceptable for use in the calculation of a DF, unless no applicable data point exceeded the standard.

OR

- ii. At least one evaporative emission test shall be conducted on all passenger car and light-duty truck durability vehicles at 5,000, 40,000, 70,000, and 100,000 mile test points. At

least one evaporative emission test shall be conducted on all medium-duty durability vehicles at 5,000, 40,000, 70,000, 90,000, and 120,000 mile test points. With prior written approval from the Executive Officer, manufacturers may terminate evaporative emissions testing at the mileage corresponding to 75 percent of the vehicle's useful life if no significant vehicle maintenance or emissions change are observed. Testing may be performed at more frequent intervals also with advance written approval from the Executive Officer. Compliance with the running loss and evaporative emission standards shall be demonstrated as follows: The results of all valid evaporative emission tests within each evaporative emission engine family shall be plotted as a function of mileage, and a least-squares-fit straight line shall be drawn through the data. The evaporative emission and running loss emission DFs are defined as the interpolated value at the useful life mileage on that line minus the interpolated 4,000 mile value on that line, but in no case shall the factor be less than zero. The interpolated 4,000 and 100,000 mile points (for passenger cars and light-duty trucks) or 4,000 and 120,000 mile points (for medium-duty vehicles) must be within the standards of paragraph 1. or the data will not be acceptable for use in the calculation of a DF, unless no applicable data point exceeded the standard.

OR

iii. The manufacturer shall propose in its preliminary application for certification a method for durability testing and for determination of evaporative emission and running loss emission DFs for each evaporative emission engine family. The 4,000, and 100,000 or 120,000 "useful life" mile test points (or their equivalent) used in determining a DF must be within the standards of paragraph 1. or data will not be acceptable for use in the calculation of a DF. The Executive Officer shall review the method, and shall approve it if it meets the following requirements:

- A. The method must cycle and test the complete evaporative emission control system for the equivalent of the applicable vehicle useful life (i.e., 100,000 or 120,000 miles) of typical customer use.
- B. The method must reflect the flow of liquid and gaseous fuel through the evaporative emission control system, and the exposure (both peak and cyclical) to heat, vibration, and ozone expected based on typical customer use through the applicable useful life.
- C. The method must have the specifications for acceptable system performance, including maximum allowable leakage

based on typical customer use through the applicable vehicle useful life.

For 1995 and subsequent model evaporative emission engine families subject to the running loss and useful life evaporative emission standards specified in paragraph 1. of this test procedure, except hybrid electric vehicles, either paragraphs 4.c.i and 4.c.iii., or paragraphs 4.c.ii. and 4.c.iii. shall apply to all families selected for exhaust emission durability testing, and paragraph 4.c.iii. shall apply to those evaporative emission engine families which are not subject to testing for exhaust emission durability. For all 1993 and subsequent model hybrid electric vehicles subject to the running loss and useful life evaporative emission standards specified in paragraph 1. of this test procedure, paragraphs 4.c.i. and 4.c.iii. shall apply to all families selected for exhaust emission durability testing, and paragraph 4.c.iii. shall apply to those evaporative emission engine families which are not subject to testing for exhaust emission durability. The DFs determined under paragraph 4.c.i. or 4.c.ii., if any, shall be averaged with the DFs determined under paragraph 4.c.iii. to determine a single evaporative emission deterioration factor for each evaporative emission engine family.

d. Instrumentation

The instrumentation necessary to perform evaporative emission testing is described in 40 CFR 86.107-90. For 1993 and subsequent model hybrid electric vehicles and 1995 and subsequent model motor vehicles subject to running loss and useful life evaporative emission standards, the following language is applicable in lieu of §86.107-90(a)(1):

i. Diurnal Evaporative Emissions Measurement Enclosure

- A. The diurnal evaporative emissions measurement enclosure shall be equipped with an internal blower or blowers coupled with an air temperature management system (typically air to water heat exchangers and associated programmable temperature controls) to provide for air mixing and temperature control. The blower(s) shall be sized to provide a nominal total flow rate within a range of 0.3 to 0.6 ft³/min per ft³ of the nominal SHED volume (V₀). The inlets and outlets of the air circulation blower(s) shall be configured to provide a well dispersed air circulation pattern that produces effective internal mixing and avoids significant temperature or hydrocarbon stratification. The discharge and intake air diffusers in the enclosure shall be configured and adjusted to eliminate localized high air velocities which could produce non-representative heat transfer rates between the vehicle fuel tank(s) and the air in the enclosure. The

enclosure temperature shall be taken with thermocouples located 3 feet above the floor of the approximate mid-length of each side wall of the enclosure and within 3 to 12 inches of each side wall. The temperature conditioning system shall be capable of controlling the internal enclosure air temperature to follow the prescribed temperature versus time cycle as specified in 40 CFR 86.133-90 within an instantaneous tolerance of $\pm 3.0^{\circ}\text{F}$ of the nominal temperature versus time profile throughout the test, and an average tolerance of $\pm 2.0^{\circ}\text{F}$ over the duration of the test. The control system shall be tuned to provide a smooth temperature pattern which has a minimum of overshoot, hunting, and instability about the desired long term temperature profile.

- B. The variable volume SHED enclosure shall be of sufficient size to contain the test vehicle with personnel access space. It shall use materials on its interior surfaces which do not adsorb or desorb hydrocarbons or methanol or ethanol (if the enclosure is used for ~~methanol~~ alcohol-fueled vehicles). The enclosure shall be insulated to enable the test temperature profile to be achieved with a heating/cooling system which has maximum surface temperatures in the enclosure no greater than 25.0°F above the maximum diurnal temperature specification, and minimum surface temperatures in the enclosure no less than 25.0°F below the minimum diurnal temperature specification. The enclosure shall be equipped with a pressure transducer with an accuracy and precision of ± 0.1 inches H_2O . The enclosure shall be constructed with a minimum number of seams and joints which provide potential leakage paths. Particular attention shall be given to sealing and gasketing of such seams and joints to prevent leakage.
- C. The variable volume SHED enclosure shall be equipped with features which provide for the effective SHED volume to expand and contract in response to both the temperature changes of the air mass in the SHED enclosure, and any fluctuations in the ambient barometric pressure during the duration of the test. The enclosure shall have the capability of latching or otherwise constraining the enclosed volume to a known, fixed value which shall be termed the nominal SHED volume (V_n). The nominal SHED volume shall be determined by measuring all pertinent dimensions of the enclosure in its latched configuration, including internal fixtures, to an accuracy of $\pm 1/8$ inch (0.5 cm) and calculating the net enclosure nominal volume to the nearest 1 ft^3 . The latching system shall provide a fixed volume with an accuracy and repeatability of

0.005xV. Two potential means of providing the volume accommodation capabilities are a moveable ceiling which is joined to the enclosure walls with a flexure; or a flexible bag or bags of Tedlar or other suitable materials which are installed in the SHED enclosure and provided with flowpaths which communicate with the ambient air outside the enclosure. By moving air into and out of the bag(s), the contained volume can be adjusted dynamically. The total enclosure volume accommodation shall be sufficient to balance the volume changes produced by the difference between the extreme enclosure temperatures and the ambient laboratory temperature with the addition of a superimposed barometric pressure change of 0.8 in. Hg. A minimum total volume accommodation range of $\pm 0.07xV$ shall be used. The action of the enclosure volume accommodation system shall limit the differential between the enclosure internal pressure and the external ambient barometric pressure to a maximum value of ± 2.0 inches H_2O .

D. An online computer system or stripchart recorder shall be used to record the following parameters during the diurnal evaporative emissions test sequence:

- SHED enclosure internal air temperature
- Diurnal ambient air temperature specified profile as defined in §86.133-90
- Vehicle fuel tank liquid temperature
- SHED enclosure internal pressure
- SHED enclosure temperature control system surface temperature(s)
- FID output voltage recording the following parameters for each sample analysis:
 - zero gas and span gas adjustments
 - zero gas reading
 - SHED sample reading
 - zero gas and span gas readings

The data recording system shall have a time resolution of 30 seconds and shall provide a permanent record in either magnetic, electronic or paper media of the above parameters for the duration of the test.

Other equipment configurations may be used if approved in advance by the Executive Officer. The Executive Officer shall approve alternative equipment configurations if the manufacturer demonstrates that the equipment will yield test results equivalent to those resulting from use of the specified equipment.

ii. Running Loss Measurement Facility

A. For all types of running loss measurement test facilities, the following shall apply:

- I. The measurement of vehicle running loss fuel vapor emissions shall be conducted in a test facility which is maintained at a nominal ambient temperature of 105.0°F. Manufacturers have the option to perform running loss testing in either an enclosure incorporating atmospheric sampling equipment, or in a cell utilizing point source sampling equipment. Confirmatory testing or in-use compliance testing may be conducted by the Executive Officer using either sampling procedure. The test facility shall have space for personnel access to all sides of the vehicle and shall be equipped with the following test equipment:

-A chassis dynamometer which meets the requirements of 40 CFR 86.108-79.

-A fuel tank temperature management system which meets the requirements specified in ii.A.III. of this paragraph.

-A running loss fuel vapor hydrocarbon analyzer which meets the requirements specified in §86.107-90(a)(2).

-A running loss test data recording system which meets the requirements specified in ii.A.IV. of this paragraph.

- II. All types of running loss test facilities shall be configured to provide an internal ambient temperature of 105°F ± 5°F maximum and ± 2°F on average throughout the running loss test sequence. This shall be accomplished by any one or combination of the following techniques:

-Using the test facility without artificial cooling and relying on the residual heat in the test vehicle for temperature achievement.

- Adding insulation to the test facility walls.
- Using the test facility artificial cooling system (if so equipped) with the setpoint of the cooling system adjusted to a value not lower than 105.0°F, where the cooling system setpoint refers to the internal test facility air temperature.
- Using a full range test facility temperature management system with heating and cooling capabilities.

III. Cell/enclosure temperature management shall be conducted at the inlet of the vehicle cooling fan. The vehicle cooling fan shall be a road speed modulated fan which is controlled to a discharge velocity which matches the dynamometer roll speed throughout the driving cycle. The fan outlet shall airflow discharge to both the vehicle radiator air inlet(s) and the vehicle underbody.

The fuel tank temperature management system shall be configured and operated to control the fuel tank temperature profile of the test vehicle during the running loss test sequence. The use of a discrete fuel tank temperature management system is not required provided that the existing temperature and airflow conditions in the test facility are sufficient to match the on-road fuel tank liquid (T_{liq}) temperature profile of the test vehicle within a tolerance of $\pm 3.0^\circ\text{F}$ throughout the running loss driving cycle, and the fuel tank vapor (T_{vap}) temperature profile of the test vehicle within a tolerance of $\pm 3.0^\circ\text{F}$ during the final 120 second idle period of the test. The system shall provide a ducted air flow directed at the vehicle fuel tank which can be adjusted in flow rate and/or temperature of the discharge air to manage the fuel tank temperature. The system shall monitor the vehicle fuel tank temperature sensors located in the tank according to the specifications in paragraph 4.f. (§86.129-80(d)(1)) during the running loss drive cycle. The measured temperature shall be compared to a reference on-road profile for the same platform/ powertrain/fuel tank combination developed according to the procedures in §86.129-80(c). The system shall adjust the discharge flow and/or temperature of the outlet duct to maintain the tank liquid temperature profile within $\pm 3.0^\circ\text{F}$ of the reference on-road profile throughout the test. Additionally, the

vapor temperature during the final 120 second idle period shall match the reference on-road vapor temperature within $\pm 3.0^{\circ}\text{F}$. The system shall provide a discharge airflow not to exceed 6000 cfm. The temperature of the air supplied to the outlet duct shall be within a range of 70°F to 160°F for systems which utilize artificial heating and/or cooling of the air supply to the outlet duct. This requirement does not apply to systems which recirculate air from inside the test cell without temperature conditioning the airflow. The control system shall be tuned and operated to provide a smooth and continuous fuel tank temperature profile which is representative of the on-road temperature profile.

IV. An on-line computer system or strip-chart recorder shall be used to record the following parameters during the running loss test sequence:

- Cell/enclosure ambient temperature
- Vehicle fuel tank liquid (T_{liq}) and vapor space (T_{vap}) temperatures
- Vehicle coolant temperature
- Vehicle fuel tank headspace pressure
- Reference on-road fuel tank temperature profile developed according to paragraph 4.f. (§86.129-80(d))
- Dynamometer rear roll speed
- FID output voltage recording the following parameters for each sample analysis:
 - zero gas and span gas adjustments
 - zero gas reading
 - dilute sample bag reading
 - dilution air sample bag reading
 - zero gas and span gas readings

B. If an enclosure, or atmospheric sampling, running loss facility is used, the following requirements (in addition to those in subparagraph A. above) shall also be applicable:

- I. The enclosure shall be readily sealable and rectangular in shape. When sealed, the enclosure shall be gas tight in accordance with 40 CFR 86.117-90. Interior surfaces shall be impermeable and non-reactive to hydrocarbons and to methanol or ethanol (if the enclosure is used for methane+ alcohol-fueled vehicles). One surface should be of flexible, impermeable, and non-reactive material to allow for minor volume changes, resulting from temperature changes.
 - II. In the event an artificial cooling or heating system is used, the surface temperature of the heat exchanging elements shall be within a range of 70.0°F to 125.0°F.
- C. If a point source running loss measurement facility (cell) is used, the following requirements (in addition to those in subparagraph A. above) shall also be applicable:
- I. The running loss vapor vent collection system shall be configured to collect all running loss emissions from each of the discrete point sources which function as vehicle fuel system vapor vents, and transport the collected vapor emissions to a CFV or PDP based dilution and measurement system. The collection system shall consist of a collector at each vehicle vapor vent, lengths of heated sample line connecting each collector to the inlet of the heated sample pump, and lengths of heated sample line connecting the outlet of the heated sample pump to the inlet of the running loss fuel vapor sampling system. Up to 3 feet of unheated line connecting each of the vapor collectors to the heated sample lines shall be allowed. Each heated sample pump and its associated sample lines shall be maintained at a temperature between 175.0°F and 200.0°F to prevent condensation of fuel vapor in the sample lines. The heated sample pump(s) and its associated flow controls shall be configured and operated to draw a flow of ambient air into each collector at a flow rate of at least 40 standard cubic feet per hour (SCFH). The flow controls on each heated sampling system shall include an indicating flow meter which provides an alarm output to the data recording system if the flow rate drops below 40 SCFH by more than 5 percent. The collector inlet for each discrete vapor vent shall be placed in proximity to the vent as necessary to capture any fuel vapor emissions without significantly affecting flow or pressure of

the normal action of the vent. The collector inlets shall be designed to interface with the configuration and orientation of each specific vapor vent. For vapor vents which terminate in a tube or hose barb, a short length of tubing of an inside diameter larger throughout its length than the inside diameter of the vent outlet, may be used to extend the vent into the mouth of the collector as illustrated in Figure 21. For those vapor vent designs which are not compatible with such collector configurations, the vehicle manufacturer shall supply a collector which is configured to interface with the vapor vent design, and which terminates in a fitting approved by the Executive Officer. The Executive Officer shall approve the fitting if the manufacturer demonstrates that it is capable of capturing all vapor emitted from the vent.

- II. The running loss fuel vapor sampling system shall be a CFV or PDP based dilution and measurement system which further dilutes the running loss fuel vapors collected by the vapor vent collection system(s) with ambient air, collects continuously proportional samples of the diluted running loss vapors and dilution air in sample bags, and ~~measures the total dilute flow through the sampling~~ system over each test interval. In practice, the system shall be configured and operated in a manner which is directly analogous to an exhaust emissions constant volume sampling system, except that the input flow to the system is the flow from the running loss vapor vent collection system(s) instead of vehicle exhaust flow. The system shall be configured and operated to meet the following requirements:

- (1) The running loss fuel vapor sampling system shall be designed to measure the true mass of fuel vapor emissions collected by the running loss vapor vent collection system from the specified fuel vapor vents. The total volume of the mixture of running loss emissions and dilution air shall be measured, and a continuously proportioned sample of volume shall be collected for analysis. Mass emissions shall be determined from the sample concentration and total flow over the test period.
- (2) The PDP-CVS shall consist of a dilution air filter and mixing assembly, heat exchanger,

positive displacement pump, sampling system, and associated valves, pressure and temperature sensors. The PDP-CVS shall conform to the following requirements:

The gas mixture temperature, measured at a point immediately ahead of the positive displacement pump, shall be within $\pm 10^{\circ}\text{F}$ of the designed operating temperature at the start of the test. The gas mixture temperature variation from its value at the start of the test shall be limited to $\pm 10^{\circ}\text{F}$ during the entire test. The temperature measuring system shall have an accuracy and precision of $\pm 2^{\circ}\text{F}$.

The pressure gauges shall have an accuracy and precision of ± 1.6 inches of water (± 0.4 kPa).

The flow capacity of the CVS shall not exceed 350 CFM ($0.165 \text{ m}^3/\text{s}$).

Sample collection bags for dilution air and running loss fuel vapor samples shall be sufficient size so as not to impede sample flow.

- (3) The CFV sample system shall consist of a dilution air filter and mixing assembly, a sampling venturi, a critical flow venturi, a sampling system and assorted valves, and pressure and temperature sensors. The CFV sample system shall conform to the following requirements:

-The temperature measuring system shall have an accuracy and precision of $\pm 2^{\circ}\text{F}$ and a response time of 0.100 seconds of 62.5 percent of a temperature change (as measured in hot silicone oil).

-The pressure measuring system shall have an accuracy and precision of ± 1.6 inches of water (0.4 kPa).

-The flow capacity of the CVS shall not exceed 350 CFM ($0.165 \text{ m}^3/\text{s}$).

-Sample collection bags for dilution air and running loss fuel vapor samples shall be of sufficient size so as not to impede sample flow.

III. The on-line computer system or strip-chart recorder specified in ii.A.IV. of this paragraph shall be used to record the following additional parameters during the running loss test sequence:

- CFV (if used) inlet temperature and pressure
- PDP (if used) inlet temperature and pressure and differential pressure
- Running loss vapor vent collection system low flow alarm(s)

Other equipment configurations may be used if approved in advance by the Executive Officer. The Executive Officer shall approve alternate equipment configurations if the manufacturer demonstrates that the equipment will yield test results equivalent to those resulting from use of the specified equipment.

iii. Hot Soak Evaporative Emissions Measurement Enclosure

The enclosure shall be readily sealable, rectangular in shape, with space for personnel access to all sides of the vehicle. When sealed, the enclosure shall be gas tight in accordance with §86.117-90. Interior surfaces shall be ~~impermeable and non-reactive to hydrocarbon and to methanol or ethanol~~ (if the enclosure is used for methanol alcohol-fueled vehicles). One surface shall be of flexible, impermeable and non-reactive material to allow for minor volume changes, resulting from temperature changes. The enclosure shall be configured to provide an internal enclosure ambient temperature of $105^{\circ}\text{F} \pm 5^{\circ}\text{F}$ maximum and $\pm 2^{\circ}\text{F}$ on average during the test time interval from 5 minutes after the enclosure is closed and sealed until the end of the one hour hot soak interval. The enclosure temperature shall be taken with thermocouples located 3 feet above the floor of the approximate mid-length of each side wall of the enclosure and within 3 to 12 inches of each side wall. This shall be accomplished by any one or combination of the following techniques:

- Using the enclosure without artificial cooling and relying on the residual heat in the test vehicle for temperature achievement.
- Adding insulation to the enclosure walls.
- Using the enclosure artificial cooling system (if so equipped) with the setpoint of the cooling system adjusted to a value not lower than 105.0°F , where the

cooling system setpoint refers to the internal enclosure air temperature.

-Using a full range enclosure temperature management system with heating and cooling capabilities.

In the event an artificial cooling or heating system is used, the surface temperature of the heat exchanging elements shall be within a range of 70.0°F to 125.0°F.

For 1995 through 1997 vehicles subject to running loss and useful life evaporative emission standards, and 1998 and subsequent motor vehicles, except petroleum-fueled diesel vehicles, electric vehicles, and motorcycles, omit §86.107-90(a)(4).

e. Calibrations

Evaporative emission enclosure calibrations are specified in 40 CFR 86.117-90. For all 1993 and subsequent model hybrid electric vehicles and 1995 and subsequent model motor vehicles subject to running loss and useful life evaporative emission standards, section 86.117-90 is amended to include an additional subsection (which shall be cited herein as subsection (e) of §86.117-90), to read:

- (e)(1) Diurnal evaporative emission enclosure. The diurnal evaporative emission measurement enclosure calibration consists of the following parts: initial and periodic determination of enclosure background emissions, initial determination of enclosure volume, and periodic hydrocarbon retention check and calibration.
 - (i) The initial and periodic determination of enclosure background emissions shall be conducted according to the procedures specified in §86.117-90(a)(1) through (a)(6). The SHED enclosure shall be maintained at a nominal temperature of 105.0°F throughout the four hour period. Variable volume SHED enclosures may be operated in either the latched volume configuration, or with the variable volume feature active. The allowable enclosure background emissions as calculated according to §86.117-90(a)(7) shall not be greater than 0.05 grams in 4 hours. The enclosure may be sealed and the mixing fan operated for a period of up to 12 hours before the initial HC concentration reading (C_{HCi}) is taken and the four hour background measurement period begins.
 - (ii) The initial determination of enclosure internal volume shall be performed according to the procedures specified in §86.117-90(b)(1) through (b)(3).

(iii) The hydrocarbon measurement and retention check shall evaluate the accuracy of enclosure HC mass measurements and the ability of the enclosure to retain trapped HC. The check shall be conducted over a 24 hour period with all of the normally functioning subsystems of the enclosure active. A known mass of propane shall be injected into the SHED enclosure and an initial SHED enclosure mass measurement shall be made. The enclosure shall be subjected to the temperature cycling specified in paragraph g.x.G. of these procedures (revising §86.133-90(1)) for a 24 hour period. A final SHED enclosure mass measurement shall be made. The following procedure shall be performed prior to the introduction of the enclosure into service, following any modifications or repairs to the enclosure that may impact the integrity of this enclosure, and on at least a quarterly basis otherwise:

- (A) Zero and span the hydrocarbon analyzer.
- (B) Purge the enclosure until a stable enclosure HC level is attained.
- (C) Turn on the enclosure air mixing and temperature control system and adjust it for an initial temperature of 105.0°F and a programmed temperature profile covering one cycle from 65.0°F to 105.0°F over a 24 hour period according to the profile specified in §86.133-90. Close the enclosure door. On variable volume SHED enclosures, latch the enclosure to the nominal volume position.
- (D) When the enclosure temperature stabilizes at 105.0°F $\pm$ 3.0°F seal the enclosure; measure the enclosure background HC concentration (C_{HCE1}) and the temperature (T_i) and pressure (P_i) in the enclosure.
- (E) Inject into the enclosure a known quantity of propane of between 4 to 8 grams. The injection method shall use a critical flow orifice to meter the propane at a measured temperature and pressure for a measured time period. Techniques which provide equivalent resolution ($\pm$ 0.2 percent) of the injected mass are also acceptable. Allow the enclosure internal HC concentration to mix and stabilize for up to 300 seconds. Measure the enclosure HC concentration after mixing (C_{HCE2}). On variable volume SHED enclosures, unlatch the enclosure from the nominal volume configuration to accommodate temperature and barometric pressure changes. Start the temperature cycling function of the enclosure air mixing and temperature control system. These steps shall be completed within 900 seconds of sealing the enclosure.

- (F) Calculate the initial recovered HC mass (M_{HCE1}) according to the following formula:

$$M_{HCE1} = (3.05 \times V_n \times 10^{-4} \times P_i \times (C_{HCE2} - C_{HCE1}))/T_i$$

where:

V_n is the enclosure nominal volume (ft^3)

P_i is the enclosure initial pressure (inches Hg absolute)

C_{HCEn} is the enclosure HC concentration at event n (ppm C)

T_i is the enclosure initial temperature ($^{\circ}R$)

If the recovered mass agrees with the injected mass within 2.0 percent, continue the test for the 24 hour temperature cycling period. If the recovered mass differs from the injected mass by greater than 2.0 percent, repeat the enclosure concentration measurement in step (E) and recalculate the initial recovered mass (M_{HCE1}). If the recovered mass based on the latest concentration measurement agrees within 2.0 percent of the injected mass, continue the test for the 24 hour temperature cycling period and substitute this second enclosure concentration measurement for C_{HCE2} in all subsequent calculations. In order to be a valid calibration, the final measurement of C_{HCE2} shall be completed within the 900 second time limit outlined above. If the discrepancy persists, the test shall be terminated and the cause of the difference determined, followed by the correction of the problems(s) and the restart of the test.

- (G) At the completion of the 24 hour temperature cycling period measure the final enclosure HC concentration (C_{HCE3}). Calculate the final recovered HC mass (M_{HCE2}) as follows:

$$M_{HCE2} = [3.05 \times V_n \times 10^{-4} \times P_i \times (C_{HCE3} - C_{HCE1})]/T_i$$

where:

V_n is the enclosure nominal volume (ft^3)

P_i is the enclosure initial pressure (inches Hg absolute)

C_{HCE3} is the enclosure HC concentration at the end of the 24 hour time period (ppm C)

T_i is the enclosure initial temperature ($^{\circ}R$)

- (H) If the calculated final recovered HC mass for variable volume SHED enclosures is not within 3 percent of the

initial enclosure mass, then action shall be required to correct the error to the acceptable level.

(e)(2) The running loss equipment shall be calibrated as follows:

- (i) The chassis dynamometer shall be calibrated according to the requirements of 40 CFR 86.118-78. The calibration shall be conducted at a typical ambient temperature of $75^{\circ}\text{F} \pm 5^{\circ}\text{F}$.
- (ii) The running loss hydrocarbon analyzer shall be calibrated according to the requirements of 40 CFR 86.121-90.
- (iii) If a point source facility is used, the running loss fuel vapor sampling system shall be calibrated according to the requirements of 40 CFR 86.119-90, with the additional requirement that the CVS System Verification at 40 CFR 86.119-90(c) be conducted by injecting the known quantity of propane into the inlet of the most frequently used fuel vapor vent collector configured to collect vapors from the vent of the evaporative emission vapor storage canister. This procedure shall be conducted in the running loss test cell with the collector installed in a vehicle in the normal test configuration, except that the vent hose from the vehicle evaporative emission canister shall be routed to a ventilation outlet to avoid unrepresentative background HC concentration levels. The propane injection shall be conducted by injecting approximately 4 grams of propane into the collector while the vehicle is operated over one Urban Dynamometer Driving Schedule (UDDS) test procedure, as described in 40 CFR 86.115-78 and Appendix I. The propane injection shall be conducted at a typical ambient temperature of $75^{\circ}\text{F} \pm 5^{\circ}\text{F}$. In this manner, the ability of the running loss vapor collection system to effectively capture and measure a representative quantity of HC vapor under realistic test conditions will be verified. In the event the running loss test is conducted using the SHED enclosure measurement technique, a propane injection recovery test shall be conducted, with a test vehicle being driven over one UDDS cycle in the enclosure during the propane injection test. The vehicle used shall be configured and operated under conditions which ensure that its own running loss contribution is negligible, by using fuel of the lowest available volatility (7.0 psi RVP), maintaining the tank temperature at low levels ($<100^{\circ}\text{F}$), and routing the canister vent to the outside of the SHED enclosure.
- (iv) Diurnal and hot soak enclosure hydrocarbon analyzer. The hydrocarbon analyzers used for measuring the diurnal and hot soak samples shall be calibrated according to the requirements of §86.121-90.

- (v) Other equipment. Other test equipment including temperature and pressure sensors and the associated amplifiers and recorders, flow measurement devices, and other instruments shall be calibrated and operated according to the manufacturer's specifications and recommendations, and good engineering practice.
- f. Road Load Power, Test Weight, Inertia Weight Class, and Running Loss Fuel Tank Temperature Profile Determination

For all 1993 and subsequent model hybrid electric vehicles and 1995 and subsequent model motor vehicles subject to running loss and useful life evaporative emission standards, §86.129-80 is amended to include an additional subsection (which shall be cited herein as subsection (d) of §86.129-80), to read:

- (d) Determination of running loss test fuel tank temperature profile

The manufacturer shall establish for each combination of vehicle platform/powertrain/fuel tank submitted for certification a representative profile of fuel tank liquid and vapor temperature versus time to be used as the target temperature profile for the running loss evaporative emissions test drive cycle. The profile shall be established by driving the vehicle on-road over the same driving schedule as is used for the running loss evaporative emissions test according to the following sequence:

- (1) The vehicle to be used for the fuel tank temperature profile determination shall be equipped with at least 2 thermocouples installed so as to provide a representative bulk liquid average fuel temperature. The specific placement of the thermocouples shall take into account the tank configuration and orientation and shall be along the major axis of the tank. The thermocouples shall not be placed within internal reservoirs or other locations which are thermally isolated from the bulk volume of the fuel. The thermocouples shall be placed at a vertical depth equivalent to the mid-volume of the liquid fuel at a fill level of 40 percent of nominal tank capacity. A third thermocouple shall be installed in the approximate center of the vapor space of the fuel tank. A pressure transducer with a minimum precision and accuracy of ± 1.0 inches H₂O shall be connected to the vapor space of the fuel tank. A means of conveniently draining the fuel tank shall be provided. The vehicle shall be equipped with a driver's aid which shall be configured to provide the test driver with the desired UDDS vehicle speed versus time trace as defined in Part 86, Appendix I, and the actual vehicle speed. Vehicle coolant temperature shall be monitored to ensure adequate vehicle coolant air to the

radiator intake(s). A computer, data logger, or strip chart data recorder shall record the following parameters during the test run:

- Desired speed
- Actual speed
- Average liquid fuel temperature (T_{liq})
- Vapor space temperature (T_{vap})
- Vapor space pressure

The data recording system shall provide a time resolution of 1 second, and an accuracy of ± 1 MPH, $\pm 2.0^{\circ}\text{F}$, and ± 1.0 inches H_2O . The temperature and pressure signals may be recorded at intervals of up to 30 seconds.

- (2) The temperature profile determination shall be conducted during ambient conditions which include:
- ambient temperature above 95°F and increasing or stable ($\pm 2^{\circ}\text{F}$)
 - sunny or mostly sunny with a maximum cloud cover of 25 percent
 - wind conditions calm to light with maximum sustained wind speed of 15 MPH
 - road surface temperature at least 20°F above ambient

The track temperature shall be measured with an embedded sensor, a portable temperature probe, or an infrared pyrometer which can provide an accuracy of $\pm 2.0^{\circ}\text{F}$. The test shall be conducted on a track or other restricted access facility so that the speed versus time schedule can be maintained without undue safety risks.

Tank pressure shall not exceed 10 inches of water at any time during the temperature profile determination unless a pressurized system is used and the manufacturer demonstrates that vapor would not be vented to the atmosphere if the fuel cap was removed at the end of the running loss fuel tank temperature profile determination.

- (3) The vehicle fuel tank shall be drained and filled to 40 percent of the nominal tank capacity with fuel meeting the requirements of paragraph 4.i. of these procedures. The vehicle shall be moved to the location where the driving cycle is to be conducted. It may be driven a maximum

distance of 5.0 miles, longer distances shall require that the vehicle be transported by other means. The vehicle shall be parked for a minimum of 12 hours in an open area on a surface that is representative of the test road. The orientation of the front of the vehicle during parking (N, SW, etc.) shall be documented. Once the 12 hour minimum parking time has been achieved and the ambient temperature and weather conditions and track surface temperature are within the allowable ranges the vehicle engine shall be started. The vehicle air conditioning system (if so equipped) shall be set to the "NORMAL" air conditioning mode and adjusted to the minimum discharge air temperature and high fan speed. Vehicles equipped with automatic temperature controlled air conditioning systems shall be operated in "AUTOMATIC" temperature and fan modes with the system set at 72°F. The vehicle may be operated at minimum throttle for periods up to 60 seconds prior to beginning the first UDDS cycle in order to move from the parking location onto the road surface. The driver's aid shall be started and the vehicle operated over three sequential UDDS cycles with the transmission operated in the same manner as specified in 40 CFR 86.128-79. The end of each UDDS cycle shall be followed by an idle period of 120 seconds during which the engine shall remain on with the vehicle in the same transmission range and clutch (if so equipped) actuation mode as during the UDDS idle periods. The data recording system shall provide a record of the required parameters over the entire sequence from the initiation of the first UDDS cycle to the end of the third 120 second idle period. Following the completion of the test, the data recording system and driver's aid shall be turned off.

- (4) In addition to the vehicle data recording, the following parameters shall be documented for the running loss test fuel tank temperature determination:

- Date and time of vehicle fueling
- Odometer reading at vehicle fueling
- Date and time vehicle was parked and parking location and orientation
- Odometer reading at parking
- Date and time engine was started
- Time of initiation of first UDDS cycle
- Time of completion of third 120 second idle period

-Ambient temperature and track surface temperature at initiation of first UDDS cycle (T_{amb1} and T_{sur1})

-Ambient temperature and track surface temperature at completion of third 120 second idle period (T_{amb2} and T_{sur2})

- (5) The three UDDS cycle driving traces shall be verified to meet the speed tolerance requirements of 40 CFR 86.115-78 (b). The following temperature conditions shall be verified:

$$(T_{amb1}) \geq 95.0^{\circ}\text{F}$$

$$(T_{amb2}) \geq (T_{amb1} - 2.0^{\circ}\text{F})$$

$$(T_{sur1} - T_{amb1}) \geq 20.0^{\circ}\text{F}$$

$$(T_{sur2} - T_{amb2}) \geq 20.0^{\circ}\text{F}$$

Failure to comply with any of these requirements shall result in a void test, and require that the entire test procedure be repeated beginning with the fuel drain specified in (d)(3) of this subparagraph. If all of these requirements are met, the following calculations shall be performed:

$$T_{corr} = 105.0 - [(T_{amb1} + T_{amb2})/2]$$

The individual tank liquid (T_{liq}) and vapor space (T_{vap}) temperatures recorded during the test run shall be adjusted by arithmetically adding the temperature correction (T_{corr}) adjustment calculated above to each liquid and vapor temperature data point. This step may be omitted if the calculated absolute value of T_{corr} is less than 2.0°F . Other methodologies for developing corrected liquid and vapor space temperature profiles are acceptable if approved in advance by the Executive Officer. The Executive Officer shall approve an alternate method if the manufacturer demonstrates equivalence to data collected at 105°F .

g. Test Procedure

For all 1993 and subsequent model hybrid electric vehicles and 1995 and subsequent model motor vehicles subject to running loss and useful life evaporative emission standards, the exhaust emission test sequence described in 40 CFR 86.130 through 86.140 shall be performed with the following modifications:

i. General Requirements.

The following language shall be applicable in lieu of §86.130-78:

The test sequence shown in Figure 12 (Figure 3 for hybrid electric vehicles) describes the steps encountered as the vehicle undergoes the procedures to determine conformity with the standards set forth. During the exhaust portion of the test procedure, i.e., from "START" to the completion of the "HOT START EXHAUST TEST," ambient temperature levels encountered by the test vehicle shall not be less than 68°F nor more than 86°F. The temperatures monitored during testing shall be representative of those experienced by the test vehicle. The test vehicle shall be approximately level during all phases of the test sequence to prevent abnormal fuel distribution. The test sequence shown in Figure 12 (and Figure 3 for hybrid electric vehicles) is briefly described as follows:

- A. The fuel tank shall be drained and filled to the prescribed tank fuel volume, as specified in 40 CFR 86.082-2, in preparation for the vehicle preconditioning.
- B. The vehicle preconditioning shall be performed in accordance with 40 CFR 86.132-90, except that following the vehicle fueling step at §86.132-90(a)(1) a soak period of 12 to 36 hours shall be provided to allow the vehicle to stabilize to ambient temperature prior to the preconditioning drive. For hybrid electric vehicles only, the manufacturer may elect to perform the All-Electric Range Test pursuant to §9.f. of the "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in §1960.1(k) of Title 13, CCR prior to vehicle preconditioning.
- C. Following the vehicle preconditioning drive, the fuel tank shall be drained and then filled to 40 percent capacity.
- D. The vehicle shall be allowed to soak for 12 to 36 hours prior to the exhaust emissions test.
- E. During the 12 to 36 hour soak specified in subparagraph D. above, the vehicle's canister shall be purged with a volume of air equivalent to 300 canister charcoal bed volumes at a flow rate of 48 SCFH (22.7 slpm). For hybrid electric vehicles, the battery pack shall be discharged to or just below the state-of-charge at which operation of the auxiliary power unit will be initiated by the vehicle's control strategy.

- F. The canister shall then be loaded to saturation using a butane-nitrogen mixture.
- G. Perform exhaust emission tests in accordance with procedures as provided in section 1960.1(k)(i), Title 13, California Code of Regulations, and these procedures.
- H. Upon completion of the hot start test, the vehicle shall be parked in a temperature controlled area to stabilize the fuel temperature at 105°F. Artificial cooling or heating of the fuel tank may be induced if a one hour soak is not sufficient to achieve a fuel temperature of 105°F. The initial fuel temperature for the running loss test may be less than 105°F if the manufacturer is able to provide data demonstrating that a lower initial temperature reflects the maximum fuel temperature achieved by a stabilized vehicle during a 105°F day.
- I. A running loss test shall be performed after the fuel tank is stabilized at 105°F. The fuel tank temperature shall be controlled using a specified tank temperature profile for that vehicle during the test. The temperature profile shall be achieved either using temperature controllers or by an air management system that would simulate airflow conditions under the vehicle during driving.
-
- J. The hot soak enclosure test shall then be performed at a SHED ambient temperature of 105°F.
- K. Upon completion of the hot soak enclosure test, fuel temperature shall be heated or cooled to a temperature of 65°F.
- L. A 72-hour diurnal test shall be performed in a variable temperature SHED. For hybrid electric vehicles, the manufacturer shall perform additional 24-hour diurnal test increments as necessary to ensure that the auxiliary power unit will be operated to purge the evaporative emission canister during the test sequence noted in M. below.
- M. For hybrid electric vehicles, the manufacturer shall perform testing of the evaporative emission control system and evaporative emission control purge system during the final 24-hour diurnal test cycle as specified in 4.x.K of these test procedures.

ii. Vehicle Preparation

Amend 40 CFR 86.131-90 to read:

- (a) Prepare the fuel tank(s) for recording the temperature of the prescribed test fuel and fuel vapor according to the requirements of paragraph 4.f. (§86.129-80(d)(1)).
- (b) The vehicle shall be equipped with a pressure transducer to monitor the fuel tank headspace pressure during the test. The transducer shall have an accuracy and precision of ± 1.0 inches water.
- (c) Provide additional fittings and adapters, as required, to accommodate a fuel drain at the lowest point possible in the fuel tank(s) as installed on the vehicle.
- (d) Provide valving or other means to allow purging and loading of the evaporative emission canister(s). Special care shall be taken during this step not to alter normal functions of the fuel vapor system components.

iii. Vehicle Preconditioning

Amend paragraph 86.132-90 by adding the following subparagraph (a)(2)(i) which reads:

(i) For hybrid electric vehicles, the battery pack shall be discharged to or just below the state-of-charge at which operation of the auxiliary power unit will be initiated by the vehicle's control strategy. One Urban Dynamometer Driving Schedule (UDDS) shall be used for preconditioning.

The following language shall be applicable in lieu of §86.132-90(a)(4):

The Executive Officer may also choose to conduct or require the performance of optional or additional preconditioning to ensure that the evaporative emission control system is subjected to conditions typical of normal driving. The optional preconditioning shall consist of no less than 20 and no more than 50 miles of on-road mileage accumulation under typical driving conditions.

The following language shall be applicable in lieu of §86.132-90(b):

- A. Within five minutes of completion of preconditioning, the vehicle shall be driven off the dynamometer to a work area.
- B. The fuel tank(s) of the prepared vehicle shall be drained and refilled with the applicable test fuel, as specified in paragraph 4.i. of these procedures, to the prescribed tank fuel volume, defined in §86.082-2.

- C. Following the fuel drain and fill described in subparagraph B. above, the test vehicle shall be allowed to soak for a period of not less than 12 or more than 36 hours prior to the exhaust emissions test. During the soak period, the canister shall be connected to a pump or compressor, purged with air, then loaded with butane as described in D. below.
- D. The evaporative emissions storage canister(s) shall be preloaded with an amount of butane equivalent to 1.5 times the nominal working capacity. The nominal working capacity of a carbon canister shall be determined by each manufacturer for each evaporative emissions engine family. This determination shall be based on the average capacity of no less than five canisters which are in a stabilized condition each having been cycled no less than 10 times and no more than 100 times according to the method specified in paragraph 4.c.iii. of this test procedure, utilizing the fuel used in normal operation. The following procedure shall be used to preload the canister:
- I. Prepare the evaporative emission canister(s) for the canister purging and loading operation. Special care shall be taken during this step so that the normal functions of the fuel system ~~components or the normal pressure relationships in~~ the system are not disturbed. The canister purge shall be performed with ambient air of controlled humidity to 75 ± 10 grains per pound of dry air. This may be accomplished by purging the canister in a room which is conditioned to this level of absolute humidity. The flow rate of the purge air shall be maintained at a nominal flow rate of 48 SCFH (22.7 slpm), and the duration shall be determined to provide a total purge volume flow through the canister equivalent to 300 canister charcoal bed volume exchanges.
 - II. The evaporative emission canister(s) shall then be loaded with an amount of commercial grade butane vapors equivalent to 1.5 times the nominal working capacity. Canister loading shall not be less than 1.5 times the nominal canister capacity. The canister shall be loaded with a mixture composed of 50 percent butane and 50 percent nitrogen by volume. The rate of butane loading shall not exceed 15 ± 2 grams of butane per hour into the canister. Either a Critical Flow Orifice (CFO) butane injection device or a gravimetric method shall be used to fulfill the requirements of this step. The time of completion of the canister(s)

loading activity shall be recorded. Manufacturers shall disclose to the Executive Officer their canister loading procedure. The protocol may not allow for the removal of the canister during loading, or for the replacement of components. In addition, manufacturers shall demonstrate that the procedure does not unduly disturb the components of the evaporative system.

III. Reconnect the evaporative emission canister(s).

iv. Dynamometer procedure.

To be conducted according to 40 CFR 86.135-90.

v. Engine starting and restarting.

To be conducted according to 40 CFR 86.136-90.

vi. Dynamometer test run, gaseous and particulate emissions.

To be conducted according to 40 CFR 86.137-90.

vii. Vehicle Fuel Tank Temperature Stabilization

Immediately after the hot transient exhaust emission test, the vehicle shall be soaked in a temperature controlled area for a maximum of one hour until the fuel temperature is stabilized at 105°F. This is a preparatory step for the running loss test. Cooling or heating of the fuel tank may be induced if the one hour soak is not sufficient to bring the fuel tank to 105°F. The vehicle fuel temperature stabilization step may be omitted on vehicles whose tank fuel temperature is already at 105°F upon completion of the exhaust emission test.

The initial fuel temperature for the running loss test may be less than 105°F if the manufacturer is able to provide data justifying a lower initial temperature. The fuel temperature shall reflect the maximum fuel temperature achieved by a stabilized vehicle during a 105°F day.

The vehicle air conditioning system (if so equipped) shall be set to the "NORMAL" air conditioning mode and adjusted to the minimum discharge air temperature and high fan speed. Vehicles equipped with automatic temperature controlled air conditioning systems shall be operated in "AUTOMATIC" temperature and fan modes with the system set at 72°F.

viii. Running Loss Test

After the fuel temperature is stabilized at 105°F or at the temperature specified by the manufacturer, the running loss test shall be performed. During the test, the running loss measurement enclosure (§86.107-90(a)(1)) shall be maintained at 105°F $\pm$ 5°F maximum and within $\pm$ 2°F on average throughout the running loss test sequence.

A. If running loss testing is conducted using an enclosure which incorporates atmospheric sampling equipment, the manufacturer shall perform the following steps for each test:

- I. Place the drive wheels of the vehicle on the dynamometer without starting the engine.
- II. Attach the exhaust tube to the vehicle tailpipe(s).
- III. The test vehicle windows and the luggage compartments shall be closed.
- IV. The fuel tank temperature sensor and the ambient temperature sensor shall be connected to the temperature recording system and, if required, to the air management and temperature controllers. Vehicle coolant temperature shall be monitored to ensure adequate vehicle coolant air to the radiator intake(s). The temperature recording system and the hydrocarbon emission data recording system shall be started.
- V. Close and seal enclosure doors.
- VI. Analyze enclosure atmosphere for hydrocarbons at the beginning of each Phase of the test (i.e., each UDDS and 120 second idle) and record. This is the background hydrocarbon concentration and is herein denoted as $C_{HCA(n)}$ for each Phase of the test.
- VII. The vehicle shall be driven through three UDDS test procedures. The end of each UDDS cycle shall be followed by an idle period of 120 seconds during which the engine shall remain on with the vehicle in the same transmission range and clutch (if so equipped) actuation mode as during the UDDS idle periods. The fuel tank liquid temperature during the dynamometer drive shall be controlled within $\pm$ 3.0°F of the fuel tank temperature profile obtained on the road according to the procedures in paragraph 4.f. (§86.129-80(d)) for the same vehicle platform/ powertrain/fuel tank configuration. The fuel tank vapor temperature during the final 120 second idle period shall agree

with the corresponding vapor temperature from the on-road profile within $\pm 3.0^{\circ}\text{F}$. The fuel tank temperatures shall be monitored at a frequency of at least once every 15 seconds.

- VIII. Tank pressure shall not exceed 10 inches of water at any time during the running loss test unless a pressurized system is used and the manufacturer demonstrates that vapor would not be vented to the atmosphere if the fuel cap was removed at the end of the test. No pressure checks of the evaporative system shall be allowed. If the manufacturer suspects faulty or malfunctioning instrumentation, a repair of the test instrumentation may be performed. Under no circumstances will any changes/repairs to the evaporative emissions control system be allowed.
- IX. The FID hydrocarbon analyzer shall be zeroed and spanned immediately prior to the end of each Phase of the test.
- X. Analyze the enclosure atmosphere for hydrocarbons following each Phase. This is the sample hydrocarbon concentration and is herein denoted as $C_{HCs(n)}$ for each Phase of the test. The sample hydrocarbon concentration for a particular Phase of the test shall serve as the background concentration for the next Phase of the test. The running loss test ends with completion of the final 120 second idle and occurs 75 ± 2 minutes after the test begins. The elapsed time of this analysis shall be recorded.
- XI. The test vehicle windows and luggage compartment shall be opened. This is a preparatory step for the hot soak evaporative emission test.
- XII. The technician may now leave the enclosure through one of the enclosure doors. The enclosure door shall be open no longer than necessary for the technician to leave.
- XIII. If background emissions adversely affect test accuracy, a manufacturer may submit data to the Executive Officer demonstrating the problem. If, based on the information provided by the manufacturer, the Executive Officer determines that background emissions do adversely affect test accuracy, the manufacturer shall submit for Executive Officer approval some means to compensate for the problem. The Executive Officer shall

approve the use of correction factors to minimize the effects of the problem if supported by experimental data submitted by the manufacturer.

B. If running loss testing is conducted using a cell which incorporates point source sampling equipment, the manufacturer shall perform the following steps for each test:

I. The running loss test shall be conducted in a test cell meeting the specifications of §86.107-90 (a)(1). Ambient temperature in the running loss test cell shall be maintained at $105 \pm 5^{\circ}\text{F}$ maximum and within $\pm 2^{\circ}\text{F}$ on average throughout the running loss test sequence. The ambient test cell temperature shall be measured in the vicinity of the vehicle cooling fan, and it shall be monitored at a frequency of at least once every 15 seconds. The vehicle running loss collection system and underbody cooling apparatus (if applicable) shall be positioned and connected. The vehicle shall be allowed to re-stabilize until the liquid fuel tank temperature is within $\pm 3.0^{\circ}\text{F}$ of the initial liquid fuel temperature calculated according to paragraph 4.f. (§86.129-80(d)(5)) before the running loss test may proceed.

II. The vehicle cooling fan shall be positioned as described in 40 CFR 86.135-90(b). During the running loss test, the cover of the vehicle engine compartment shall be closed, windows closed, and air conditioning system (if so equipped) shall be operated according to the requirements of paragraph 4.f. (§86.129-80 (d)(3)). Vehicle coolant temperature shall be monitored to ensure adequate vehicle coolant air to the radiator intake(s).

III. The vehicle shall be operated on the dynamometer over three UDDS schedules. Idle periods of 120 seconds shall be added to the end of each of the UDDS driving schedules. For hybrid electric vehicles, if the vehicle is unable to maintain the UDDS trace, the vehicle shall be operated at wide open throttle.

IV. The fuel tank liquid temperature during the dynamometer drive shall be controlled within $\pm 3.0^{\circ}\text{F}$ of the fuel tank liquid temperature profile obtained on the road according to the procedures in paragraph 4.f. (§86.129-80(d)) for the same vehicle platform/powertrain/fuel tank configuration. The fuel tank vapor temperature

during the final 120 second idle period shall agree with the corresponding vapor temperature from the on-road profile within $\pm 3.0^{\circ}\text{F}$. The fuel tank temperatures shall be monitored at a frequency of at least once every 15 seconds.

- V. After the test vehicle is positioned on the dynamometer, the running loss vapor vent collection system shall be properly positioned at the specified fuel vapor vents of the vehicle's fuel system, if not already positioned. The typical vapor vents for current fuel systems are the vents of the evaporative emission canister(s) and the tank pressure relief vent typically integrated into the fuel tank cap as depicted in Figure 21. Other designated places, if any, where fuel vapor can escape, shall also be included.
- VI. The running loss vapor vent collection system shall be connected to the PDP-CVS or CFV bag collection system.
- VII. The temperature of the collection system until it enters the main dilution airstream shall be maintained between 175°F to 200°F throughout the test to prevent fuel vapor condensation.
- VIII. The sample bags shall be analyzed within 20 minutes of their respective sample collection phases, as described in §86.137-90(b)(15).
- C. Manufacturers may use an alternative running loss test procedure if it provides an equivalent demonstration of compliance. However, confirmatory testing or in-use compliance testing may be conducted by the Executive Officer using either the running loss measurement enclosure incorporating atmospheric sampling equipment or point source sampling equipment as specified in §86.107-90(a)(1), and the procedure as outlined in either paragraph 4.g.viii.A. or 4.g.viii.B. of this test procedure.
- D. For hybrid electric vehicles, the manufacturer shall record the weight of the evaporative emission canister at the conclusion of the running loss test procedure.

ix. Hot-soak test.

Amend 40 CFR 86.138-90 as follows:

Revise the first paragraph of this section to read: The hot soak evaporative emission test shall be conducted immediately

following the running loss test. The hot soak test shall be performed at an average ambient temperature of $105^{\circ}\text{F} \pm 5.0^{\circ}\text{F}$ maximum and $\pm 2.0^{\circ}\text{F}$ on average.

- A. Omit §86.138-90(a),(e), and (f).
- B. Revise §86.138-90(i) to read: If hot soak testing is not conducted in the same enclosure as running loss testing, the hot soak enclosure doors shall be closed and sealed within five minutes of engine shutdown following the running loss test. If running loss and hot soak testing is conducted in the same enclosure, the hot soak test shall commence immediately after the completion of the running loss test.
- C. Add section (p) to read: If background emissions adversely affect test accuracy, a manufacturer may submit data to the Executive Officer demonstrating the problem. If, based on the information provided by the manufacturer, the Executive Officer determines that background emissions do adversely affect test accuracy, the manufacturer shall submit for Executive Officer approval some means to compensate for the problem. The Executive Officer shall approve the use of correction factors to minimize the effects of the problem if supported by experimental data submitted by the manufacturer.

x. Diurnal breathing loss test.

A 72-hour diurnal test shall be performed in a variable temperature SHED, described in paragraph 4.d.i. of this test procedure. The test consists of three 24-hour cycles. For purposes of this diurnal breathing loss test, all references to methanol shall be applicable to ethanol.

Revise 40 CFR 86.133-90 to read as follows:

- A. Revise section (a)(1) to read: Upon completion of the hot soak test, the start of the diurnal breathing loss test shall follow within 24 hours. The diurnal breathing loss test shall consist of three 24-hour test cycles. For hybrid electric vehicles, the manufacturer shall perform additional 24-hour diurnal test cycles as necessary to ensure that the auxiliary power unit will be operated to purge the evaporative emission control canister during the test sequence specified in 4.x.K. of this test procedure.
- B. Omit section (f)

- C. Revise section (i) to read: The diurnal breathing loss test shall commence with a fuel temperature of 65°F. The fuel may be artificially cooled or heated to the starting diurnal temperature.
- D. Revise section (j) to read: When the fuel temperature recording system reaches at least 63°F, immediately:
- E. Revise section (k) to read: When the fuel temperature recording system reaches 65°F ± 2°F, immediately:
- F. Revise section (k)(3) to read: Start diurnal heat build and record time. This commences the 24 hour ± 2 minute test cycle.
- G. Revise section (l) to read: For each 24-hour cycle of the diurnal breathing loss test, the ambient temperature in the SHED enclosure shall be changed in real time as specified in the following table:

Hour	Temperature (°F)	Hour	Temperature (°F)
0	65.0	12	104.2
1	66.6	13	101.1
2	72.6	14	95.3
3	80.3	15	88.8
4	86.1	16	84.4
5	90.6	17	80.8
6	94.6	18	77.8
7	98.1	19	75.3
8	101.2	20	72.0
9	103.4	21	70.0
10	104.9	22	68.2
11	105.0	23	66.5
		24	65.0

- H. Revise section (n) to read: The end of the first 24-hour cycle of the diurnal test occurs 24 hours ± 2 minutes after the heat build begins, paragraph (j)(2). Analyze the enclosure atmosphere for hydrocarbons and record. This is the final hydrocarbon concentration, C_{HCF} in §86.143-90, for this test cycle. The time (or elapsed time) of this analysis shall be recorded. The procedure, commencing with paragraph (k)(1) shall be repeated until three consecutive 24-hour tests are completed. For hybrid electric vehicles, additional 24-hour tests may be required to ensure that the auxiliary power unit will be operated to purge the evaporative emission control canister during the test sequence specified in 4.x.K. The data from the test cycle yielding the highest diurnal hydrocarbon mass shall be

used in evaporative emissions calculations as required by §86.143-90.

- I. Revise section (q) to read: Upon completion of the final 24-hour test cycle, and after the final ethanol sample has been collected, the heat source shall be turned off and the enclosure doors unsealed and opened.
- J. Add section (t) to read: If background emissions adversely affect test accuracy, a manufacturer may submit data to the Executive Officer demonstrating the problem. If, based on the information provided by the manufacturer, the Executive Officer determines that background emissions do adversely affect test accuracy, the manufacturer shall submit for Executive Officer approval some means to compensate for the problem. The Executive Officer shall approve the use of correction factors to minimize the effects of the problem if supported by experimental data submitted by the manufacturer.
- K. Add section (u) to read: For all hybrid electric vehicles, testing of the evaporative emission control system and evaporative emission control purge emission testing shall occur after the final 24-hour diurnal test cycle to ensure proper operation of the evaporative emission control system and to collect exhaust emissions due to any purging operation. The testing shall be conducted in accordance with the following procedure:
 - 1. Prior to evaporative purge system testing, the hybrid electric vehicle battery pack shall be charged to 100% state-of-charge (SOC).
 - 2. After completing the required number of 24-hour diurnal periods (at least 3), evaporative purge testing shall begin within 24 hours of the final diurnal period.
 - 3. With exhaust collection instrumentation in place, the ignition shall be turned "ON", and the vehicle shall be driven over repeat CVS-72 driving schedules. The CVS-72 driving schedule shall be repeated until the APU has automatically shut off. Emission sampling of hydrocarbons shall begin at APU ignition and terminate when the APU has automatically shut off.
 - 4. Evaporative purge emissions shall be calculated by dividing the total emissions by the product of the time required to completely purge the evaporative emission canister and 20 mph (the

average speed of the CVS-72 test schedule). This calculation will produce a grams/mile value for hydrocarbons which will then be divided by the number of 24-hour diurnals certified to (at least 3). For methanol vehicles, the manufacturer shall first convert the hydrocarbon emissions into an OMHCE value. The following equation provides a summary of this procedure:

$$\begin{aligned} \text{Evaporative Emission Level} &= \frac{\text{hydrocarbon or OMHCE emissions (grams)}}{\text{APU ON Time (sec)} \times (1 \text{ hour} / 3600 \text{ sec}) \times (20 \text{ mph})} \\ &\quad \text{Certified number of 24-hour diurnals} \\ &= \frac{\text{grams}}{\text{mile}} \\ &\quad \text{day} \end{aligned}$$

5. To determine if the evaporative emission canister has been completely purged, the manufacturer shall record the weight of the canister at the conclusion of the repeat CVS-72 test schedules. The evaporative emission canister shall be considered to be completely purged if the weight of the canister is increased by no more than 5 percent of the nominal working capacity compared to the weight of the canister recorded after the completion of the running loss test procedure.

The results of the evaporative emission control system purge test shall be added to the official running loss emission results of the vehicle for hydrocarbons or OMHCE and submitted in the application for certification of the vehicle. The sum of the evaporative emission control system purge test and the official running loss emission results of the vehicle shall be compared with the running loss emission standard to determine compliance with the running loss emission standard.

xi. Calculations; evaporative emissions.

For purposes of this section, all references to methanol shall also be applicable to ethanol.

Revise 40 CFR 86.143-90 as follows:

- A. Revise section (a) to read: The calculation of the net hydrocarbon plus methanol (organic material hydrocarbon equivalent) mass change in the enclosure is used to determine the diurnal, hot soak, and running loss mass emissions. The mass changes are calculated from initial and final hydrocarbon and methanol concentrations in ppm

carbon, initial and final enclosure ambient temperatures, initial and final barometric pressures, and net enclosure volume using the following equations:

B. Revise section (a)(2) to read:

(2) For hydrocarbons:

(a) Hot soak HC mass. The hot soak enclosure mass is determined as:

$$M_{HChs} = [2.95 \times (V_n - 50) \times 10^{-4} \times P_i \times (C_{HCE2} - C_{HCE1})] / T_i$$

where: M_{HChs} is the hot soak HC mass emissions (grams)

V_n is the enclosure nominal volume (ft³)

P_i is the initial barometric pressure (inches Hg)

C_{HCE2} is the final enclosure concentration (ppm C)

C_{HCE1} is the initial enclosure concentration (ppm C)

T_i is the initial enclosure temperature (°R)

(b) Running loss HC mass. The running loss HC mass per distance traveled is defined as:

$$M_{HCr1t} = (M_{HCr1(1)} + M_{HCr1(2)} + M_{HCr1(3)}) / (D_{r1(1)} + D_{r1(2)} + D_{r1(3)})$$

where: M_{HCr1t} is the total running loss HC mass per distance traveled (grams HC per mile)

$M_{HCr1(n)}$ is the running loss HC mass for Phase n of the test (grams HC)

$D_{r1(n)}$ is the actual distance traveled over the driving cycle for Phase n of the test (miles)

and: $M_{HCr1(n)} = (C_{HCS(n)} - C_{HCA(n)}) \times 17.10 \times V_{mix} \times 10^{-6}$

where: $C_{HCS(n)}$ is the sample bag HC concentration for Phase n of the test (ppm C)

$C_{HCA(n)}$ is the background bag concentration for Phase n of the test (ppm C)

17.10 is the density of butane divided by 4 (grams/ft³)

V_{mix} is the total dilute CVS volume (std. ft³)

and: V_{mix} is calculated per §86.144-90

- (c) Diurnal mass. The HC mass for each of the three diurnals is defined for a variable volume SHED enclosure as:

$$M_{HCd} = [2.98 \times (V_n - 50) \times 10^{-4} \times P_i \times (C_{HCE2} - C_{HCE1})] / T_i$$

where: M_{HCd} is the diurnal HC mass emissions (grams)
 V_n is the enclosure nominal volume (ft³)
 P_i is the initial barometric pressure (inches Hg)
 C_{HCE2} is the final enclosure concentration (ppm C)
 C_{HCE1} is the initial enclosure concentration (ppm C)
 T_i is the initial enclosure temperature (°R)

- C. Revise section (b) to read: The final evaporative emission test results reported shall be computed by summing the evaporative emission result determined for the hot soak test and the highest 24-hour result determined for the diurnal breathing loss test. The final reported result for the running loss test shall be computed by dividing the sum of the three masses by the total miles traveled over the three Phases of the test.

- h. For 1983 and subsequent model-year LPG-fueled motor vehicles, the introduction of 40 percent by volume of chilled fuel and the heating of the fuel tank under the diurnal part of the evaporative test procedures shall be eliminated.
- i. Evaporative emission test fuel shall be the fuel specified for exhaust emission testing in the applicable exhaust emission test procedures.

The maximum Reid Vapor Pressure of gasoline used for testing and in service accumulation shall be consistent with the fuel specification applicable to vehicles in California.

Fuel additives and ignition improvers intended for use in methanol test fuels shall be subject to the approval of the Executive Officer. In order for such approval to be granted, a manufacturer must demonstrate that vehicle performance will be adversely affected without the use of the fuel additive.

5. Approval of heavy-duty vehicles, excluding medium-duty vehicles from 6,000 to 8,500 lbs GVWR and complete medium-duty vehicles 14,000 lbs GVWR or less, shall be based on an engineering evaluation of the system and data submitted by the applicant. Such evaluation may include

successful public usage on light-duty or medium-duty vehicles, adequate capacity of storage containers, routing of lines to prevent siphoning, and other emissions-related factors deemed appropriate by the Executive Officer. For LPG systems, this engineering evaluation shall include: emissions from pressure relief valves, carburetion systems and other sources of leakage; emissions due to fuel system wear and aging; and evaporative emission test data from light-duty or medium-duty vehicles with comparable fuel systems.

6. For the 1980 model year, the measured evaporative emissions from all test vehicles, except vehicles tested pursuant to paragraph 4. above and motorcycles, shall be corrected for background emissions by subtracting 1.0 gram per test. This correction for background emissions may be extended to include the 1981 model year, on a case-by-case basis, if the Executive Officer finds that a manufacturer has had insufficient lead-time to comply with the April 23, 1980 amendment to this procedure.
7. For the purposes of these test procedures, the following references in 40 CFR, Part 86, Subpart B, to light-duty vehicle evaporative testing shall also apply to motorcycles: §§86.117-78, 86.117-90, 86.121-82, and 86.121-90. In addition, 40 CFR, Part 86, Subparts E, F, and other cited sections of Subpart B are incorporated into this test procedure by reference.
8. Certification of a motorcycle evaporative emission control system ~~requires that the manufacturer demonstrate the durability of each~~ evaporative emission control system family.
 - a. The motorcycle manufacturer can satisfy the vehicle durability testing requirement by performing an evaporative emission test at each scheduled exhaust emission test (§86.427-78) during the motorcycle exhaust emissions certification test (§86.425-78) for each evaporative emission family. The minimum mileage accumulated shall be the total distance (one-half the useful life distance), although the manufacturer may choose to extend the durability test to the useful life distance (§86.436-78). The displacement classes and test distances are shown below:

<u>Displacement</u> <u>Class</u>	<u>Engine</u> <u>Displacement</u> <u>Range (CC)</u>	<u>Total Test</u> <u>Distance (km)</u>	<u>Useful Life</u> <u>Distance (km)</u>
I	50-169	6,000	12,000
II	170-279	9,000	18,000
III	280 and greater	15,000	30,000

- i. All durability vehicles shall be built at least one month before the evaporative emissions test, or the manufacturer must demonstrate that the non-fuel related evaporative emissions have stabilized.

- ii. Testing at more frequent intervals than the scheduled exhaust emissions tests may be performed only when authorized in writing by the Executive Officer.
- iii. The DF (deterioration factor) shall be determined by calculating a least-squares linear regression of the evaporative emissions data with respect to mileage. The DF is defined as the extrapolated (from the regression) value at the useful life distance minus the interpolated value at the total test distance, where these distances are taken from the table in paragraph 8.a.
- iv. The extrapolated useful life and total test distance emissions shall be less than the applicable evaporative emission standards of paragraph 1. or the data will not be acceptable for use in the calculation of a DF and demonstration of compliance.
- v. Motorcycle manufacturers may use the ARB Component Bench Test Procedures or propose in their application a method for durability bench testing and determination of a DF for each evaporative emission engine family. The Executive Officer shall review the method, and shall approve it if it is similar to the requirements specified in paragraph 4.a.ii. Any reference to 4,000 miles and 50,000 miles in paragraph 4.a.ii. shall mean total test distance and useful life distance, respectively, as defined in paragraph 8.a. for the appropriate engine displacement class.
- vi. The DF determined under paragraph 8.a.iii. shall be averaged with the DF determined under paragraph 8.a.v. to determine a single evaporative emission DF for each evaporative emission engine family. For those motorcycles which do not require exhaust emission control system durability testing, the evaporative emission control system DF shall be determined under paragraph 8.a.v. only. Compliance with the standard shall be demonstrated by performing an evaporative emission test on a stabilized motorcycle. The motorcycle shall have accumulated at least the minimum test distance. The extrapolated useful life distance emissions after applying the bench test-derived DF shall be less than the applicable evaporative emission standards of paragraph 1.
- vii. (A) Manufacturers of Class III motorcycles may elect to use an assigned evaporative emission control system DF, provided they meet the following requirements:
 - Annual California motorcycle sales do not exceed 500 units, and
 - The evaporative emission control system has been previously certified to meet the emission standards

specified in these procedures, or the manufacturer provides test data from previous certification demonstrating that the system complies with the durability requirements set forth in this paragraph.

- (B) Manufacturers of Class III motorcycles using an assigned evaporative emission control system DF pursuant to subparagraph 8.a.vii.A. may submit a written request for a waiver of evaporative emission testing. The waiver shall be granted if the Executive Officer determines that the motorcycles will comply with the evaporative emission standard. The determination shall be based on the performance of the evaporative emission control system on other motorcycles, the capacity of vapor storage containers, the routing of lines to prevent siphoning, and other emission-related factors determined by the Executive Officer to be relevant to evaluation of the waiver request.
- (C) Nothing in this paragraph shall be construed as an exemption from the exhaust emission standards and test procedures applicable pursuant to section 1958, Title 13, California Code of Regulations, or paragraph 8.c.ii. of these procedures.

viii. The emission label (§86.413-78) shall identify the evaporative emission family.

- ix. Preconditioning shall be performed in accordance with §86.532-78. The provisions of §86.132-78 which prohibit abnormal loading of the evaporative emission control system during fueling and setting the dynamometer horsepower using a test vehicle shall be observed. Additional preconditioning (§86.132-82(a)(3) and §86.132-90(a)(3)) may be allowed by the Executive Officer under unusual circumstances.

b. Instrumentation

The instrumentation necessary to perform the motorcycle evaporative emission test is described in 40 CFR 86.107-78 and 86.107-90, with the following changes:

- i. Revise section (a)(4) to read: Tank fuel heating system. The tank fuel heating system shall consist of two separate heat sources with two temperature controllers. A typical heat source is a pair of heating strips. Other sources may be used as required by circumstances and the Executive Officer may allow manufacturers to provide the heating apparatus for compliance testing. The temperature controllers may be manual, such as variable transformers, or they may be automated. Since vapor and fuel temperature are

to be controlled independently, an automatic controller is recommended for the fuel. The heating system must not cause hot spots on the tank wetted surface which could cause local overheating of the fuel or vapor. Heating strips for the fuel, if used, should be located as low as practicable on the tank and should cover at least 10 percent of the wetted surface. The centerline of the fuel heating strips, if used, shall be below 30 percent of the fuel depth as measured from the bottom of the fuel tank and approximately parallel to the fuel level in the tank. The centerline of the vapor heating strips, if used, should be located at the approximate height of the center of the vapor volume. The temperature controller must be capable of controlling the fuel and vapor temperatures to the diurnal heating profile within the specified tolerance.

- ii. Revise section (a)(5) (Temperature Recording System) to read: In addition to the specifications in this section, the vapor temperature in the fuel tank shall be measured. When the fuel or vapor temperature sensors cannot be located in the fuel tank to measure the temperature of the prescribed test fuel or vapor at the approximate mid-volume, sensors shall be located at the approximate mid-volume of each fuel or vapor containing cavity. The average of the readings from these sensors shall constitute the fuel or vapor temperature. The fuel and vapor temperature sensors shall be located at least one inch away from any heated tank surface. The Executive Officer may approve alternate sensor locations where the specifications above cannot be met or where tank symmetry provides redundant measurements.
 - iii. Calibration shall be performed in accordance with 40 CFR 86.516-78 or 86.516-90.
- c. Test Procedure

- i. The motorcycle exhaust emission test sequence is described in 40 CFR 86.530-78 through 86.540-78. The Sealed Housing Evaporative Determination (SHED) test shall be accomplished by performing the diurnal portion of the SHED test (\$86.133-78 except subsections a(1), k, and p; §86.133-90 except subsections a(1), l, and s; and neglecting references to windows and luggage compartments in these sections) after preconditioning and soak but prior to the "cold" start test. The fuel will be cooled to below 30°C after the diurnal test. The "cold" and "hot" start exhaust emission tests shall then be run. The motorcycle will then be returned for the hot soak portion of the SHED test. This general sequence is shown in Figure E78-10, under §86.130-78. The specified time limits shall be followed with the exception of soak times which are specified in §86.532-78 for motorcycles.

Running loss tests, when necessary, will be performed in accordance with §86.134-78, except references to §§86.135-82 through 86.137-82 and §§86.135-90 through 86.137-90 shall mean §§86.535-78 through 86.537-78.

- ii. Manufacturers of Class III motorcycles with annual California sales of less than 500 units using an assigned evaporative emission control system DF pursuant to paragraph 8.a.vii. shall measure and report to the Executive Officer exhaust emissions from the CVS test between the diurnal and the hot soak tests even if the test is being conducted for evaporative emissions only. The exhaust emission levels projected for the motorcycle's useful life utilizing the exhaust emission deterioration factor determined during previous federal or California certification testing shall not exceed the standards set forth in section 1958, Title 13, California Code of Regulations.
- iii. The fuel and vapor temperatures for the diurnal portion of the evaporative emission test shall conform to the following functions within $\pm 1.7^{\circ}\text{C}$ with the tank filled to 50 percent ± 2.5 of its actual capacity, and with the motorcycle resting on its center kickstand (or a similar support) in the vertical position.

$$T_f = (1/3) t + 15.5^{\circ}\text{C}$$

$$T_v = (1/3) t + 21.0^{\circ}\text{C}$$

Where: T_f = fuel temperature, $^{\circ}\text{C}$

T_v = vapor temperature, $^{\circ}\text{C}$

t = time since the start of the diurnal temperature rise, minutes.

The test duration shall be 60 ± 2 minutes, giving a fuel and vapor temperature rise of 20°C . The final fuel temperature shall be $35.5^{\circ}\text{C} \pm .5^{\circ}\text{C}$.

An initial vapor temperature up to 5°C above 21°C may be used. For this condition, the vapor shall not be heated at the beginning of the diurnal test. When the fuel temperature has been raised to 5.5°C below the vapor temperature by following the T_f function, the remainder of the vapor heating profile shall be followed.

- iv. An alternate temperature rise for the diurnal test may be approved by the Executive Officer. If a manufacturer has information which shows that a particular fuel tank design will change the temperature rise significantly from the

function above, the manufacturer may present the information to the Executive Officer for evaluation and consideration.

- v. The hot soak evaporative emission test shall be performed immediately following the "hot" start exhaust emission test. This test is described in §§86.138-78 and 86.138-90, except for §§86.138-78(d) and 86.138-90(e) which are revised to require that the motorcycle be pushed with the engine off rather than driven at minimum throttle from the dynamometer to the SHED.
- vi. Calculations shall be performed in accordance with §86.143-78 or 86.143-90, except the standard volume for a motorcycle shall be 5 ft³ instead of 50 ft³.
- d. Motorcycle manufacturers with annual sales of less than 2,000 units for the three displacement classes in California are not required to submit the information specified by these test procedures to the Executive Officer. However, all information required by these test procedures must be retained on file and be made available upon request to the Executive Officer for inspection. These manufacturers shall submit the following information for evaporative emission certification:
 - i. A brief description of the vehicles to be covered by the Executive Order. (The manufacturer's sales data book or advertising, including specifications, will satisfy this requirement for most manufacturers.)
 - ii. A statement signed by an authorized representative of the manufacturer stating "The vehicles described herein have been tested in accordance with the provisions of the 'California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles', and on the basis of those tests, are in conformance with the aforementioned standards and test procedures."
- 9. The evaporative emissions for LPG systems shall be calculated in accordance with §86.143-78 or 86.143-90 except that a H/C ratio of 2.658 shall be used for both the diurnal and hot soak emissions.

Definitions:

Motorcycle Evaporative Emission Family: The group of motorcycle models which meet the criteria of EPA's MSAPC Advisory Circular No. 59, section D.




Figure 1. Running Loss Vapor Vent Collection System




FIGURE 2. EVAPORATIVE EMISSIONS TEST PROCEDURE




FIGURE 3. TEST PROCEDURE FOR HYBRID ELECTRIC VEHICLES

State of California
AIR RESOURCES BOARD

CALIFORNIA NON-METHANE ORGANIC GAS
TEST PROCEDURES

Adopted: July 12, 1991
Amended:

State of California

AIR RESOURCES BOARD

California Non-Methane Organic Gas Test Procedures

A. GENERAL APPLICABILITY AND REQUIREMENTS

1. These test procedures shall apply to all 1993 and subsequent model-year transitional low-emission vehicles (TLEV), low-emission vehicles (LEV), and ultra-low-emission vehicles (ULEV) certifying to non-methane organic gas (NMOG) emission standards.

2. This document sets forth the analysis and calculation procedures that shall be performed to determine NMOG mass emissions. The document consists of the following parts:

- A. General Applicability and Requirements
- B. Determination of Non-Methane Hydrocarbon Mass Emissions by Flame Ionization Detection
- C. Determination of Alcohols in Automotive Source Samples by Gas Chromatography (method no. 1001)
- D. Determination of C₂ to C₅ Hydrocarbons in Automotive Source Samples by Gas Chromatography (method no. 1002)
- E. Determination of C₆ to C₁₂ Hydrocarbons in Automotive Source Samples by Gas Chromatography (method no. 1003)
- F. Determination of Aldehyde and Ketone Compounds in Automotive Source Samples by High Performance Liquid Chromatography (method no. 1004)
- G. Determination of Ethers in Automotive Source Samples by Gas Chromatography (method no. 1005)
- H. Determination of NMOG Mass Emissions

Alternative procedures may be used if shown to yield equivalent results and if approved in advance by the Executive Officer of the Air Resources Board.

3. The analyses specified in the table below shall be performed to determine mass emission rates of NMOG in grams per mile (g/mile) or milligrams per mile (mg/mile) for vehicles operated on the listed fuel:

Fuel	NMHC by FID	NMHC by GC	Alcohols	Carbonyls	Ethers
Alcohol	X		X	X	
CNG		X		X	
Diesel		X		X	
Gasoline	X			X	X
LPG	X			X	

where "LPG" means "liquified petroleum gas", "CNG" means "compressed natural gas", "NMHC" means "non-methane hydrocarbon", "FID" means "flame ionization detector", and "GC" means "gas chromatograph".

The specified analyses shall be performed in accordance with the following parts of this document:

- NMHC by FID -- B. Determination of Non-Methane Hydrocarbon Mass Emissions by Flame Ionization Detection
- NMHC by GC -- D. Determination of C₂ to C₅ Hydrocarbons in Automotive Source Samples by Gas Chromatography (method no. 1002) and
E. Determination of C₆ to C₁₂ Hydrocarbons in Automotive Source Samples by Gas Chromatography (method no. 1003)
- Carbonyls -- F. Determination of Aldehyde and Ketone Compounds in Automotive Source Samples by High Performance Liquid Chromatography (method no. 1004)
- Alcohols -- C. Determination of Alcohols in Automotive Source Samples by Gas Chromatography (method no. 1001)
- Ethers -- G. Determination of Ethers in Automotive Source Samples by Gas Chromatography (method no. 1005)

4. For those manufacturers which choose to develop reactivity adjustment factors unique to a specific engine family, exhaust NMOG emissions shall be fully speciated. NMHC emissions shall be analyzed in accordance with parts D and E (method nos. 1002 and 1003). In addition, aldehydes and ketones, alcohols, and ethers shall be analyzed according to parts F, C, and G (method nos. 1004, 1001, and 1005). Analysis for alcohols shall be required ~~only for vehicles which are operated on fuels containing alcohols, and for ethers on fuels containing ethers.~~

5. For diesel-fueled vehicles, the development of speciated hydrocarbon emission profiles is of concern from a technical standpoint. At present, sampling and analysis of diesel-fueled vehicle exhaust emissions shall be performed according to the following guidelines:

A sample of motor vehicle diesel exhaust at an elevated temperature would be passed through a porous polymer sample tube (XAD-2 or equivalent). The sample tube would be extracted with a solvent (methylene chloride or equivalent), concentrated and introduced into a GC/FID with a high temperature capillary column (SE-30 or similar) for analysis. Other methods may be utilized but should be submitted to the Board for prior approval. See also Technical Reports: EPA/AA/CTAB/PA/80-5 (September, 1980) "Comparison of Gas Phase Hydrocarbon from Light-Duty Gasoline Vehicles and Light-Duty Vehicles Equipped with Diesel Engines," and F. Black and L. High (SAE No. 790422) "Methodology for Determining Particulate and Gaseous Diesel Hydrocarbon Emissions."

Because the composition of the exhaust emissions from diesel-fueled vehicles is highly complex, the mass of hydrocarbons grouped according to carbon number rather than fully speciated data may be submitted.

6. For natural gas-fueled vehicles, the methane concentration in the exhaust sample shall be measured with a methane analyzer. A GC combined with a FID is used for direct measurement of methane concentrations. SAE Recommended Practice J1151 is a reference on generally accepted GC principles and analytical techniques for this application. A density of 18.89 g/ft³ shall be used to determine the methane mass emissions. The methane mass emissions shall be multiplied by the appropriate methane reactivity adjustment factor and then added to the reactivity-adjusted NMOG emissions as specified in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

7. The mass of NMOG emissions shall be calculated in accordance with part H, "Determination of NMOG Mass Emissions". The mass of NMOG emissions in g/mile or mg/mile shall be calculated by summing the mass of NMHC determined by the FID, the mass of aldehydes and ketones, and the mass of alcohols and ethers if any.

AIR RESOURCES BOARD

DETERMINATION OF
NON-METHANE HYDROCARBON MASS EMISSIONS
BY FLAME IONIZATION DETECTION

California Air Resources Board
Mobile Source Division
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

DETERMINATION OF NON-METHANE HYDROCARBON MASS EMISSIONS
BY FLAME IONIZATION DETECTION

1. INTRODUCTION

- 1.1 This procedure describes a method for determining non-methane hydrocarbon (NMHC) exhaust mass emissions from motor vehicles. Other applicable forms of instrumentation and analytical techniques which prove to yield equivalent results to those specified in this procedure may be used subject to the approval of the Executive Officer of the Air Resources Board.

2. TOTAL HYDROCARBON MEASUREMENT

- 2.1 A flame ionization detector (FID) is used to measure total hydrocarbon concentration in vehicle exhaust in accordance with the Code of Federal Regulations(1). SAE Recommended Practices J254(2) and J1094a(3) are references on generally accepted gas analysis and constant volume sampling techniques. For Beckman 400 FIDs only, implementation of the recommendations outlined in SAE paper 770141, "Optimization of Flame Ionization Detector for Determination of Hydrocarbons in Diluted Automobile Exhaust"; author, Glenn D. Reschke (4) shall be required. Other FID analyzer models shall be checked and adjusted, if necessary, to minimize any non-linearity of relative response to different hydrocarbons.

3. METHANE MEASUREMENT

- 3.1 A gas chromatograph (GC) combined with a FID constitute a methane analyzer and shall be used for direct measurement of methane concentrations. The SAE Recommended Practice J1151(5) is a reference on generally accepted GC principles and analytical techniques for this specific application.

4. TOTAL HC FID RESPONSE TO METHANE

- 4.1 The FID is calibrated to propane and therefore tends to over respond to the methane portion of the vehicle exhaust sample during hydrocarbon analysis. In order to calculate the NMHC concentration, a methane response factor must be applied to the methane concentration (as measured by the methane analyzer) before it can be deducted from the total hydrocarbon concentration. To determine the total hydrocarbon FID response to methane, known methane in air concentrations traceable to National Institute of Standards and Technology (NIST) shall be analyzed by the FID. Several methane concentrations shall be analyzed by the FID in the range of the exhaust sample concentration. The total hydrocarbon FID response to methane is calculated as follows:

$$r_{CH_4} = FID_{ppm} / SAM_{ppm}$$

where:

r_{CH_4} = FID methane response factor.

FIDppm = FID reading in ppmC.

SAMppm = the known methane concentration in ppmC.

The FID response to methane shall be checked at each calibration interval.

5. NMHC MASS EMISSION PER TEST PHASE

5.1 The following calculations shall be used to determine the NMHC mass emissions for each phase of the Federal Test Procedure(1).

5.2 Non-Alcohol Fueled Vehicles

5.2.1 $NMHC_e = FID\ THC_e - (r_{CH_4} * CH_{4e})$

NOTE: If $NMHC_e$ is calculated to be less than zero, then $NMHC_e = 0$.

5.2.2 $NMHC_d = FID\ THC_d - (r_{CH_4} * CH_{4d})$

NOTE: If $NMHC_d$ is calculated to be less than zero, then $NMHC_d = 0$.

5.2.3 $CO_e = (1 - (0.01 + 0.005 * HCR) * CO_{2e} - 0.000323 * R_a) * CO_{em}$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

a) For gasoline, $CH_{1.85}$, where $HCR = 1.85$:

$$CO_e = (1 - 0.01925 * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

b) For LPG, $CH_{2.66}$, where $HCR = 2.66$:

$$CO_e = (1 - 0.02330 * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

5.2.4 $DF = \frac{100 * \frac{x}{x + y/2 + 3.76 * (x + y/4 - z/2)}}{CO_{2e} + (NMHC_e + CH_{4e} + CO_e) * 10^{-4}}$

(where fuel composition is $C_xH_yO_z$ as measured for the fuel used.)

a) For gasoline, $CH_{1.85}$, where $x = 1$, $y = 1.85$, and $z = 0$:

$$DF = 13.46 / [CO_{2e} + (NMHC_e + CH_{4e} + CO_e) * 10^{-4}]$$

b) For LPG, $\text{CH}_{2.66}$, where $x = 1$, $y = 2.66$, and $z = 0$:

$$\text{DF} = 11.63 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e) * 10^{-4}]$$

5.3 Vehicles Operating on Fuels Containing Methanol

5.3.1 $\text{NMHC}_e = \text{FID THC}_e - (r_{\text{CH}_4} * \text{CH}_{4e}) - (r_{\text{CH}_3\text{OH}} * \text{CH}_3\text{OH}_e)$

NOTE: If NMHC_e is calculated to be less than zero, then $\text{NMHC}_e = 0$.

5.3.2 $\text{NMHC}_d = \text{FID THC}_d - (r_{\text{CH}_4} * \text{CH}_{4d}) - (r_{\text{CH}_3\text{OH}} * \text{CH}_3\text{OH}_d)$

NOTE: If NMHC_d is calculated to be less than zero, then $\text{NMHC}_d = 0$.

5.3.3 $\text{CO}_e = (1 - (0.01 + 0.005 * \text{HCR}) * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

a) For M100 (100% methanol), CH_3OH , where $\text{HCR} = 4$:

$$\text{CO}_e = (1 - 0.03000 * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

b) For M85 (85% methanol, 15% indolene), $\text{CH}_{3.41}\text{O}_{0.72}$, where $\text{HCR} = 3.41$:

$$\text{CO}_e = (1 - 0.02705 * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

5.3.4
$$\text{DF} = \frac{100 * \frac{x}{x + y/2 + 3.76 * (x + y/4 - z/2)}}{\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{CH}_3\text{OH}_e) * 10^{-4}}$$

(where fuel composition is $\text{C}_x\text{H}_y\text{O}_z$ as measured for the fuel used.)

a) For M100 (100% methanol), CH_3OH , where $x = 1$, $y = 4$, and $z = 1$:

$$\text{DF} = 11.57 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{CH}_3\text{OH}_e) * 10^{-4}]$$

b) For M85 (85% methanol, 15% Indolene), $\text{CH}_{3.41}\text{O}_{0.72}$, where $x = 1$, $y = 3.41$, and $z = 0.72$:

$$\text{DF} = 12.01 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{CH}_3\text{OH}_e) * 10^{-4}]$$

5.4 Vehicles Operating on Fuels Containing Ethanol

5.4.1 $\text{NMHC}_e = \text{FID THC}_e - (r_{\text{CH}_4} * \text{CH}_{4e}) - (r_{\text{C}_2\text{H}_5\text{OH}} * \text{C}_2\text{H}_5\text{OH}_e)$

NOTE: If NMHC_e is calculated to be less than zero, then $\text{NMHC}_e = 0$.

$$5.4.2 \quad \text{NMHC}_d = \text{FID THC}_d - (r_{\text{CH}_4} * \text{CH}_{4d}) - (r_{\text{C}_2\text{H}_5\text{OH}} * \text{C}_2\text{H}_5\text{OH}_d)$$

NOTE: If NMHC_d is calculated to be less than zero, then $\text{NMHC}_d = 0$.

$$5.4.3 \quad \text{CO}_e = (1 - (0.01 + 0.005 * \text{HCR}) * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

a) For E100 (100% ethanol), $\text{C}_2\text{H}_5\text{OH}$, where $\text{HCR} = 3$:

$$\text{CO}_e = (1 - 0.02500 * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

$$5.4.4 \quad \text{DF} = \frac{100 * \frac{x}{x + y/2 + 3.76 * (x + y/4 - z/2)}}{\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{C}_2\text{H}_5\text{OH}_e) * 10^{-4}}$$

(where fuel composition is $\text{C}_x\text{H}_y\text{O}_z$ as measured for the fuel used.)

a) For E100 (100% ethanol), $\text{C}_2\text{H}_5\text{OH}$, where $x = 1$, $y = 3$, and $z = 0.5$:

$$\text{DF} = 12.27 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{C}_2\text{H}_5\text{OH}_e) * 10^{-4}]$$

5.5 All Vehicles

$$5.5.1 \quad \text{NMHC}_{\text{conc}} = \text{NMHC}_e - \text{NMHC}_d * [1 - (1 / \text{DF})]$$

NOTE: If $\text{NMHC}_{\text{conc}}$ is calculated to be less than zero, then

$$\text{NMHC}_{\text{conc}} = 0.$$

$$5.5.2 \quad \text{NMHC}_{\text{mass}_n} = \text{NMHC}_{\text{conc}} * \text{NMHC}_{\text{dens}} * \text{VMIX} * 10^{-6}$$

6. TOTAL WEIGHTED NMHC MASS EMISSIONS

6.1 All Vehicles

$$6.1.1 \quad \text{NMHC}_{\text{wm}} = 0.43 * \frac{\text{NMHC}_{\text{mass}_1} + \text{NMHC}_{\text{mass}_2}}{D_{\text{phase}_1} + D_{\text{phase}_2}} + 0.57 * \frac{\text{NMHC}_{\text{mass}_3} + \text{NMHC}_{\text{mass}_2}}{D_{\text{phase}_3} + D_{\text{phase}_2}}$$

7. SAMPLE CALCULATIONS

7.1 Given the following data for a gasoline vehicle, calculate the weighted NMHC mass emission.

Test Phase	FID THC _e (ppmC)	FID THC _d (ppmC)	CH _{4e} (ppmC)	CH _{4d} (ppmC)	CO _{em} (ppm)	CO _{2e} (%)	VMIX (ft ³)	D _{phase_n} (mile)	R _a (%)
1	41.8	8.6	7.53	5.27	147.2	1.19	2846	3.583	38
2	13.0	8.4	5.68	5.10	20.8	0.80	4856	3.848	38
3	15.4	8.9	6.16	5.20	36.7	1.04	2839	3.586	38

For Phase 1:

$$\begin{aligned}
 \text{NMHC}_e &= \text{FID THC}_e - (r_{\text{CH}_4} * \text{CH}_{4e}) \\
 &= 41.8 \text{ ppmC} - (1.20 * 7.53 \text{ ppmC}) \\
 &= 32.76 \text{ ppmC}
 \end{aligned}$$

$$\begin{aligned}
 \text{NMHC}_d &= \text{FID THC}_d - (r_{\text{CH}_4} * \text{CH}_{4d}) \\
 &= 8.6 \text{ ppmC} - (1.20 * 5.27 \text{ ppmC}) \\
 &= 2.28 \text{ ppmC}
 \end{aligned}$$

$$\text{CO}_e = (1 - 0.01925 * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e.

$$\begin{aligned}
 &= (1 - 0.01925 * 1.19\% - 0.000323 * 38\%) * 147.18 \text{ ppm} \\
 &= 142.0 \text{ ppm}
 \end{aligned}$$

$$\begin{aligned}
 \text{DF} &= 13.46 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e) * 10^{-4}] \\
 &= 13.46 / [1.19\% + (32.76 \text{ ppmC} + 7.53 \text{ ppmC} + 142.0 \text{ ppmC}) * 10^{-4}] \\
 &= 11.14
 \end{aligned}$$

$$\begin{aligned}
 \text{NMHC}_{\text{conc}} &= \text{NMHC}_e - \text{NMHC}_d * [1 - (1 / \text{DF})] \\
 &= 32.76 \text{ ppmC} - 2.28 \text{ ppmC} * [1 - (1 / 11.14)] \\
 &= 30.68 \text{ ppmC}
 \end{aligned}$$

$$\begin{aligned}\text{NMHC}_{\text{mass}_n} &= \text{NMHC}_{\text{conc}} * \text{NMHC}_{\text{dens}} * \text{VMIX} * 10^{-6} \\ &= 30.68 \text{ ppmC} * 16.33 \text{ g/ft}^3 * 2846 \text{ ft}^3 * 10^{-6}\end{aligned}$$

$$\text{NMHC}_{\text{mass}_1} = 1.42 \text{ g}$$

Similarly, for Phase 2:

$$\text{NMHC}_{\text{mass}_2} = 0.32 \text{ g}$$

and for Phase 3:

$$\text{NMHC}_{\text{mass}_3} = 0.26 \text{ g}$$

Therefore,

$$\begin{aligned}\text{NMHC}_{\text{wm}} &= 0.43 * \frac{\text{NMHC}_{\text{mass}_1} + \text{NMHC}_{\text{mass}_2}}{D_{\text{phase}_1} + D_{\text{phase}_2}} + 0.57 * \frac{\text{NMHC}_{\text{mass}_3} + \text{NMHC}_{\text{mass}_2}}{D_{\text{phase}_3} + D_{\text{phase}_2}} \\ &= 0.43 * \frac{1.42 \text{ g} + 0.32 \text{ g}}{3.583 \text{ mile} + 3.848 \text{ mile}} + 0.57 * \frac{0.26 \text{ g} + 0.32 \text{ g}}{3.586 \text{ mile} + 3.848 \text{ mile}}\end{aligned}$$

$$\text{NMHC}_{\text{wm}} = 0.14 \text{ g/mile}$$

7.2 Given the following data for a vehicle operating on 85% methanol and 15% gasoline (M85), calculate the weighted NMHC mass emission.

Test	FID THC _e	FID THC _d	CH _{4e}	CH _{4d}	CH _{3OH_e}	CO _{em}	CO _{2e}	VMIX	D _{phase_n}	R _a
Phase	(ppmC)	(ppmC)	(ppmC)	(ppmC)	(ppmC)	(ppm)	(%)	(ft ³)	(mile)	(%)
1	88.5	5.5	17.76	2.82	72.9	303.2	1.28	2832	3.570	32
2	14.5	7.0	8.01	2.82	5.1	9.7	0.83	4827	3.850	32
3	21.8	7.7	10.13	2.93	7.4	18.2	1.13	2825	3.586	32

[For this example, CH_{3OH_d} was assumed to be 0.0 ppmC for all three background bag samples.]

For Phase 1:

$$\begin{aligned}\text{NMHC}_e &= \text{FID THC}_e - (r_{\text{CH}_4} * \text{CH}_{4e}) - (r_{\text{CH}_3\text{OH}} * \text{CH}_3\text{OH}_e) \\ &= 88.5 \text{ ppmC} - (1.20 * 17.76 \text{ ppmC}) - (0.78 * 72.9 \text{ ppmC}) \\ &= 10.33 \text{ ppmC}\end{aligned}$$

$$\begin{aligned}\text{NMHC}_d &= \text{FID THC}_d - (r_{\text{CH}_4} * \text{CH}_{4d}) - (r_{\text{CH}_3\text{OH}} * \text{CH}_3\text{OH}_d) \\ &= 5.5 \text{ ppmC} - (1.20 * 2.82 \text{ ppmC}) - (0.78 * 0.0 \text{ ppmC}) \\ &= 2.12 \text{ ppmC}\end{aligned}$$

$$\text{CO}_e = (1 - 0.02705 * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

$$\begin{aligned}&= (1 - 0.02705 * 1.28\% - 0.000323 * 32\%) * 303.2 \text{ ppm} \\ &= 289.6 \text{ ppm}\end{aligned}$$

$$\begin{aligned}\text{DF} &= 12.01 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{CH}_3\text{OH}_e) * 10^{-4}] \\ &= \frac{12.01}{1.28\% + (10.33 \text{ ppmC} + 17.76 \text{ ppmC} + 289.6 \text{ ppmC} + 72.9 \text{ ppmC}) * 10^{-4}} \\ &= 9.10\end{aligned}$$

$$\begin{aligned}\text{NMHC}_{\text{conc}} &= \text{NMHC}_e - \text{NMHC}_d * [1 - (1 / \text{DF})] \\ &= 10.33 \text{ ppmC} - 2.12 \text{ ppmC} * [1 - (1 / 9.10)] \\ &= 8.44 \text{ ppmC}\end{aligned}$$

$$\begin{aligned}\text{NMHC}_{\text{mass}_n} &= \text{NMHC}_{\text{conc}} * \text{NMHC}_{\text{dens}} * \text{VMIX} * 10^{-6} \\ &= 8.44 \text{ ppmC} * 16.33 \text{ g/ft}^3 * 2832 \text{ ft}^3 * 10^{-6}\end{aligned}$$

$$\text{NMHC}_{\text{mass}_1} = 0.39 \text{ g}$$

Similarly, for Phase 2:

$$\text{NMHC}_{\text{mass}_2} = 0.0 \text{ g}$$

and for Phase 3:

$$\text{NMHC}_{\text{mass}_3} = 0.004 \text{ g}$$

Therefore,

$$\begin{aligned} \text{NMHC}_{\text{wm}} &= 0.43 * \frac{\text{NMHC}_{\text{mass}_1} + \text{NMHC}_{\text{mass}_2}}{D_{\text{phase}_1} + D_{\text{phase}_2}} + 0.57 * \frac{\text{NMHC}_{\text{mass}_3} + \text{NMHC}_{\text{mass}_2}}{D_{\text{phase}_3} + D_{\text{phase}_2}} \\ &= 0.43 * \frac{0.39 \text{ g} + 0.0 \text{ g}}{3.570 \text{ mile} + 3.850 \text{ mile}} + 0.57 * \frac{0.004 \text{ g} + 0.0 \text{ g}}{3.586 \text{ mile} + 3.850 \text{ mile}} \end{aligned}$$

$$\text{NMHC}_{\text{wm}} = 0.023 \text{ g/mile}$$

8. DEFINITIONS

- CH_3OH_d = the methanol concentration in the dilution air as determined from the dilution air methanol sample using the procedure specified in method no. 1001, ppmC.
- CH_3OH_e = the methanol concentration in the dilute exhaust as determined from the dilute exhaust methanol sample using the procedure specified in method no. 1001, ppmC.
- CH_4_d = the methane concentration in the dilution air, ppmC.
- CH_4_e = the methane concentration in the dilute exhaust, ppmC.
- $\text{C}_2\text{H}_5\text{OH}_d$ = the ethanol concentration in the dilution air as determined from the dilution air ethanol sample using the procedure specified in method no. 1001, ppmC.
- $\text{C}_2\text{H}_5\text{OH}_e$ = the ethanol concentration in the dilute exhaust as determined from the dilute exhaust ethanol sample using the procedure specified in method no. 1001, ppmC.
- CO_e = the carbon monoxide concentration in the dilute exhaust corrected for carbon dioxide and water removal, ppm.
- CO_{em} = the carbon monoxide concentration in the dilute exhaust uncorrected for carbon dioxide and water removal, ppm.
- CO_{2e} = the carbon dioxide concentration in the dilute exhaust, %.
- D_{phase_n} = the distance driven by the test vehicle on a chassis dynamometer during test phase n (where n is either 1, 2, or 3), mile.
- DF = dilution factor.

- FID THC_d = the total hydrocarbon concentration including methane and methanol (for methanol-fueled engines) or ethanol (for ethanol-fueled engines) in the dilution air as measured by the FID, ppmC.
- FID THC_e = the total hydrocarbon concentration including methane and methanol (for methanol-fueled engines) or ethanol (for ethanol-fueled engines) in the dilute exhaust as measured by the FID, ppmC.
- HCR = the hydrogen-to-carbon ratio for the fuel used.
- NMHC_{conc} = the non-methane hydrocarbon concentration in the dilute exhaust corrected for background, ppmC.
- NMHC_d = the non-methane hydrocarbon concentration in the dilution air corrected for methane and alcohol removal, ppmC.
- NMHC_{dens} = the mass per unit volume of non-methane hydrocarbon corrected to standard conditions (16.33 g/ft³ at 293.16°K and 760 mm Hg assuming a C:H ratio of 1:1.85 and 17.28 g/ft³ for LPG at 293.16°K and 760 mm Hg), g/ft³.
- NMHC_e = the non-methane hydrocarbon concentration in the dilute exhaust corrected for methane and alcohol removal, ppmC.
- NMHC_{mass_n} = the mass emission of non-methane hydrocarbon per test phase n (where n is either 1, 2, or 3), g.
- NMHC_{wm} = the total weighted mass of non-methane hydrocarbon per mile for all three phases of the FTP, g/mile.
- R_a = the relative humidity of the ambient air, percent.
- $r_{\text{CH}_3\text{OH}}$ = the FID response factor to methanol (see CFR 40, 86.121-90(c)).
- r_{CH_4} = the FID response factor to methane (see section 4).
- $r_{\text{C}_2\text{H}_5\text{OH}}$ = the FID response factor to ethanol (same procedure for methanol response factor, see CFR 40, 86.121-90(c)).
- VMIX = the total dilute exhaust volume measured per test phase and corrected to standard conditions (293.16°K and 760 mm Hg), ft³.

9. REFERENCES

- (1) Code of Federal Regulations, title 40, part 86, subpart B
- (2) SAE J254, "Instrumentation and Techniques for Exhaust Gas Emissions Measurement"
- (3) SAE J1094a, "Constant Volume Sampler System for Exhaust Emissions Measurement"
- (4) SAE 770141, "Optimization of a Flame Ionization Detector for Determination of Hydrocarbon in Diluted Automotive Exhausts". G.D. Reschke, Vehicle Emissions Laboratory, General Motors Proving Ground
- (5) SAE J1154, "Methane Measurement Using Gas Chromatography", (revised December 1991)

AIR RESOURCES BOARD

DETERMINATION OF
ALCOHOLS
IN AUTOMOTIVE SOURCE SAMPLES BY GAS CHROMATOGRAPHY

METHOD NO. 1001

California Air Resources Board
Southern Laboratory Branch
Monitoring and Laboratory Division
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

1. INTRODUCTION

- 1.1 This document describes a method of sampling and analyzing automotive exhaust for alcohols in the range of 4 to 1200 micrograms (ug) per 15 milliliters (mL) of solution. Currently, the target alcohols are methanol and ethanol.
- 1.2 This procedure is based on a method developed by the EPA (Ref 9.1) which involves flowing diluted engine exhaust through deionized water contained in glass impingers and analyzing this solution by gas chromatography (GC).

2. METHOD SUMMARY

- 2.1 The samples are received by the laboratory in impingers. Compound separation and analysis are performed using a GC. The sample is injected into the GC by means of a liquid autosampler. Separation of the sample mixture into its component constituents is performed using a capillary column operated with a temperature gradient. A flame ionization detector (FID) is used for alcohol detection.
- 2.2 The computerized GC data system identifies the alcohol associated with each of the peaks. The alcohol concentrations are determined by integrating the peak areas and using calibration factors determined with external standards.

3. INTERFERENCES AND LIMITATIONS

- 3.1 An interference is any component present in the sample with a retention time similar to that of the target alcohols described in this method. To reduce interference error, proof of chemical identity may require performance of periodic confirmations using an alternate method and/or instrumentation, e.g., gas chromatograph/mass spectrometer (GC/MS).
- 3.2 The concentration of the alcohols in the range of interest is stable for thirty days as long as the samples are sealed and refrigerated at a temperature below 40°F.

4. INSTRUMENTATION AND APPARATUS

- 4.1 For each mode of the CVS test, two sampling impingers, each containing 15 ml deionized water, are used to contain the sample.
 - 4.1.1 A temperature-programmable GC, equipped with a DB-Wax Megabore column (30 meter (m), 0.53 millimeter (mm) ID, 1.0 micron (u) film thickness) and FID. A different column may be used, provided that it is demonstrated to the Executive Officer of the Air Resources Board to be equivalent or better with respect to precision, accuracy, and resolution of all the target alcohols.
 - 4.1.2 A liquid autosampler.

- 4.1.3 A PC-controlled data acquisition system for quantitation of peak areas is required.

5. REAGENTS AND MATERIALS

- 5.1 Methanol shall have a purity of 99.9 percent, high performance liquid chromatography grade, EM Science or equivalent.
- 5.2 Ethanol, absolute, ACS reagent grade.
- 5.3 American Standards for Testing Materials Type I deionized water.
- 5.4 A stock solution of 1 percent methanol and 1 percent ethanol is prepared by diluting 1 mL each of methanol and ethanol to 100 mL with deionized water.
- 5.4.1 A calibration standard of 50 parts per million (v/v) (ppm) is prepared by successive dilutions of the stock solution. Figure 1 illustrates a typical chromatogram of the analysis of the target alcohols.
- 5.4.2 A control standard containing all target alcohols is prepared by successive dilutions of a stock solution different from that of Section 5.4.1. This standard, at an approximate concentration of the samples, is used to update control charts for each target alcohol.
- 5.4.3 All standards should be refrigerated at less than 40°F during storage.
- 5.5 Gas requirements.
- 5.5.1 Air shall be "Zero" grade.
- 5.5.2 Nitrogen shall have a minimum purity of 99.998 percent.
- 5.5.3 Helium shall have a minimum purity of 99.995 percent.
- 5.5.4 Hydrogen shall have a minimum purity of 99.995 percent.

6. PROCEDURE

- 6.1 Each of six graduated fritted midget sampling impingers is filled with 15 mL of deionized water.
- 6.2 The six impingers are divided into three sets of two. A seventh is used as a field blank. Each set is connected in series and placed in an ice bath. The impingers are now ready for sample collection.
- 6.3 After sampling the impingers are allowed to warm to room temperature and the solution contained in each impinger is transferred to a vial and sealed.
- 6.3.1 Samples should be refrigerated (at 40°F or lower) if immediate analysis is not feasible, or if reanalysis at a later date may be required.

- 6.4 A 1 microliter aliquot of each unmodified sample is injected via autosampler into a GC, configured as follows:

Column: DB-wax, 30 m, 0.53 mm ID, 1.0 u film thickness
Carrier gas: Helium at 5 milliliters per minute (mL/min)
Make-up gas: Nitrogen at 25 mL/min
Detector: FID, Hydrogen at 30 mL/min and Air at 300 mL/min
Injector: Packed column injector with Megabore adapter insert; on-column injection
Temperature: 50°C (1 min), 50°C to 70°C (5°C/min), 70°C to 110°C (15°C/min), 110°C (4 min)
Data system: PC-based data acquisition system

Other operating conditions may be substituted provided that is demonstrated to the Executive Officer of the Air Resources Board that they produce equivalent or better resolution, precision, and accuracy than this method.

- 6.4.1 One calibration standard, one control standard, and one deionized water blank are analyzed daily at the beginning of each set of samples.
- 6.4.2 A replicate analysis is performed on one of every 10 samples, or at least once per shift.
- 6.4.3 The control standard is repeated every 10 samples and again at the end of the sample batch or day.
- 6.4.4 For compounds having concentrations above the documented range of instrument linearity, the sample must be diluted and reanalyzed.
- 6.4.5 The peak integrations are corrected as necessary in the data system. Any misplaced baseline segments are corrected in the reconstructed chromatogram.
- 6.4.6 The peak identifications provided by the computer are checked and corrected if necessary.
- 6.4.7 The level of peak rejection is set just below the lowest limit of detection (LOD).

7. CALCULATIONS

- 7.1 The concentration of each target alcohol, in ppm, is determined by the following calculation that compares the sample peak area with that of an external standard:

$$\text{Concentration (volume ppm)}_{\text{sample}} = \text{Area}_{\text{sample}} \times \text{Response Factor}$$

- 7.2 The response factor (RF) is calculated during the calibration by:

$$\text{RF} = \frac{\text{Concentration}_{\text{standard}}(\text{volume ppm})}{\text{Peak Area}_{\text{standard}}}$$

- 7.3 This concentration is then used to calculate the total amount of alcohol in each impinger:

$$\text{Mass (ug)} = \frac{\text{Concentration (volume ppm)} \times \text{Impinger volume (mL)}}{\text{Alcohol density (g/mL)}}$$

The alcohol densities are 0.7915 g/mL for methanol and 0.7890 g/mL for ethanol.

8. QUALITY CONTROL

- 8.1 Calibration and control standards are prepared every six months and analyzed daily.

8.2 Blank Run

A blank run is performed before running the calibration standard, control standard, and samples. All target alcohol concentrations from the blank analysis must be below the LOD before the analysis may proceed.

8.3 Calibration Run

One run of the calibration standard is performed to generate the calibration factor needed for quantitating sample analyses.

8.4 Control Standard Run

One run of the quality control standard is performed after the calibration run. Measurements of all target alcohols in the control standard must fall within the control limits before sample analysis may proceed. To meet this requirement, it may be necessary to inspect and repair the GC, and rerun the calibration and/or control standards.

8.5 Control Charts

Quality control chart(s) are maintained for each analyte of the control sample. The control chart, used on a daily basis, establishes that the method is in "statistical control". The following describes how to construct a typical control chart:

1. Obtain at least 20 daily control sample results,
2. Calculate the average control sample concentration and standard deviation(s) for the target analyte(s), and
3. Create a control chart for each target analyte by placing the concentration on the Y-axis and the date on the X-axis. Draw an upper warning limit and a lower warning limit at two standard deviations (2s) above and below the average concentration. Draw an upper control limit and a lower control limit at three standard deviations (3s) above and below the average concentration.

The control sample must be "in-control" for all target analytes for the sample results to be considered acceptable. A control sample measurement is considered to be "out-of-control" when the analyzed

value exceeds the 3s limit, or two successive control sample measurements of the same analyte exceed the 2s limit.

8.6 Duplicates

A duplicate analysis of one sample is performed for every 10 samples or at least once a day.

The relative percent difference (RPD) is calculated for each duplicate run:

$$\text{RPD (\%)} = \frac{\text{Difference between duplicate and original measurements}}{\text{Average of duplicate and original measurements}} \times 100$$

For each compound, the allowable RPD depends on the average concentration level for the duplicate runs, as shown in the following table:

<u>Average Measurement for Duplicate Runs</u>	<u>Allowable RPD (%)</u>
1 to 10 times LOD	100
10 to 20 " "	30
20 to 50 " "	20
Greater than 50 " "	15

If the results of the duplicate analyses do not meet these criteria for all target alcohols, the sample must be reanalyzed. If the criteria are still not met, all samples for the day/shift must be reanalyzed or deleted.

8.7 Linearity

A multipoint calibration to check for instrument linearity is performed for all target alcohols at least once every six months. The multipoint calibration consists of at least five concentration or mass loading levels above the LOD, evenly distributed over the range of expected linearity of the instrument. Each concentration level is measured at least twice. A linear regression analysis is performed using concentration and area counts to determine the regression correlation coefficient (r). The r must be greater than 0.995 to be considered sufficiently linear for one point calibrations.

8.8 Limit of Detection

The limit of detection for the target alcohols must be determined at least every six months. To make the necessary calculations, it is necessary to perform a multipoint calibration consisting of at least four "low" concentration levels above the LOD. The LOD must be calculated using the following equation (Ref 9.2):

$$\text{LOD} = |A| + 3.3(S)$$

where each term in the equation is expressed in concentration units, and |A| is the absolute value of the least squares X-intercept calculated from the multipoint data.

S is the standard deviation of replicate determinations of the lowest standard. At least three replicates are required. The lowest standard

must be run at one to five times the estimated detection limit. If data is not available in the concentration range near the detection limit, $\underline{S}$ may be estimated by:

$$\underline{S} = \text{RSD} \times |\Delta|$$

where RSD is the relative standard deviation of the lowest standard analyzed.

An example of typical LODs is given in the table below:

<u>COMPOUND</u>	<u>LOD (ppm)</u>
methanol	0.24
ethanol	0.17


The maximum allowable LOD for each alcohol is 0.50 ppm.

9. REFERENCES

- 9.1 U.S. Environmental Protection Agency, Characterization of Exhaust Emissions from Methanol and Gasoline Fueled Automobiles, EPA 460/3-82-004.
- 9.2 U.S. Environmental Protection Agency, Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air, (Method T03-15) EPA-600/4-89-017 Research Triangle Park, North Carolina, June, 1989.

SAMPLE NO.: 89005893.01
 TEST NO.: ALCOH
 METHOD NO.: ALCO1 / ALCO1
 100.00

INSTRUMENT: 18
 DATE TIME: 05/25/89 14:13:25
 PAGE NO.: 01



Y MAXIMUM: 545.
 Y MINIMUM: 54.

START TIME: 0.00
 END TIME: 6.00

Figure 1. A typical chromatogram of the analysis of the target alcohols.

AIR RESOURCES BOARD

DETERMINATION
OF C₂ TO C₅ HYDROCARBONS
IN AUTOMOTIVE SOURCE SAMPLES BY GAS CHROMATOGRAPHY

METHOD NO. 1002

California Air Resources Board
Southern Laboratory Branch
Monitoring and Laboratory Division
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

1. INTRODUCTION

- 1.1 This document describes a method of determining, by gas chromatograph, C₂ to C₅ hydrocarbons (light-end hydrocarbons) in the range of parts per billion carbon (ppbC) from automotive source samples. This method does not include sample collection procedures (Ref 9.1). Currently, the target hydrocarbons analyzed and reported by this method are listed in Attachment 1. Hexane is also measured as a light/mid-range crossover compound for quality control purposes, but is not reported.

2. METHOD SUMMARY

- 2.1 This is a rapid method intended for routine analysis.
- 2.2 The samples are received by the laboratory in Tedlar bags, which are sub-sampled into a gas chromatograph (GC) for separation and analyses.
- 2.3 The gas chromatographic analysis is performed on a packed column operated isothermally at 35°C, or a Alumina (Al) Porous Layer Open Tubular (PLOT) column temperature programmed from 0°C to 200°C. A flame ionization detector (FID) is used for detection. Other columns and operating conditions may be used, provided baseline resolution of peaks can be achieved.
- 2.4 The sample is cryogenically preconcentrated and injected into the GC by means of gas sampling valves. Separation of the sample hydrocarbon mixture into its component constituents takes place in the chromatographic column. The chromatographic column and the corresponding operating parameters described in this method normally provide complete resolution of most target hydrocarbons.
- 2.5 The computerized GC data system identifies the hydrocarbons associated with each of the peaks. The hydrocarbon concentrations are determined by integrating the peak areas and using calibration factors determined with NIST-traceable standards.

3. INTERFERENCES AND LIMITATIONS

- 3.1 An interference is any component present in the sample with a retention time very similar to that of the target hydrocarbons described in this method. To reduce interference error, proof of chemical identity may require performance of periodic confirmations using an alternate method and/or instrumentation, e.g., gas chromatograph/mass spectrometer, photoionization detector, etc.
- 3.2 To maximize sample integrity, sample bags should not leak or be exposed to bright light or excessive heat. Sampling bags must be shielded from direct sunlight to avoid changes as a result of reaction of the reactive hydrocarbons. The compound 1,3-butadiene, most of which is in CVS bag no. 1, is unstable. Therefore all CVS bag no. 1 samples must be analyzed within 2 hours; CVS bag no. 2, CVS bag no. 3, and background samples must be analyzed within 24 hours, although analysis within 8 hours is recommended.

4. INSTRUMENTS AND APPARATUS

- 4.1 Tedlar bags, 2 mil in thickness, nominally 5 to 10 liters in capacity and equipped with quick-connect fittings, are used to contain the sample.
- 4.2 For manual sub-sampling into a GC, a ground glass syringe (100 milliliters (ml) capacity) is used to transfer gaseous samples from Tedlar bags to the GC sample inlet. For automated systems, a metering valve and timing system are used to transfer a minimum of 10 ml from the Tedlar bag to the sample inlet of the GC. The sample aliquot size is nominally 100 ml. Other aliquot sizes may be chosen, based on considerations of instrument sensitivity or linearity.
- 4.3 A temperature programmable GC equipped with a gas sampling valve system, a FID, and accessories is required (See Figure 1).
- 4.4 A stainless steel column [6 feet (ft) x 1/8 inch (in)] packed with phenylisocyanate Durapak 80/100 mesh. Other column(s) may be used, provided that it can be demonstrated to the Executive Officer of the Air Resources Board that the alternate system is equivalent or better with respect to precision, accuracy and resolution of all the target hydrocarbons. An Al PLOT column (60 m x 0.32 mm) has been shown to be equivalent.
- 4.5 A stainless steel sample trap capable of being cryogenically cooled is required.
- 4.6 An electronic integrator for quantitation of peak areas is required. If the data cannot record the chromatogram, an analog recorder is also required.
- 4.7 Dewar flasks (250 ml) are used to contain liquid nitrogen or hot water.

5. REAGENTS AND MATERIALS

- 5.1 Helium shall have a minimum purity of 99.995 percent. Pass the helium through a trap immersed in liquid nitrogen to ensure purity before entering the GC. For automated systems, helium purity of 99.9999 percent is required.
- 5.2 Hydrogen shall have a minimum purity of 99.995 percent.
- 5.3 Air shall be "Zero" grade.
- 5.4 Calibration Standard - The quantitative calibration standard for all target hydrocarbons shall be propane at a concentration level between 40 to 60 ppb-mole. This propane standard shall be analyzed by the National Institute of Standards and Technology (NIST) in order to verify traceability with a NIST primary propane standard. The use of NIST-certified weights in the gravimetric preparation of standards will not alone satisfy NIST traceability. It is recommended that at least the following target compounds be included in the NIST propane calibration standard for the purpose of qualitative verification: ethane, ethene, propene, methylpropane, n-butane, ethyne, 2-methylpropene, 1-butene, methylbutane, and n-pentane. Figure 2 illustrates a typical chromatogram of the analysis of the light-end hydrocarbons.

Alternative standards (non-NIST) may be used if shown to yield equivalent or better results and if approved in advance by the Executive Officer of the Air Resources Board.

- 5.5 Control Standard - A quality control standard, containing ethane, ethene, propane, propene, methylpropane, n-butane, ethyne, 2-methylpropene, 1-butene, methylbutane and n-pentane within a concentration range of samples (30 to 50 ppb-mole), is used for the following quality control purposes:

1. Daily update of control charts,
2. Daily determination of retention time windows if target compounds are not in the NIST calibration standard mixture, and
3. Semi-annual determination of LOD and linearity checks if NIST-traceable standards are not available.

The control standard(s) must have concentrations verified against a NIST-traceable propane standard (See Section 5.4 for definition of NIST-traceable) when used for either LOD determinations or linearity checks. This verification can be performed at the laboratory conducting the sample analysis.

- 5.6 A high concentration calibration standard, containing the target hydrocarbons listed in Section 5.4, nominally 2 ppm (4 to 10 parts per million carbon (ppmC)), is used semi-annually for LOD and linearity determinations. The high calibration standard must have concentrations verified against a NIST-traceable propane standard. This verification can be performed at the laboratory performing the analysis.
- 5.7 Liquid nitrogen is used to cool the cryogenic sample trap and column oven where applicable.

6. PROCEDURE

- 6.1 The gaseous sample is analyzed for the target hydrocarbons C₂ through C₆ by using a cryogenic preconcentration method.
- 6.2 Typical standard operating conditions for the gas chromatograph are:

Helium carrier gas flow:	50 milliliter/minute (ml/min)
Hydrogen gas flow:	32 ml/min
Oxygen gas flow:	153 ml/min
Sample valve temperature:	ambient
Heating bath temperature:	60 - 80°C
Injector temperature:	35°C
Column temperature:	35°C (isothermal)
	0° to 200°C (temperature program)
Detector temperature:	200°C

Other operating conditions may be substituted provided that it can be demonstrated to the Executive Officer of the Air Resources Board that

they produce equivalent or better resolution, precision, and accuracy, than this method.

- 6.3 Cool the sample trap with liquid nitrogen and allow temperature to stabilize. For traps immersed in liquid nitrogen, temperature equilibrium is achieved when liquid nitrogen stops boiling.
- 6.4 Withdraw a precisely measured sample (± 2 percent) aliquot (nominally 100 ml) from the sample and inject the sample into the freeze-out sample trap.
- 6.5 For manual GC analysis using a 100 ml syringe, refill the syringe with another 20 ml of helium and flush the 20 ml through the trap. Then flush helium through the loop for two mins to flush out the condensed oxygen.
- 6.6 Isolate the cryogenic trap by using the isolation valve, to prevent loss of sample when the trap is heated.
- 6.7 Replace the liquid nitrogen Dewar with a hot water Dewar at about 60-80°C.
- 6.8 Allow sufficient time for the temperature of the trap to rise until the ice accumulated on the surface of the trap is melted completely.
- 6.9 Introduce the sample into the carrier gas stream through the injection valve.
- 6.10 For automated systems, connect the sample bag to the GC queue and begin the analytical process.
- 6.11 Each separated component exits from the column through the FID where a response is generated.
- 6.12 Concentrations of hydrocarbons are calculated by an electronic integrator device, which has been calibrated using a NIST-traceable propane calibration standard.
- 6.13 For compounds having concentrations above the documented range of instrument linearity, the sample must be diluted and reanalyzed.
- 6.14 The peak integrations are corrected as necessary in the data system. Any misplaced baseline segments are corrected in the reconstructed chromatogram.
- 6.15 The peak identifications provided by the computer are checked and corrected if necessary.
- 6.16 The level of peak rejection is set just below the limit of detection of the lowest LOD.
- 6.17 The maximum retention time in this analysis is typically about 16 mins.
- 6.18 After each run, the column is back-flushed with helium while the column temperature is raised and maintained at 60°C for 15 mins, or as required to flush the column. The A1 PLOT column is programmed to 200°C to assure all compounds are eluted before the next run.

- 6.19 Before the next run, sufficient time (typically 15 mins) is allowed after back-flush of column to re-establish the required temperature of the column.
- 6.20 The total run time is typically about 45-50 mins.

7. CALCULATIONS

- 7.1 The hydrocarbon concentrations, in ppbC, are calculated by the data system using an external standard method.

$$\text{Concentration}_{\text{sample}} = \frac{\text{Peak Area}_{\text{sample}}}{\text{Area}_{\text{standard}}} \times \text{Response Factor}$$

- 7.2 The response factor (RF) is calculated during the calibration by:

$$\text{RF} = \frac{\text{Concentration of NIST-traceable propane standard, ppbC}}{\text{Area of propane peak}}$$

8. QUALITY CONTROL

8.1 Blank Run

A blank (pure nitrogen or helium) run is performed before running the calibration standard (see 5.4 for method's definition of calibration standard), control standard (see 5.5 for method's definition of quality control standard), and samples. All target hydrocarbons concentrations from the blank analysis must be below the LOD before the analysis may proceed.

8.2 Calibration Run

One run of the calibration standard is performed to generate the calibration factor needed for quantitating sample analyses.

8.3 Control Standard Run

One run of the quality control standard is performed after the calibration run. Measurements of all compounds in the control standard must fall within the control limits before sample analysis may proceed. To meet this requirement, it may be necessary to inspect and repair the GC, and rerun the calibration and/or control standards.

8.4 Control Charts

Quality control chart(s) are maintained for each component of the control sample. The control chart, used on a daily basis, establishes that the method is in "statistical control". The following describes how to construct a typical control chart:

1. Obtain at least 20 daily control sample results,
2. Calculate the average control sample concentration and standard deviation(s) for each target hydrocarbon, and
3. Create a control chart for each target hydrocarbon by placing concentration on Y-axis and the date on the X-axis. Draw an upper warning limit and a lower warning limit at two standard

deviations (2s) above and below the average concentration. Draw an upper control limit and a lower control limit at three standard deviations (3s) above and below the average concentration.

The control sample must be "in-control" for all target hydrocarbons listed in Section 5.4 for the sample results to be considered acceptable. A control sample measurement is considered to be "out-of-control" when the analyzed value sample measurement exceeds the 3s limit, or two successive control sample measurements of the same analyte exceed the 2s limit.

8.5 Duplicates

A duplicate analysis of one sample is performed for every 10 samples or at least once a day. The relative percent difference (RPD) is calculated for each duplicate run:

$$\text{RPD (\%)} = \frac{\text{Difference between duplicate and original measurements}}{\text{Average of duplicate and original measurements}} \times 100$$

For each compound, the allowable RPD depends on the average measurement for the duplicate runs, as shown in the following table:

<u>Average Measurement for the Duplicate Runs</u>			<u>Allowable RPD (%)</u>
1 to 10 times	LOD		100
10 to 20	"	"	30
20 to 50	"	"	20
Greater than 50	"	"	15

~~If the results of the duplicate analyses do not meet these criteria for all target hydrocarbons, the sample must be reanalyzed. If the criteria are still not met, all samples for the day/shift must be reanalyzed or deleted.~~

8.6 Linearity

A multipoint calibration to check for instrument linearity is performed for the target hydrocarbons listed in Section 5.4 at least once every six months. The multipoint calibration consists of at least five concentration or mass loading levels (using smaller or larger volume sample sizes of existing standards is acceptable) above the LOD, evenly distributed over the range of expected linearity of the instrument. Each concentration level is measured at least twice. A linear regression analysis is performed using concentration and average area counts to determine the regression correlation coefficient (r). The r must be greater than 0.995 to be considered sufficiently linear for one point calibrations.

8.7 Limit of Detection

The limit of detection for the target hydrocarbons must be determined at least every six months. To make the necessary calculations, it is necessary to perform a multipoint calibration consisting of at least four "low" concentration levels above the LOD. The LOD must be calculated using the following equation (Ref 9.2):

$$\text{LOD} = |A| + 3.3(S)$$

where $|\Delta|$ is the least squares X-intercept calculated from the multipoint data.

$\underline{S}$ is the standard deviation of replicate determinations of the lowest standard. At least three replicates are required. The lowest standard must be run at one to five times the estimated detection limit. If data is not available in the concentration range near the detection limit, $\underline{S}$ may be estimated by:

$$\underline{S} = \text{RSD} \times |\Delta|$$

where RSD is the relative standard deviation of the lowest standard analyzed.

An example of typical LODs is given in the table below:

<u>COMPOUND</u>	<u>LOD (ppbC)</u>
ethane	1.0
ethene	1.7
propane	0.9
ethyne	1.7
methylpropane	1.2
butane	1.4
propene	2.3
methylbutane	4.3
pentane	3.5
1-butene	2.4
2-methylpropene	1.2

The maximum allowable LOD for each compound is 5 ppbC propane.

For purposes of calculating the total mass (ppbC) of all species, the concentrations of all compounds below the LOD are considered to be zero.

8.8 Method 1002/Method No. 1003 Crossover Check

For each sample, hexane shall be measured by both Method No. 1002 (C_2 to C_5 hydrocarbons) and Method No. 1003 (C_6 to C_{12} hydrocarbons). The RPD is calculated as in Section 8.5. The allowable RPD depends on the average concentration level for the two analyses, as shown in the following table:

<u>Method Nos. 1002, 1003 Average Hexane Measurement</u>	<u>Allowable RPD (%)</u>
1 to 10 times Method 1003 hexane LOD	150
10 to 20 " " " " "	50
20 to 50 " " " " "	35
Greater than 50 " " " " "	30

All samples analyzed during the day/shift for which this criteria is not met for hexane must be reanalyzed or deleted.

9. REFERENCES

- 9.1 Standard Test Method for C₁ Through C₆ Hydrocarbons in the Atmosphere by Gas Chromatography, American Standards for Testing Materials (ASTM) Standards on Chromatography (1981).
- 9.2 U.S. Environmental Protection Agency, Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air (Method T03-15), EPA-600/4-84-041, Research Triangle Park, North Carolina, April, 1989.

Attachment 1
List of C₂ to C₅ Hydrocarbons
(listed by approximate order of elution)

ethane
ethene
propane
propene
methylpropane
n-butane
ethyne
propadiene*
1-propyne
t-2-butene
1-butene
2-methylpropene
dimethylpropane
1-butyne
c-2-butene
methylbutane
n-pentane
1,3-butadiene
3-methyl-1-butene
t-2-pentene
2-butyne
1-pentene
2-methyl-1-butene
c-2-pentene
2-methyl-1,3-butadiene
2-methyl-2-butene
cyclopentadiene
cyclopentene
cyclopentane

* Propadiene may coelute with 1-propyne

AIR RESOURCES BOARD

DETERMINATION
OF C₆ TO C₁₂ HYDROCARBONS
IN AUTOMOTIVE SOURCE SAMPLES BY GAS CHROMATOGRAPHY

METHOD NO. 1003

California Air Resources Board
Southern Laboratory Branch
Monitoring and Laboratory Division
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

1. INTRODUCTION

- 1.1 This procedure describes a method of analyzing, by gas chromatography, C₆ to C₁₂ hydrocarbons (midrange hydrocarbons) in the range of parts per billion carbon (ppbC) from automotive source samples. This method does not include sample collection procedures. The target hydrocarbons analyzed and reported by this method are listed in Attachment 1.

2. METHOD SUMMARY

- 2.1 This is a rapid method intended for routine analysis.
- 2.2 The samples are received by the laboratory in Tedlar bags, which are sub-sampled into a gas chromatograph (GC) for separation and analyses.
- 2.3 The gas chromatographic analysis is performed through a capillary column operated using gradient temperature. A flame ionization detector (FID) is used for detection. A photoionization detector (PID) may be used to help with compound identification.
- 2.4 The sample is injected into the GC by means of gas sampling valves. Separation of the sample hydrocarbon mixture into its component constituents takes place in the chromatographic column. The chromatographic column and the corresponding operating parameters described in this method normally provide complete resolution of most target hydrocarbons. When collution exists, periodic measurements with another method (GC/MS, for example) are perfoemd to estimate the expected relative sizes of the colluting peaks.
- 2.5 The computerized GC data acquisition system identifies the hydrocarbons associated with each of the peaks. The hydrocarbon concentrations are determined by integrating the peak areas and using a calibration factor determined with an external standard.

3. INTERFERENCES AND LIMITATIONS

- 3.1 An interference is any component present in the sample with a retention time similar to that of the target hydrocarbons described in this method. To reduce interference error, proof of chemical identity may require performance of periodic confirmations using an alternate method and/or instrumentation, e.g., gas chromatograph/mass spectrometer (GC/MS), photoionization detector (PID), different column, etc.
- 3.2 The concentration of hydrocarbons in the range of interest is stable for at least 72 hours in the Tedlar sampling bags, provided the sample bags do not leak and are not exposed to bright light or excessive heat. Sampling bags must be shielded from direct sunlight to avoid losses from reaction of the reactive hydrocarbons. Samples should be analyzed within 24 hours whenever possible.

4. INSTRUMENTATION AND APPARATUS

- 4.1 Tedlar bags, 2 mil in thickness, nominally 5 to 10 liters in capacity and equipped with quick-connect fittings, are used to contain the sample.

- 4.2 For manual subsampling into a GC, a ground glass syringe (nominally 250 milliliter (ml) capacity) is used to transfer the gaseous samples from Tedlar bags to a nominal 50 ml sample loop for concentration in the cryogenic trap. For automated systems, a valve, metering and timer system is used to transfer an aliquot from the Tedlar bag to the cryogenic trap. Other aliquot sizes may be chosen, or dilution of the sample performed, based on considerations of instrument sensitivity or linearity.
- 4.3 The GC is equipped with a FID, a PID, and a gas sampling valve system connected to a cryogenic trap.
- 4.4 A Valco rotary valve is connected to a cryogenic sample concentration system. A schematic of the valve system is shown in Figure 1.
- 4.5 A capillary column [J&W DB-1, 60 m x 0.32 mm ID, film thickness 1.0 micron] is used. Other column(s) may be used, provided that it can be demonstrated to the Executive Officer of the Air Resources Board that the alternate system is equivalent or better with respect to precision, accuracy, and resolution of all the target hydrocarbons.
- 4.6 A computer-controlled data acquisition system is required for the quantitation of peak areas.
- 4.7 Dewar flasks are used to contain liquid nitrogen or hot water. A convenient size is 250 ml.

5. REAGENTS AND MATERIALS

- 5.1 Helium shall have a minimum purity of 99.995 percent. For automated systems, 99.9999 percent is required.
- 5.2 Hydrogen shall have a minimum purity of 99.995 percent.
- 5.3 Air shall be "Zero" grade.
- 5.4 Nitrogen shall have a minimum purity of 99.9 percent.
- 5.5 Calibration Standard - The quantitative calibration standard for all target hydrocarbons shall be benzene at a concentration level between 80 to 120 ppb-mole. This benzene standard shall be analyzed by the National Institute of Standards and Technology (NIST) in order to verify traceability with a NIST primary benzene standard. The use of NIST-certified weights in the gravimetric preparation of standards will not alone satisfy NIST traceability. It is recommended that at least n-hexane, n-octane, n-decane, toluene, and m-xylene also be included in the NIST calibration standard for the purpose of qualitative verification.

Alternative standards (non-NIST) may be used provided that it is demonstrated to the Executive Officer of the Air Resources Board that they produce equivalent or better resolution, precision and accuracy than this method.

- 5.6 Control Standard - A quality control standard, containing at least n-hexane, n-octane, n-decane, benzene, toluene, and m-xylene species within a concentration range of samples (20 to 100 ppb-mole) is used for the following quality control purposes:

1. Daily update of control charts,
2. Daily determination of retention time windows if control compounds are not in the NIST calibration standard mixture, and
3. Semi-annual determination of limit of detection (LOD) and linearity checks if NIST-traceable standards are not available.

The control standard(s) must have concentrations verified against a NIST-traceable benzene (See Section 5.5 for definition of NIST-traceable) when used for either LOD determinations or linearity checks. This verification can be performed at the laboratory conducting the sample analysis.

- 5.7 A high concentration calibration standard, containing the control hydrocarbons, nominally 0.4 to 1.0 parts per million carbon (ppmC) concentration is used semi-annually for LOD and linearity determinations. The high calibration standard must have concentrations verified against a NIST-traceable benzene standard (See Section 5.5 for definition of NIST-traceable). This verification can be performed at the laboratory performing the analysis.
- 5.8 Liquid nitrogen is used to cool the cryogenic trap and column oven.

6. PROCEDURE

- 6.1 The vehicle exhaust sample is analyzed for the target hydrocarbons by using a cryogenic preconcentration method.
- 6.2 Typical operating conditions
- 6.2.1 Typical operating conditions for the manual GC are:

Helium carrier gas average linear velocity 30 centimeters/second at 200°C
Nitrogen make-up gas flow 30 ml/minute (min)
Hydrogen gas flow (for FID) 30 ml/min
"Zero" air gas flow (for FID) 300 ml/min
Autozero FID and PID at 0.0 min
Range 11, Attenuation 8 (or another suitable value)
Sample valve temperature: 150°C
Injector temperature: 150°C
Column Entrance Port temperature: 95°C
Detector temperature: 250°C
Column temperature: Initial temperature 0°C; 10°C/min to 200°C

6.2.2 Typical operating conditions for the automated GC are:

Helium carrier gas average linear velocity 20 centimeters/second at 200°C

Nitrogen make-up gas flow 30 ml/min

Hydrogen gas flow (for FID) 30 ml/min

"Zero" air gas flow (for FID) 300 ml/min

Autozero FID and PID at 0.0 min

Range 11, attenuation 8 (or another suitable value)

Sample valve temperature: 150°C

Detector temperature: 250°C

Column temperature: Initial temperature 0°C (5 min), 5°C/min to 50°C, 10°C/min to 200°C

Other operating conditions may be substituted provided that it can be demonstrated to the Executive Officer of the Air Resources Board that they produce equivalent or better resolution, precision, and accuracy.

6.3 Manual Sample Preconcentration

6.3.1 The trap is immersed in a Dewar filled with liquid nitrogen before obtaining the sample.

6.3.2 An aliquot of the sample is transferred from the sample bag via a 250 ml syringe to a nominal 50 ml sample loop and concentrated in the cryogenic trap.

6.3.3 The cryogenic trap is flushed for 3 minutes with helium at a flow rate of 40 ml/min.

6.3.4 The GC is cooled down to 0°C while the sample is being sub-sampled into the trap.

6.3.5 The analysis begins when the start button on the GC and the data acquisition system are activated simultaneously. An external event signal triggers the turning of the sample valve, thereby diverting carrier gas through the cryogenic trap. The Dewar of liquid nitrogen in which the trap is immersed is immediately replaced by a flask of boiling water. This vaporizes and transfers the sample through a heated entrance port into the capillary column.

6.3.6 Each separated compound passes through the PID and afterwards through the FID.

6.4 Automated Sample Preconcentration

6.4.1 With cryotrap cooled to 120°C (instrument setting of -30) valves 3 and 3A are turned on to flush the sample from the 100ml sample loop into the cryotrap. This flushing is continued for 2.9 min to be sure all the sample is transferred and to flush the air components (oxygen and nitrogen) out of the cryotrap.

6.4.2 The cryotrap is isolated and heated to 200°C (instrument setting of 250) to re-evaporate the analyte.

6.4.3 Valves 2 and 4 are turned to inject the evaporated analyte into the analytical column.

6.5 Data Reduction

6.5.1 The peak reject for shall be set at or below the lowest LOD.

6.5.2 The results are calculated from the FID responses. The PID responses are used to help with peak identifications as the PID responds more strongly to aromatics and olefins.

6.5.3 The results are examined to see that the peaks are correctly identified and integrated.

6.5.4 After running a particularly "dirty" sample, the analyst should run a blank before proceeding to the next sample as there may be sample carryover, or flush the sampling system with air.

6.5.5 The peak identifications provided by the computer are reviewed and, if necessary, corrected using the following procedure and criteria:

(1) The relative retention indices from GC/MS analyses are used to help confirm peak identifications.

(2) The primary peak identification is done by the computer using the relative retention times based on reference calibration runs.

(3) Confirm that the largest peaks of the sample run ("fingerprint") match the typical fingerprint seen in past sample runs.

(4) Compare the relative retention time of the sample peaks with those of reference runs.

(5) Any peak with a reasonable doubt is labeled 'Unidentified'.

6.5.6 The concentrations of the hydrocarbons are calculated by an electronic integrator device.

7. CALCULATIONS

7.1 The target hydrocarbon concentrations, in ppbC, are calculated by the data system using benzene as an external standard.

$$\text{Concentration}_{\text{sample}} \text{ PPbC} = \frac{\text{Peak Area}_{\text{sample}}}{\text{Area of benzene peak}} \times \text{Response Factor}$$

7.2 The Calibration Factor (RF) is calculated during daily calibration by:

$$\text{RF} = \frac{\text{Concentration of NIST-traceable benzene, ppbC}}{\text{Area of benzene peak}}$$

8. QUALITY CONTROL

8.1 Blank Run

A blank (pure nitrogen or helium) run is performed before running the calibration standard, control standard, and samples. All target hydrocarbons concentrations from the blank analysis must be below the LOD before the analysis may proceed.

8.2 Calibration Run

One run of the calibration standard (see section 5.5 for definition of calibration standard) is performed to generate the calibration factor needed for quantitating sample analyses.

8.3 Control Standard Run

One run of the quality control standard (see section 5.6 for definition of quality control standard) is performed after the calibration run. Measurements of all compounds in the control standard must fall within the control limits before sample analysis may proceed. To meet this requirement, it may be necessary to inspect and repair the GC, and rerun the calibration and/or control standards.

8.4 Control Charts

Quality control chart(s) are maintained for each component of the control sample. The control chart, used on a daily basis, establishes that the method is in "statistical control". The following describes how to construct a typical control chart:

1. Obtain at least 20 daily control sample results,
2. Calculate the average control sample concentration and standard deviation(s) for each target hydrocarbon, and
3. Create a control chart for each target hydrocarbon by placing the concentration on Y-axis and the date on the X-axis. Draw an upper warning limit and a lower warning limit at two standard deviations (2s) above and below the average concentration. Draw an upper control limit and a lower control limit at three standard deviations (3s) above and below the average concentration.

The control sample must be "in-control" for all target hydrocarbons for the sample results to be considered acceptable. A control sample measurement is considered to be "out-of-control" when the analyzed value exceeds the 3s limit, or two successive control sample measurements of the same analyte exceed the 2s limit.

8.5 Duplicates

A duplicate analysis of one sample is performed for every 10 samples or at least once per day/shift.

The relative percent difference (RPD) is calculated for each duplicate run:

$$\text{RPD (\%)} = \frac{\text{Difference between duplicate and original measurements}}{\text{Average of duplicate original measurements}} \times 100$$

For each compound, the allowable RPD depends on the average concentration level for the duplicate runs, as shown in the following table:

<u>Average Measurement for Duplicate Runs</u>		<u>Allowable RPD (%)</u>
1 to 10	times LOD	100
10 to 20	" "	30
20 to 50	" "	20
Greater than 50	" "	15

If the results of the duplicate analyses do not meet these criteria for all target hydrocarbons, the sample must be reanalyzed. If the criteria are still not met, all samples for the day/shift must be reanalyzed or deleted.

8.6 Linearity

A multipoint calibration to check for instrument linearity is performed for all target hydrocarbons in the control standard at least once every six months. The multipoint calibration consists of at least five concentration or mass loading levels (using smaller or larger volume sample sizes of existing standards is acceptable) above the LOD, evenly distributed over the range of expected linearity of the instrument. Each concentration level is measured at least twice. A linear regression analysis is performed using concentration and average area counts to determine the regression correlation coefficient (r). The r must be greater than 0.995 to be considered sufficiently linear for one point calibrations.

8.7 Limit of Detection

The limit of detection for the target hydrocarbons in the control standard must be determined at least every six months. To make the necessary calculations, it is necessary to perform a multipoint calibration consisting of at least four "low" concentration levels above the LOD. The LOD must be calculated using the following equation (Ref 9.1):

$$\text{LOD} = |\Delta| + 3.3(\underline{S})$$

where each term in the equation is expressed in concentration units, and $|\Delta|$ is the absolute value of the least squares X-intercept calculated from the multipoint data.

$\underline{S}$ is the standard deviation of replicate determinations of the lowest standard. At least three replicates are required. The lowest standard must be run at one to five times the estimated detection limit. If data is not available in the concentration range near the detection limit, $\underline{S}$ may be estimated by:

$$\underline{S} = \text{RSD} \times |\Delta|$$

where RSD is the relative standard deviation of the lowest standard analyzed.

An example of typical LODs is given in the table below:

<u>COMPOUND</u>	<u>LOD (ppbC)</u>
n-hexane	20
n-octane	7
n-decane	10
benzene	10
toluene	7
m-xylene	9

The maximum allowable LOD for any compound is 20 ppbC benzene.

For purposes of calculating the total mass (ppbC) of all species, the concentrations of the compounds below the LOD are considered to be zero.

8.8 Method No. 1002/Method No. 1003 Crossover Check

For each sample, hexane shall be measured by both Method No. 1002 (C₂ to C₅ hydrocarbons) and Method No. 1003 (C₆ to C₁₂ hydrocarbons). The RPD is calculated as in Section 8.5. The allowable RPD depends on the average concentration for the two analyses, as shown in the following table:

<u>Method 1002, 1003 Average Hexane Concentration</u>	<u>Allowable RPD (%)</u>
1 to 10 times Method 1003 hexane LOD	100
10 to 20 " " " " "	30
20 to 50 " " " " "	25
Greater than 50 " " " " "	20

All samples analyzed during the day/shift for which this criteria is not met for hexane must be reanalyzed or deleted.

9. REFERENCE

- 9.1 U.S. Environmental Protection Agency, Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air (Method T03-15), EPA-600/4-89-017, Research Triangle Park, North Carolina, June 1989.

Attachment 1
List of Mid-Range Hydrocarbons
(listed by approximate order of elution)

3,3-dimethyl-1-butene
2,2-dimethylbutane
4-methyl-1-pentene
3-methyl-1-pentene
2,3-dimethylbutane
4-methyl-cis-2-pentene
2-methylpentane
4-methyl-trans-2-pentene
3-methylpentane
2-methyl-1-pentene
1-hexene
n-hexane
trans-3-hexene
cis-3-hexene
trans-2-hexene
3-methyl-trans-2-pentene
2-methyl-2-pentene
3-methylcyclopentene
cis-2-hexene
3-methyl-cis-2-pentene
2,2-dimethylpentane
methylcyclopentane
2,4-dimethylpentane
2,2,3-trimethylbutane
3,4-dimethyl-1-pentene
1-methylcyclopentene*
benzene*
3-methyl-1-hexene
3,3-dimethylpentane
cyclohexane
2-methylhexane
ethylcyclopentane
2,3-dimethylpentane
1,1-dimethylcyclopentane
cyclohexene
3-methylhexane
cis-1,3-dimethylcyclopentane
3-ethylpentane
2,2,4-trimethylpentane
trans-1,2-dimethylcyclopentane
1-heptene
trans-3-heptene
n-heptane
2-methyl-2-hexene
3-methyl-t-3-hexene

trans-2-heptene
3-ethyl-cis-2-pentene
2,4,4-trimethyl-1-pentene
2,3-dimethyl-2-pentene
cis-2-heptene
methylcyclohexane
2,2-dimethylhexane
2,4,4-trimethyl-2-pentene
2,5-dimethylhexane
2,4-dimethylhexane
3,3-dimethylhexane
2,3,4-trimethylpentane
5-ethylcyclopentene
2,3,3-trimethylpentane**
toluene**
2,3-dimethylhexane
2-methylheptane
4-methylheptane
3-methylheptane
1-cis,2-trans,3-trimethylcyclopentane
cis-1,3-dimethylcyclohexane
trans-1,4-dimethylcyclohexane
2,2,5-trimethylhexane
1-octene
trans-4-octene
n-octane
trans-2-octene
trans-1,3-dimethylcyclohexane
cis-2-octene
2,3,5-trimethylhexane
2,4-dimethylheptane
cis-1,2-dimethylcyclohexane
ethylcyclohexane
3,5-dimethylheptane
ethylbenzene
2,3-dimethylheptane
m- & p-xylene
4-methyloctane
2-methyloctane
3-methyloctane
styrene
o-xylene
1-nonene
2,2,4-trimethylheptane
n-nonane
ethylmethylcyclohexane
(1-methylethyl)benzene
2,2-dimethyloctane
2,4-dimethyloctane
n-propylbenzene

1-methyl-3-ethylbenzene
 1-methyl-4-ethylbenzene
 1,3,5-trimethylbenzene
 1-methyl-2-ethylbenzene
 1,2,4-trimethylbenzene
 n-decane
 (2-methylpropyl)benzene
 (1-methylpropyl)benzene
 1-methyl-3-(1-methylethyl)benzene
 1,2,3-trimethylbenzene
 1-methyl-4-(1-methylethyl)benzene
 2,3-dihydroindene (indan)
 1-methyl-2-(1-methylethyl)benzene
 1,3-diethylbenzene
 1,4-diethylbenzene
 1-methyl-3-n-propylbenzene
 1-methyl-4-n-propylbenzene
 1,2-diethylbenzene
 1-methyl-2-n-propylbenzene
 1-methyl-4-(2-methylpropyl)benzene
 1,4-dimethyl-2-ethylbenzene
 1,3-dimethyl-4-ethylbenzene
 1,2-dimethyl-4-ethylbenzene
 1,3-dimethyl-2-ethylbenzene
 n-undecane
 1,2-dimethyl-3-ethylbenzene
 1,2,4,5-tetramethylbenzene
 2-methylbutylbenzene
 1,2,3,5-tetramethylbenzene
 1-(1,1-dimethylethyl)-2-methylbenzene
 1,2,3,4-tetramethylbenzene
 n-pentylbenzene
 1-(1,1-dimethylethyl)-3,5-dimethylbenzene
 naphthalene
 n-dodecane

- * benzene may coelute with 1-methylcyclopentene
- ** toluene may coelute with 2,3,3-trimethylpentane

AIR RESOURCES BOARD

DETERMINATION
OF ALDEHYDE AND KETONE COMPOUNDS
IN AUTOMOTIVE SOURCE SAMPLES
BY HIGH PERFORMANCE LIQUID CHROMATOGRAPHY

METHOD NO. 1004

California Air Resources Board
Southern Laboratory Branch
Monitoring and Laboratory Division
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

1 INTRODUCTION

- 1.1 This document describes a method of analyzing automotive engine exhaust for aldehyde and ketone compounds (carbonyls) using impingers containing 2,4-dinitrophenylhydrazine (DNPH) absorbing solution. Carbonyl masses ranging between 0.02 and 200 ug are measured by this method. Currently, the target carbonyls analyzed and reported include formaldehyde, acetaldehyde, acrolein, acetone, propionaldehyde, butyraldehyde, hexaldehyde, and benzaldehyde.
- 1.2 This procedure is derived from a method used by Hull (Ref. 9.1).

2. METHOD SUMMARY

- 2.1 The samples are received by the laboratory in sample collection impingers. The absorbing solution (2,4-DNPH) complexes the carbonyl compounds into their diphenylhydrazone derivatives. Separation and analysis is performed using a High Performance Liquid Chromatograph (HPLC) a spectrophotometer.

3. INTERFERENCES AND LIMITATIONS

- 3.1 An interference is any detectable compound present in the sample with a retention time very similar to that of the target carbonyls described in this method. To reduce interference error, proof of chemical identity may require performance of periodic confirmations using an alternate method and/or instrumentation, e.g., using alternative HPLC columns or mobile phase compositions.
- 3.2 If samples are not analyzed the same day as received, they must be transferred to glass bottles, sealed, and refrigerated at 40°F. Refrigerated samples are stable for 30 days.

4. INSTRUMENT AND APPARATUS

- 4.1 The HPLC analytical system consists of the following:
 - 4.1.1 Dual high pressure pumps.
 - 4.1.2 Automated gradient controller.
 - 4.1.3 A liquid autosampler.
 - 4.1.4 Two DuPont Zorbax ODS columns in tandem and a guard column (2 centimeters (cm) long packed with C18 5 micrometers (um) pellicular beads). Other column(s) may be used, provided that it is demonstrated to the Executive Officer of the Air Resources Board that the alternate system is equivalent or better with respect to precision, accuracy, and resolution of all the target carbonyls.
 - 4.1.5 An ultraviolet/visible (UV/VIS) spectrophotometer.
 - 4.1.6 Data system for peak integration.

- 4.2 Sample collection containers are glass impingers. DNPH-impregnated cartridges may also be used.

5. REAGENTS AND MATERIALS

- 5.1 Acetonitrile, HPLC grade, Burdick and Jackson or equivalent.
- 5.2 Water, HPLC grade, Burdick and Jackson or equivalent.
- 5.3 2,4-Dinitrophenylhydrazine (DNPH), Eastman or equivalent, recrystallized twice from acetonitrile. The recrystallized DNPH is checked for contaminants by injecting a dilute solution of DNPH in contaminant-free acetonitrile into the HPLC.
- 5.4 Sulfuric acid, analytical reagent grade, Baker Analyzed or equivalent.
- 5.5 Synthesized 2,4-dinitrophenylhydrazones (Ref 9.2) are:
- 5.5.1 Formaldehyde/2,4-dinitrophenylhydrazone, recrystallized three times from 95 percent ethanol, melting point (m.p.) 168°C.
- 5.5.2 Acetaldehyde/2,4-dinitrophenylhydrazone, recrystallized three times from 95 percent ethanol, m.p. 166-168°C.
- 5.5.3 Acrolein/2,4-dinitrophenylhydrazone, recrystallized from acetonitrile and 95 percent ethanol, m.p. 158-159.5°C.
- 5.5.4 Acetone/2,4-dinitrophenylhydrazone, recrystallized three times from 95 percent ethanol, m.p. 126-128°C.
- 5.5.5 Propionaldehyde/2,4-dinitrophenylhydrazone, recrystallized three times from 95 percent ethanol, m.p. 138-140°C.
- 5.5.6 Butyraldehyde/2,4-dinitrophenylhydrazone, recrystallized three times from 95 percent ethanol, m.p. 109-111°C.
- 5.5.7 Hexaldehyde/2,4-dinitrophenylhydrazone, recrystallized three times from 95 percent ethanol, m.p. 105-106°C.
- 5.5.8 Benzaldehyde/2,4-dinitrophenylhydrazone, recrystallized three times from 95 percent ethanol, m.p. 235-237°C.
- 5.6 Stock Calibration Standard - A typical 100 ml acetonitrile standard stock solution contains:
- 14.8 milligrams (mg) formaldehyde/2,4-dinitrophenylhydrazone
 - 8.4 mg acetaldehyde/2,4-dinitrophenylhydrazone
 - 6.0 mg acrolein/2,4-dinitrophenylhydrazone
 - 5.7 mg acetone/2,4-dinitrophenylhydrazone
 - 4.7 mg propionaldehyde/2,4-dinitrophenylhydrazone
 - 5.0 mg butyraldehyde/2,4-dinitrophenylhydrazone
 - 5.0 mg benzaldehyde/2,4-dinitrophenylhydrazone
 - 5.0 mg hexaldehyde/2,4-dinitrophenylhydrazone
- 5.7 Working Standard - A working standard is prepared every two weeks by diluting 1 mL of the stock calibration solution to 100 mL.

- 5.8 Control Standard - A quality control standard, containing all target carbonyl/2,4-dinitrophenylhydrazones complexes, within the typical concentration range of real samples is analyzed to update daily control charts. The control standard may be prepared by batch mixing old samples and stirring for 24 hours. All target compounds except acrolein have been found to be stable in the control standard.

6. PROCEDURE

- 6.1.1 An absorbing solution is prepared by dissolving 0.11 - 0.13 grams of recrystallized DNPH in 1 liter (L) of HPLC grade acetonitrile. The absorbing solution should be stored in the refrigerator at 40°F or lower and prepared at least every two weeks. Each batch of acetonitrile used in this procedure is checked for oxygenated impurities by addition of contaminant-free dilute solution of DNPH and analyzed in the HPLC.
- 6.1.2 In the laboratory, pipette 15 mL of the DNPH absorbing solution into each of nine 30 mL graduated fritted midjet impingers for each emission test. Add 0.1 mL of 5.7 N sulfuric acid to each impinger. The ninth impinger is reserved as a field blank. One pair of impingers is reserved for the composite background sample.
- 6.1.3 DNPH impregnated cartridges may also be used to collect carbonyl samples. At the volumes being sampled (1 L/minute), no back-up cartridge is needed. Leave the cartridge capped.
- 6.2 Connect the impinger pairs in series and cap the open ends to prevent contamination. (These sets of impingers (cartridges) are picked up by the automotive test personnel for sampling).
- 6.3 After the sampling has been completed and the impingers have been capped and returned to the laboratory, uncap and place the eight impingers and the field blank impinger in a preheated water bath at 70-80°C for 30 minutes (min) to complete derivatization. Heating samples in the water bath may be omitted if omission of this step is demonstrated to the Executive Office of the Air Resources Board to result in equivalent or better resolution, precision and accuracy of all target carbonyls.
- 6.3.1 For sampling with cartridges, remove the caps and extract with 10 mL acetonitrile running the extract into glass storage bottles.
- 6.4 Remove the nine impingers from the water bath and cool to room temperature. Replace any lost solvent by adding acetonitrile to the 15 ml mark.
- 6.5 Transfer 3 mL of the solution from each impinger/cartridge to 4 mL glass vials and seal with new septum screw caps.
- 6.6 Place the vials containing blank, working standard, control standard, and samples in the autosampler for subsequent injection into an HPLC configured as follows:

Columns - 4.6 millimeters (mm) ID x 250 mm x 1/4 inches OD Dupont Zorbax ODS two columns in series, Guard column - 2 cm long packed with C18 5 um pellicular beads.

Detector - UV/VIS at 360 nanometers

Sample volume - 20 microliters

Solvent A - acetonitrile

Solvent B - 10 percent (volume/volume) methanol in water

Flow - 1 mL per min

Program - 50 percent A, 50 percent B 0 (initial time)
- 65 percent A, 35 percent B 0 to 5 min
100 percent A, 0 percent B 5 to 35 min
50 percent A, 50 percent B 36 to 46 min

Data System: The outputs from the UV/VIS spectrophotometer are sent to a PC-controlled data acquisition system.

Other operating conditions and/or columns may be substituted provided that it is demonstrated to the Executive Officer of the Air Resources Board that they produce equivalent or better resolution, precision, and accuracy than this method. A sample chromatogram is shown in Figure 1.

- 6.7 The peak integrations are corrected as necessary in the data system. Any misplaced baseline segments are corrected in the reconstructed chromatogram.
- 6.8 The level of peak rejection is set just below the lowest limit of detection (LOD).
- 6.9 The maximum allowable LOD for any target carbonyl is 0.02 ug/mL.

7. CALCULATIONS

- 7.1 The concentration of each target carbonyl compound is determined with the following calculation that compares the sample peak area with that of an external standard.
- 7.1.1 For each target carbonyl, the carbonyl mass is calculated from its carbonyl 2,4-dinitrophenylhydrazone mass.
- 7.1.2 The mass of each carbonyl compound, ug per 15 mL impinger, is determined by the following calculation:

$$\text{Mass}_{\text{sample}} = \text{Peak Area}_{\text{sample}} \times \text{Response Factor} \times \text{Impinger volume (mL)} \times B$$

where B is the ratio of the molecular weight of the carbonyl compound to its 2,4-dinitrophenylhydrazone.

- 7.1.3 The ratios B for the target carbonyls are:

Formaldehyde	B = .1428	Butyraldehyde	B = .288
Acetaldehyde	.1965	Benzaldehyde	.371
Acrolein	.2374	Hexaldehyde	.357
Acetone	.2438		
Propionaldehyde	.2438		

- 7.1.4 The Response Factor (RF) for each carbonyl is calculated during the calibration by:

$$RF = \frac{\text{Concentration}_{\text{standard}} (\text{units ug 2,4-DNPH species/mL})}{\text{Peak Area}_{\text{standard}}}$$

8. QUALITY CONTROL

8.1 Blanks

The solvents used are of the highest HPLC grade and are checked for impurities by conducting blank analyses.

8.2 Phenylhydrazone Purity

The 2,4-dinitrophenylhydrazones are checked for purity by their melting points and their chromatograms. Analysis of the solution of phenylhydrazone must yield only the peak of interest.

8.3 Calibration Run

One run of the calibration standard is performed to generate the calibration factors needed for quantifying sample analyses each day/shift.

8.4 Control Standard Run

One run of the quality control standard is performed after the calibration run. Measurements of all compounds in the control standard except acrolein must fall within the control limits before sample analysis may proceed. To meet this requirement, it may be necessary to rerun the calibration and control standards, and inspect and repair the HPLC.

8.5 Control Charts

Quality control chart(s) are maintained for each component of the control sample except acrolein. The control chart, used on a daily basis, establishes that the method is in "statistical control". The following describes how to construct a typical control chart:

1. Obtain at least 20 daily control sample results,
2. Calculate the average control sample concentration and standard deviation(s) for each target analyte, and
3. Create a control chart for each target analyte by placing the concentration on the Y-axis and the date on the X-axis. Draw an upper warning limit and a lower warning limit at two standard deviations (2s) above and below the average concentration. Draw an upper control limit and a lower control limit at three standard deviations (3s) above and below the average concentration.

The control sample must be "in-control" for all target analytes for the sample results to be considered acceptable. A control sample measurement is considered to be "out-of-control" when the analyzed value exceeds the 3s limit, or two successive control sample measurements of the same analyte exceed the 2s limit.

8.6 Field Blanks

One field blank is analyzed for each set of eight bubblers.

8.7 One cartridge per batch number is analyzed as a blank.

8.8 Duplicates

A duplicate analysis of one sample is performed for every 10 samples or at least once a day/shift.

The relative percent difference (RPD) is calculated for each duplicate run:

$$\text{RPD (\%)} = \frac{\text{Difference between duplicate and original measurements}}{\text{Average of duplicate and original measurements}} \times 100$$

For each compound, the allowable RPD depends on the average concentration level for the duplicate runs, as shown in the following table:

<u>Average Measurement for Duplicate Runs</u>	<u>Allowable RPD (%)</u>
1 to 10 times LOD	100
10 to 20 " "	30
20 to 50 " "	20
Greater than 50 " "	15

If the results of the duplicate analyses do not meet these criteria for all target carbonyls, the sample must be reanalyzed. If the criteria are still not met, all samples analyzed during the day/shift must be reanalyzed or deleted.

8.9 Linearity

A multipoint calibration to check for instrument linearity is performed for all target analytes at least once every six months. The multipoint calibration consists of at least five concentration or mass loading levels (using smaller or larger volume sample sizes of existing standards is acceptable) above the LOD, evenly distributed over the range of expected linearity of the instrument. Each concentration level is measured at least twice. A linear regression analysis is performed using concentration and average area counts to determine the regression correlation coefficient (r). The r must be greater than 0.995 to be considered sufficiently linear for one point calibrations.

8.10 Limit of Detection

The limit of detection for the target analytes must be determined at least every six months. To make the necessary calculations, it is necessary to perform a multipoint calibration consisting of at least five concentration levels above the LOD. The LOD must be calculated using the following equation (Ref 9.3):

$$\text{LOD} = |A| + 3.3(s)$$

where each term in the equation is expressed in concentration units, and |A| is the absolute value of the least squares X-intercept calculated from the multipoint data.

$\bar{S}$ is the standard deviation of replicate determinations of the lowest standard. At least three replicates are required. The lowest standard must be run at one to five times the estimated detection limit. If data is not available in the concentration range near the detection limit, $\bar{S}$ may be estimated by:

$$\bar{S} = \text{RSD} \times |\Delta|$$

where RSD is the relative standard deviation of the lowest standard analyzed.

An example of typical LODs is given in the table below:

<u>Compound</u>	<u>LOD (ug/mL)</u>
Formaldehyde/2,4-dinitrophenylhydrazone	0.023
Acetaldehyde/2,4-dinitrophenylhydrazone	0.006
Acrolein/2,4-dinitrophenylhydrazone	0.011
Acetone/2,4-dinitrophenylhydrazone	0.015
Propionaldehyde/2,4-dinitrophenylhydrazone	0.045
Butyraldehyde/2,4-dinitrophenylhydrazone	0.039
Hexaldehyde/2,4-dinitrophenylhydrazone	0.035
Benzaldehyde/2,4-dinitrophenylhydrazone	0.047
Formaldehyde	0.003
Acetaldehyde	0.001
Acrolein	0.003
Acetone	0.004
Propionaldehyde	0.011
Butyraldehyde	0.011
Hexaldehyde	0.013
Benzaldehyde	0.017


The maximum allowable LOD is 0.06 ug carbonyl derivative/mL.

9. REFERENCES

- 9.1 Hull, L.A., Procedures for 2,4-Dinitrophenylhydrazone Aldehyde-Ketone Air Analysis, Internal Report at U.S. EPA.
- 9.2 Shriner, R.L. and Fuson, R.C., Identification of Organic Compounds, 2nd. Ed., John Wiley and Sons, Inc., 1940, p. 143.
- 9.3 U.S. Environmental Protection Agency, Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air (Method T03-15), EPA-600/4-89-017, Research Triangle Park, North Carolina, June 1989.

CHANNEL A INJECT

REF PM RT 16



ER 0

HCHO

16:09:11

CH= "A" PS= 1.

FILE 1. METHOD 5. RUN 4 INDEX 1

ANALYST: HCD

NAME	UG/ML	RT	AREA BC	RF	RRT
HCHO	3.386	11.73	483128 01	142701.667	1.
ACD	1.975	13.36	330605 01	167354.	1.139
ACRO	1.117	15.08	182063 02	163004.	1.286
ACET	1.009	15.34	159991 03	158488.	1.308
PROP	0.918	15.93	157844 01	172000.	1.358
6	0.	17.47	156717 01		1.489
BUTY	2.022	18.5	301340 01	149036.	1.577
BENZ	0.954	19.46	148378 01	155596.	1.659
9	0.	21.45	148355 01		1.829
10	0.	22.35	133577 01		1.905
HEXA	1.087	24.59	139894 01	128660.	2.096
TOTALS	12.468		2341892		

Figure 1. A typical chromatogram of the analysis of the target carbonyl compounds.

AIR RESOURCES BOARD

DETERMINATION OF
OXYGENATED COMPOUNDS
IN AUTOMOTIVE SOURCE SAMPLES BY GAS CHROMATOGRAPHY

METHOD NO. 1005

California Air Resources Board
Southern Laboratory Branch
Monitoring and Laboratory Division
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

1. INTRODUCTION

- 1.1 This document describes a method of sampling and analyzing automotive exhaust for oxygenated compounds. Currently, the target oxygenates are methyl tertiary-butyl ether (MTBE) and ethyl tertiary-butyl ether (ETBE).
- 1.2 This procedure involves flowing diluted engine exhaust into Tedlar bags and analyzing this solution by gas chromatography (GC).
- 1.3 This method is currently under development.

2. METHOD SUMMARY

- 2.1 The samples are received by the laboratory in Tedlar bags. Compound separation and analysis are performed using a GC. The sample is injected into the GC by means of a gas sampling valve system with a pump. Separation of the sample mixture into its component constituents takes place on a capillary column operated with a temperature gradient. A thermionic ionization detector (TID) is used for oxygenate detection.
- 2.2 The computerized GC data system identifies the oxygenate associated with each of the chromatographic peaks. The oxygenate concentrations are determined by integrating the peak areas and using calibration factors determined with external standards.

3. INTERFERENCES AND LIMITATIONS

- 3.1 An interference is any oxygenated component present in the sample with a retention time similar to that of the target oxygenate described in this method. Proof of chemical identity may require performance of periodic confirmations using an alternate method and/or instrumentation, e.g., gas chromatograph/mass spectrometer (GC/MS).

4. INSTRUMENTATION AND APPARATUS

- 4.1 A Tedlar bag is used to contain the sample for each mode of the test. Each bag is 2 mm thick, has a capacity of 5 to 10 liters, and is equipped with quick-connect fittings.
 - 4.1.1 A temperature-programmable GC, equipped with a gas sampling valve system, a DB-1 Megabore column (30 meter (m), 0.53 millimeter (mm) ID, 1.5 micron (u) film thickness) and a TID. A different column may be used, provided that it is demonstrated to the Executive Officer of the Air Resources Board to be equivalent to or better than the specified column with respect to precision, accuracy, and resolution of all the target oxygenates.
 - 4.1.2 A PC-controlled data acquisition system for quantitation of peak areas is required.

5. REAGENTS AND MATERIALS

5.1 Standards

- 5.1.1 A gas phase calibration standard contains all of the oxygenates of interest, with the balance nitrogen. Figure 1 illustrates a typical chromatogram of the analysis of MTBE.
- 5.1.2 A gas phase control standard contains all of the oxygenates of interest, with the balance nitrogen. This standard, at the approximate concentration of the samples, is used to update control charts for each target alcohol.

5.2 Gas Requirements

- 5.2.1 Air shall be "Zero" grade.
- 5.2.2 Nitrogen shall have a minimum purity of 99.998 percent.
- 5.2.3 Helium shall have a minimum purity of 99.995 percent.

6. PROCEDURE

- 6.1 A 10 mL aliquot of each unmodified sample is injected into a GC, configured as follows:

Column: DB-1, 30 m, 0.53 mm ID, 1.5 μ film thickness
Carrier gas: Helium at 6 milliliters per minute (ml/min)
Detector: TID, 320 $^{\circ}$ C, Nitrogen at 115 ml/min
Injector: Air-actuated gas sample valve system with 10 mL fixed volume sample loop
Temperature: 0 $^{\circ}$ C (5 min), 0 $^{\circ}$ C to 200 $^{\circ}$ C (30 $^{\circ}$ C/min, hold 8.34 min)
Data system: PC-based data acquisition system

Other operating conditions may be substituted provided that they can be demonstrated to the Executive Officer of the Air Resources Board to produce resolution, precision, and accuracy equivalent to or better than this method.

- 6.2.1 One calibration standard, one control standard, and one nitrogen blank are analyzed daily at the beginning of each set of samples.
- 6.2.2 A replicate analysis is performed at least once per sample batch.
- 6.2.3 The control standard is repeated at the end of the sample batch or day.
- 6.3 For compounds having concentrations above the documented range of instrument linearity, the sample must be diluted and reanalyzed.
- 6.4 The peak integrations are corrected as necessary in the data system. Any misplaced baseline segments are corrected in the reconstructed chromatogram.

- 6.4.1 The peak identifications provided by the computer are checked and corrected if necessary.
- 6.4.2 The level of peak rejection is set just below the lowest limit of detection (LOD).

7. CALCULATIONS

- 7.1 The concentration, in ppm, of each target oxygenate is determined by the following calculation that compares the sample peak area with that of an external standard:

$$\text{Concentration}_{\text{sample}} = \text{Area}_{\text{sample}} \times \text{Response Factor}$$

- 7.2 The response factor (RF) is calculated by:

$$\text{RF} = \frac{\text{Concentration}_{\text{standard}}}{\text{Peak Area}_{\text{standard}}}$$

8. QUALITY CONTROL

- 8.1 Calibration and control standards will be analyzed by FTIR upon arrival to confirm the concentration of the target compounds and on a weekly basis to determine stability.

8.2 Blank Run

A blank run is performed before running the calibration standard, control standard, and samples. All target oxygenate concentrations in the blank must be below the LOD before the analysis may proceed.

8.3 Calibration Run

One run of the calibration standard is performed to generate the response factor(s) needed for quantitating sample analyses.

8.4 Control Standard Run

One run of the quality control standard is performed after the calibration run. Measurements of all target oxygenates in the control standard must fall within the control limits before sample analysis may proceed. To meet this requirement, it may be necessary to inspect and repair the GC and/or rerun the calibration and/or control standards.

8.5 Control Charts

Quality control chart(s) are maintained for each analyte of the control sample. The control charts, used on a daily basis, establishes that the method is in "statistical control". The following describes how to construct a typical control chart:

1. Obtain at least 20 daily control sample results,
2. Calculate the average control sample concentration and standard deviation(s) for the target analyte(s), and
3. Create a control chart for each target analyte by placing the concentration on the Y-axis and the date on the X-axis. Draw an upper warning limit and a lower warning limit at two standard deviations (2s) above and below the average concentration. Draw an upper control limit and a lower control limit at three standard deviations (3s) above and below the average concentration.

The control sample must be "in-control" for all target analytes for the sample results to be considered acceptable. A control sample measurement is considered to be "out-of-control" when the analyzed value exceeds the 3s limit, or two successive control sample measurements of the same analyte exceed the 2s limit.

8.6 Duplicates

A duplicate analysis of one sample is performed at least once a day.

The relative percent difference (RPD) is calculated for each duplicate run:

$$\text{RPD (\%)} = \frac{\text{Difference between duplicate and original measurements}}{\text{Average of duplicate and original measurements}} \times 100$$

For each compound, the allowable RPD for each duplicate run depends on the average concentration level of the duplicate runs, as shown in the following table:

<u>Average Measurement for Duplicate Runs</u>	<u>Allowable RPD (%)</u>
1 to 10 times LOD	100
10 to 20 times LOD	30
20 to 50 times LOD	20
Greater than 50 times LOD	15

If the results of the duplicate analyses do not meet these criteria for all target oxygenates, the sample must be reanalyzed. If the criteria are still not met, all samples for the day/shift must be reanalyzed or deleted.

8.7 Linearity

A multipoint calibration to check for instrument linearity is performed for all target oxygenates at least once every six months. The multipoint calibration consists of at least five concentration or mass loading levels above the LOD, evenly distributed over the range of expected sample concentration. Each concentration level is measured at least twice. A linear regression analysis is performed using concentration and area counts to determine the regression correlation coefficient (r). The r must be greater than 0.995 to be considered sufficiently linear for one point calibrations.

8.8 Limit of Detection

The limit of detection for the target oxygenates must be determined at least every six months. To make the necessary calculations, it is necessary to perform a multipoint calibration consisting of at least four "low" concentration levels, all above the LOD. The LOD must be calculated using the following equation (Ref 9.2):

$$LOD = |A| + 3.3(S)$$

where each term in the equation is expressed in concentration units, and $|A|$ is the absolute value of the least squares X-intercept calculated from the multipoint data.

S is the standard deviation of replicate determinations of the lowest standard. At least three replicates are required. The concentration of the lowest standard must be one to five times the estimated detection limit. If data is not available in the concentration range near the detection limit, S may be estimated by:

$$S = RSD \times |A|$$

where RSD is the relative standard deviation of the lowest standard analyzed.

9. REFERENCES

U.S. Environmental Protection Agency, Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air (Method T03-15), EPA-600/4-89-017, Research Triangle Park, North Carolina, June 1989.

AIR RESOURCES BOARD

DETERMINATION OF
NMOG MASS EMISSIONS

California Air Resources Board
Mobile Source Division
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

DETERMINATION OF NMOG MASS EMISSIONS

1. INTRODUCTION

- 1.1 Non-methane organic gases (NMOG) mass emissions consist of non-methane hydrocarbons and oxygenated hydrocarbons.

2. NMOG WEIGHTED MASS EMISSIONS

- 2.1 NMOG weighted mass (w_m) emissions shall be calculated as follows:

$$NMOG_{w_m} = \Sigma NMHC_{w_m} + \Sigma ROH_{w_m} + \Sigma RHO_{w_m} + \Sigma ROR_{w_m}$$

Non-methane hydrocarbon weighted mass emissions ($NMHC_{w_m}$) can be determined by either flame ionization detection (FID) or gas chromatography (GC). If the FID method is used to calculate $NMHC_{w_m}$, refer to "Determination of Non-Methane Hydrocarbon Mass Emissions by Flame Ionization Detection". If the GC method is used to calculate $NMHC_{w_m}$, refer to the "Speciated Hydrocarbon Mass Emissions Calculation" section contained herein. Carbonyl weighted mass emissions (RHO_{w_m}) are to be calculated according to the "Carbonyl Mass Emissions Calculation" section contained herein. For alcohol fueled vehicles, alcohol weighted mass emissions (ROH_{w_m}) are to be calculated according to the "Alcohol Mass Emissions Calculation" section contained herein. Ethers weighted mass emissions (ROR_{w_m}) are to be treated as speciated hydrocarbons and determined by the "Speciated Hydrocarbon Mass Emissions Calculation" section.

SPECIATED HYDROCARBON MASS EMISSIONS CALCULATION

1. INTRODUCTION

- 1.1 Vehicular exhaust emissions are measured according to the Federal Test Procedure (FTP)(1). For each of the three phases of the FTP, a tedlar bag of 0.5 ft³ capacity is used to collect a dilute exhaust sample. A fourth 0.5 ft³ tedlar bag is used to collect a composite dilution air (background) sample from all three phases of the FTP. All bag samples are analyzed according to method no. 1002 and method no. 1003 to determine the dilute exhaust and dilution air concentrations of individual hydrocarbon compounds. The measured hydrocarbon compound concentrations are used in the following equations to calculate the weighted mass emissions of each hydrocarbon compound.

2. HC MASS EMISSIONS CALCULATION PER TEST PHASE

$$2.1 \quad HC_{mass_n} = (HC_{conc} * HC_{dens} * VMIX * 10^{-6}) / (\text{Carbon No.})$$

$$2.2 \quad HC_{conc} = HC_e - (HC_d * (1 - (1 / DF)))$$

NOTE: If HC_{conc} is calculated to be less than zero, then $HC_{conc} = 0$.

3. WEIGHTED HC MASS EMISSIONS CALCULATION

$$3.1 \quad HC_{wm} = 0.43 * \frac{(HC_{mass_1} + HC_{mass_2})}{(D_{phase_1} + D_{phase_2})} + 0.57 * \frac{(HC_{mass_3} + HC_{mass_2})}{(D_{phase_3} + D_{phase_2})}$$

4. SAMPLE CALCULATION

- 4.1 Exhaust emissions from a gasoline vehicle are collected in three dilute exhaust sample bags and one dilution air (background) sample bag during the FTP. Gas chromatography is used to determine the benzene concentration of each bag sample. Calculate the weighted benzene mass emissions based on the following data:

Test	HC _e	HC _d	FID THC _e	CH _{4e}	CO _{2e}	CO _{em}	R _a	VMIX	D _{phase_n}
Phase	(ppbC)	(ppbC)	(ppmC)	(ppmC)	(%)	(ppm)	(%)	(ft ³)	(mile)
1	500	25	98	6	1.20	280	28	2846	3.584
2	100	25	22	4	0.95	87	25	4854	3.842
3	120	25	29	5	1.07	101	24	2840	3.586

For Phase 1:

$$DF = 13.46 / [CO_{2e} + (NMHC_e + CH_{4e} + CO_e) * 10^{-4}] \quad (\text{see DF Calc.})$$

$$\begin{aligned} NMHC_e &= FID\ THC_e - (r_{CH_4} * CH_{4e}) \\ &= 98\ \text{ppmC} - (1.20 * 6\ \text{ppmC}) \\ &= 90.8\ \text{ppmC} \end{aligned}$$

$$CO_e = (1 - (0.01 + 0.005 * HCR) * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

$$\begin{aligned} &= (1 - (0.01925) * 1.2\% - 0.000323 * 28\%) * 280\ \text{ppm} \\ &= 271\ \text{ppm} \end{aligned}$$

$$\begin{aligned} DF &= 13.46 / [1.2\% + (90.8\ \text{ppmC} + 6\ \text{ppmC} + 271\ \text{ppm}) * 10^{-4}] \\ &= 10.88 \end{aligned}$$

$$\begin{aligned} HC_{conc} &= HC_e - (HC_d * (1 - (1 / DF))) \\ &= 500\ \text{ppbC} - (25\ \text{ppbC} * (1 - (1 / 10.88))) \\ &= 477\ \text{ppbC} \end{aligned}$$

$$\begin{aligned} \text{Mol. Wt. of } C_6H_6 &= (6 * 12.01115) + (6 * 1.00797) \\ &= 78.11472\ \text{g/mole} \end{aligned}$$

$$\begin{aligned} HC_{dens} &= (\text{Mol. Wt.} * \text{conversion of liter to ft}^3) / (\text{Mol. Vol.}) \\ &= (78.11472\ \text{g/mole} * 28.316\ \text{liter/ft}^3) / 24.055\ \text{liter/mole} \\ &= 91.952\ \text{g/ft}^3 \end{aligned}$$

$$HC_{mass_n} = (HC_{conc} * HC_{dens} * VMIX * 10^{-6}) / (\text{Carbon No.})$$

$$\begin{aligned} HC_{mass_1} &= (477\ \text{ppbC} * 91.952\ \text{g/ft}^3 * 2846\ \text{ft}^3 * 10^{-6}) / 6 \\ &= 20.82\ \text{mg} \end{aligned}$$

Similarly, for Phase 2:

$$HC_{mass_2} = 5.71\ \text{mg}$$

and for Phase 3:

$$HC_{mass_3} = 4.22 \text{ mg}$$

Therefore,

$$HC_{wm} = 0.43 * \frac{(HC_{mass_1} + HC_{mass_2})}{(D_{phase_1} + D_{phase_2})} + 0.57 * \frac{(HC_{mass_3} + HC_{mass_2})}{(D_{phase_3} + D_{phase_2})}$$

$$HC_{wm} = 0.43 * \frac{(20.82 \text{ mg} + 5.71 \text{ mg})}{(3.584 \text{ mile} + 3.842 \text{ mile})} + 0.57 * \frac{(4.22 \text{ mg} + 5.71 \text{ mg})}{(3.586 \text{ mile} + 3.842 \text{ mile})}$$

$$HC_{wm} = 2.30 \text{ mg/mile (benzene weighted mass emissions)}$$

ALCOHOL MASS EMISSIONS CALCULATION

1. INTRODUCTION

- 1.1 Vehicular emissions are measured according to the Federal Test Procedure (FTP)(1). For each of the three phases of the FTP, a set of two impingers is used to collect alcohol emissions in the dilute exhaust. A fourth set of two impingers is used to collect a composite dilution air (background) alcohol sample from all three phases of the FTP. All impingers are analyzed according to method no. 1001 to determine the alcohol concentration in each impinger. The measured alcohol concentrations are used in the following equations to calculate the weighted mass emissions of alcohol compounds.

2. ALCOHOL MASS EMISSIONS CALCULATION PER TEST PHASE

- 2.1 $ROH_{mass_n} = (ROH_{conc} * ROH_{dens} * VMIX * 10^{-6}) / (\text{Carbon No.})$
- 2.2 $ROH_{conc} = ROH_e - (ROH_d * (1 - (1 / DF)))$
- NOTE: If ROH_{conc} is calculated to be less than zero, then $ROH_{conc} = 0$.
- 2.3 $ROH_e = (Imass_e / Ivol_e) * (\text{Mol. Vol.} / \text{Mol. Wt.})$
- 2.4 $Imass_e = (Iconc_{e1} + Iconc_{e2}) * Dens_{ROH} * Ivol_r$
- 2.5 $Ivol_e = Ivol_{em} * (Itemp_e / 293.16^{\circ}K) * (760 \text{ mm Hg} / P_b)$
- 2.6 $ROH_d = (Imass_d / Ivol_d) * (\text{Mol. Vol.} / \text{Mol. Wt.})$
- 2.7 $Imass_d = (Iconc_{d1} + Iconc_{d2}) * Dens_{ROH} * Ivol_r$
- 2.8 $Ivol_d = Ivol_{dm} * (Itemp_d / 293.16^{\circ}K) * (760 \text{ mm Hg} / P_b)$

3. WEIGHTED ALCOHOL MASS EMISSIONS CALCULATION

$$3.1 \quad ROH_{wm} = 0.43 * \frac{(ROH_{mass_1} + ROH_{mass_2})}{(D_{phase_1} + D_{phase_2})} + 0.57 * \frac{(ROH_{mass_3} + ROH_{mass_2})}{(D_{phase_3} + D_{phase_2})}$$

4. SAMPLE CALCULATION

- 4.1 Alcohol emissions from an M85 fueled vehicle are collected in three sets of dilute exhaust impingers and one set of dilution air impingers during the FTP. Gas chromatography is used to determine the methanol concentration in each impinger. Calculate the weighted methanol mass emissions based on the following data:

Test Phase	I _{vol_r} (ml)	I _{conc_{e1}} (ppmC)	I _{conc_{e2}} (ppmC)	I _{vol_{em}} (liter)	I _{conc_{d1}} (ppmC)	I _{conc_{d2}} (ppmC)	I _{vol_{dm}} (liter)	I _{temp_e} (°K)	I _{temp_d} (°K)
1	15	2.24	0.05	3.90	0.07	0.01	13.50	295	294
2	15	0.29	0.06	6.50	0.07	0.01	13.50	297	294
3	15	0.32	0.02	4.00	0.07	0.01	13.50	298	294

Test Phase	FID THC _e (ppmC)	CH _{4e} (ppmC)	CO _{2e} (%)	CO _{em} (ppm)	R _a (%)	VMIX (ft ³)	D _{phase_n} (mile)	P _b (mm Hg)
1	82	9	1.5	250	30	2834	3.581	760
2	19	5	0.7	20	32	4862	3.845	760
3	22	6	0.8	32	29	2835	3.583	760

For Phase 1:

$$\begin{aligned}
 \text{Imass}_e &= (\text{Iconc}_{e1} + \text{Iconc}_{e2}) * \text{Dens}_{\text{ROH}} * \text{Ivol}_r \\
 &= (2.24 \text{ ppmC} + 0.05 \text{ ppmC}) * 0.7914 \text{ g/ml} * 15 \text{ ml} * 10^6 \text{ ug/g} \\
 &= 27.2 \text{ ug}
 \end{aligned}$$

$$\begin{aligned}
 \text{Mol. Wt. of CH}_3\text{OH} &= (1 * 12.01115) + (4 * 1.00797) + (1 * 15.9994) \\
 &= 32.0428 \text{ g/mole}
 \end{aligned}$$

$$\begin{aligned}
 \text{Ivol}_e &= \text{Ivol}_{em} * (\text{Itemp}_e / 293.16^\circ\text{K}) * (760 \text{ mm Hg} / P_b) \\
 &= 3.90 \text{ liter} * (295^\circ\text{K} / 293.16^\circ\text{K}) * (760 \text{ mm Hg} / 760 \text{ mm Hg}) \\
 &= 3.92 \text{ liter}
 \end{aligned}$$

$$\begin{aligned}
 \text{ROH}_e &= (\text{Imass}_e / \text{Ivol}_e) * (\text{Mol. Vol.} / \text{Mol. Wt.}) \\
 &= (27.2 * 10^{-6} \text{ g} / 3.92 \text{ liter}) * (24.37 \text{ liter/mole} / 32.0428 \text{ g/mole}) \\
 &= 5.27 \text{ ppmC}
 \end{aligned}$$

$$\begin{aligned}
 \text{Imass}_d &= (\text{Iconc}_{d1} + \text{Iconc}_{d2}) * \text{Dens}_{\text{ROH}} * \text{Ivol}_r \\
 &= (0.07 \text{ ppmC} + 0.01 \text{ ppmC}) * 0.7914 \text{ g/ml} * 15 \text{ ml} * 10^6 \text{ ug/g} \\
 &= 0.95 \text{ ug}
 \end{aligned}$$

$$\begin{aligned}
Ivol_d &= Ivol_{dm} * (Itemp_d / 293.16^{\circ}K) * (760 \text{ mm Hg} / P_b) \\
&= 13.50 \text{ liter} * (294^{\circ}K / 293.16^{\circ}K) * (760 \text{ mm Hg} / 760 \text{ mm Hg}) \\
&= 13.54 \text{ liter}
\end{aligned}$$

$$\begin{aligned}
ROH_d &= (Imass_d / Ivol_d) * (Mol. Vol. / Mol. Wt.) \\
&= (0.95 * 10^{-6} \text{ g} / 13.54 \text{ liter}) * (24.37 \text{ liter/mole} / 32.0428 \text{ g/mole}) \\
&= 0.05 \text{ ppmC}
\end{aligned}$$

$$DF = 12.01 / [CO_{2e} + (NMHC_e + CH_{4e} + CO_e + ROH_e) * 10^{-4}] \text{ (see DF Calc.)}$$

$$\begin{aligned}
NMHC_e &= FID \text{ THC}_e - (r_{CH_4} * CH_{4e}) - (r_{CH_3OH} * ROH_e) \\
&= 82 \text{ ppmC} - (1.20 * 9 \text{ ppmC}) - (0.78 * 5.27 \text{ ppmC}) \\
&= 67 \text{ ppmC}
\end{aligned}$$

$$CO_e = (1 - (0.01 + 0.005 * HCR) * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

$$\begin{aligned}
&= (1 - (0.02705) * 1.5\% - 0.000323 * 30\%) * 250 \text{ ppm} \\
&= 237 \text{ ppm}
\end{aligned}$$

$$\begin{aligned}
DF &= 12.01 / [1.5\% + (67 \text{ ppmC} + 9 \text{ ppmC} + 236 \text{ ppm} + 5.30 \text{ ppmC}) * 10^{-4}] \\
&= 7.84
\end{aligned}$$

$$\begin{aligned}
ROH_{conc} &= ROH_e - (ROH_d * (1 - (1 / DF))) \\
&= 5.27 \text{ ppmC} - (0.05 \text{ ppmC} * (1 - (1 / 7.84))) \\
&= 5.22 \text{ ppmC}
\end{aligned}$$

$$\begin{aligned}
ROH_{dens} &= (Mol. Wt. * \text{conversion of liter to ft}^3) / (Mol. Vol.) \\
&= (32.0428 \text{ g/mole} * 28.316 \text{ liter/ft}^3) / 24.055 \text{ liter/mole} \\
&= 37.719 \text{ g/ft}^3
\end{aligned}$$

$$ROH_{mass_n} = (ROH_{conc} * ROH_{dens} * VMIX * 10^{-6}) / (\text{Carbon No.})$$

$$\begin{aligned}
ROH_{mass_1} &= (5.22 \text{ ppmC} * 37.719 \text{ g/ft}^3 * 2834 \text{ ft}^3 * 10^{-6}) / 1 \\
&= 0.56 \text{ g}
\end{aligned}$$

Similarly, for Phase 2:

$$ROH_{mass_2} = 0.08 \text{ g}$$

and for Phase 3:

$$ROH_{mass_3} = 0.08 \text{ g}$$

Therefore,

$$\begin{aligned} ROH_{wm} &= 0.43 * \frac{(ROH_{mass_1} + ROH_{mass_2})}{(D_{phase_1} + D_{phase_2})} + 0.57 * \frac{(ROH_{mass_3} + ROH_{mass_2})}{(D_{phase_3} + D_{phase_2})} \\ &= 0.43 * \frac{(0.56 \text{ g} + 0.08 \text{ g})}{(3.581 \text{ mile} + 3.845 \text{ mile})} + 0.57 * \frac{(0.08 \text{ g} + 0.08 \text{ g})}{(3.583 \text{ mile} + 3.845 \text{ mile})} \end{aligned}$$

$$ROH_{wm} = 0.05 \text{ g (methanol weighted mass emissions)}$$

CARBONYL MASS EMISSIONS CALCULATIONS

1. INTRODUCTION

- 1.1 Vehicular emissions are measured according to the Federal Test Procedure (FTP)(1). For each of the three phases of the FTP, a set of two impingers is used to collect carbonyl emissions in the dilute exhaust. A fourth set of two impingers is used to collect a composite dilution air (background) carbonyl sample from all three phases of the FTP. All impingers are analyzed according to method no. 1004 to determine the mass of individual carbonyl compounds in each impinger. The measured carbonyl masses are used in the following equations to calculate the weighted mass emissions of each carbonyl compound.

2. CARBONYL MASS EMISSIONS CALCULATION PER TEST PHASE

$$2.1 \quad RHO_{mass_n} = (RHO_{conc} * RHO_{dens} * VMIX * 10^{-6}) / (\text{Carbon No.})$$

$$2.2 \quad RHO_{conc} = RHO_e - (RHO_d * (1 - (1 / DF)))$$

NOTE: If RHO_{conc} is calculated to be less than zero, then $RHO_{conc} = 0$.

$$2.3 \quad RHO_e = (Imass_e / Ivol_e) * (\text{Mol. Vol.} / \text{Mol. Wt.})$$

$$2.4 \quad Ivol_e = Ivol_{em} * (Itemp_e / 293.16^{\circ}K) * (760 \text{ mm Hg} / P_b)$$

$$2.5 \quad RHO_d = (Imass_d / Ivol_d) * (\text{Mol. Vol.} / \text{Mol. Wt.})$$

$$2.6 \quad Ivol_d = Ivol_{dm} * (Itemp_d / 293.16^{\circ}K) * (760 \text{ mm Hg} / P_b)$$

3. WEIGHTED CARBONYL MASS EMISSIONS CALCULATION

$$3.1 \quad RHO_{wm} = 0.43 * \frac{(RHO_{mass_1} + RHO_{mass_2})}{(D_{phase_1} + D_{phase_2})} + 0.57 * \frac{(RHO_{mass_3} + RHO_{mass_2})}{(D_{phase_3} + D_{phase_2})}$$

4. SAMPLE CALCULATION

- 4.1 Carbonyl emissions from a compressed natural gas (CNG) vehicle are collected in three sets of dilute exhaust impingers and one set of dilution air impingers during the FTP. High performance liquid chromatography is used to determine the formaldehyde mass in each impinger. Calculate the weighted formaldehyde mass emissions based on the following data:

Test Phase	I_{vol_r} (ml)	I_{mass_e} (ug)	$I_{vol_{em}}$ (liter)	I_{mass_d} (ug)	$I_{vol_{dm}}$ (liter)	I_{temp_e} (°K)	I_{temp_d} (°K)
1	15	2.45	8.49	0.17	31.57	295	292
2	15	0.76	14.55	0.17	31.57	298	292
3	15	0.64	4.00	0.17	31.57	298	292

Test Phase	FID THC _e (ppmC)	CH _{4e} (ppmC)	CO _{2e} (%)	CO _{em} (ppm)	R _a (%)	VMIX (ft ³)	D _{phase_n} (mile)	P _b (mm Hg)
1	132	108	0.9	8	68	2866	3.581	760
2	4	3	0.1	4	67	4841	3.845	760
3	22	9	0.5	5	65	2837	3.583	760

For Phase 1:

$$\begin{aligned} \text{Mol. Wt. of HCHO} &= (1 * 12.01115) + (2 * 1.00797) + (1 * 15.9994) \\ &= 30.0268 \text{ g/mole} \end{aligned}$$

$$\begin{aligned} I_{vol_e} &= I_{vol_{em}} * (I_{temp_e} / 293.16^{\circ}\text{K}) * (760 \text{ mm Hg} / P_b) \\ &= 8.49 \text{ liter} * (295^{\circ}\text{K} / 293.16^{\circ}\text{K}) * (760 \text{ mm Hg} / 760 \text{ mm Hg}) \\ &= 8.54 \text{ liter} \end{aligned}$$

$$\begin{aligned} RHO_e &= (I_{mass_e} / I_{vol_e}) * (\text{Mol. Vol.} / \text{Mol. Wt.}) \\ &= (2.45 * 10^{-6} \text{ g} / 8.54 \text{ liter}) * (24.24 \text{ liter/mole} / 30.0268 \text{ g/mole}) \\ &= 232 \text{ ppbC} \end{aligned}$$

$$\begin{aligned} I_{vol_d} &= I_{vol_{dm}} * (I_{temp_d} / 293.16^{\circ}\text{K}) * (760 \text{ mm Hg} / P_b) \\ &= 31.57 \text{ liter} * (292^{\circ}\text{K} / 293.16^{\circ}\text{K}) * (760 \text{ mm Hg} / 760 \text{ mm Hg}) \\ &= 31.45 \text{ liter} \end{aligned}$$

$$\begin{aligned} RHO_d &= (I_{mass_d} / I_{vol_d}) * \text{Mol. Vol.} / \text{Mol. Wt.} \\ &= (0.17 * 10^{-6} \text{ g} / 31.45 \text{ liter}) * (24.24 \text{ liter/mole} / 30.0268 \text{ g/mole}) \\ &= 4.36 \text{ ppbC} \end{aligned}$$

$$DF = 9.76 / [CO_{2e} + (NMHC_e + CH_{4e} + CO_e) * 10^{-4}] \text{ (see DF Calc.)}$$

$$\begin{aligned} NMHC_e &= FID \text{ THC}_e - (r_{CH_4} * CH_{4e}) \\ &= 132 \text{ ppmC} - (1.20 * 108 \text{ ppmC}) \\ &= 2.4 \text{ ppmC} \end{aligned}$$

$$CO_e = (1 - (0.01 + 0.005 * HCR) * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

$$\begin{aligned} &= (1 - 0.02900 * 0.9\% - 0.000323 * 68\%) * 8 \text{ ppm} \\ &= 7.6 \text{ ppm} \end{aligned}$$

$$\begin{aligned} DF &= 9.76 / [0.9\% + (2.4 \text{ ppmC} + 108 \text{ ppmC} + 7.6 \text{ ppm}) * 10^{-4}] \\ &= 10.70 \end{aligned}$$

$$\begin{aligned} RHO_{conc} &= RHO_e - (RHO_d * (1 - (1 / DF))) \\ &= 232 \text{ ppbC} - (4.36 \text{ ppbC} * (1 - (1 / 10.70))) \\ &= 228 \text{ ppbC} \end{aligned}$$

$$\begin{aligned} RHO_{dens} &= (\text{Mol. Wt.}) * (\text{conversion of liter to ft}^3) / (\text{Mol. Vol.}) \\ &= (30.0268 \text{ g/mole} * 28.316 \text{ liter/ft}^3) / 24.237 \text{ liter/mole} \\ &= 35.080 \text{ g/ft}^3 \end{aligned}$$

$$RHO_{mass_n} = (RHO_{conc} * RHO_{dens} * VMIX * 10^{-6}) / (\text{Carbon No.})$$

$$\begin{aligned} RHO_{mass_1} &= (228 \text{ ppbC} * 35.080 \text{ g/ft}^3 * 2866 \text{ ft}^3 * 10^{-6}) / 1 \text{ carbon atom} \\ &= 22.9 \text{ mg} \end{aligned}$$

Similarly, for Phase 2:

$$RHO_{mass_2} = 6.3 \text{ mg}$$

and for Phase 3:

$$RHO_{mass_3} = 12.2 \text{ mg}$$

Therefore,

$$RHO_{wm} = 0.43 * \frac{(RHO_{mass_1} + RHO_{mass_2})}{(D_{phase_1} + D_{phase_2})} + 0.57 * \frac{(RHO_{mass_3} + RHO_{mass_2})}{(D_{phase_3} + D_{phase_2})}$$

$$RHO_{wm} = 0.43 * \frac{(22.9 \text{ mg} + 6.3 \text{ mg})}{(3.581 \text{ mile} + 3.845 \text{ mile})} + 0.57 * \frac{(12.2 \text{ mg} + 6.3 \text{ mg})}{(3.583 \text{ mile} + 3.845 \text{ mile})}$$

$$RHO_{wm} = 3.1 \text{ mg/mile (formaldehyde weighted mass emissions)}$$

DILUTION FACTOR CALCULATION

1. DILUTION FACTORS

1.1 For Non-Alcohol Fueled Vehicles:

$$1.1.1 \quad DF = \frac{100 * \frac{x}{x + y/2 + 3.76 * (x + y/4 - z/2)}}{CO_{2e} + (NMHC_e + CH_{4e} + CO_e) * 10^{-4}}$$

(where fuel composition is $C_xH_yO_z$ as measured for the fuel used.)

$$1.1.2 \quad CO_e = (1 - (0.01 + 0.005 * HCR) * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

a) For gasoline, $CH_{1.85}$, where $x = 1$, $y = 1.85$, and $z = 0$:

$$DF = 13.46 / [CO_{2e} + (NMHC_e + CH_{4e} + CO_e) * 10^{-4}]$$

$$CO_e = (1 - 0.01925 * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

b) For LPG, $CH_{2.66}$, where $x = 1$, $y = 2.66$, and $z = 0$:

$$DF = 11.63 / [CO_{2e} + (NMHC_e + CH_{4e} + CO_e) * 10^{-4}]$$

$$CO_e = (1 - 0.02330 * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

c) For CNG, $CH_{3.80}$, where $x = 1$, $y = 3.80$, and $z = 0$:

$$DF = 9.76 / [CO_{2e} + (NMHC_e + CH_{4e} + CO_e) * 10^{-4}]$$

$$CO_e = (1 - 0.02900 * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

1.2 For Alcohol Fueled Vehicles:

$$1.2.1 \quad DF = \frac{100 * \frac{x}{x + y/2 + 3.76 * (x + y/4 - z/2)}}{CO_{2e} + (NMHC_e + CH_4 + CO_e + ROH_e) * 10^{-4}}$$

(where fuel composition is $C_xH_yO_z$ as measured for the fuel used.)

$$1.2.2 \quad CO_e = (1 - (0.01 + 0.005 * HCR) * CO_{2e} - 0.000323 * R_a) * CO_{em}$$

NOTE: If a CO instrument which meets the criteria specified in CFR 40, 86.111 is used and the conditioning column has been deleted, CO_{em} must be substituted directly for CO_e .

a) For M100 (100% methanol), CH_3OH , where $x = 1$, $y = 4$, and $z = 1$:

$$\text{DF} = 11.57 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{ROH}_e) * 10^{-4}]$$

$$\text{CO}_e = (1 - 0.03000 * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

b) For M85 (85% methanol, 15% indolene), $\text{CH}_{3.41}\text{O}_{0.72}$, where $x = 1$, $y = 3.41$, and $z = 0.72$:

$$\text{DF} = 12.01 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{ROH}_e) * 10^{-4}]$$

$$\text{CO}_e = (1 - 0.02705 * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

c) For E100 (100% ethanol), $\text{C}_2\text{H}_5\text{OH}$, where $x = 1$, $y = 3$, and $z = 0.5$:

$$\text{DF} = 12.27 / [\text{CO}_{2e} + (\text{NMHC}_e + \text{CH}_{4e} + \text{CO}_e + \text{ROH}_e) * 10^{-4}]$$

$$\text{CO}_e = (1 - 0.02500 * \text{CO}_{2e} - 0.000323 * R_a) * \text{CO}_{em}$$

DEFINITIONS

- Carbon No. = number of carbon atoms in the hydrocarbon or organic compound being measured.
- CH_{4e} = methane concentration in the dilute exhaust, ppmC.
- CO_e = carbon monoxide concentration in the dilute exhaust corrected for carbon dioxide and water removal, ppm.
- CO_{em} = carbon monoxide concentration in the dilute exhaust uncorrected for carbon dioxide and water removal, ppm.
- CO_{2e} = carbon dioxide concentration in the dilute exhaust, %.
- $D_{phase\ n}$ = distance driven by the test vehicle on a chassis dynamometer during test phase n (where n is either 1, 2, or 3), mile.
- $Dens_{ROH}$ = density of alcohol, g/ml.
- DF = dilution factor (see Dilution Factor Calculation).
- FID THC_e = total hydrocarbon concentration including methane and alcohol in the dilute exhaust as measured by the FID, ppmC.
- HC_{conc} = net concentration of an HC compound in the dilute exhaust corrected for background per test phase, ppbC.
- HC_d = composite concentration of an HC compound in the dilution air (background) for all three test phases as determined from the composite dilution air sample using the procedure specified in method no. 1002 and method no. 1003, ppbC.
- HC_{dens} = mass per unit volume of an HC compound corrected to standard conditions (293.16°K and 760 mm Hg), g/ft³.
- HC_e = concentration of an HC compound in the dilute exhaust per test phase as determined from the dilute exhaust sample using the procedure specified in method no. 1002 and method no. 1003, ppbC.
- $HC_{mass\ n}$ = mass emissions of an HC compound per test phase n (where n is either 1, 2, or 3), mg.
- HC_{wm} = total weighted mass emissions of an HC compound per mile, g/mile.
- HCR = hydrogen-to-carbon ratio for the fuel used.

I_{conc_d1}	= dilution air (background) alcohol concentration in the primary impinger for all three test phases as determined by the procedure specified in method no. 1001, ppmC.
I_{conc_d2}	= dilution air (background) alcohol concentration in the secondary impinger for all three test phases as determined by the procedure specified in method no. 1001, ppmC.
I_{conc_e1}	= dilute exhaust alcohol concentration in the primary impinger per test phase as determined by the procedure specified in method no. 1001, ppmC.
I_{conc_e2}	= dilute exhaust alcohol concentration in the secondary impinger per test phase as determined by the procedure specified in method no. 1001, ppmC.
I_{mass_d}	= total mass of an alcohol or carbonyl compound collected from the dilution air (background) in both primary and secondary impingers for all three test phases as determined by the procedure specified in method no. 1001 (alcohol) or method no. 1004 (carbonyl), ug.
I_{mass_e}	= total mass of an alcohol or carbonyl compound collected from the dilute exhaust in both primary and secondary impingers per test phase as determined by the procedure specified in method no. 1001 (alcohol) or method no. 1004 (carbonyl), ug.
I_{temp_d}	= dilution air temperature at the flowmeter inlet for impinger sampling, °K.
I_{temp_e}	= dilute exhaust temperature at the flowmeter inlet for impinger sampling, °K.
I_{vol_d}	= total volume of dilution air (background) bubbled through the impingers for all three test phases corrected to standard conditions (293.16°K and 760 mm Hg), liter.
$I_{vol_{dm}}$	= total volume of dilution air (background) bubbled through the impingers for all three test phases as measured during testing, liter.
I_{vol_e}	= total volume of dilute exhaust bubbled through the impingers per test phase corrected to standard conditions (293.16°K and 760 mm Hg), liter.
$I_{vol_{em}}$	= total volume of dilute exhaust bubbled through the impingers per test phase as measured during testing, liter..
I_{vol_r}	= volume of the reagent used in an impinger, ml.
Mol. Vol.	= molecular volume which is 24.055 liter/mole at standard conditions (293.16°K and 760 mm Hg).

Mol. Wt.	= molecular weight of the compound being measured, g/mole.
NMHC _e	= non-methane hydrocarbon concentration in the dilute exhaust corrected for methane and alcohol removal, ppmC.
P _B	= barometric pressure during testing, mm Hg.
R _a	= relative humidity of the ambient air, %.
r _{CH₃OH}	= FID response factor to methanol (see CFR 40, 86.121-90(c)).
r _{CH₄}	= FID response factor to methane (see "Determination of NMHC by FID", section 4).
r _{C₂H₅OH}	= FID response factor to ethanol (same procedure for methanol response factor, see CFR 40, 86.121-90(c)).
RHO	= generic symbol representing a carbonyl compound such as formaldehyde, acetaldehyde, acetone, etc.
RHO _{conc}	= net concentration of a carbonyl compound in the dilute exhaust corrected for background per test phase, ppmC.
RHO _d	= composite concentration of a carbonyl compound in the dilution air (background) for all three test phases, ppmC.
RHO _{dens}	= mass per unit volume of a carbonyl compound corrected to standard conditions (293.16°K and 760 mm Hg), g/ft ³ .
RHO _e	= concentration of a carbonyl compound in the dilute exhaust per test phase, ppmC.
RHO _{mass_n}	= mass emissions of a carbonyl compound per test phase n (where n is either 1, 2, or 3), g.
RHO _{wm}	= total weighted mass emissions of a carbonyl compound per mile, g/mile.
ROH	= generic symbol representing an alcohol compound such as methanol or ethanol.
ROH _{conc}	= net concentration of an alcohol compound in the dilute exhaust corrected for background per test phase, ppmC.
ROH _d	= composite concentration of an alcohol compound in the dilution air (background) for all three test phases, ppmC.
ROH _{dens}	= mass per unit volume of an alcohol compound corrected to standard conditions (293.16°K and 760 mm Hg), g/ft ³ .
ROH _e	= concentration of an alcohol compound in the dilute exhaust per test phase, ppmC.

ROH_{mass_n} = mass emissions of an alcohol compound per test phase n
(where n is either 1, 2, or 3), g.

ROH_{wm} = total weighted mass emissions of an alcohol compound per
mile, g/mile.

ROR = generic symbol representing an ether compound such as MTBE.

ROR_{wm} = total weighted mass emissions of an ether compound per
mile, g/mil.

$VMIX$ = total dilute exhaust volume measured per test phase
corrected to standard conditions (293.16°K and 760 mm Hg),
ft³.

REFERENCE

- (1) Code of Federal Regulations, title 40, part 86, subpart B

These procedures have been superceded.

State of California
AIR RESOURCES BOARD

CALIFORNIA NON-METHANE ORGANIC GAS
TEST PROCEDURES

Adopted: July 12, 1991

NOTE: These test procedures apply only to 1992 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles certified to California emission standards for transitional low-emission vehicles (TLEVs), low-emission vehicles (LEVs), or ultra-low-emission vehicles (ULEVs).

State of California

AIR RESOURCES BOARD

California Non-Methane Organic Gas Test Procedures

With the establishment of non-methane organic gas (NMOG) standards, sampling and analytical procedures for non-methane hydrocarbons (NMHC) will be supplemented to include procedures for measuring oxygenated hydrocarbons. Analytical procedures utilizing gas or high pressure liquid chromatography, developed by the Monitoring and Laboratory Division of the Air Resources Board (ARB) are described for use as the standard operating procedures for measuring alcohols, NMHCs, and carbonyls. These procedures are described in detail in accompanying chapters designated M.L.D. No. 101, 102, 103A and 104. Alternate procedures may be used if shown to yield equivalent results, and if approved in advance by the Executive Officer of the ARB. The 'California Non-Methane Organic Gas Test Procedures' consist of the aforementioned M.L.D. procedures and the 'California Non-Methane Hydrocarbon Procedures.'

For manufacturers which choose to utilize the reactivity adjustment factors determined by the ARB for different vehicle/fuel systems, the following analyses shall be performed to determine emissions of NMOG:

Fuel	NMHC*	NMHC by GC	Alcohols	Carbonyls
Gasoline	X			
Alcohol	X			X
LPG+	X		X	X
CNG+		X		X
Diesel		X		X

- (*) NMHC -- requires 'California Non-Methane Hydrocarbon Test Procedures' be used to quantify emissions of NMHC.
Carbonyls -- requires emissions of aldehydes and ketones be quantified according to M.L.D. No. 104.
Alcohols -- requires emissions of alcohols be quantified according to M.L.D. No. 101.
NMHC by GC -- requires emissions of non-methane hydrocarbons be quantified according to M.L.D. No. 102 and 103A.

(+) LPG = Liquified Petroleum Gas; CNG = Compressed Natural Gas.

For manufacturers of gasoline-, alcohol-, LPG- or CNG-fueled vehicles, which choose to develop reactivity adjustment factors unique to their vehicle/fuel system, exhaust NMOG emissions would need to be fully speciated. These requirements would also apply to flexible- or dual-fueled vehicles, and hybrid electric vehicles which utilize a combustion engine as a range extender. Gaseous hydrocarbon samples would be analyzed according to M.L.D. No. 102 and 103A; all non-oxygenated hydrocarbons and ethers containing 12 or fewer carbon atoms would need to be identified and measured. Exhaust emissions of alcohols and carbonyls would be collected in impingers and analyzed according to M.L.D. No. 101 and 104, respectively. Only vehicles powered by alcohol fuels or gasoline containing alcohol would be required to perform tests for alcohols.

For diesel-fueled vehicles, the development of speciated hydrocarbon emission profiles is of concern from a technical standpoint. To facilitate the process of identifying a test procedure and reactivity adjustment factor for certifying vehicles, manufacturers are encouraged to provide comments and/or suggestions on sampling and analytical procedures. At present, sampling and analysis procedures would be developed according to the following interim guidelines:

A sample of motor vehicle diesel exhaust at an elevated temperature would be passed through a porous polymer sample tube (XAD-2 or equivalent). The sample tube would be extracted with a solvent (methylene chloride or equivalent), concentrated and introduced into a gas chromatograph/flame ionization detector (GC/FID) with a high temperature capillary column (SE-30 or similar) for analysis. Other methods may be utilized but should be submitted to the Board for prior approval. See also Technical Reports: EPA/AA/CTAB/PA/80-5 (September, 1980) "Comparison of Gas Phase Hydrocarbon from Light-Duty Gasoline Vehicles and Light-Duty Vehicles Equipped with Diesel Engines," and F. Black and L. High (SAE No. 790422) "Methodology for Determining Particulate and Gaseous Diesel Hydrocarbon Emissions."

Because the composition of the exhaust emissions from diesel-fueled vehicles is highly complex, complete identification of each hydrocarbon species is not practical. The staff recommends reporting of data grouped according to carbon number rather than fully speciated data. Additional complexity is recognized for hydrocarbons that would be identified from the n-C15 and n-C25 peaks, which are known to coexist in the vapor and particulate stages. Hydrocarbons which are larger than n-C25 are generally found only in the particulate form.

It is recognized that the speciation of hydrocarbons in the vapor stage does not address the composition of the particulate portion of the sample. Specifically, the soluble organic fraction of the diesel particulates would not be subject to speciated analysis. Emission profiles from diesel-fueled vehicles would also need to include measurements of carbonyls according to M.L.D. No. 104.

NOTE: This is a new test procedure. It consists of the following documents:

1. California Non-Methane Hydrocarbon Test Procedures
2. Procedure for the Analysis of Automotive Exhaust for Methanol and Ethanol, SOP No. MLD 101
3. Procedure for the Determination of C_2 to C_6 Hydrocarbons in Automotive Sources Samples by GC, SOP No. MLD 102
4. Procedure for the Determination of Midrange Hydrocarbons in Automotive Exhaust by Gas Chromatography, SOP No. MLD 103A
5. Procedure for the Analysis of Automotive Exhaust for Formaldehyde and Other Carbonyl Compounds, SOP No. MLD 104

All of these documents with the exception of "California Non-Methane Hydrocarbon Test Procedures" are newly adopted. The "California Non-Methane Hydrocarbon Test Procedures" are printed in a way to reflect amendments to the previously adopted test procedures: additions are shown in underline and deletions are shown in ~~strikeout~~.

State of California
AIR RESOURCES BOARD

CALIFORNIA NON-METHANE HYDROCARBON
TEST PROCEDURES

Adopted: May 24, 1978.

Amended: May 15, 1990; effective July 15, 1990

Amended: July 12, 1991

NOTE: This document is printed in a style which indicates amendments to the Test Procedures as adopted May 15, 1990. The amendments are shown in underline to indicate additions to the text and ~~strikeout~~ to indicate deletions.

California Non-Methane Hydrocarbon Test Procedures

I. Introduction

This procedure describes a method for determining the non-methane hydrocarbon exhaust emissions from motor vehicles. A gas chromatograph combined with a flame ionization detector is the basic instrument package specified in this procedure for direct measurement of methane concentrations. An example of the system is shown in Figure 1. The SAE Recommended Practice J1151 is a reference on generally accepted GC principles and analytical techniques for this specific application. Other applicable forms of instrumentation such as those described in SAE J1151 which prove to yield equivalent results to those specified in this procedure may be used subject to the approval of the Executive Officer.

II. Instruments

A gas chromatograph (GC) along with a flame ionization detector (FID) shall be used for measuring the methane (CH_4) concentrations of exhaust samples collected in bags from a constant volume sampler (CVS). The instrument performance specifications shall be in compliance with the principles established in SAE Recommended Practice J1151.

III. Sampling Procedures

A 10-minute warm-up period shall be allowed for the GC/FID and recorder. A calibration of the instrument with a 1.0% gravimetric CH_4 in air, traceable to the National Bureau of Standards (NBS) National Institute of Standards and Technology (NIST), shall be done immediately before and after each CVS-75 test analysis. Exhaust samples for CH_4 analysis shall be taken from the sample bags of the CVS unit. Either the syringe method or the continuous method may be used.

A. Syringe Method

Two samples (30 cc each) from each exhaust gas bag and one 30 cc sample from each background bag (for a total of 9 samples for each cold start CVS test) shall be taken with laboratory quality syringes. The analysis for each syringe sample shall be performed in the following sequence:

1. Calibrate instrument for anticipated range.
2. Inject 10 cc of sample from the syringe into the sample loop of the GC.
3. Push sample through columns and read instrument response.
4. Backflush column.
5. Verify calibration point.

Steps 2 through 4 shall be repeated until all 9 syringe samples have been analyzed.

B. Continuous Sampling Method

An independent sampling system for CH_4 analysis is required. This sampling system may be integral with the existing CVS sampling train.

1. Component Parts

The CH₄ sampling system consists of the following component parts:

- a) A pump to transfer gas samples from CVS sample bags to the GC.
- b) A filter to remove particulate matter from the sample gases.
- c) A flow control valve (V₁) to regulate gas flow to the GC.
- d) A selector valve (V₂) for directing either sample or calibration gas to the GC.
- e) A recorder to provide permanent records of calibration gas and sample gas measurements.
- f) A control panel
 - to start or stop the sample pump;
 - to operate the selector valve;
 - to start or stop the recorder.

2. Sampling Sequence

- a) Calibrate instrument for anticipated range.
- b) Connect sample bag to quick-connector.
- c) Start pump to fill sample loop of the GC.
- d) Push sample through column and read instrument response.
- e) Backflush.
- f) Stop pump.
- g) Disconnect sample bag.
- h) Verify calibration point.

Perform steps (b) through (g) for all 6 sample bags.

IV. Instrument Calibration

A series of standard gases (1.0% gravimetric CH_4 in air) traceable to NIST NBS, covering the range of concentrations within which sample gases may be expected to fall, should be used for calibration. The calibration procedures, operating parameters and instrument performance specifications should be in compliance with principles established in SAE J1151, Sections 7.3, 7.4, 8 and 9.

V. Sample Analysis

The response of the GC recorder is in millimeters of peak height. Divide peak height by the mm/ppm from the calibration data to obtain ppm methane.

The non-methane hydrocarbon emissions shall be computed as follows:

(1) Definitions

HC_e ----- Hydrocarbon exhaust bag concentration in ppm carbon equivalent.

NMHC_e = Non-methane hydrocarbon dilute exhaust bag concentration corrected for methane and alcohol content in ppm carbon equivalent.

FID HC_e = Concentration of hydrocarbon plus methane and methanol (for methanol-fueled engines) or ethanol (for ethanol-fueled engines) in dilute exhaust as measured by the FID in ppm carbon equivalent.

FCH_4_e = FID response to methane

FCH_2OH_e = FID response to methanol

$\text{FC}_2\text{H}_5\text{OH}_e$ = FID response to ethanol

CH_{4e} = Methane exhaust bag concentration in RPM ppm carbon equivalent.

$C_{CH_2OH}_e$ = Concentration of methanol in dilute exhaust as determined from the dilute exhaust methanol sample using the procedure specified in M.L.D. No. 101, in ppm carbon.

$C_{C_2H_5OH}_e$ = Concentration of ethanol in dilute exhaust as determined from the dilute exhaust ethanol sample using the procedure specified in M.L.D. No. 101, in ppm carbon.

$NMHC_e$ = $FID\ HC_e - (r_{CH_4})CH_{4e}$; for non-alcohol fuels

$NMHC_e$ = $FID\ HC_e - (r_{CH_4})CH_{4e} - (r_{CH_2OH})C_{CH_2OH}_e$; for fuels containing methanol

$NMHC_e$ = $FID\ HC_e - (r_{CH_4})CH_{4e} - (r_{C_2H_5OH})C_{C_2H_5OH}_e$; for fuels containing ethanol

HC_a ----- Hydrocarbon-ambient-bag-concentration-in-RPM-carbon-equivalent.

$NMHC_d$ = Hydrocarbon ambient bag concentration corrected for methane and alcohol content in ppm carbon equivalent.

$FID\ HC_d$ = Concentration of hydrocarbon plus methane and methanol (for methanol-fueled engines) or ethanol (for ethanol-fueled engines) in dilution air as measured by the FID in ppm carbon equivalent.

$C_{CH_2OH}_d$ = Concentration of methanol in dilution air as determined from dilution air methanol sample using the procedure specified in M.L.D. No. 101, in ppm carbon.

$C_{C_2H_5OH}_d$ = Concentration of ethanol in dilution air as determined from the dilution air ethanol sample using the procedure specified in M.L.D. No. 101, in ppm carbon.

CH_{4d} = Methane ambient bag concentration in RPM ppm carbon equivalent.

$NMHC_d$ = $FID\ HC_d - (r_{CH_4})CH_{4d}$; for non-alcohol fuels

$NMHC_d$ = $FID\ HC_d - (r_{CH_4})CH_{4d} - (r_{CH_2OH})C_{CH_2OH}_d$; for fuels containing methanol.

$$NMHC_d = FID\ HC_d - (r_{CH_4})CH_{4d} - (r_{C_2H_5OH_d})C_{2H_5OH_d} ; \text{ for fuels containing ethanol}$$

CO_{em} = CO exhaust bag concentration in PPM ppm (uncorrected for CO_2 and H_2O removal).

CO_{2e} = CO_2 exhaust bag concentration in PPM %.

R_a = Relative humidity of the ambient air in percent

CO_e = $(1 - 0.01295CO_{2e} - 0.000323R_a)CO_{em}$; for gasoline- and diesel-fueled vehicles.

CO_e = $(1 - (0.01 + 0.005HCR)CO_{2e} - 0.000323R_a)CO_{em}$; where HCR is the hydrogen-to-carbon ratio as measured for the fuel used.

CO_e = CO exhaust bag concentration in PPM (corrected for CO_2 and H_2O removal).

CO_{dm} = CO ambient bag concentration in PPM (uncorrected for H_2O removal).

CO_d = CO ambient bag concentration in PPM (corrected for H_2O removal).

CO_d = $(1 - 0.000323 R_a)CO_{dm}$

NOTE: If a CO instrument which meets the criteria specified in Title 40, section 86.111 of the Code of Federal Regulations is used and the conditioning column has been deleted, CO_e must be substituted directly for CO_d and CO_{dm} must be substituted directly for CO_d .

D_{phase} = Distance per phase (calculated from roll count).

HG_{mass} --- Mass-in-grams-of-hydrocarbon-per-test-phase-

GH_{4mass} --- Mass-in-grams-of-methane-per-test-phase-

$NMHC_{mass}$ = Mass in grams of non-methane hydrocarbon per test phase.

V_{mix} = Total dilute exhaust volume in cubic feet per test phase corrected to 68°F and 760 mm Hg.

$$BF = \frac{13.4}{(HG_e + 69_e + 69_{2e})} \times 10^{-4}$$

$$DF = \frac{13.4}{CO_{2e} + (NMHC_e + CH_4 + CO_e) \times 10^{-4}} \quad ; \text{ for gasoline fueled vehicles}$$

$$DF = \frac{11.7}{CO_{2e} + (NMHC_e + CH_4 + CO_e) \times 10^{-4}} \quad ; \text{ for LPG fueled vehicles}$$

$$DF = \frac{100 \times \left(\frac{1}{x + y/2 + 3.76(x + y/4 - z/2)} \right)}{CO_{2e} + (NMHC_e + CH_4 + CO_e + C_{CH_3OH_e}) \times 10^{-4}} \quad ; \text{ for fuels containing methanol where the fuel composition is expressed as } C_xH_yO_z$$

$$DF = \frac{100 \times \left(\frac{1}{x + y/2 + 3.76(x + y/4 - w/2)} \right)}{CO_{2e} + (NMHC_e + CH_4 + CO_e + C_{C_2H_5OH_e}) \times 10^{-4}} \quad ; \text{ for fuels containing ethanol where the fuel composition is expressed as } C_xH_yO_z$$

$$W_f = \frac{1}{DF}$$

$\frac{P}{P_a}$ = Relative humidity of the ambient air in percent

$NMHC_{dens}$ = Density of Hydrocarbon in grams/ft³
 (16.33 gm/ft³ @ 68°F and 760 mm Hg assuming a C:H ratio of 1:1.85; 17.46 gm/ft³ for compressed natural gas and 17.28 gm/ft³ for LPG @ 68°F and 760 mm Hg and assuming an average C:H ratio of 1+2+8 for natural gas and 1:2.656 for LPG respectively).

$$HG_{e0re} = HG_e - W_f \cdot (HG_d)$$

$$GH_{e0re} = GH_{4e} - W_f \cdot (GH_{4d})$$

$$NMHC_{e0re} = HG_{e0re} - GH_{4e0re}$$

$NMHC_{conc}$ = Non-methane hydrocarbon concentration of the dilute exhaust sample corrected for background, in ppm carbon equivalent.

$$NMHC_{conc} = NMHC_e - NMHC_d (1 - 1/DF)$$

$$NMHC_{mass} = \frac{NMHC_{conc} \times NMHC_{dens} \times V_{mix}}{10^6}$$

$NMHC_{W_m}$ = Weighted Mass of Non-Methane Hydrocarbon in grams/mile

$$NMHC_{W_m} = 0.43 \frac{(NMHC_{mass_1} + NMHC_{mass_2})}{(D_{phase_1} + D_{phase_2})} + 0.57 \frac{(NMHC_{mass_3} + NMHC_{mass_2})}{(D_{phase_3} + D_{phase_2})}$$

(2)

Sample Calculation For a Gasoline-Fueled Vehicle

	Data	HC_e	HC_d	CH_{4e}	CH_{4d}	CO_e	CO_{2e}	V_{mix}	D_{phase}
1. Cold Trans.	49.3	29.3	10.74	2.20	152.0	15466	2713.2	3.598	
2. Cold Stab.	26.2	19.1	7.23	2.20	23.0	9845	4650.5	3.902	
3. Hot Trans.	27.7	18.5	7.79	2.20	46.6	13626	2707.9	3.589	
1. Cold Trans.	41.8	8.6	7.53	5.27	142.0	1.19	2846	3.583	
2. Cold Stab.	13.0	8.4	5.68	5.10	20.2	0.80	4856	3.248	
3. Hot Trans.	15.4	8.9	6.16	5.20	35.5	1.04	2839	3.586	

$$BF_1 = \frac{13.4}{(49.3 + 152.0 + 15466) \times 10^{-4}} = 8.563$$

$$W_{F_1} = \frac{1}{8.563} = 0.1168$$

$$NMHC_d = 8.6 - (1.23 \times 5.27) = 2.12 \text{ ppm}$$

for this example assume $r(CH_4) = 1.23$

$$NMHC_e = 41.8 - (1.23 \times 7.53) = 32.54 \text{ ppm}$$

$$DF_1 = \frac{13.4}{1.19 + (32.54 + 7.53 + 142.0) \times 10^{-4}} = 11.091$$

$$1-1/DF = 1 - 1/11.091 = 0.9098$$

$$HC_{core_1} = 49.3 - 0.863(29.3) = 31.375 \text{ ppm}$$

$$CH_{4core_1} = 10.74 - 0.863(2.2) = 8.797 \text{ ppm}$$

$$NMHC_{core_1} = (31.375 - 8.797) = 22.578 \text{ ppm}$$

$$NMHC_{conc_1} = (32.54 - [0.9098 \times 2.12]) = 30.61 \text{ ppm}$$

$$NMHC_{mass_1} = \frac{22.578 \times 16.33 \times 2846}{10^6} = 1.000 \text{ grams}$$

$$NMHC_{mass_1} = \frac{30.61 \times 16.33 \times 2846}{10^6} = 1.423 \text{ grams}$$

Similarly,

$$NMHC_{mass_2} = 0.176 \text{ 0.318 grams}$$

$$NMHC_{mass_3} = 0.233 \text{ 0.256 grams}$$

$$NMHC_w = 0.43 \times \frac{(1.423 + 0.318)}{(3.583 + 3.902)} + 0.57 \times \frac{(0.233 + 0.176)}{(3.583 + 3.902)}$$

$$NMHC_w = 0.43 \times \frac{(1.423 + 0.318)}{(3.583 + 3.902)} + 0.57 \times \frac{(0.233 + 0.176)}{(3.583 + 3.902)}$$

$$NMHC_w = 0.999 \text{ 0.145 gm/mi}$$

(2)

Sample calculation for a vehicle fueled with 85% gasoline and 15% methanol by volume (M-85).

Data	HC _e	HC _d	CH _{4e}	CH _{4d}	CH _{3OH}	CO _e	CO _{2e}	V _{mix}	D _{phase}
1. Cold Trans.	88.5	5.4	17.76	2.82	72.9	302.8	1.23	2832	3.570
2. Cold Stab.	14.5	7.0	8.01	2.82	0.0	5.0	0.83	4827	3.850
3. Hot Trans.	21.8	7.7	10.13	2.93	7.4	16.2	1.13	2925	3.558

$$\text{NMHC}_2 = 5.4 - (1.23 \times 2.82) = 1.93 \text{ ppm}$$

$$\text{assume } r_{\text{CH}_4} = 1.23$$

$$\text{NMHC}_3 = 88.5 - (1.23 \times 17.76) - (0.75 \times 72.9) = 11.98 \text{ ppm}$$

$$\text{assume } r_{\text{CH}_3\text{OH}} = 0.75$$

$$\text{DF}_1 = \frac{12.04}{1.28 + (11.98 + 17.76 + 302.8 + 72.9) \times 10^{-4}} = 9.117$$

for M-85 fueled vehicle where the fuel composition is expressed as $\text{CH}_{2.4068}\text{O}_{0.7241}$.

$$1 - 1/\text{DF} = 1 - 1/9.117 = 0.8903$$

$$\text{NMHC}_{\text{conc}_1} = (11.98 - [0.8903 \times 1.93]) = 10.26 \text{ ppm}$$

$$\text{NMHC}_{\text{mass}_1} = \frac{10.26 \times 16.33 \times 2832}{10^6} = 0.474 \text{ grams}$$

Similarly,

$$\text{NMHC}_{\text{mass}_2} = 0.176 \text{ grams}$$

$$\text{NMHC}_{\text{mass}_3} = 0.233 \text{ grams}$$

$$\text{NMHC}_{\text{W}_m} = 0.43 \times \frac{(0.474 + 0.107)}{(3.584 + 3.842)} + 0.57 \times \frac{(0.107 + 0.250)}{(3.842 + 3.581)}$$

$$\text{NMHC}_{\text{W}_m} = 0.062 \text{ gm/ml}$$

A. Negative NMHC Determinations

With high methane fractions, the above procedure may result in negative NMHC_{W_m} values. In these cases, any negative NMHC_{W_m} value whose absolute value is less than 10 percent of the NMHC standard shall be rounded to

zero. Negative NMHC_{w_m} values whose absolute value is more than 10 percent of the NMHC standard shall require instrument recalibration and sample remeasurement, or repetition of the emission testing if the above 10-percent criterion cannot be met.

Sampling techniques other than the one above for the determination of NMHC_{w_m} may be used subject to the approval of the Executive Officer.

ARB System for
Continuous Sampling
of Methane





Figure 1



November 1985

AIR RESOURCES BOARD

PROCEDURE FOR THE ANALYSIS OF
AUTOMOTIVE EXHAUST FOR
METHANOL AND ETHANOL

SOP NO. MLD 101

Southern Laboratory Branch
Monitoring and Laboratory Division
State of California
9528 Telstar Avenue
El Monte, CA 91731

This report has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policies of the Air Resources Board, nor does mention of trade names or commercial products constitute endorsement or recommendation for use.

05848

CALIFORNIA AIR RESOURCES BOARD
MONITORING AND LABORATORY DIVISION

Procedure for the Analysis of
Automotive Exhaust for
Methanol and Ethanol

1 Introduction

1.1 This document describes a method of analyzing automotive exhaust for methanol and ethanol in the range of 4 to 1200 micrograms per 15 mL of solution.

1.2 This procedure is based on a method developed by the EPA¹ which involves flowing diluted engine exhaust through deionized water contained in glass impingers and analyzing this solution by gas chromatography.

1.3 Lower alcohol concentrations may be analyzed by increasing the volume of exhaust sampled.

1.4 Higher concentrations may be determined by quantitatively diluting the aqueous impinger solution with deionized water or extending the calibration curve to include higher standard concentrations.

1.5 There are no known chemical interferences with this method.

2 Method

2.1 The sampling procedure is conducted according to the Federal Test Procedure (FTP), specified in the Code of Federal Regulations².

2.2 Two impingers, each containing 15 mL deionized water, are used for each mode of the FTP Constant Volume Sampler (CVS) test.

2.3 Upon completion of the CVS test, the impinger samples are analyzed by gas chromatography.

3 Apparatus

3.1 The analytical system is comprised of the following:

3.1.1 Varian model 3400 or 6000 gas chromatograph (GC), equipped with DB-Wax Megabore column and flame ionization detector (FID).

- 3.1.2 Varian model 8000 autosampler
- 3.1.3 Perkin Elmer LIMS (or similar) data system.

4 Reagents

- 4.1 Methanol, 99.9%, HPLC grade, EM Science or equivalent.
- 4.2 Ethanol, absolute.
- 4.3 ASTM Type I deionized water.
- 4.4 A stock solution of 1% methanol and 1% ethanol is prepared by diluting 1.00 mL each of methanol and ethanol to 100.0 mL with deionized water.
 - 4.4.1 A working standard of 50 ppm is prepared by successive dilutions of the stock solution. Figure 1 illustrates a typical chromatogram.
 - 4.4.2 A control standard is also prepared by successive dilutions of the stock solution. The concentration should be approximately that of the samples, typically 25 to 35 ppm.
 - 4.4.3 All standards should be refrigerated during storage.
- 4.5 If other alcohols are found in the exhaust, standards containing these additional compounds should be prepared, as above.

5 Procedure

- 5.1 Each of six graduated fritted midget impingers is filled with 15 mL of deionized water.
- 5.2 The six impingers are divided into three sets of two; a seventh is used as a trap. Each set is connected in series and placed in an ice bath (fig. 2). Dilute exhaust is drawn through the three pairs of impingers during FTP modes 1, 2, and 3, respectively.
- 5.3 The impingers are allowed to warm to room temperature and the solution contained in each impinger is transferred to a vial and sealed.
 - 5.3.1 Samples should be refrigerated (ca. 40°F or lower) if immediate analysis is not feasible or if reanalysis at a later date may be required.
- 5.4 A 1 microliter aliquot of each unmodified sample is injected via autosampler into a gas chromatograph, configured as follows:

Column: DB-wax, 30 m, 0.53 mm ID, 1.0 micron film thickness
 Carrier gas: Helium at 5 mL/min
 Make-up gas: Helium at 25 mL/min
 Detector: FID, Hydrogen at 30 mL/min and Air at 300 mL/min
 Injector: Packed column injector with megabore adapter
 insert; on-column injection.
 Temperature: 50°C (1 min), 50°C to 100°C (5°C/min), 100°C (1 min)
 Data system: LIMS data system

- 5.4.1 Two calibration standards, one control standard, and one water blank are analyzed daily at the beginning of each set of samples.
- 5.4.2 A replicate analysis is performed on one of every ten samples, or at least once per day.
- 5.4.3 The calibration standard is repeated every ten samples and again at the end.
- 5.5 The above procedure may be modified for analysis of higher alcohols by increasing the final temperature and adjusting the temperature ramping to achieve good separation of the desired components. In addition, a less polar impinger solution would be required to capture alcohols above C₅.

6 Calculations

- 6.1 The concentration of each alcohol is determined by comparing the sample peak area with that of an external standard:

$$\text{Concentration}_{\text{sample}} = \frac{\text{Concentration}_{\text{standard}} \times \text{Area}_{\text{sample}}}{\text{Area}_{\text{standard}}}$$

- 6.1.1 This concentration is then used to calculate the total amount of methanol in each impinger:

$$\text{Mass (ug)} = \text{Concentration (ppm)} \times 15 \text{ mL} \times \text{density (g/mL)}$$

- 6.2 A multi-point calibration was conducted on May 24, 1989, to determine the linearity of response of the FID.

	Conc (ppm)	Area Counts				Std. Dev.	% RSD
		Run #1	Run #2	Run #3	Mean		
Methanol:	0.5	112	106	--	109	--	--
	1.0	224	208	--	216	--	--
	5.0	1142	1117	1101	1120	14.6	1.30
	10	2285	2349	2336	2323	23.9	1.03
	50	11997	11776	11539	11770	162	1.39
	100	23530	23486	23038	23351	192	0.824

	(PPM)	Run #1	Run #2	Run #3	Mean	Dev.	RSD
Ethanol:	0.5	163	144	--	153.5	--	--
	1.0	323	310	--	316.5	--	--
	5.0	1642	1638	1619	1633	8.69	0.532
	10	3267	3357	3325	3316	32.3	0.973
	50	17053	16739	16378	16723	239	1.43
	100	33555	33561	33110	33409	183	0.547

Note that only two analyses of the 0.5 and 1.0 ppm solutions were successfully completed on this date.

6.2.2 Linear plots of the multi-point data are shown in figs. 3 and 4. For methanol:

slope (m) = 234.02 Area Counts/ppm
intercept (b) = -12.54 Area Counts
correlation coefficient = 0.9999

For ethanol:

slope (m) = 334.41 Area Counts/ppm
intercept (b) = -21.32 Area Counts
correlation coefficient = 1.000

6.3 The precision of the GC analysis and data reduction is shown in the table below and the corresponding plots (figs. 5 and 6) for the 50 ppm standard, analyzed May 25, 1989.

Run #	MeOH Area Counts	EtOH Area Counts
1	11446	16266
2	12006	17040
3	12000	17034
4	11958	16982
5	11699	16618
6	11811	16864
7	11459	16282
8	11632	16598
9	11930	16934
10	11914	16922
Mean	11786	16754
Std. dev.	203.8	280.8
% RSD	1.73 %	1.68 %

6.4 The limit of detection (LOD) is determined from the multi-point data (6.2). Since at least three data points are required for the calculation, the 5.0 ppm standard is used.

$$LOD = \frac{161 + (3)(std. dev.)}{m}$$

$$LOD_{MeOH} = \frac{1-12.541 + (3)(20.7)}{234} = 0.32 \text{ ppm}$$

$$LOD_{EtOH} = \frac{1-21.321 + (3)(12.3)}{334.41} = 0.17 \text{ ppm}$$

The LOD could be lowered by obtaining more data points at the 0.5 or 1.0 ppm level.

Quality Control

- 7.1 Calibration and control standards (working standards) are prepared every six months and analyzed daily.
- 7.2 Quality Control (Q.C.) charts are maintained for both calibration and control standards.
 - 7.2.1 The calibration standard Q.C. chart is used to monitor both instrument response and standard stability. Examples are shown in figures 7 and 8. (Note: the injection port septum was replaced following the 17th data point.)

For methanol:

Mean = 7679
Std. dev. = 102
% RSD = 1.33
n = 20

For ethanol:

Mean = 10511
Std. dev. = 151
% RSD = 1.44
n = 20

- 7.2.2 The control standard Q.C. chart is used to monitor the precision of results measured on different days. This will be maintained and updated daily.
- 7.3 A recent Chevron³ study indicates that the stability of methanol in impinger solutions is best preserved by refrigerating or freezing the samples until such time as analysis is feasible, or if preservation of the sample is required following analysis. The Air Resources Board is currently conducting a study of the relative stability of these solutions at different temperatures. Until the completion of this study, all samples not immediately analyzed are refrigerated.
 - 7.3.1 A 24-hour stability test was conducted following a routine dync test. According to the above procedure, the impingers were allowed to warm to room temperature. A portion of each impinger solution was then analyzed by GC. Meanwhile, the remaining mode 1 primary impinger solution was divided into several autosampler.

vials. These vials were then refrigerated. At two to three-hour intervals, a vial was removed from the refrigerator, allowed to warm to room temperature, and subsequently analyzed by GC. One vial remained in the refrigerator overnight and was analyzed the following day. In addition, the last vial analyzed had been left at room temperature for the preceding 12 hours. A plot of concentration versus the time difference between sampling and analysis is shown in fig. 9.

Mean = 2.13
Std. dev. = 0.0582
% RSD = 2.73

This study seems to indicate that refrigeration preserves the stability of impinger solutions for at least 24 hours. Further study is required to determine the stability of samples left at room temperature.

- 7.4 Replicate samples are run for every ten samples analyzed. For those that vary by more than 10%, all samples run that day are reanalyzed.

$$\% \text{ Difference} = \frac{\text{Difference (ppm)}}{\text{Average (ppm)}} \times 100$$

- 7.5 A water blank is analyzed daily to check the analytical system for contamination.
- 7.5.1 If the blank shows a peak (>LOD) in the region of interest, the blank is repeated.
- 7.5.2 If the peak area is consistent, the blank is subtracted from the standards and samples.
- 7.5.3 If the peak area is not consistent, the Q.C. coordinator should be consulted to determine the source of the peak, such as carry-over from a sample of high concentration.
- 7.6 A multi-point calibration is performed semi-annually. At this time, the precision and LOD of the method are determined.
- 7.6.1 A multi-point calibration is also performed when the column is changed, major instrument repair or modification is performed, or analysis of additional compounds is required.
- 7.7 Additional compounds may be identified by GC/Mass Spectroscopy (GC/MS) or GC/Fourier Transform Infrared Spectroscopy (GC/FTIR).
- 7.7.1 The presence of alcohol in samples which show an interference or an unidentified peak may be confirmed by GC/MS, GC/FTIR, or by a second GC method.

7.8 Recovery tests have not been performed, due to the instability and resulting unavailability of gas phase methanol standards.

7.10 Quality control of the sampling procedure is overseen by Mobile Sources Division.

8 References

8.1 "Characterization of Exhaust Emissions from Methanol and Gasoline Fueled Automobiles", EPA 460/3-82-004.

8.2 Code of Federal Regulations, Title 40, Part 86.

8.3 Horn, Jerome C., "Methanol-Fueled Light-Duty Vehicle Exhaust Emissions", Chevron Research Company internal report, 1989.

Figure 1: 50 PPM METHANOL STANDARD

SAMPLE NO.: 89005893.01


TEST NO.: ALCOH

METHOD NO.: ALCO1 / ALCO1

INSTRUMENT: 18

DATE TIME: 05/25/89 14:13:25

PAGE NO.: 01



Y MAXIMUM: 545.

Y MINIMUM: 54.

START TIME: 0.00
END TIME: 6.00

RETENTION TIME (MINUTES)

Figure 2: METHANOL SAMPLING
SCHEMATIC DIAGRAM




Figure 3: METHANOL

MULTI-POINT CALIBRATION




Figure 4: ETHANOL

MULTI-POINT CALIBRATION




Figure 5: 50 PPM METHANOL




Figure 6: 50 PPM ETHANOL




Figure 7: 50 PPM METHANOL
Control Chart




Figure 8: 50 PPM ETHANOL
Control Chart





Figure 9: IMPINGER SAMPLE STABILITY



November 1989

AIR RESOURCES BOARD

PROCEDURE FOR THE DETERMINATION
OF C₂ TO C₅ HYDROCARBONS
IN AUTOMOTIVE SOURCES SAMPLES BY GC

S.O.P. NO. MLD 102

Southern Laboratory Branch
Monitoring and Laboratory Division
State of California
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

05862

CALIFORNIA AIR RESOURCES BOARD
MONITORING AND LABORATORY DIVISION

PROCEDURE FOR THE DETERMINATION
OF C₂ TO C₅ HYDROCARBONS
IN AUTOMOTIVE SOURCES SAMPLES BY GC

1. INTRODUCTION

- 1.1 This procedure describes a method of determining C₂ to C₅ hydrocarbons (light-end hydrocarbons) in the range² of parts per billion carbon (ppbC) from automotive sources samples. The method does not include sampling procedure.

2. METHOD SUMMARY

- 2.1 This is a rapid method intended for routine analysis.
- 2.2 A portion of the sample, received by the lab in Tedlar bags, is transferred by syringe to a gas chromatograph (GC).
- 2.3 The gas chromatographic analysis is performed on a packed column operated isothermally at 35 °C. Flame ionization (FID) is used for detection with pure oxygen supplied to the hydrogen to enhance its sensitivity.
- 2.4 The sample is injected into the GC by means of gas sampling valves. Separation of the sample hydrocarbon mixture into its component constituents takes place in the chromatographic column.
- 2.5 The GC data system identifies the peaks and quantifies the hydrocarbon contents by integrating the peak areas and calculating concentrations from factors determined during calibrations with standards.

3. INTERFERENCES AND LIMITATIONS

- 3.1 Any component (e.g., Freon group) present in the sample having a retention time very similar to that of the hydrocarbons being measured and under the operating conditions described in this method is an interference. Therefore, proof of chemical identity may require confirmation by other methods and instrumentation, e.g., GC/MS.
- 3.2 The concentration of hydrocarbons in the range of interest is stable for at least 72 hours in the Tedlar sampling bags (Table 1), provided the sample bags do not leak and are not exposed to bright light or excessive heat. Sampling bags must be shielded from direct sunlight to avoid losses from reaction of the reactive hydrocarbons.

4. INSTRUMENTS AND APPARATUS

- 4.1 Ground glass syringes (100 ml capacity) are used to transfer gaseous samples from Tedlar bags to the sample inlet of the GC.
- 4.2 Tedlar bags, 2 mil thickness, nominally 10 to 25 liters capacity and equipped with quick-connect fittings, are used to contain the sample from the dyno train.
- 4.3 A gas chromatograph (VARIAN 3300) equipped with a gas sampling valve system (Figure 1) is required. A flame ionization detector (FID) is used.
- 4.4 A stainless steel column (6 ft x 1/8 in) packed with phenylisocyanate Durapak 80/100 mesh is used.
- 4.5 A U-shaped stainless steel sample trap (10 in x 1/4 in) packed with stainless steel chips is used.
- 4.6 An analog recorder (SOLTEC 1241) and an electronic integrator (Perkin-Elmer LIMS 3212) for quantitation of peak areas are required.
- 4.7 Dewar flasks (250 ml) are used to contain liquid nitrogen or hot water.

5. REAGENTS AND MATERIALS

- 5.1 All gases used to support the GC analysis shall be of the highest commercial purity available.
- 5.2 Helium shall have a minimum purity of 99.99% and pass through a trap immersed in liquid nitrogen to ensure purity before entering the GC.
- 5.3 Hydrogen shall have a minimum purity of 99.99%.
- 5.4 Oxygen shall have a minimum purity of 99.6%.
- 5.5 A high calibration standard in the ppmC range containing 11 hydrocarbons is prepared in a 48.5 liter glass flask. Methylbutane and pentane are introduced by means of a fixed volume liquid injection valve while the nine other compounds are introduced in gaseous form using a gas sampling valve. The concentrations of these compounds in the high calibration standard are as follows:

COMPOUND	CONC. (ppmC)	CONC. (ppm)
ethane	47.4	23.7
ethene	47.4	23.7
propane	71.1	23.7
ethyne	47.4	23.7
methylpropane	94.8	23.7
butane	94.8	23.7
propene	71.1	23.7
methylbutane	215.0	43.0
pentane	215.0	43.0
1-butene	94.8	23.7
2-methylpropene	94.8	23.7

- 5.6 A low calibration standard in ppbC range is prepared by transferring 50 mL of the high calibration standard into a second flask of 50 L capacity and filling with nitrogen to accomplish a 1:1000 dilution. Concentrations of compounds in the low calibration standard are as follows:

COMPOUND	CONC. (ppbC)
ethane	47.4
ethene	47.4
propane	71.1
ethyne	47.4
methylpropane	94.8
butane	94.8
propene	71.1
methylbutane	215.0
pentane	215.0
1-butene	94.8
2-methylpropene	94.8

- 5.7 Liquid nitrogen is used to cool the U-shaped sample cryogenic trap.

6. PROCEDURES

- 6.1 The air sample is analyzed for C₂ to C₅ hydrocarbons by using a cryogenic preconcentration method.
- 6.2 Standard operating conditions for the gas chromatograph are:

Helium carrier gas flow:	60 mL/min
Hydrogen gas flow:	40 mL/min
Oxygen gas flow:	200 mL/min
Sample valve temperature:	ambient
Heating bath temperature:	60 - 80 °C
Injector temperature:	35 °C
Column temperature:	35 °C
Detector temperature:	200 °C (isothermal)

- 6.3 Immerse the sample trap in liquid nitrogen and allow temperature to stabilize. The temperature equilibrium is achieved when liquid nitrogen stops boiling.

- 6.4 Withdraw exactly 100 mL from the sample bag with a 100 mL syringe and inject the sample into the freeze-out sample trap.
- 6.5 Refill the syringe with another 20 mL of helium and flush the 20 mL through the trap; then flush helium through the loop for three minutes to flush out the condensed oxygen.
- 6.6 Isolate the cryogenic trap by using the isolation valve, which prevents loss of sample when the trap is heated.
- 6.7 Replace the liquid nitrogen Dewar with a Dewar containing hot water at about 60-80 °C.
- 6.8 Allow sufficient time for the temperature of the trap to rise until the ice accumulated on the surface of the trap is melted completely.
- 6.9 Introduce the sample into the carrier gas stream by means of the injection valve.
- 6.10 Each separated component exits from the column through the flame ionization detector, where a response is generated.
- 6.11 Concentrations of hydrocarbons are calculated by an electronic integrator device, which has been calibrated using low calibration standard.
- 6.12 The peak integrations are corrected as necessary in the data system. Any misplaced baseline segments are corrected in the reconstructed chromatogram.
- 6.13 The peak identifications provided by the computer are checked and corrected, if necessary.
- 6.14 The maximum retention time in this analysis is set to be 15 minutes.
- 6.15 After each run, the column is back-flushed with helium while the column temperature is raised and kept at 60 °C. for 20 minutes.
- 6.16 Before the next run, 15 minutes is needed after back-flush of column to re-establish the required temperature of the column.
- 6.17 The total run time is about 50 minutes.

7. CALCULATIONS

- 7.1 The hydrocarbon concentrations, in ppbC, are calculated by the data system using an external standard method

$$\text{Concentration} = \text{Peak Area} \times \text{Calibration Factor}$$

- 7.2 The calibration factor (CF) is calculated during the calibration by:

$$CF = \frac{\text{Concentration of standard}}{\text{Area of standard}}$$

- 7.3 Only the low calibration standard (in ppbC range) is used in the calibration run.

8. QUALITY CONTROL

- 8.1 A blank (pure nitrogen or helium) run is performed before the analysis of samples.

- 8.2 One run of the low calibration standards (Figure 2) is performed before the analysis of samples. The set of calibration factors generated by calibration run is used for quantitating sample analyses.

- 8.3 A duplicate run of one sample is performed daily.

- 8.4 A quality control chart (Figure 3) of one compound (ethane, for example) in the low calibration standard is maintained, showing into which zone the current calibration falls. (Ref 9.3):

	area ethane (count)
the upper control limit (mean + 3*SD)	4005
the upper warning limit (mean + 2*SD)	3808
the average value (mean)	3414
the lower warning limit (mean - 2*SD)	3020
the lower control limit (mean - 3*SD)	2823

(SD stands for standard deviation)

- 8.5 The standard and control standard will be changed as they become available to contain more components other than ethane covering the whole range of C₂ to C₅.

- 8.6 A multi-point calibration is performed for 11 compounds at least annually. Ethane (Figure 4), for example:

MULTI-POINT CALIBRATION FOR ETHANE

Ethane (ppbC)	Response Area Count
4.74	466/304/326
47.40	3185/3500/3765
474.00	31974/32379/32772
4740.00	319394/319542/323078
47400.00	2851985/2905773/2917903

The linear regression equation derived from multi-point calibration is

$$\text{area count} = 67.595 (\text{concentration}) + 305.81$$

The standard deviation for the lowest concentration level (4.74) is

87.87

The LOD of ethane equals three times standard deviation divided by slope of the linear equation (Ref 9.3).

$$\begin{aligned}\text{LOD (ethane)} &= 3 \times 87.87 / 67.595 \\ &= 3.90 \text{ ppbC}\end{aligned}$$

- 8.7 The precision test was performed for ethane (47.4 ppbC) with the following response area counts:
(3281/3311/3485/3310/3686/3350/3252/3349/3686/3759/3241/3421/3281/3229/3727/3544/3135)

population: 17
average value: 3414.53
standard deviation: 196.90
relative standard deviation: 5.77%

- 8.8 A stability test was performed for the eleven hydrocarbons occurring in an automotive source sample (Table 1 and 3.2). The stability test for ethane is shown as an example (Figure 5). The test result suggests that the hydrocarbons are stable for at least 72 hours in the Tedlar sampling bags.

- 8.9 The samples are run as soon as they arrive or within three days.

S.O.P. No. MLD 102
Effective Date: 11/01/89
Revision No. 1.2
Approved: /s/ign/SHM
Page 8 of 14

9. REFERENCE

- 9.1 ARB Method 104
- 9.2 Standard Test Method for C₁ Through C₅ Hydrocarbons in the Atmosphere by Gas Chromatography, ASTM Standards on Chromatography (1981).
- 9.3 Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air. EPA manual (1984).

Table 1 Stability test for eleven light-end hydrocarbons.

CALIFORNIA AIR RESOURCES BOARD
MONITORING AND LABORATORY
ORGANIC ANALYSIS SECTION

Test Name : LIGHT END HYDROCARBONS
Instrument : VARIAN GC-3300 (FID) WITH LIMS

Project Code : MS12345
Analyst : CHIN LAI

Logged-in Date : 06/05/89
Analysis Date : 06/05/89
Report Date : 06/13/89

LIMS Sample Number : 89006238
Client's Sample ID : 6/5 STABILITY

No.	Compound	Name	TIME (HR.)			
			0	2	8	90
			PPBC	PPBC	PPBC	PPBC
1.	ETHANE					
2.	ETHENE (ETHYLENE)	170	180	170	190	
3.	PROPANE	1600	1600	1600	1600	
4.	ETHYNE (ACETYLENE)	49	47	49	51	
5.	METHYLPROPANE (ISOBUTANE)	420	390	450	430	
		71	71	82	87	
6.	BUTANE					
7.	PROPENE (PROPYLENE)	310	300	320	330	
8.	METHYLBUTANE (ISOPENTANE)	670	640	700	610	
9.	PENTANE	500	520	570	510	
10.	1-BUTENE	330	320	360	320	
		130	130	140	120	
11.	2-METHYLPROPENE (ISOBUTYLENE)	240	240	180	190	
11	Compounds Measured	Total	4490	4432	4621	4438

Figure 1 Diagram of gas sampling valve system




Fig. 1 (A) Sample




Fig. 1 (B) Isolate




Fig. 1 (C) Inject

Figure 2 Chromatogram of the low calibration standard

6/13 CAL2 (Low Calibration)

SAMPLE NO.: 89006601.01


TEST NO.: LEHC1

METHOD NO.: CL2 / CL2

INSTRUMENT: 30

DATE TIME: 06/13/89 09:30:05

PAGE NO.: 01



RETENTION TIME (MINUTES)

Y MAXIMUM: 196.

Y MIN. NUM: 71

196.

71

START TIME: 0.00

END TIME: 15.00

PAGE 01

05873

Figure 3 Quality control chart for ethane

ETHANE

TEST: LEH01

AVERAGE VALUE = 3414.53

MINIMUM VALUE = 3135.0

STANDARD DEVIATION = 196.858

MAXIMUM VALUE = 3759.0

95% CONFIDENCE LIMIT = +/-393.797

POPULATION = 17

UPPERLIMIT

4006.0

AVERAGE

3414.53

LOWERLIMIT

2923.0

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17

SAMPLE NUMBER


Figure 4 Multi point calibration for ethane

ARB LABORATORY INFORMATION SYSTEM

Page 1/1 ETHANE3

$Y = 67.595 X + 305.81$

Curve fit -- Linear Fit
Error is 6170.0



ANNOO YEEY


05875

YMax: .323E+06
YMin: .319E+04
XMax: .474E+04
XMin: 47.4

9 Points Linear-Linear

PPBC

x 10**2



YMax: 190.
YMin: 170.
XMax: 90.0
XMin: 0.0

CONCENTRATION (PPBC) X 10**1

JUNE 1990

AIR RESOURCES BOARD

PROCEDURE FOR THE DETERMINATION
OF
MIDRANGE HYDROCARBONS
IN AUTOMOTIVE EXHAUST
BY
GAS CHROMATOGRAPHY

S.O.P. No. MLD 103A

Southern Laboratory Branch
Monitoring & Laboratory Division
State of California
9528 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

CALIFORNIA AIR RESOURCES BOARD
MONITORING & LABORATORY DIVISION

PROCEDURE FOR THE DETERMINATION OF
MIDRANGE HYDROCARBONS IN
AUTO EXHAUST BY GC.

=====

1. INTRODUCTION.

- 1.1 This procedure describes a method of analyzing hydrocarbons in diluted automotive exhaust.
- 1.2 Using the cryotrap preconcentration method described in the procedure section, the sample is analyzed for hydrocarbons whose boiling points range from that of n-butane to n-undecane.
- 1.3 The sample could be taken from a Federal Test Procedure dynamometer test (Constant Volume Sampler (CVS) diluted auto exhaust) or from a sealed housing evaporative determination (SHED test). (Ref.: 9.2).

2. METHOD SUMMARY.

- 2.1 A portion of the sample is transferred by syringe to a gas chromatograph (GC).
- 2.2 The sample is introduced into the GC from a cryogenic trap by means of a sampling valve. (PAGE 8)
- 2.3 The GC data system quantifies the hydrocarbon contents by integrating the peak area and calculating concentrations from factors determined from traceable standards.

3 APPARATUS/INSTRUMENTATION

- 3.1 The samples are collected in Tedlar bags and transported to the laboratory.
- 3.2 Ground glass syringes (B.D. Multfit, 50 ml. capacity or equivalent) are required to transfer the gaseous samples from Tedlar bags to the sample inlet of the G.C.
- 3.3 The gas chromatograph (Varian model 3400 or equivalent) used is equipped with a flame ionization detector (FID) and a gas sampling valve system connected to a cryogenic trap.

- 3.4 A Valco rotary valve used to introduce the sample is connected to a cryogenic sample concentration system. A schematic of the valve system is shown on page 8.
- 3.5 The column used is a J&W DB-1 (60 M.x 0.32 mm ID, film thickness 1.0 u, (Cat.No.1231063) or equivalent).
- 3.6 An analog recorder (Soltec, Model 1241 or equivalent) and an electronic integrator (PE Nelson 2600 Chromatographic Integrator System or equivalent) are required for the quantitization of peak areas.
- 4 REAGENTS.
- 4.1.1 All gases used to support the GC analysis shall equal or exceed the following purity:
- 4.1.2 Helium shall have a minimum purity of 99.995 %
- 4.1.3 Hydrogen shall have a minimum purity of 99.995 %
- 4.1.4 Air shall be zero grade (purity: 1ppm THC)
- 4.1.5 Nitrogen shall have a minimum purity of 99.9 %
- 4.2 Hydrocarbon standard and control samples:
- 4.2.1 The reference standard is a NIST standard containing n-hexane, benzene, toluene, n-octane, m-xylene and n-decane at 98, 103, 100, 51, 49 and 26 ppb in nitrogen, respectively.
- 4.2.2 The control sample used for quality control purposes is a cylinder containing benzene, 2,2,4-trimethylpentane, toluene and n-nonane purchased from Scott Specialty Gases. Referred to as MS5 in the analyses.
- 4.3 Liquid nitrogen to cool down the cryogenic preconcentration trap and the GC oven.
- 5 PROCEDURE.
- 5.1 Injection
- 5.1.1 The trap is immersed in a Dewar filled with liquid nitrogen before obtaining the sample.
- 5.1.2 An aliquot of the sample is transferred from the sample bag via a 50 ml. syringe and concentrated in the cryogenic trap.

- 5.1.3 The GC is cooled down to -60 degrees Celsius while the sample is being injected into the trap.
- 5.1.4 The cryogenic trap is flushed, first using 80 mL of helium from a clean syringe, then flushed for an additional 2 minutes with helium at a flow rate of 40 mL/min.
- 5.1.5 The analysis begins by pressing the start button on the GC and the data acquisition system simultaneously. An external event signal triggers the turning of the sample valve, thereby diverting carrier gas through the cryogenic trap. The Dewar of liquid nitrogen in which the trap is immersed is immediately replaced by a Dewar of boiling water. This vaporizes and transfers the sample through a heated entrance port onto the head of the capillary column.

5.2 Chromatography

- 5.2.1 Typical operating conditions for the GC are:

He carrier gas average linear velocity	30	cm/sec
He make-up gas flow	70	mL/min
H2 gas flow (for FID)	50	mL/min
Zero air gas flow (for FID)	500	mL/min

Autozero FID at 0.0 min.

Range 11, Attenuation 1

Sample valve temperature: 140° C

Detector temperature: 250° C

Column Entrance Port: 95° C

Column temperature:

Initial temperature -60° C;
held for 1 minutes, then to -20° C at 40° C/min,
to 100° C at 3° C/min; to 100° C at 4° C/min;
to 180° C at 6° C/min and hold for 16 minutes.

- 5.2.2 Each separated compound passes through the flame ionization detector where a response is generated.

5.3 Data Analysis

- 5.3.1 The results are examined to see that the peaks are correctly integrated.
- 5.3.2 The peak identification provided by the computer are reviewed and, if necessary, corrected using the following procedure and criteria:

- 5.3.2.1 The relative retention indices from GC/MS analyses are used to confirm peak identifications.
- 5.3.2.2 The primary peak identification is done by the computer using the relative retention times based on reference runs.
- 5.3.2.3 Compare the fingerprint of the sample run with the reference run.
- 5.3.2.4 Compare the relative retention times of the sample peaks with those of reference runs.
- 5.3.2.5 Any peak not identified nor confirmed by other means such as GC/MS, is labeled "Unidentified".
- 5.3.3 The concentrations of the hydrocarbons may be calculated by an electronic integrator device.

6. CALCULATIONS

- 6.1 The calculation of all the hydrocarbon concentrations is based on the responses of the compounds in the calibration standard.
- 6.2 The concentration is calculated by the data system using an external standard method.

$$\text{Concentration} = \text{Area} \times \text{Calibration Factor}$$

- 6.3 The Calibration Factor (CF) is calculated during daily calibration with a NIST calibration standard (4.2.1)

$$CF = \frac{\text{Concentration of the standard}}{\text{area of standard}}$$

The CF used is the average of the CF's for each of the components in the standard. Replicate calibrations are averaged and the arithmetic mean is stored as the CF to be used in subsequent analyses.

- 6.4 Linearity of the instrument response should be checked annually by multipoint calibration.
- 6.5 Experimental data for a multipoint calibration of four control compounds are in the following tables (see also figures 1-4 in appendix A). (r-correlation coefficient).

The different compound concentrations are obtained by syringe dilution in Tedler bags of the Control Standard (MS5). (See 4.2.2).

TABLE 1: MULTIPOINT CALIBRATION FOR BENZENE ($r=.9874$)

<u>PPBC BENZENE</u>	<u>AREA RESPONSE</u>
1.8	46/ 45/ 48 /48/ 45/ 49/ 50
9.0	215/ 180/ 178
45.0	695/ 592/ 565
225.0	2782/ 3337/ 2679
450.0	6661/ 5989/ 6586
900.0	8975/ 9924/ 10781

TABLE 2: MULTIPOINT CALIBRATION FOR 2,2,4-TRIMETHYLPENTANE ($r=.9961$)

<u>PPBC 2,2,4-TMP</u>	<u>AREA RESPONSE</u>
1.6	55/ 57/ 66/ 41/ 42/ 37/ 41
8.0	148/ 173/ 169
40.0	600/ 570/ 538
200.0	3161/ 2580/ 2486
400.0	5454/ 5407/ 5719
800.0	9178/ 9754/ 9571

TABLE 3: MULTIPOINT CALIBRATION FOR TOLUENE ($r=.9852$)

<u>PPBC TOLUENE</u>	<u>AREA RESPONSE</u>
2.1	112/ 106/ 101/ 110/ 98/ 114/ 132
10.5	330/ 323/ 280
52.5	826/ 762/ 755
262.5	4340/ 3710/ 3560
525.0	8323/ 7720/ 8322
1050.0	11063/ 12326/ 12600

TABLE 4: MULTIPOINT CALIBRATION FOR N-NONANE ($r=.9883$)

<u>PPBC N-NONANE</u>	<u>AREA RESPONSE</u>
9	41/ 55/ 34/ 29/ 23/ 25/ 24
4.5	88/ 99/ 100
22.5	418/ 434/ 370
112.5	1881/ 2005/ 1857
225.0	3935/ 3884/ 4109
450.0	5960/ 6506/ 5732

6.6. The Limit of Detection (LOD) is calculated using the formula:

$$LOD = \frac{|b| + 3s}{m} \quad (\text{Ref. 9.3})$$

S = sample standard deviation of the lowest concentration level.
m = slope linear regression line
b = intercept of a multipoint calibration curve at the low concentration range, the term $|b|/m$ may be ignored if b is positive

Only the four lowest concentrations are used in the calculation of LODs (See calculation sheets and figures 5-8 in appendix B). The LOD used for quality control is 3.0 ppbc.

COMPONENT	LOD	"LOD"-mg/mi	
		Modes 1&3	Mode 2
Benzene	0.46 ppbc	0.03	0.06
2,2,4-TMP	2.4 ppbc	0.25	0.41
Toluene	2.3 ppbc	0.19	0.31
N-Nonane	2.1 ppbc	0.24	0.39

6.7 The precision of the instrument is checked annually in conjunction with the multipoint calibration.

Precision is calculated using the following formula:

$$\text{Precision}(\%) = (\text{sd}/\text{mean}) \times 100$$

where, sd - standard deviation of replicates

mean - mean of replicates

TABLE 5: PRECISION OF 1/2 MS5 (See tables 5-8 in appendix C)

COMPONENT	PRECISION(%)
BENZENE	10.0
2,2,4-TRIMETHYLPENTANE	8.5
TOLUENE	8.2
n-NONANE	4.2

7. QUALITY CONTROL.

- 7.1. The samples are run as soon as they arrive or within two days.
- 7.2. Stability studies for some components in a CVS sample are documented in Appendix D. The sample appeared to be stable over two days in the Tedlar bag.
- 7.3. The NIST calibration standard is run daily.
- 7.4. After running a sample which contains unusually high peaks, the analyst should run a blank before proceeding to the next sample if, based upon previous experience, there may be suspected sample carryover.
- 7.5. A control standard is run daily. This control standard is another cylinder containing benzene, 2,2,4-trimethylpentane, toluene and n-nonane. (4.2.2)
- 7.7. Quality control charts of the components in the control standard are maintained showing the mean value, warning limit of mean $\pm 2SD$, action limit of mean $\pm 3SD$.
- 7.8. The precision of the instrument response should be determined periodically by replicate analysis of the samples. The level should be appropriate for the samples normally analyzed.

8. CRITIQUE AND COMMENTS.

- 8.1. Some peaks are incompletely resolved.
- 8.2. Any organic compound present in the sample which produces an FID response under the operating conditions described in this method and has a retention time very similar to that of one of the hydrocarbons being measured, is an interference.

9. REFERENCE

- 9.1. ARB Method 104
- 9.2. C.F.R. 40 paragraphs 86.133-78 and 86.138-78
- 9.3. Anal. Chem. 55 (1983) 2217




Fig 1 (A) Sample Concentration

CCW (+1)





Fig 1 (B) Sample Injection

CW (+2)

Appendix A
Multipoint Graphs

BENZENE MULTIPPOINT




COEFFICIENTS OF LEAST SQUARES FIT TO A LINEAR EQUATION
 $R = 0.9874269$ $KB = 11.389537$ $KC = 212.08301$
 CORRELATION COEFFICIENT OF X-Y PAIRS = 0.9874269
 COEFFICIENT OF DETERMINATION = 0.9750118

Fig. 1

05887

2,2,4-TMP MULTIPPOINT



COEFFICIENTS OF LEAST SQUARES FIT TO A LINEAR EQUATION

KA= 0. KB= 12.086025 KC= 150.4519


CORRELATION COEFFICIENT OF X-Y PAIRS = 0.99606

COEFFICIENT OF DETERMINATION = 0.9921355

Fig. 2

05888

TOLUENE MULTIPPOINT



044


Spectra-Physics

COEFFICIENTS OF LEAST SQUARES FIT TO A LINEAR EQUATION
 $A = 0.$
 $KS = 11.866347$ $KC = 376.48129$
 CORRELATION COEFFICIENT OF X-Y PAIRS = 0.9852251
 COEFFICIENT OF DETERMINATION = 0.9706685

Fig. 3

05889

N-ROHANE MULTIPPOINT



COEFFICIENTS OF LEAST SQUARES FIT TO A LINEAR EQUATION
 $K_A = 0$ $K_B = 12.988963$ $K_C = 151.76539$
 CORRELATION COEFFICIENT OF X-Y PAIRS = 0.9883123
 COEFFICIENT OF DETERMINATION = 0.9767612

05890

Fig. 4

Appendix B
LOD Calculations and Graphs

CALCULATION OF LIMIT OF DETECTION (LOD)

Benzene

I. Name of Compound _____
 5/22-5/24 1990

II. Multipoint Calibration Date _____
 Note: The instrument zero or blank should be measured to obtain net measurement values but (0,0) is not included as a calibration point.

	y = Net absorbance or area count*	x = concentration
1. <u>500</u> MS5 (Low conc.)	46,45,48,48,45,49,50	1.8
2. <u>100</u> MS5	215, 180, 178	9.0
3. <u>20</u> MS5	695, 592, 565	45.0
4. <u>2</u> MS5	2782, 3337, 2679	225.0
5.		
6.		
7.		
8.		

* Net measurement after correction for zero or blank
 ** Mean measurement for lowest concentration standard

Slope $m = 12.865612$
 Intercept $b = 38.961012$ units area counts
 Correlation coefficient $r = .0020621$

III. Replicate Measurements of Low Concentration Standard Date 5/23/90
 Number of Replicates 7

Standard Deviation $s = 1.976$ units area counts

IV. $LOD = \frac{|b|}{m} + 3 \frac{s}{m}$ ***
 $= \frac{38.961012}{12.865612} + 3 \frac{1.976}{12.865612} = 4.608$ units ppbc

NOTE: If a 2nd degree curve fit is performed, replace "m" with the linear term and "b" with the constant term and show the regression equation below.


*** If b is positive, $\frac{b}{m}$ is ignored in the

V. Comments _____
 calculations of LOD.

Chemist Annette D. Hebert Date 6/4/90

05892

PERENE LOD-4



COEFFICIENTS OF LEAST SQUARES FIT TO A LINEAR EQUATION
 $K_A = 0$ $K_B = 12.865612$ $K_C = 38.961012$
 CORRELATION COEFFICIENT OF X-Y PAIRS = 0.9929621
 COEFFICIENT OF DETERMINATION = 0.9859738

Fig. 5

CALCULATION OF LIMIT OF DETECTION (LOD)

I. Name of Compound 2,2,4-Trimethylpentane
5/22-5/24 1990

II. Multipoint Calibration Date _____
Note: The instrument zero or blank should be measured to obtain net measurement values but (0,0) is not included as a calibration point.

	y = Net absorbance or area count*	x = concentration
1. $\frac{1}{500}$ MS5 (Low conc.)	55,57,66,41,42,37,41	1.6
2. $\frac{1}{100}$ MS5	148,173,169	8.0
3. $\frac{1}{20}$ MS5	600,570,538	40.0
4. $\frac{1}{4}$ MS5	1316, 2680, 2486	200.0
5.		
6.		
7.		
8.		

* Net measurement after correction for zero or blank

** Mean measurement for lowest concentration standard

Slope $m = 13.712401$

Intercept $b = 31.774666$ units area counts

Correlation coefficient $r = .9927441$

III. Replicate Measurements of Low Concentration Standard Date 5/23/90

Number of Replicates 7

Standard Deviation $s = 10.861$ units area counts

IV. $LOD = \frac{|b|}{m} + 3 \frac{s}{m}$ ***

$= \frac{31.774666}{13.712401} + 3 \frac{10.861}{13.712401} = 2.3762$ units ppbc

NOTE: If a 2nd degree curve fit is performed, replace "m" with the linear term and "b" with the constant term and show the regression equation below.

*** If b is positive, m is ignored in calculating


V. Comments _____

LOD _____

Chemist Annette D. Hebert Date 6/4/90

05894

2,2,4-THP LOD



COEFFICIENTS OF LEAST SQUARES FIT TO A LINEAR EQUATION

KA= 0. LB= 13.712401 KC= 31.774866

CORRELATION COEFFICIENT OF X-Y PAIRS = 0.9927441

COEFFICIENT OF DETERMINATION = 0.9855408

Fig. 6

05895

SPECTROPHYSICS

CALCULATION OF LIMIT OF DETECTION (LOD)

Toluene

I. Name of Compound _____

5/22-5/24 1990

II. Multipoint Calibration Date _____

Note: The instrument zero or blank should be measured to obtain net measurement values but (0,0) is not included as a calibration point.

	y = Net absorbance or area count*	x = concentration
1. $\frac{1}{500}$ MS5 (Low conc.)	112,106,101,110,98,114,132	2.1
2. $\frac{1}{100}$ MS5	330,323,280	10.5
3. $\frac{1}{20}$ MS5	926,762,755	52.5
4. $\frac{1}{4}$ MS5	4340,3710,3560	262.5
5.		
6.		
7.		
8.		

* Net measurement after correction for zero or blank

** Mean measurement for lowest concentration standard

14.362549

Slope $m =$ _____

Intercept $b =$ 95.177507 units area counts

Correlation coefficient $r =$.994047

III. Replicate Measurements of Low Concentration Standard Date 5/23/90

Number of Replicates 7

Standard Deviation $s =$ 11.133 units area counts

IV. $LOD = \frac{b}{m} + 3 \frac{s}{m}$ ***

$=$ _____ $+ \frac{2.3254}{2.3254}$ units ppbc


NOTE: If a 2nd degree curve fit is performed, replace "m" with the linear term and "b" with the constant term and show the regression equation below.

V. Comments *** If b is positive, $\frac{b}{m}$ is ignored in calculating LOD

Chemist Annette D. Hebert Date 6/4/90

05896

TOLUENE LOD



COEFFICIENTS OF LEAST SQUARES FIT TO A LINEAR EQUATION

KA= 0. KB= 14.362549 KC= 95.177597

CORRELATION COEFFICIENT OF X-Y PAIRS = 0.994047

COEFFICIENT OF DETERMINATION = 0.9881295

Fig. 7

05897

[illegible]

CALCULATION OF LIMIT OF DETECTION (LOD)

I. Name of Compound N-Nonane
 II. Multipoint Calibration Date 5/22-5/24 1990

Note: The instrument zero or blank should be measured to obtain net measurement values but (0,0) is not included as a calibration point.

	y = Net absorbance or area count*	x = concentration
1. $\frac{1}{500}$ MS5 (Low conc.)	41.55, 34.29, 23.25, 24**	0
2. $\frac{1}{100}$ MS5	88.99, 100	1.5
3. $\frac{1}{20}$ MS5	418.43, 370	22.5
4. $\frac{1}{4}$ MS5	1881, 2005, 1857	112.5
5.		
6.		
7.		
8.		

* Net measurement after correction for zero or blank

** Mean measurement for lowest concentration standard

16.848812

Slope, m =

Intercept b = 20.351530 units area counts

Correlation coefficient r = .9990064

III. Replicate Measurements of Low Concentration Standard Date 5/23/90

Number of Replicates 7

Standard Deviation s = 11.619 units area counts

IV. $LOD = \frac{|b|}{m} + 3 \frac{s}{m}$ ***

= 2.0688 + 2.0688 units ppbc

NOTE: If a 2nd degree curve fit is performed, replace "m" with the linear term and "b" with the constant term and show the regression equation below.


*** If b is positive, b is ignored in

V. Comments calculating LOD

Chemist Annette D. Hebert Date 6/4/90

05898

N-HONANE LOD



COEFFICIENTS OF LEAST SQUARES FIT TO A LINEAR EQUATION

KA= 0. FB= 16.848812 KC= 20.351539

CORRELATION COEFFICIENT OF X-Y PAIRS = 0.9990064

COEFFICIENT OF DETERMINATION = 0.9980138

05899

Fig. 8

Appendix C
Precision Tables

KLD DAILY QUALITY CONTROL ANALYST: ANNETTE

instrument: GC 3430 silenziaultit3.ctr 05/22/90

method: MI item: 224PRIN237LDPENTANE 10:33:26

Low Ctrl. Low Warn. (CONTR) High Warn. High Ctrl. unit: PPGC n = 7 C-O-N-T-R-O-L C-H-A-R-T + - + - + - + -

(mean-3sd) (mean-2sd) (mean) (mean+2sd) (mean+3sd) (sd) precision(100sd/a) 285.3 317.7 382.4 447.2 479.6 32.4 8.5

D A T R	time	sample ID	no.	v	a	l	u	e	100(v-a)/a	100(v-a)/sd	status	n-3sd	n-2sd	n-1sd	n	n+1sd	n+2sd	n+3sd	H.V.	B.C.
MM/DD/YY	hh:mm		!!!	=====	=====	=====	=====	=====	REL. ERROR%	P>300 W>200	0 K	W	F	I	I	I	I	I	I	I
05/22/90	00:00	RUN #1	1	430.000	12.44	146.93	-174.28	-19.85	-2.47	-29.12	0 K	3	4	5	6	7				
05/22/90	00:00	RUN #2	2	326.000	-14.76						0 K									
05/22/90	00:00	RUN #3	3	376.000	-1.68						0 K									
05/22/90	00:00	RUN #4	4	373.000	-2.47						0 K									
05/22/90	00:00	RUN #5	5	395.000	3.29						0 K									
05/22/90	00:00	RUN #6	6	373.000	-2.47						0 K									
05/22/90	00:00	RUN #7	7	404.000	5.64						0 K									

Table 6: 2,2,4-Trimethylpentane Precision

```

KLD DAILY QUALITY CONTROL analyst:AHN2Y18      05/22/90
instrument:GC 3400      method:M1      filenaz:multitol.ctr
                               10:41:41
Low Ctrl. Low Warn. (CONTROL) High Warn. High Ctrl. unit:PPBC
(mean-3sd) (mean-2sd) (mean) (mean+2sd) (mean+3sd) (sd) precision(100sd/a)
417.3 462.7 553.4 644.2 689.5 45.4 8.2
D A T R time sample ID no. v a l u e 100(v-n)/n 100(v-n)/sd status n-3sd n-2sd
MM/DD/YY hh:mm          *****
05/22/90 00:00 RUN #1 1 623.000 12.57 153.35 0 K 0 K 1 1
05/22/90 00:00 RUN #2 2 475.000 14.17 -172.87 0 K 0 K 1 2
05/22/90 00:00 RUN #3 3 551.000 -0.44 -5.35 0 K 0 K 1 1
05/22/90 00:00 RUN #4 4 544.000 -1.70 -20.78 0 K 0 K 1 1
05/22/90 00:00 RUN #5 5 574.000 3.72 45.34 0 K 0 K 1 1
05/22/90 00:00 RUN #6 6 533.000 -3.69 -45.03 0 K 0 K 1 1
05/22/90 00:00 RUN #7 7 574.000 3.72 45.34 0 K 0 K 1 1

```

Table 7: Toluene Precision

D A T E	time	sample ID	no.	v	a	e	100(v-a)/n	RBL ERROR%	F>300 W>200	status	n-3sd	x-2sd	L.V.
05/22/90	00:00	RUN #1	1	280.000	3.10	74.61	-8.31	-199.80	0 K	0 K	I	I	H.C.
05/22/90	00:00	RUN #2	2	249.000	-0.21	-5.06	-1.32	-31.61	0 K	0 K	I	I	mean
05/22/90	00:00	RUN #3	3	271.000	4.21	101.17	0.16	3.79	0 K	0 K	I	I	mean
05/22/90	00:00	RUN #4	4	268.000	0.16	3.79	2.37	56.91	0 K	0 K	I	I	mean
05/22/90	00:00	RUN #5	5	283.000					0 K	0 K	I	I	mean
05/22/90	00:00	RUN #6	6	272.000					0 K	0 K	I	I	mean
05/22/90	00:00	RUN #7	7	278.000					0 K	0 K	I	I	mean

Table 8: N-Nonane Precision

Appendix D
Stability Study

STABILITY STUDY AUTO EXHAUST SAMPLE

SAMPLE COLLECTION TIME: 6/5 11:00

DATE: 1989
ANALYSIS TIME:

6/5 6/5 6/6 6/6 6/7 6/7
11:45 16:50 11:39 16:51 11:24 16:48

COMPOUND NAME

PPBC COMPOUND

Cyclopentane	177	185	179	162	168	156
2,3-Dimethylbutane	161	155	158	148	163	155
2-Methylpentane	659	699	675	638	728	729
3-Methylpentane	396	431	427	396	442	442
Unidentified	-	-	198	128	118	113
C6-Alkenes	242	240	-	-	-	-
N-Hexane	445	502	469	423	443	496
C6-Alkenes	92	101	77	69	66	65
Unidentified	20	-	-	15	18	18
Methylcyclopentane	596	649	630	576	646	659
Dimethylpentanes	233	268	240	238	252	252
Benzene	2818	3021	2875	2597	2837	2878
Cyclohexane	192	207	205	183	206	207
Unidentified	24	32	27	26	34	33
2,3-Dimethylpentane	597	636	619	564	624	653
2-Methylhexane	442	474	460	413	458	477
3-Methylhexane	592	644	615	567	628	631
Dimethylcyclopentane	309	336	306	292	309	303
2,2,4-Trimethylpentane	1496	1620	1554	1441	1583	1595
Unidentified	32	37	28	33	36	37
Unidentified	-	-	-	-	19	20
N-Heptane	405	395	372	352	383	383
Unidentified	-	-	-	43	20	44
Unidentified	-	-	-	-	22	-
Methylcyclohexane	217	205	176	208	227	228
Unidentified	47	79	45	53	49	52
Unidentified	-	-	-	19	17	-
Ethylcyclopentane	51	70	43	46	51	45
C8-Alkanes	340	416	352	329	373	353
Unidentified	22	19	24	25	31	23
Unidentified	26	22	28	26	29	30
Trimethylpentanes	471	521	506	445	476	496
Toluene	5897	6548	6033	5506	5781	5813
2,3-Dimethylhexane	119	139	135	123	142	132
Unidentified	443	483	470	419	476	486
Unidentified	27	35	25	30	26	-
3-Methylheptane	376	418	399	367	393	388
Unidentified	17	21	21	19	-	21
Trimethylhexanes	156	173	170	156	158	165
Dimethylcyclohexane	29	30	34	27	28	27
Unidentified	-	18	-	-	-	-
N-Octane	233	309	272	253	243	276

05906

C9-Alkanes	195	234	223	177	195	188
Unidentified	139	166	151	136	156	146
Ethylbenzene	812	1089	955	1053	896	995
M & P Xylenes	3334	4624	3815	4317	3852	4050
Unidentified	19	22	21	33	19	35
Unidentified	22	-	28	-	-	17
C9-Alkanes	200	252	266	218	262	246
O-Xylene	1489	1875	1658	1726	1611	1642
Unidentified	72	83	78	73	76	65
C10-Alkanes	146	154	152	166	175	145
N-Nonane	74	108	96	90	103	77
Unidentified	27	27	18	28	28	33
Unidentified	32	36	35	37	35	44
Unidentified	33	45	36	53	44	-
Unidentified	-	-	-	20	-	-
Propylbenzene	96	186	131	184	133	134
Ethyltoluene	664	1020	837	1002	821	915
Trimethylbenzenes	286	314	261	328	254	294
Ethyltoluene	152	232	180	201	156	169
Trimethyloctanes	155	138	160	187	179	153
Trimethylbenzenes	988	1301	1026	1184	1043	1049
Unidentified	35	48	31	24	44	46
Unidentified	25	37	37	17	27	-
Unidentified	27	44	18	30	30	48
Unidentified	51	68	-	61	52	-
N-Decane	173	247	200	219	162	175
Unidentified	40	52	53	45	49	42
P-isopropyltoluene	81	32	105	59	89	64
Unidentified	23	18	32	28	42	36
Unidentified	15	17	20	17	35	35
Unidentified	33	16	77	110	86	82
Unidentified	77	75	40	65	67	54
Unidentified	58	-	-	-	-	-
Butylbenzene	68	57	77	104	90	78
Unidentified	45	26	21	23	74	19
Unidentified	41	25	25	62	39	17
Unidentified	67	94	-	38	33	87
Unidentified	42	32	-	61	31	50
Unidentified	32	59	-	39	-	40
n-Undecane	47	-	-	27	-	-
Total	28062	33015	29737	29621	29715	30176

November 1989

AIR RESOURCES BOARD

PROCEDURE FOR THE ANALYSIS OF
AUTOMOTIVE EXHAUST FOR
FORMALDEHYDE AND OTHER CARBONAL COMPOUNDS

SOP NO. MLD 104

Southern Laboratory Branch
Monitoring & Laboratory Division
State of California
9828 Telstar Avenue
El Monte, CA 91731

This has been reviewed by the staff of the California Air Resources Board and approved for publication. Approval does not signify that the contents necessarily reflect the views and policy of the Air Resources Board, nor does the mention of trade names or commercial products constitute endorsement or recommendation for use.

S.O.P. No. MLD 104
Effective Date: 11/01/89
Revision No. 1.0
Approved: /s/ SHM
Page 1 of 12

CALIFORNIA AIR RESOURCES BOARD
MONITORING & LABORATORY DIVISION

Procedure for the Analysis of Automotive
Engine Exhaust for Formaldehyde and
Other Carbonyl Compounds

1 Introduction

1.1 This procedure describes a method of sampling and analyzing automotive engine exhaust for formaldehyde (and other carbonyl compounds) in the range of 0.2 to 200 micrograms per 15 ml of 2,4-dinitrophenylhydrazine (DNPH) absorbing solution.

1.2 This procedure is derived from a method used by Hull.

1.3 Lower concentrations may be analyzed by increasing the exhaust sample volume through the impingers. Samples collected by use of DNPH-coated silica gel cartridges may also be analyzed by a variation of this method.

1.4 Higher concentrations may be analyzed by using a smaller exhaust sample volume or by dilution of the concentrated solution with acetonitrile.

2 Method

2.1 The sampling procedure is conducted according to the Code of Federal Regulations.

2.2 Two impingers, each containing 15 ml DNPH absorbing solution, are used for each mode of the CVS test.

2.3 Upon completion of the dyno test, the impinger samples are analyzed by liquid chromatography.

Doc ID A81343/11/8/89/34V

3 Apparatus

3.1 Each sampling train consists of two 30 ml. graduated
fritted magnet impingers plus a dry impinger, pulse
camper, rotameter, pump and a wet test meter.

3.2 The HPLC system consists of the following:

Waters dual model 510 high pressure pumps

Waters model 680 Automated Gradient Controller

Waters model 712 WISP sample processor

Du Pont Zorbax ODS columns

Kratos SF769 Variable Wavelength Spectrophotometer

Perkin Elmer LIMS Data System, or equivalent

4 Reagents

4.1 Acetonitrile, HPLC grade, Burdick and Jackson or
equivalent

4.2 Water, HPLC grade, Burdick and Jackson or equivalent

4.3 2,4-Dinitrophenylhydrazine (DNPH), Eastman or
equivalent, recrystallized twice from acetonitrile.

4.3.1 The recrystallized DNPH is checked for contaminants by
injecting a dilute solution of DNPH in contaminant-free
acetonitrile into the HPLC.

4.3.2 An absorbing solution is prepared by dissolving 0.11 -
0.13 g of recrystallized DNPH in 1 liter of HPLC grade
acetonitrile. After all the crystals are dissolved, 0.1
ml of concentrated sulfuric acid is added.

The acetonitrile used in this procedure is checked for oxygenated impurities by addition of contaminant-free dilute solution of DNPH.

4.3.3 A typical 100 ml acetonitrile standard stock solution contains:

- 14.8 mg formaldehyde/2,4-dinitrophenylhydrazones
- 8.4 mg acetaldehyde/2,4-dinitrophenylhydrazones
- 6.0 mg acrolein/2,4-dinitrophenylhydrazones
- 8.7 mg acetone/2,4-dinitrophenylhydrazones
- 4.7 mg propionaldehyde/2,4-dinitrophenylhydrazones

4.3.4 A working standard of 1:25 dilution of the stock solution is used (Figure 1).

4.4 Sulfuric acid, reagent grade, Baker Analyzed or equivalent

4.5 Synthesized 2,4-dinitrophenylhydrazones⁴ are:

4.5.1 Formaldehyde/2,4-dinitrophenylhydrazones, recrystallized 3X from 95% ethanol, m.p. 163-165° C

4.5.2 Acetaldehyde/2,4-dinitrophenylhydrazones, recrystallized 3X from 95% ethanol, m.p. 142-149° C

4.5.3 Acrolein/2,4-dinitrophenylhydrazones, recrystallized from acetonitrile and 95% ethanol, m.p. 158-159.5° C

4.5.4 Acetone/2,4-dinitrophenylhydrazones, recrystallized 3X from 95% ethanol, m.p. 123-125° C

4.5.5 Propionaldehyde/2,4-dinitrophenylhydrazones, recrystallized 3X from 95% ethanol, m.p. 136-138° C

5. Procedure

- 5.1 Pipet 15 ml of the DNPH absorbing solution into each of seven 30 ml graduated frosted midget impingers, keeping the seventh impinger as a reagent blank.
- 5.2 Connect pairs of these impingers in series and cap the open ends to prevent contamination. (These sets of impingers are transferred to the automotive test personnel for sampling).
- 5.3 After the sampling has been completed and the impingers have been capped and returned to the laboratory, place the six impingers plus the reagent blank impinger in a preheated water bath at 70-80°C for 30 minutes.
- 5.4 Remove the seven impingers from the water bath and cool to room temperature. Replace any lost solvent by adding acetonitrile to the 15 ml mark.
- 5.5 Transfer three milliliters of the solution from each impinger to 4 ml glass vials and seal with new septum-screw caps.
- 5.6 Place the vials containing blank, working standard and samples in the WISP autosampler for subsequent injection into the HPLC system.
- 5.7 The following HPLC conditions or equivalent are used:
- Columns - 4.6 mm ID x 250 mm x 1/4 in OD DuPont Zorbax CDS or equivalent-two column in series
 - Guard column - 2 cm long packed with LC18 5um pellicular or equivalent
 - Detector - UV-VIS at 360 nm
 - Sample volume - 20 µl

Solvent A - acetonitrile
Solvent B - water

Flow - 1.5 ml per minute

Program	60%A to 75%A	0-20 minutes
	75%A to 100%A	20-25 "
	100%A	25-30 "
	100%A to 60%A	30-31 "
	60%A	31-40 "

Data System: The outputs from the spectrophotometric detector are sent to a Perkin Elmer LIMS data system or equivalent system for data reduction.

6 Calculations

6.1 The concentrations of formaldehyde (and other carbonyl compounds) are calculated using an electronic integrator to measure peak areas and compute concentrations using an external standard method.

6.1.1 The carbonyl/2,4-dinitrophenylhydrazone species are determined in the analysis.

6.1.2 The amount of carbonyl (μg) in 15 ml of absorbing solution is:

6.1.3 Amount (μg) = Area x Response Factor x 15 ml x B

where B is the ratio of the molecular weight of formaldehyde (or other carbonyl compounds) to its 2,4-dinitrophenylhydrazone.

6.1.4 Response Factor is calculated during calibration by the equation:

$$\text{RF} = \frac{\text{concentration } (\mu\text{g/ml})}{\text{Area}}$$

S.G.P. No. MLD 104
 Effective Date: 11/01/89
 Revision No. 1.0
 Approved: /s/SHM
 Page 6 of 12

6.2

A calibration curve for formaldehyde/2,4-dinitrophenylhydrazine (HCHO/DNPH) was determined by diluting an appropriate amount of standard stock solution of HCHO/DNPH in acetonitrile. Results of such a calibration are as follows:

HCHO/DNPH			
0.0464 ug/ml	0.232 ug/ml	1.16 ug/ml	5.80 ug/ml
Area	Area	Area	Area
1420	4545	19542	97577
1217	4359	20627	98120
946	4269	19404	90145
972	3931	19998	95350
1413	4711	21249	101716
790	4086	19874	95992
Mean	1126	4312	96483
SD	263	283	701
% RSD	23.4	6.6	3.5
			4.0

% RSD is SD divided by the mean times 100%.

6.3

The limit of detection (LOD)⁶ for formaldehyde is calculated by the following formula:

$$LOD = \frac{3 \times SD}{m}$$

Where:

SD = standard deviation near the lowest detectable concentration

S.O.P. No. MLD 104
Effective Date: 11/01/89
Revision No. 1.0
Approved: /s/ SHM
Page 7 of 12

m = slope of calibration curve

- 6.3.1 Based on the calibration curve, $y = 16550x + 581$, the LOD was determined to be 0.06 $\mu\text{g}/\text{mL}$ HCHO/DNPH. This corresponds to a concentration of 0.1 μg formaldehyde in 15 mL of DNPH solution.

Quality Control

- 7.1 The solvents used are of the highest HPLC grade and are checked for impurities by conducting blank analyses.
- 7.2 The 2,4-dinitrophenylhydrazones are checked for purity by their melting points and their chromatograms.
- 7.3 The quality control procedures followed during analysis are:
- 7.3.1 Analysis of blank absorbing solution each analysis day.
- 7.3.2 Analyses of working standard and control sample each analysis day.
- 7.3.3 Maintenance of control charts for formaldehyde and other carbonyl compounds of interest.
- 7.3.4 Semi-annual linearity check of the instrument by multipoint calibration (Figure 3).
- 7.3.5 A 40 day stability study of formaldehyde/2,4-dinitrophenylhydrazine in acetonitrile absorbing solution showed no significant change in concentration over this time period (Figure 4).

8 References

- 8.1. Hull, L.A., "Procedures for 2,4-Dinitrophenylhydrazones, Aldehyde-Ketone Air Analysis", Internal report, Office of leave at U.S. EPA.
- 8.2. Tejada, S.B., "DNPH-Coated Silica Cartridges for Sampling Carbonyl Compounds in Air and Analysis by High Performance Liquid Chromatography", EPA/MSEB internal report, 1985 and Tejada, S.B., "Evaluation of Silica Gel Cartridges Coated in Situ with Acidified 2,4-Dinitrophenylhydrazine for Sampling Aldehydes and Ketones in Air", Intern. J. Environ. Anal. Chem., 1986, Vol. 26, pp. 167-185.
- 8.3. Code of Federal Regulations, Title 40, Part 66.
- 8.4. Shriner, R.L. and Fuson, R.C., "Identification of Organic Compounds" 2nd. Ed., John Wiley and Sons, Inc., 1940, p. 143.
- 8.5. EPA/MSEB "Round Robin" procedure, 1988.
- 8.6. Long, G.L. and Winefordner, J.D., Anal. Chem. 55, 713A (1983).

CALIB. STD 9/8-11

SAMPLE NO.: 89000913.01


TEST NO.: RCH01

METHOD NO.: RCH01 / RCH01

INSTRUMENT: 05

DATE TIME: 02/02/89 10:07:35

PAGE NO.: 01



05917

Y MAXIMUM: 1125.

Y MINIMUM: 116.

RETENTION TIME (MINUTES)

START TIME: 0.00

END TIME: 17.00

FORMALDEHYDE-2, 4-DINITROPHENYL HYDRAZINE TEST: GC100

AVERAGE VALUE = 98573.0

STANDARD DEVIATION = 4307.61

95% CONFIDENCE LIMITS = 970615.23

MINIMUM VALUE = 87367.0

MAXIMUM VALUE = 108013.0

POPULATION = 90

UPPER LIMIT


111496.0

AVERAGE

98573.0

LOWER LIMIT

85251.0



SAMPLE NUMBER

Curve Fit -- Linear Fit
Error is 22158.

Y = 16550.
X + 560.78

10.50

9.45

8.40

7.35

6.30

5.25

4.20

3.15

2.10

1.05

0.00

0.00

Linear-Linear

0.60

1.20

1.80

2.40

3.00

3.60

4.20

4.80

5.40

6.00

HCHO/DNPH (---UG/ML---)

Y * 10⁴ X

(---YMAX---)

YMax: .102E+06

YMin: 790.

XMax: 5.8


XMin: .464E-01

24 Points

05919

Curve Fit --- Linear Fit
 Error is 2.7261

$$Y = -.3419E-02 X + 13.573$$



---FORMALDEHYDE---
 (---UG---)

YMax: 14.0
 YMin: 13.1
 XMax: 43.0
 XMin: 1.0